

Documentation of the RMAGEML package

Steffen Durinck^{‡,*}, Joke Allemeersch^{‡,†}, Vincent J Carey[¶], Yves Moreau[‡],
Bart De Moor[‡]

March 18, 2006

[‡]Department of Electronical Engineering, ESAT-SCD, K.U.Leuven,
Kasteelpark Arenberg 10, 3001 Leuven-Heverlee, Belgium,
<http://www.esat.kuleuven.ac.be/~dna/BioI>

and [¶]Channing Laboratory, Brigham and Women's Hospital, 75 Francis Street, Boston
02115, USA

Contents

1 Introduction

MAGE-ML or Microarray Gene Expression Markup Language is a language designed to describe and exchange information about microarray experiments. MAGE-ML is based on XML and can describe microarray designs, microarray experiment setups, gene expression data, and data analysis results.

This package provides the link between MAGE-ML files and BioConductor. It gives the possibility to read in MAGE-ML files that describe cDNA microarray experiments. The functions convert the MAGE-ML files into the customary BioConductor objects (i.e., `marrayLayout`, `marrayInfo` and `marrayRaw` objects or `limma RGList` objects).

Here we give a short introduction to the Microarray and GeneExpression Object Model (MAGE-OM) and how we implemented the extraction of information necessary to make BioConductor objects. For a full description of MAGE-OM, we refer to the Gene Expression Specification: <http://www.omg.org/cgi-bin/doc?formal/03-02-03>.

The main classes of the MAGE object model are `BioSequence`, `Quantitationtype`, `ArrayDesign`, `DesignElement`, `Array`, `BioMaterial`, `BioAssay`, `BioAssayData`, `Experiment`, `HigherLevelAnalysis`, `Protocol`, `Description`, `AuditAndSecurity`, `Measurement`, and `BioEvent`.

In MAGE-ML these translate into packages with the same name. The packages needed for

*Steffen.Durinck@esat.kuleuven.ac.be

†Joke.Allemeersch@esat.kuleuven.ac.be

building BioConductor objects are BioAssayData, BioAssay, BioMaterial, BioSequence, ArrayDesign, and DesignElement.

The DesignElement package contains a mapping of *Features*, which are the actual features present on the array, to *Reporters*, the reporter a feature represents. The DesignElement package also provides a mapping from *Reporters* to their corresponding *BioSequence* references. These *BioSequence* objects are characterized by their name and database entries in the BioSequence package. The ArrayDesign package contains information on the layout of the array. From this package, we can derive the position of each *Feature* on the array in terms of *Zone* (block or grid) and row and column within each *Zone*. The BioAssayData package describes the feature references that were assayed and the measured and derived *QuantitationTypes*. The BioAssay package describes the different steps in the microarray experiment. The last package used to make BioConductor objects is the BioMaterial package and describes how a sample is treated to obtain, for example, labeled samples used for hybridization.

2 Prerequisites

The RMAGEML package depends on SJava(>= 0.68) and a Java VM, e.g. j2resdk1.4.0. Other dependencies are as the Java-MAGEstk API and Java Xerces included in the package itself.

3 Getting started

Installing the package. The package can be installed as a normal R package: download the RMAGEML_2.0.4.tar.gz package and under Unix use the command

```
R CMD INSTALL RMAGEML_2.1.0.tar.gz.
```

The equivalent command for Windows is

```
Rcmd INSTALL RMAGEML_2.1.0.zip.
```

The package automatically loads the Biobase and marrayInput packages from BioConductor and the SJava libraries, so these should be installed as well.

Starting R. Before starting R one should be aware that the RMAGEML package uses SJava and that SJava requires to set the LD_LIBRARY_PATH environment variable before starting R.

Without setting this variable the package won't work

Loading the package. You can load the package into R by typing

```
> library(RMAGEML)
```

```
Loading required package: marray  
Loading required package: limma  
Loading required package: limma  
Loading required package: Biobase
```

```
Welcome to Bioconductor
```

```
Vignettes contain introductory material.  
To view, simply type 'openVignette()' or start with 'help(Biobase)'.  
For details on reading vignettes, see the openVignette help page.
```

4 Import to marray packages

4.1 One step import and creation of an `marrayRaw` object from MAGE-ML files

In the `marray` packages of BioConductor the design of an array experiment is typically described by an `marrayLayout` and `marrayInfo` object. The function `importMAGEML` parses all MAGE-ML files present in the directory, which is given as a parameter to the function. From these files it creates an `marrayLayout` object, containing the Layout of one type of microarrays, and an `marrayInfo` object containing the gene names and database entries of the features spotted on the array. The name of the database to which the entries refer, is given in the 'notes' slot of the `Gnames` object. Next the function will extract the raw data values and output a complete `marrayRaw` object as a result.

The function can be tested on the MEXP-14 dataset. This example is available from Array-Express at <http://www.ebi.ac.uk/arrayexpress/>.

If one knows which *DesignElement Dimension*, *QuantitationType Dimension* and *Quantitation Types* are required, the import function can be used as:

```
> datadir <- system.file("MAGEMLdata", package = "RMAGEML")  
> raw <- importMAGEML(directory = datadir, package = "marray",  
+   arrayID = "A-MEXP-14", DED = "DED:707", QTD = "QTD:707",  
+   name.Rf = "QT:F635 Mean", name.Rb = "QT:B635 Median", name.Gf = "QT:F532 Mean",  
+   name.Gb = "QT:B532 Median")
```

```
- Java Virtual Machine is running -  
parsing MAGEML files  
making Layout and Gnames objects  
Reading am2730miame.txt  
Reading am2731miame.txt  
Reading am2732m.txt
```

```
Reading am2736m.txt
Reading am2737m.txt
Reading tm1826m.txt
Reading tm1827m.txt
Reading tm1829m.txt
Reading tm1830m.txt
Reading tm1831m.txt
```

```
> print(raw)
```

```
An object of class "marrayRaw"
```

```
@maRf
```

```
      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10]
[1,] 5841 2030 2968   45 1828 1975 2077 1775 2202   841
[2,] 2002 1312  421   96  399  557  295  748  465    83
[3,] 2254 2057 1097 1163  649  917  755 1276  985   335
[4,] 2212 1492  782  767  709 1114  620 1004  860   488
[5,]   73   76   42   54   45   49   49   46   47    43
955 more rows ...
```

```
@maGf
```

```
      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10]
[1,]  852  750 1587  135 1625 1183 1598 1108  807  1746
[2,]  652  529  404  162  397  515  285  390  291   190
[3,]  576  615  634  386  734  820  696  573  457   572
[4,]  781  589  733  366  758  848  667  597  559   716
[5,]  157  143  111  124  130  148  135  137  146   131
955 more rows ...
```

```
@maRb
```

```
      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10]
[1,]   42   42   36   39   41   47   40   45   49   42
[2,]   41   41   35   39   40   45   39   43   42   41
[3,]   41   42   34   41   40   44   40   43   42   42
[4,]   41   40   34   41   40   43   39   43   41   41
[5,]   41   39   34   40   40   42   39   43   41   41
955 more rows ...
```

```
@maGb
```

```
      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10]
[1,]  150  130   87  120  104  135  117  137  168  127
[2,]  147  128   88  111  105  136  116  131  137  121
[3,]  140  124   85  106  105  133  116  128  135  121
[4,]  138  122   88  108  106  133  116  128  134  120
[5,]  138  122   87  106  104  133  114  128  133  118
```

955 more rows ...

@maW

<0 x 0 matrix>

@maLayout

An object of class "marrayLayout"

@maNgr

[1] 4

@maNgc

[1] 4

@maNsr

[1] 10

@maNsc

[1] 6

@maNspots

[1] 960

@maSub

[1] TRUE

@maPlate

factor(0)

Levels:

@maControls

factor(0)

Levels:

@maNotes

[1] ""

@maGnames

An object of class "marrayInfo"

@maLabels

[1] "none" "none" "none" "none" "none"

955 more elements ...

@maInfo

```
[1] aj508733 V00618 aj291984 aj306233 aj310439
142 Levels: af025843 af034412 af135499 aj132353 aj291832 aj291833 ... y17187
955 more rows ...
```

```
@maNotes
```

```
[1] "Identifiers refer to database: DB:embl"
```

```
@maTargets
```

```
An object of class "marrayInfo"
```

```
@maLabels
```

```
[1] "am2730miame.txt" "am2731miame.txt" "am2732m.txt" "am2736m.txt"
[5] "am2737m.txt" "tm1826m.txt" "tm1827m.txt" "tm1829m.txt"
[9] "tm1830m.txt" "tm1831m.txt"
```

```
@maInfo
```

```
      Cy3      Cy5
1 AM-Pool AM2730-I
2 AM-Pool AM2731-1
3 AM-Pool AM2732-I
4 AM-Pool AM2736-I
5 AM-Pool AM2737-I
6 AM-Pool TM1826-I
7 AM-Pool TM1827-I
8 AM-Pool TM1829-I
9 AM-Pool TM1830-I
10 AM-Pool TM1831-I
```

```
@maNotes
```

```
[1] "Description of the targets"
```

```
@maNotes
```

```
character(0)
```

If however you do not know which *DesignElement Dimension*, *QuantitationType Dimension* and *Quantitation Types* to use, you can call the function as follows:

```
> datadir <- system.file("MAGEMLdata", package = "RMAGEML")
> if (interactive()) {
+   raw <- importMAGEML(directory = datadir, package = "marray")
+ }
```

This will generate a few selection panels which allow selection of the appropriate *DesignElement Dimension*, *QuantitationType Dimension* and *Quantitation Types*.

4.2 Creation of a Gnames marrayInfo object

If one just wants to make an marrayInfo object containing the gene names and database identifiers of the spotted features the function getGnames can be used.

```
> data <- system.file("MAGEMLdata", package = "RMAGEML")
> mageom <- importMAGEOM(directory = data)
```

parsing MAGEML files

```
> getGnames(mageom, arrayID = "A-MEXP-14", DED = "DED:707", package = "marray")
```

An object of class "marrayInfo"

@maLabels

```
[1] "none" "none" "none" "none" "none"
955 more elements ...
```

@maInfo

```
[1] aj508733 V00618 aj291984 aj306233 aj310439
142 Levels: af025843 af034412 af135499 aj132353 aj291832 aj291833 ... y17187
955 more rows ...
```

@maNotes

```
[1] "Identifiers refer to database: DB:embl"
```

Again leaving out the 'DED' parameter will cause selection panels to pop up displaying the available *DesignElement Dimensions*.

4.3 Creation of an marrayLayout object

In the marray packages the information on the array layout is stored in an marrayLayout object which can be created by the getArrayLayout function.

```
> data <- system.file("MAGEMLdata", package = "RMAGEML")
> mageom <- importMAGEOM(directory = data)
```

parsing MAGEML files

```
> getArrayLayout(mageom, arrayID = "A-MEXP-14", DED = "DED:707")
```

An object of class "marrayLayout"

@maNgr

```
[1] 4
```

@maNgc

```
[1] 4
```

```

@maNsr
[1] 10

@maNsc
[1] 6

@maNspots
[1] 960

@maSub
[1] TRUE

```

```

@maPlate
factor(0)
Levels:

```

```

@maControls
factor(0)
Levels:

```

```

@maNotes
[1] ""

```

4.4 Make an marrayRaw object

The function `makeMarrayRaw` takes a `Gnames` and `Layout` object and parameters corresponding to the *DesignElement Dimension*, *QuantitationType Dimension* and *Quantitation Types* to create an *marrayRaw* object.

```

> data <- system.file("MAGEMLdata", package = "RMAGEML")
> mageom <- importMAGEOM(directory = data)

```

parsing MAGEML files

```

> gnames <- getGnames(mageom, arrayID = "A-MEXP-14", DED = "DED:707",
+   package = "marray")
> layout <- getArrayLayout(mageom, arrayID = "A-MEXP-14", DED = "DED:707")
> raw <- makeMarrayRaw(mageOM = mageom, layout = layout, gnames = gnames,
+   directory = data, arrayID = "A-MEXP-14", DED = "DED:707",
+   QTD = "QTD:707", name.Rf = "QT:F635 Mean", name.Rb = "QT:B635 Median",
+   name.Gf = "QT:F532 Mean", name.Gb = "QT:B532 Median")

```

```

Reading am2730miame.txt
Reading am2731miame.txt
Reading am2732m.txt

```

```
Reading am2736m.txt
Reading am2737m.txt
Reading tm1826m.txt
Reading tm1827m.txt
Reading tm1829m.txt
Reading tm1830m.txt
Reading tm1831m.txt
```

5 Import to limma package

5.1 One step import and creation of a limma RGList object from MAGE-ML files

In the limma package of BioConductor the raw data is stored in an `RGList` object. The function `importMAGEML` parses all MAGE-ML files present in the directory which is given as a parameter to the function. From these files it creates the `RGList` object, containing the layout, gene names and database entries of the features spotted on the array and the foreground and background intensities for the green and red channels.

The function can be tested on the MEXP-14 dataset. This example is available from Array-Express at <http://www.ebi.ac.uk/arrayexpress/>.

For import to limma the same function as MAGEML import to marray packages can be used, just adapt the name of the package into limma as follows:

```
> datadir <- system.file("MAGEMLdata", package = "RMAGEML")
> raw <- importMAGEML(directory = datadir, package = "limma", arrayID = "A-MEXP-14",
+   DED = "DED:707", QTD = "QTD:707", name.Rf = "QT:F635 Mean",
+   name.Rb = "QT:B635 Median", name.Gf = "QT:F532 Mean", name.Gb = "QT:B532 Median")
```

parsing MAGEML files

```
Reading am2730miame.txt
Reading am2731miame.txt
Reading am2732m.txt
Reading am2736m.txt
Reading am2737m.txt
Reading tm1826m.txt
Reading tm1827m.txt
Reading tm1829m.txt
Reading tm1830m.txt
Reading tm1831m.txt
```

```
> print(raw)
```

An object of class "RGList"

```
$R
```

	am2730miame.txt	am2731miame.txt	am2732m.txt	am2736m.txt	am2737m.txt
[1,]	5841	2030	2968	45	1828
[2,]	2002	1312	421	96	399
[3,]	2254	2057	1097	1163	649
[4,]	2212	1492	782	767	709
[5,]	73	76	42	54	45

	tm1826m.txt	tm1827m.txt	tm1829m.txt	tm1830m.txt	tm1831m.txt
[1,]	1975	2077	1775	2202	841
[2,]	557	295	748	465	83
[3,]	917	755	1276	985	335
[4,]	1114	620	1004	860	488
[5,]	49	49	46	47	43

955 more rows ...

\$G

	am2730miame.txt	am2731miame.txt	am2732m.txt	am2736m.txt	am2737m.txt
[1,]	852	750	1587	135	1625
[2,]	652	529	404	162	397
[3,]	576	615	634	386	734
[4,]	781	589	733	366	758
[5,]	157	143	111	124	130

	tm1826m.txt	tm1827m.txt	tm1829m.txt	tm1830m.txt	tm1831m.txt
[1,]	1183	1598	1108	807	1746
[2,]	515	285	390	291	190
[3,]	820	696	573	457	572
[4,]	848	667	597	559	716
[5,]	148	135	137	146	131

955 more rows ...

\$Rb

	am2730miame.txt	am2731miame.txt	am2732m.txt	am2736m.txt	am2737m.txt
[1,]	42	42	36	39	41
[2,]	41	41	35	39	40
[3,]	41	42	34	41	40
[4,]	41	40	34	41	40
[5,]	41	39	34	40	40

	tm1826m.txt	tm1827m.txt	tm1829m.txt	tm1830m.txt	tm1831m.txt
[1,]	47	40	45	49	42
[2,]	45	39	43	42	41
[3,]	44	40	43	42	42
[4,]	43	39	43	41	41
[5,]	42	39	43	41	41

955 more rows ...

```

$Gb
      am2730miame.txt am2731miame.txt am2732m.txt am2736m.txt am2737m.txt
[1,]           150           130           87           120           104
[2,]           147           128           88           111           105
[3,]           140           124           85           106           105
[4,]           138           122           88           108           106
[5,]           138           122           87           106           104
      tm1826m.txt tm1827m.txt tm1829m.txt tm1830m.txt tm1831m.txt
[1,]           135           117           137           168           127
[2,]           136           116           131           137           121
[3,]           133           116           128           135           121
[4,]           133           116           128           134           120
[5,]           133           114           128           133           118
955 more rows ...

```

```

$genes
  Block Row Column      ID Name
1     1   1     1 aj508733 none
2     1   1     2  V00618 none
3     1   1     3 aj291984 none
4     1   1     4 aj306233 none
5     1   1     5 aj310439 none
955 more rows ...

```

Similarly if one only specifies the ‘directory’ and the ‘package’, selection panels will pop up to select the *DesignElement Dimension*, *QuantitationType Dimension* and *Quantitation Types*.

5.2 Creating the genes dataframe of an RGList object

In limma the gene names, gene identifiers and layout information is stored in a dataframe which can be created by the `getArrayLayoutLimma` function.

```

> data <- system.file("MAGEMLdata", package = "RMAGEML")
> mageom <- importMAGEOM(directory = data)

```

parsing MAGEML files

```

> genes <- getArrayLayoutLimma(mageom, arrayID = "A-MEXP-14", DED = "DED:707")
> print(genes[1:10, ])

```

```

  Block Row Column      ID Name
1     1   1     1 aj508733 none
2     1   1     2  V00618 none
3     1   1     3 aj291984 none
4     1   1     4 aj306233 none

```

```

5      1      1      5 aj310439 none
6      1      1      6 aj409363 none
7      1      1      7 aj310516 none
8      1      1      8 aj306230 none
9      1      1      9 aj310436 none
10     1      1     10 aj291834 none

```

5.3 Make an RGList object

The function `makeRG` takes a genes dataframe (containing the layout, gene identifiers and gene names), and parameters corresponding to *DesignElement Dimension*, *QuantitationType Dimension* and *Quantitation Types* to create a limma RGList object.

```

> data <- system.file("MAGEMLdata", package = "RMAGEML")
> mageom <- importMAGEOM(directory = data)

```

parsing MAGEML files

```

> genes <- getArrayLayoutLimma(mageom, arrayID = "A-MEXP-14", DED = "DED:707")
> raw <- makeRG(mageOM = mageom, genes = genes, directory = data,
+   arrayID = "A-MEXP-14", DED = "DED:707", QTD = "QTD:707",
+   name.Rf = "QT:F635 Mean", name.Rb = "QT:B635 Median", name.Gf = "QT:F532 Mean",
+   name.Gb = "QT:B532 Median")

```

```

Reading am2730miame.txt
Reading am2731miame.txt
Reading am2732m.txt
Reading am2736m.txt
Reading am2737m.txt
Reading tm1826m.txt
Reading tm1827m.txt
Reading tm1829m.txt
Reading tm1830m.txt
Reading tm1831m.txt

```

```

>raw <- importMAGEML(directory = "/home/steffen/data/MEXP-14", name.Gf = "QT:F635 Mean",
>norm<-maNorm(raw)
>mageom <- importMAGEOM(directory = "/home/steffen/data/E-MEXP-14")
>outputDirectory <- "/home/steffen/XMLout"
>magemlFile <- "RMAGEMLtest2.xml"
>rawDataFiles <- raw@maTargets@maLabels
>externalDataFiles <- c("deriv_test1.txt","deriv_test2.txt","deriv_test3.txt","deriv_tes
>test8.txt","deriv_test9.txt","deriv_test10.txt")
>protocolID <- "P-maNorm-test"
>protocol <- "This is a test protocol! Applied maNorm to the raw signal intensities"

```

```

>qtID <- c("esat.kuleuven.ac.be:maNorm")
>qtName <- c("applied marrayNorm")
>qtDescription <- c("some description")
>qtScale <- c("linear")
>qtDataType <- c("scalar")
>qtDimID <- "esat.kuleuven.ac.be:QTD-test"
>date <- "testdate"
>tfmID <- "TFM-testID"
>BADIDs <- c("esat.kuleuven.ac.be:BAD-test1","esat.kuleuven.ac.be:BAD-test2","esat.kuleuven.ac.be:BAD-test5","esat.kuleuven.ac.be:BAD-test6","esat.kuleuven.ac.be:BAD-test7","esat.kuleuven.ac.be:BAD-test10")
>derivedBioAssayIDs <- c("esat.kuleuven.ac.be:DBA-test1","esat.kuleuven.ac.be:DBA-test2","esat.kuleuven.ac.be:DBA-test5","esat.kuleuven.ac.be:DBA-test6","esat.kuleuven.ac.be:DBA-test10")
>derivedBioAssayDataIDs <- c("esat.kuleuven.ac.be:DBD-test1", "esat.kuleuven.ac.be:DBD-test5", "esat.kuleuven.ac.be:DBD-test6", "esat.kuleuven.ac.be:DBD-test9", "esat.kuleuven.ac.be:DBD-test10")
>addNormToMAGEML(mageOM = mageom, norm = norm, outputDirectory = outputDirectory, externalProtocol, date=date, qtID = qtID, qtName = qtName, qtDescription = qtDescription, qtScale = qtScale, qtDimID = qtDimID, tfmID = tfmID, arrayID="A-MEXP-14",DED = "none", BADIDs = BADIDs, derivedBioAssayIDs = derivedBioAssayIDs, rawDataFiles=rawDataFiles)
>writeMAGEML(mageOM = mageom, directory = outputDirectory, file = magemlFile)

```