

# Package ‘ggtut’

September 23, 2012

**Title** support for tutorial on genetics of gene expression ISMB 2011

**Version** 0.0.42

**Author** VJ Carey <stvjc@channing.harvard.edu>

**Description** various resources for genetics of expression with R/bioc

**Suggests** rtracklayer, GenomicFeatures, ChIPpeakAnno, TxDb.Hsapiens.UCSC.hg18.knownGene

**Depends** R (>= 2.14.0), GGtools (>= 3.11.32), ff, GenomicRanges, snpStats, GGdata, GenomicFeatures, ChIPpeakAnno, Rsamtools (>= 1.5.35), cheung2010, SNPlocs.Hsapiens.dbSNP.20090506, hmyriB36

**Maintainer** VJ Carey <stvjc@channing.harvard.edu>

**License** Artistic-2.0

**LazyLoad** yes

## R topics documented:

ggtut-package . . . . .	1
c17imp . . . . .	2
g17rngsnr . . . . .	3
observed17ceu . . . . .	4
rules.n43 . . . . .	5
snpr17 . . . . .	6
<b>Index</b>	<b>7</b>

---

ggtut-package	<i>support for tutorial on genetics of gene expression ISMB 2011</i>
---------------	--

---

## Description

various resources for genetics of expression with R/bioc



**Format**

The format is:  
 Formal class 'SnpMatrix' [package "snpStats"] with 1 slots  
 ..@ .Data: raw [1:90, 1:175170] 77 d6 77 2d ...  
 .. ..- attr(\*, "dimnames")=List of 2  
 .. .. ..\$: chr [1:90] "NA06985" "NA06991" "NA06993" "NA06994" ...  
 .. .. ..\$: chr [1:175170] "chr17:1869" "rs17055023" "rs6565733" "rs34663111" ...

**Source**

uses rules.n43

**Examples**

```
library(snpStats)
data(c17imp)
c17imp
```

---

g17rngsnr

*ranges of genes on chrom 17 (uses hg18)*


---

**Description**

ranges of genes on chrom 17 (uses hg18)

**Usage**

```
data(g17rngsnr)
```

**Format**

The format is:  
 Formal class 'GRanges' [package "GenomicRanges"] with 6 slots  
 ..@ seqnames :Formal class 'Rle' [package "IRanges"] with 4 slots  
 .. ..@ values : Factor w/ 1 level "chr17": 1  
 .. ..@ lengths : int 475  
 .. ..@ elementMetadata: NULL  
 .. ..@ metadata : list()  
 ..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots  
 .. ..@ start : int [1:475] 39509647 50333051 46294586 77439016 38229969 37098653 45133689  
 58981554 44263371 17349602 ...  
 .. ..@ width : int [1:475] 46894 61277 5753 3743 19335 2772 6839 43820 33858 86118 ...  
 .. ..@ NAMES : chr [1:475] "GI\_21237796-A" "GI\_4885638-S" "GI\_22035666-S" "GI\_17572809-S" ...  
 .. ..@ elementType : chr "integer"  
 .. ..@ elementMetadata: NULL  
 .. ..@ metadata : list()  
 ..@ strand :Formal class 'Rle' [package "IRanges"] with 4 slots  
 .. ..@ values : Factor w/ 3 levels "+","-","\*": 3  
 .. ..@ lengths : int 475

```

.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ elementMetadata:Formal class 'DataFrame' [package "IRanges"] with 6 slots
.. ..@ rownames : NULL
.. ..@ nrows : int 475
.. ..@ listData :List of 1
.. .. .$ probeid: chr [1:475] "GI_21237796-A" "GI_4885638-S" "GI_22035666-S" "GI_17572809-
S" ...
.. ..@ elementType : chr "ANY"
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ seqinfo :Formal class 'Seqinfo' [package "GenomicRanges"] with 3 slots
.. ..@ seqnames : chr "chr17"
.. ..@ seqlengths : int NA
.. ..@ is_circular: logi NA
..@ metadata : list()

```

## Examples

```

data(g17rngsnr)
g17rngsnr
## maybe str(g17rngsnr) ; plot(g17rngsnr) ...

```

---

observed17ceu

*obtain access to ff-based archives of eQTL test results*

---

## Description

obtain access to ff-based archives of eQTL test results

## Usage

```

observed17ceu()
onePerm17ceu()

```

## Details

The underlying ff data were obtained as follows

```

dropMonomorphies = function(sms) { sl = smList(sms) summs = lapply(sl, col.summary)
todrop = lapply(summs, function(x) which(x[,"RAF"]==1 | x[,"RAF"]==0)) for (i in 1:length(todrop))
if (length(todrop[[i]])>0) sl[[i]] = sl[[i]][,-todrop[[i]]] sms@smEnv$smList = sl
sms } library(GGdata) library(multicore) data(eset) ex library(genefilter) exf1 = nsFilter(ex)
length(get("17", revmap(illuminaHumanv1CHR)))->ZZ) kp = intersect(ZZ, featureNames(exf1[[1]]))
c17 = getSS("GGdata", "17", renameChrs="chr17", probesToKeep=kp, wrapperEndo=dropMonomorphies)
f1dm = eqtlTests(c17, ~male, targdir="c17c", genegran=1, geneApply=mclapply) save(f1dm, file="f1dm.rda")
set.seed(1234); permf1dm = eqtlTests(permEx(c17), ~male, targdir="c17c_perm", genegran=1, geneApply=mclapply)
save(permf1dm, file="permf1dm.rda")

```

## Value

an instance of [eqtlTestsManager-class](#)

**Examples**

```
f1 = observed17ceu()
f1
f1@call
f1[ rsid("rs7502145"), probeId("GI_10190685-S")]
pf1 = onePerm17ceu()
pf1[ rsid("rs7502145"), probeId("GI_10190685-S")]
```

rules.n43

*snpStats imputation rules instance***Description**

snpStats imputation rules instance

**Usage**

```
data(rules.n43)
```

**Format**

The format is:

Formal class 'ImputationRules' [package "snpStats"] with 1 slots

```
..@ .Data:List of 470806
```

```
.. ..$: NULL
```

```
.. ..$:List of 4
```

```
.. ...$ maf : num 0.128
```

```
.. ...$ r.squared: num 0.901
```

```
.. ...$ snps : chr [1:4] "rs11654695" "rs9789059" "rs8073513" "rs7225087"
```

```
.. ...$ hap.probs: num [1:32] 0.00 1.02e-21 0.00 1.45e-07 1.52e-07 ...
```

```
.. ..$:List of 4
```

```
.. ...$ maf : num 0.163
```

```
.. ...$ r.squared: num 0.802
```

```
.. ...$ snps : chr [1:4] "rs11654695" "rs12449775" "rs8078223" "rs9907102"
```

```
.. ...$ hap.probs: num [1:32] 0.02863 0.0253 0.00342 0.07866 0.01717 ...
```

```
.. ..$:List of 4
```

```
.. ...$ maf : num 0.116
```

```
.. ...$ r.squared: num 0.881
```

```
.. ...$ snps : chr [1:4] "rs11654695" "rs9789059" "rs8073513" "rs4968164"
```

```
.. ...$ hap.probs: num [1:32] 0.00 1.96e-13 0.00 4.91e-05 1.05e-06 ...
```

```
.. ..$: NULL
```

```
.. .. [list output truncated]
```

**Examples**

```
library(snpStats)
data(rules.n43)
rules.n43[1:4]
## maybe str(rules.n43) ; plot(rules.n43) ...
```

snpr17

*SNP locations for chr 17***Description**

SNP locations for chr 17

**Usage**

data(snpr17)

**Format**

The format is:

```

Formal class 'GRanges' [package "GenomicRanges"] with 6 slots
..@ seqnames :Formal class 'Rle' [package "IRanges"] with 4 slots
.. ..@ values : Factor w/ 1 level "chr17": 1
.. ..@ lengths : int 316396
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots
.. ..@ start : int [1:316396] 6934 7214 7242 8611 11743 11830 13546 13905 14122 14300 ...
.. ..@ width : int [1:316396] 1 1 1 1 1 1 1 1 1 1 ...
.. ..@ NAMES : chr [1:316396] "rs1106176" "rs6420494" "rs6420495" "rs62054996" ...
.. ..@ elementType : chr "integer"
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ strand :Formal class 'Rle' [package "IRanges"] with 4 slots
.. ..@ values : Factor w/ 3 levels "+","-","*": 3
.. ..@ lengths : int 316396
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ elementMetadata:Formal class 'DataFrame' [package "IRanges"] with 6 slots
.. ..@ rownames : NULL
.. ..@ nrows : int 316396
.. ..@ listData : Named list()
.. ..@ elementType : chr "ANY"
.. ..@ elementMetadata: NULL
.. ..@ metadata : list()
..@ seqinfo :Formal class 'Seqinfo' [package "GenomicRanges"] with 3 slots
.. ..@ seqnames : chr "chr17"
.. ..@ seqlengths : int NA
.. ..@ is_circular: logi NA
..@ metadata : list()

```

**Examples**

```

data(snpr17)
snpr17
## maybe str(snpr17) ; plot(snpr17) ...

```

# Index

## \*Topic **datasets**

- c17imp, [2](#)
- g17rngsnr, [3](#)
- rules.n43, [5](#)
- snpgr17, [6](#)

## \*Topic **models**

- observed17ceu, [4](#)

## \*Topic **package**

- ggtut-package, [1](#)

bestGenesPerSNP\_obs (ggtut-package), [1](#)  
bestGenesPerSNP\_perm (ggtut-package), [1](#)

c17imp, [2](#)  
CPS17 (ggtut-package), [1](#)

g17rngsnr, [3](#)  
getFixedBFL (ggtut-package), [1](#)  
ggtut (ggtut-package), [1](#)  
ggtut-package, [1](#)

hg18tx (ggtut-package), [1](#)

observed17ceu, [4](#)  
onePerm17ceu (observed17ceu), [4](#)

PERMCPS17 (ggtut-package), [1](#)  
permsb1 (ggtut-package), [1](#)

rsb2\_list (ggtut-package), [1](#)  
rsb2\_perm\_list (ggtut-package), [1](#)  
rules.n43, [5](#)

sb1 (ggtut-package), [1](#)  
snpgr17, [6](#)  
SVA1 (ggtut-package), [1](#)

tr17\_1\_9 (observed17ceu), [4](#)  
tr17\_1\_9\_perm (observed17ceu), [4](#)