

# Package ‘DEXSeq’

October 7, 2014

**Version** 1.10.8

**Title** Inference of differential exon usage in RNA-Seq

**Author** Simon Anders <sanders@fs.tum.de> and Alejandro Reyes  
<alejandro.reyes@embl.de>, both at EMBL Heidelberg

**Maintainer** Alejandro Reyes <alejandro.reyes@embl.de>

**Imports** BiocGenerics, biomaRt, hwriter, methods, stringr, Rsamtools, statmod, geneplotter, gene-filter, RColorBrewer

**Depends** Biobase, GenomicRanges, IRanges, DESeq2 (>= 1.3.69), BiocParallel

**Suggests** GenomicFeatures (>= 1.13.29), pasilla (>= 0.2.22), parathyroidSE, BiocStyle, knitr

**Enhances** parallel

**Description** The package is focused on finding differential exon usage using RNA-seq exon counts between samples with different experimental designs. It provides functions that allows the user to make the necessary statistical tests based on a model that uses the negative binomial distribution to estimate the variance between biological replicates and generalized linear models for testing. The package also provides functions for the visualization and exploration of the results.

**License** GPL (>= 3)

**URL**

**biocViews** Sequencing, RNASeq, DifferentialExpression

**VignetteBuilder** knitr

**R topics documented:**

counts . . . . .	2
DEXSeq . . . . .	3
DEXSeq-defunct . . . . .	3
DEXSeq-deprecated . . . . .	4
DEXSeqDataSet-class . . . . .	5
DEXSeqHTML . . . . .	8
DEXSeqResults-class . . . . .	9
estimateDispersions . . . . .	10
estimateExonFoldChanges . . . . .	11
estimateSizeFactors . . . . .	12
ExonCountSet-class . . . . .	12
ExonCountSet-deprecated,methods . . . . .	13
featureCounts . . . . .	13
findOverlaps . . . . .	14
perGeneQValue . . . . .	15
plotDEXSeq . . . . .	16
plotDispEsts . . . . .	17
plotMA-methods . . . . .	18
testForDEU . . . . .	19
<b>Index</b>	<b>21</b>

---

counts	<i>Accessors for the 'counts' slot of a DEXSeqResults object.</i>
--------	---

---

**Description**

The counts slot holds the count data as a matrix of non-negative integer count values, one row for each observational unit (gene or the like), and one column for each sample.

**Usage**

```
## S4 method for signature DEXSeqResults
counts(object,normalized=FALSE)
```

**Arguments**

object	a DEXSeqResults object.
normalized	logical indicating whether or not to divide the counts by the size factors or normalization factors before returning (normalization factors always preempt size factors)

**Value**

an integer matrix

**Examples**

```
data(pasillaDEXSeqDataSet, package="pasilla")
head( counts( dxd ))
```

---

DEXSeq

*Performs the differential exon usage test in a single command*


---

**Description**

This function is a wrapper that calls the necessary functions to perform a differential exon usage test in a single command.

**Usage**

```
DEXSeq(object,
  fullModel=design(object),
  reducedModel = ~ sample + exon,
  BPPARAM=MulticoreParam(workers=1),
  fitExpToVar="condition", quiet=TRUE )
```

**Arguments**

object	An DEXSeqDataSet object.
fullModel	The full model formula
reducedModel	Null model formula.
BPPARAM	A "BiocParallelParam" instance. See ?bplapply for details.
fitExpToVar	A variable name contained in the sample data. The expression values will be fitted to this variable using the the formula " $\sim$ sample + fitExpToVar * exon".
quiet	Whether to print messages at each step

**Value**

A DEXSeqResults object.

**Examples**

```
data(pasillaDEXSeqDataSet, package="pasilla")
dxr <- DEXSeq( dxd )
```

---

DEXSeq-defunct

*This functions are defunct and will be deleted*


---

**Description**

The functions that are defunct, they will be removed in the next release.

---

DEXSeq-deprecated      *This functions are deprecated and will become defunct.*

---

## Description

The ExonCountSet object has been deprecated and substituted by the DEXSeqDataSet object. Therefore, all the functions and methods for the ExonCountSet object will be deprecated and defunct at the next releases. These functions have been substituted by new functions that are compatible with the newer versions of DEXSeq.

## Details

The replacements of deprecated function are summarized in the following items.

- newExonCountSet: DEXseqDataSet
- DEUresultTable: DEXseqResults
- subsetByGenes:
- geneCountTable:
- estimateExonDispersionsForModelFrame\_BM: estimateDispersions-DEXSeqDataSet
- estimateDispersions\_BM: estimateDispersions-DEXSeqDataSet
- testGeneForDEU\_BM: testForDEU
- testForDEU\_BM: testForDEU
- doCompleteDEUAnalysis: DEXSeq
- makeCompleteDEUAnalysis\_BM: DEXSeq
- read.HTSeqCounts: DEXSeqDataSetFromHTSeq
- countTableForGene:
- fitDispersionFunction: estimateDispersions-DEXSeqDataSet
- estimatelog2FoldChange: estimateExonFoldChanges
- modelFrameForGene:
- buildExonCountSet: DEXSeqDataSetFromSE
- constructModelFrame:
- getCountVector:
- estimateExonDispersion: estimateDispersions-DEXSeqDataSet
- testExonForDEU: testForDEU
- doCompleteDEUAnalysis: DEXSeq

---

 DEXSeqDataSet-class     *DEXSeqDataSet object and constructors*


---

## Description

The DEXSeqDataSet is a subclass of DESeqDataSet, specifically designed to adapt the DESeqDataSet to test for differences in exon usage.

## Usage

```
DEXSeqDataSet( countData, sampleData,
  design= ~ sample + exon + condition:exon,
  featureID, groupID, featureRanges=NULL,
  transcripts=NULL)
```

```
DEXSeqDataSetFromHTSeq(
  countfiles, sampleData,
  design= ~ sample + exon + condition:exon,
  flattenedfile=NULL )
```

```
DEXSeqDataSetFromSE( SE,
  design= ~ sample + exon + condition:exon )
```

## Arguments

- |            |  |
|------------|--|
| countData  | A matrix of count data of non-negative integer values. The rows correspond to counts for each exon counting bin, the columns correspond to samples. Note that biological replicates should each get their own column, while the counts of technical replicates (i.e., several sequencing runs/lanes from the same sample) should be summed up into a single column   |
| countfiles | A character vector containing the path to the files that were originated with the script 'dexseq_count.py'.  |
| sampleData | A data.frame with the annotation (e.g. treatments, or tissue types, or phenotypes, or the like). The number of rows in the data frame must to be equal to the number of columns of the countData matrix, assigning the annotation of each sample.  |
| design     | A formula which specifies the design of the experiment. It must specify an interaction term between a variable from the sampleData columns with the 'exon' variable. By default, the design will be '~ sample + exon + condition:exon'. This formula indicates the contrast between 'condition' and exon', i.e. differences in exon usage due to changes in the 'condition' variable. See the vignette for more examples of other designs. |

featureID	A character vector of counting regions identifiers ordered according to the rows in countData. The identifiers names can be repeated between groups but not within groups.
groupID	A vector of group identifiers ordered according to its respective row in countData. It must reflect the sets of counting regions belonging to the same group, for example, exon bins in belonging to the same gene should have the same group identifier.
featureRanges	Optional. GRanges or GRangesList describing the genomic coordinates of each of the rows of countData.
transcripts	Optional. A list of the same length as the number of columns of countData. Each element of the list should contain the transcript identifiers of the
flattenedfile	A character vector containing the path to the flattened annotation file that was originated with the script 'dexseq_prepare_annotation.py'.
SE	A SummarizedExperiments object, originated using the function SummarizeOverlaps. See examples for more details.

**Value**

A DEXSeqDataSet object.

**See Also**

DEXSeqDataSetFromHTSeq DEXSeqDataSetFromSE

**Examples**

```
## Not run:
#####
### From the output of the      ###
### accompanying python scripts ###
#####

inDir = system.file("extdata", package="pasilla", mustWork=TRUE)
flattenedfile = file.path(inDir, "Dmel.BDGP5.25.62.DEXSeq.chr.gff")
sampleData = data.frame(
  condition = c( rep("treated", 3), rep("untreated", 4) ),
  type = c("single", "paired", "paired", "single", "single", "paired", "paired") )

countFiles <- list.files(inDir, pattern="fb.txt")
rownames( sampleData ) <- countFiles

DEXSeqDataSetFromHTSeq(
  countfiles=file.path( inDir, countFiles ),
  sampleData = sampleData,
  design = ~ sample + exon + type:exon + condition:exon,
  flattenedfile=flattenedfile )

#####
```

```

### From GRanges derived objects   ###
#####

library(GenomicRanges)
library(GenomicFeatures)
library(GenomicAlignments)

hse <- makeTranscriptDbFromBiomart(
  biomart="ensembl", dataset="hsapiens_gene_ensembl" )

bamDir <- system.file(
  "extdata", package="parathyroidSE", mustWork=TRUE )
fls <- list.files( bamDir, pattern="bam$", full=TRUE )

bamlst <- BamFileList(
  fls, index=character(),
  yieldSize=100000, obeyQname=TRUE )

exonicParts <- disjointExons( hse, aggregateGenes=FALSE )

SE <- summarizeOverlaps( exonicParts, bamlst,
  mode="Union", singleEnd=FALSE,
  ignore.strand=TRUE, inter.feature=FALSE, fragments=TRUE )

colData(SE)$condition <- c("A", "A", "B")

DEXSeqDataSetFromSE( SE,
  design= ~ sample + exon + condition:exon )

#####
### From elementary data structures ###
#####
countData <- matrix( rpois(10000, 100), nrow=1000 )
sampleData <- data.frame(
  condition=rep( c("untreated", "treated"), each=5 ) )
design <- formula( ~ sample + exon + condition:exon )
groupID <- rep(
  sprintf("gene
  each= 100 )
featureID <- rep(
  sprintf("exon
  times= 100 )
DEXSeqDataSet( countData, sampleData, design,
  featureID, groupID )

## End(Not run)

```

---

 DEXSeqHTML

*DEXSeq HTML report writer*


---

## Description

This function generates an HTML report from the results of a DEXSeqResults object. Gives an simple report to explore differential exon usage results.

## Usage

```
DEXSeqHTML(object, genes=NULL, path="DEXSeqReport", file="testForDEU.html",
  fitExpToVar="condition", FDR=0.1, color=NULL, color.samples=NULL,
  mart="", filter="", attributes="", extraCols=NULL, BPPARAM=MulticoreParam(workers=1))
```

## Arguments

object	An DEXSeqResults object
genes	A character vector of gene identifiers to be included in the report. If NULL, the genes included in the report will be the significant hits at the given false discovery rate. See "FDR" below.
path	A path in the system where to write the report.
file	The name of the html file.
fitExpToVar	A variable contained in the design of the ecs; the counts will be fitted to this variable to get the plotting values.
FDR	A false discovery rate
color	A vector of colors, one for each of the levels of the values of "fitExpToVar".
color.samples	A vector of colors for each of the samples. If NULL, the colors of each sample will be assigned according to its corresponding condition. Useful to visualize complex experimental designs.
mart	object of class Mart, created with the useMart function, with dataset specified
filter	Filters (ONLY ONE) that should be used in the query. A possible list of filters can be retrieved using the function listFilters. Please note that the value of this filter will always be the geneIDs in the DEXSeqResults object.
attributes	Attributes you want to retrieve. A possible list of attributes can be retrieved using the biomaRt function listAttributes.
extraCols	A data frame with one or more columns to add to the report. For example, additional information about the genes. The data frame should be indexed by the gene names of the ExonCountSet object, e.g. the rownames of the data frame should correspond to the gene names.
BPPARAM	A 'BiocParallelParam' instance. See ?bplapply for details.



**Value**

This function will write an HTML report in the directory specified by 'path'. There, it will create an html file with the initial report page and a directory called "files" in which SVG files with the plots and other html files are placed. Different plots with different labels are generated for each gene:

- counts: the raw data, for each sample
- fitted expression: the fitted coefficients per compared condition (e.g.: treated, untreated)
- fitted splicing: as 'expression', but after removing overall gene-level differential expression: this is the view most relevant for the interpretation of DEXSeq results, which are about changes in relative exon usage (i.e.: relative to overall gene expression)

**Examples**

```
## Not run:
data(pasillaDEXSeqDataSet, package="pasilla")
dxr <- DEXSeq( dxd )
DEXSeqHTML( object=dxr )

## End(Not run)
```

---

DEXSeqResults-class    *DEXSeqResults* object

---

**Description**

The DEXSeqResults object is a subclass of a DataFrame. It collects relevant information from a DEXSeqDataSet object with the results generated from testing for differences in exon usage.

**Usage**

```
DEXSeqResults( object )
```

**Arguments**

object            A DEXSeqDataSet object.

**Value**

A DEXSeqResults object.

**Examples**

```
data(pasillaDEXSeqDataSet, package="pasilla")
dxd <- estimateSizeFactors( dxd )
dxd <- estimateDispersions( dxd )
dxd <- testForDEU( dxd )
dxr <- DEXSeqResults( dxd )
```

---

estimateDispersions     *Estimate the dispersions for a DEXSeqDataSet*

---

## Description

This function obtains dispersion estimates for negative binomial distributed data for the specific case for DEXSeq.

## Usage

```
## S4 method for signature DEXSeqDataSet
estimateDispersions( object, fitType=c("parametric","local","mean"),maxit=100, quiet=FALSE, formula=
```

## Arguments

object	A DEXSeqDataSet
fitType	Either "parametric", "local", or "mean" for the type of fitting of dispersions to the mean intensity. See ?estimateDispersions,DESeqDataSet-method for details.
maxit	Control parameter: maximum number of iterations to allow for convergence
quiet	Whether to print messages at each step
formula	Formula used to fit the dispersion estimates
BPPARAM	A "BiocParallelParam" instance. See ?bplapply for details.

## Details

See ?estimateDispersions,DESeqDataSet-method for details.

## Value

A DEXSeqDataSet with the dispersion information filled in as metadata columns.

## Examples

```
data(pasillaDEXSeqDataSet, package="pasilla")
dxd <- estimateSizeFactors( dxd )
dxd <- estimateDispersions( dxd )
```

---

`estimateExonFoldChanges`*Estimates exon usage coefficients from the fitted terms of the GLM.*

---

## Description

This function calculates the exon usage coefficients and fold changes (on log<sub>2</sub> scale) between the different conditions.

## Usage

```
estimateExonFoldChanges( object,  
  fitExpToVar = "condition", denominator = "",  
  BPPARAM=MulticoreParam(workers=1))
```

## Arguments

<code>object</code>	An DEXSeqDataSet object.
<code>fitExpToVar</code>	A variable contained in <code>design(ecs)</code> . The expression values will be fitted to this variable using the the formula " <code>~ sample + fitExpToVar * exon</code> ".
<code>denominator</code>	A value of the sample annotation (e.g. <code>condition</code> ) to use as a denominator in the log <sub>2</sub> fold change. As a default, the function will take the annotation of the first sample.
<code>BPPARAM</code>	A "BiocParallelParam" instance. See <code>?bplapply</code> for details.

## Details

Exon usage coefficients are calculated by fitting a GLM from the joint data of all exons of the same gene. The model frame can be found in the slot `object@modelFrameBM` of a DEXSeqDataSet object. The model '`~ sample + fitExpToVar * exon`' is fitted. The resulted coefficients are arranged and reformatted in order to remove gene expression effects (absorbed by the 'sample' variable in the formula), leaving only exon usage effects for each individual exon in each level of 'fitExpToVar'. These values are used by the function `plotDEXSeq`.

## Examples

```
data(pasillaDEXSeqDataSet, package="pasilla")  
dxd <- estimateSizeFactors( dxd )  
dxd <- estimateDispersions( dxd )  
dxd <- testForDEU( dxd )  
dxd <- estimateExonFoldChanges( dxd )
```

---

estimateSizeFactors     *Estimate the size factors for a DEXSeqDataSet*

---

### Description

Estimate the size factors for a DEXSeqDataSet

### Usage

```
## S4 method for signature DEXSeqDataSet
estimateSizeFactors(object, locfunc=median, geoMeans)
```

### Arguments

object	a DEXSeqDataSet
locfunc	a function to compute a location for a sample. By default, the median is used. However, especially for low counts, the <code>shorth</code> function from the <code>genefilter</code> package may give better results.
geoMeans	by default this is not provided and the geometric means of the counts are calculated within the function. A vector of geometric means from another count matrix can be provided for a "frozen" size factor calculation

### Details

This function calls the method `estimateSizeFactors` for the `DESeqDataSet` object, and adapts it to the specific use to the `DEXSeqDataSet`.

### Value

The `DEXSeqDataSet` passed as parameters, with the size factors filled in.

### References

- Simon Anders, Wolfgang Huber: Differential expression analysis for sequence count data. *Genome Biology* 11 (2010) R106, <http://dx.doi.org/10.1186/gb-2010-11-10-r106>

---

ExonCountSet-class     *This class has been deprecated and will become defunct.*

---

### Description

The `ExonCountSet` object has been deprecated and substituted by the `DEXSeqDataSet` object. Therefore, all the functions and methods for the `ExonCountSet` object will be deprecated and defunct at the next releases. These functions have been substituted by new functions that are compatible with the newer versions of `DEXSeq`.

---

 ExonCountSet-deprecated,methods

*Deprecated methods for ExonCountSet object*


---

### Description

The ExonCountSet object has been deprecated and substituted by the DEXSeqDataSet object. Therefore, all the functions and methods for the ExonCountSet object will be deprecated and defunct at the next releases. These functions have been substituted by new functions that are compatible with the newer versions of DEXSeq.

### Details

The replacements of deprecated function are summarized in the following items.

- plotDispEsts,ExonCountSet: plotDispEsts,DESeqDataSet
- plotMA-ExonCountSet: plotMA-DESeqDataSet and plotMA-DESeqResults
- counts-ExonCountSet: counts-DESeqDataSet, featureCounts-DEXSeqDataSet, counts-DEXSeqResults
- sizeFactors-ExonCountSet: sizeFactors-DESeqDataSet
- design-ExonCountSet: sampleAnnotation-DEXSeqDataSet
- estimateSizeFactors-ExonCountSet: estimateSizeFactors-DEXSeqDataSet
- estimateDispersions-ExonCountSet: estimateDispersions-DEXSeqDataSet

---

 featureCounts

*Accessor functions for DEXSeqDataSet details*


---

### Description

Accessor functions of the DEXSeqDataSet object.

### Usage

```
featureCounts(object, normalized=FALSE)
```

```
featureIDs( object )
featureIDs( object ) <- value
```

```
exonIDs( object )
exonIDs( object ) <- value
```

```
groupIDs( object )
groupIDs( object ) <- value
```

```
geneIDs( object )
geneIDs( object ) <- value

sampleAnnotation( object )
```

### Arguments

object	An DEXSeqDataSet object.
value	A character vector to replace previous values.
normalized	Logical indicating whether or not to divide the counts by the size factors or normalization factors before returning (normalization factors always preempt size factors)

### Value

'featureCounts' access the counts per exonic region or feature region names. 'featureIDs' and 'exonIDs' are accessor functions for the exon bin or features identifiers. 'groupIDs' and 'geneIDs' are accessor functions for the character vector grouping the features, for example exonIDs from the same gene are grouped together by having the same value in the geneIDs. 'sampleAnnotation' is an accessor for the information from the samples.

### Examples

```
data(pasillaDEXSeqDataSet, package="pasilla")
head( featureCounts( dxd ) )
head( featureIDs(dxd))
head( exonIDs(dxd))
```

---

findOverlaps

*Methods from GRanges overlaps for the DEXSeq object*

---

### Description

This function generates an MA plot.

### Usage

```
## S4 method for signature DEXSeqResults,GenomicRanges
subsetByOverlaps( query, subject, maxgap = 0L,
  minoverlap = 1L, type = c("any", "start", "end", "within", "equal"), ignore.strand = FALSE )

## S4 method for signature DEXSeqResults,GenomicRanges
findOverlaps( query, subject, maxgap = 0L,
  minoverlap = 1L, type = c("any", "start", "end", "within", "equal"), ignore.strand = FALSE )
```

**Arguments**

**query** Either a DEXSeqResults object.  
**subject** A GRanges or GRangesList object.  
**maxgap, minoverlap, type** See [findOverlaps](#) in the IRanges package for a description of these arguments.  
**ignore.strand** See [findOverlaps](#) in the GenomicRanges package for a description of this.

**Examples**

```

data(pasillaDEXSeqDataSet, package="pasilla")
dxd <- estimateSizeFactors( dxd )
dxd <- estimateDispersions( dxd )
dxd <- testForDEU( dxd )
dxr <- DEXSeqResults( dxd )

interestingRegion = GRanges("chr2L", IRanges(start=3872658, end=3875302))

subsetByOverlaps( query=dxr, subject=interestingRegion )
findOverlaps( query=dxr, subject=interestingRegion )

```

---

perGeneQValue      *Summarize per-exon p-values into per-gene q-values.*

---

**Description**

The use case for this function is the following analysis: given per-exon p-values for null hypothesis  $H_0$ , we can determine the number of genes in which at least for one exon  $H_0$  is rejected. What is the associated false discovery rate?

**Usage**

```
perGeneQValue(object, p = "pvalue", method = perGeneQValueExact)
```

**Arguments**

**object** An DEXSeqResults object.  
**p** A character string indicating the name of the columns in DEXSeqResults from which to take the per-exon p-values.  
**method** Use the default value. This is for debugging only.

**Details**

Details

**Value**

A named numeric vector, values are per-gene q-values, names are gene.

**Examples**

```
data(pasillaDEXSeqDataSet, package="pasilla")
dxd <- estimateSizeFactors( dxd )
dxd <- estimateDispersions( dxd )
dxd <- testForDEU( dxd )
dxr <- DEXSeqResults( dxd )

perGeneQValue(dxr)
```

---

plotDEXSeq

*Visualization of the per gene DEXSeq results.*


---

**Description**

The function provides a plot to visualize read count data, expression and exon usage coefficients estimated from fitting a GLM model 'counts ~ fitExpToVar \* exon'. The model frame used can be found in `object@modelFrameBM`. One GLM is fitted for each gene.

**Usage**

```
plotDEXSeq(object, geneID, FDR=0.1, fitExpToVar="condition",
  norCounts=FALSE, expression=TRUE, splicing=FALSE,
  displayTranscripts=FALSE, names=FALSE, legend=FALSE,
  color=NULL, color.samples=NULL, ...)
```

**Arguments**

<code>object</code>	An DEXSeqResults object.
<code>geneID</code>	Gene identifier to visualize.
<code>FDR</code>	A false discovery rate.
<code>fitExpToVar</code>	A variable contained in the sample annotation of the DEXSeqDataSet, the expression values will be fitted to this variable using the formula <code>count ~ fitExpToVar * exon</code> .
<code>norCounts</code>	If TRUE, provides a plot of the counts normalized by the size factors.
<code>expression</code>	If TRUE, the function plots the fitted EXPRESSION estimates from the glm regression.
<code>splicing</code>	If TRUE, the samples gene expression effects are averaged out, leaving only exon usage coefficients.
<code>displayTranscripts</code>	If TRUE, the transcripts are displayed in the plot.



names	If TRUE, the names of the transcripts are shown.
legend	If TRUE, a legend is displayed.
color	A vector of colors for each of the levels of the factor in the design of the Exon-CountSet object indicated by "fitExpToVar".
color.samples	A vector of colors for each of the samples. If NULL, the colors of each sample will be assigned according to its corresponding level from "fitExpToVar". This option is useful to visualize complex experimental designs.
...	Further graphical parameters (see par).

**See Also**

graphics, segments

**Examples**

```
## Not run:
data(pasillaDEXSeqDataSet, package="pasilla")
dxd <- estimateSizeFactors( dxd )
dxd <- estimateDispersions( dxd )
dxd <- testForDEU( dxd )
dxr <- DEXSeqResults( dxd )

plotDEXSeq( dxr, "FBgn0010909" )

## End(Not run)
```

---

plotDispEsts	<i>Plot dispersion estimates</i>
--------------	----------------------------------

---

**Description**

A simple helper function that plots the per-gene dispersion estimates together with the fitted mean-dispersion relationship. Internally, it is a wrapper for the plotDispEsts method from DESeq2.

**Usage**

```
## S4 method for signature DEXSeqDataSet
plotDispEsts(object, ymin,
             genecol = "black", fitcol = "red", finalcol = "dodgerblue",
             legend=TRUE, xlab, ylab, log = "xy", cex = 0.45, ...)
```

**Arguments**

object	a DESeqDataSet
ymin	the lower bound for points on the plot, points beyond this are drawn as triangles at ymin
genecol	the color for gene-wise dispersion estimates

fitcol	the color of the fitted estimates
finalcol	the color of the final estimates used for testing
legend	logical, whether to draw a legend
xlab	xlab
ylab	ylab
log	log
cex	cex
...	further arguments to plot

---

plotMA-methods      *Generate an MA plot*

---

### Description

This function generates an MA plot.

### Usage

```
## S4 method for signature DEXSeqDataSet
plotMA( object, alpha=0.1, ylim=c(-2, 2), foldChangeColumn=NULL, ... )

## S4 method for signature DEXSeqResults
plotMA( object, alpha=0.1, ylim=c(-2, 2), foldChangeColumn=NULL, ... )
```

### Arguments

object	Either a DEXSeqDataSet or a DEXSeqResults.
alpha	the false discovery rate, i.e., threshold to the adjusted p values, to be used to colour the dots
ylim	y-limits of the plot
foldChangeColumn	Name of the column containing the fold changes to plot. If NULL, the first fold change column from the object will be taken.
...	Further parameters to be passed through to <a href="#">plot</a> .

**Examples**

```
## Not run:
data(pasillaDEXSeqDataSet, package="pasilla")
dxd <- estimateSizeFactors( dxd )
dxd <- estimateDispersions( dxd )
dxd <- testForDEU( dxd )
dxd <- estimateExonFoldChanges( dxd )
dxr <- DEXSeqResults( dxd )

plotMA( dxr )

plotMA( dxd )

## End(Not run)
```

---

testForDEU	<i>Test for Differential Exon Usage.</i>
------------	--

---

**Description**

This will perform a likelihood ratio test for differential exon usage. Internally, it calls the DESeq2 function `nbinomLRT`.

**Usage**

```
testForDEU( object,
  fullModel = design(object),
  reducedModel = ~ sample + exon,
  BPPARAM=MulticoreParam(workers=1) )
```

**Arguments**

object	A DEXSeqDataSet object.
fullModel	The full model formula
reducedModel	Null model formula.
BPPARAM	A "BiocParallelParam" instance. See <code>?bplapply</code> for details.

**Details**

The information of the variables of the formulas should be present in the `colData` of the `DEXSeqDataSet` object.

**Value**

A `DEXSeqDataSet` with slots filled with information about the test.

**Examples**

```
data(pasillaDEXSeqDataSet, package="pasilla")
dxd <- estimateSizeFactors( dxd )
dxd <- estimateDispersions( dxd )
dxd <- testForDEU( dxd )
```

# Index

buildExonCountSet (DEXSeq-deprecated), 4  
buildExonCountSet-deprecated  
(DEXSeq-deprecated), 4

constructModelFrame  
(DEXSeq-deprecated), 4  
constructModelFrame-deprecated  
(DEXSeq-deprecated), 4  
countReadsForDEXSeq (DEXSeq-defunct), 3  
countReadsForDEXSeq-defunct  
(DEXSeq-defunct), 3  
counts, 2  
counts, DEXSeqResults-method (counts), 2  
counts, ExonCountSet-method (counts), 2  
counts, ExonCountSet-method, deprecated  
(counts), 2  
countTableForGene (DEXSeq-deprecated), 4  
countTableForGene-deprecated  
(DEXSeq-deprecated), 4

design, ExonCountSet  
(DEXSeq-deprecated), 4  
design, ExonCountSet-deprecated  
(DEXSeq-deprecated), 4  
DEUresultTable (DEXSeq-deprecated), 4  
DEUresultTable-deprecated  
(DEXSeq-deprecated), 4  
DEXSeq, 3  
DEXSeq-defunct, 3  
DEXSeq-deprecated, 4  
DEXSeqDataSet (DEXSeqDataSet-class), 5  
DEXSeqDataSet-class, 5  
DEXSeqDataSetFromHTSeq  
(DEXSeqDataSet-class), 5  
DEXSeqDataSetFromSE  
(DEXSeqDataSet-class), 5  
DEXSeqHTML, 8  
DEXSeqResults (DEXSeqResults-class), 9  
DEXSeqResults-class, 9

doCompleteDEUAnalysis  
(DEXSeq-deprecated), 4  
doCompleteDEUAnalysis-deprecated  
(DEXSeq-deprecated), 4

estimateDispersions, 10  
estimateDispersions, DEXSeqDataSet-method  
(estimateDispersions), 10  
estimateDispersions, ExonCountSet-method  
(estimateDispersions), 10  
estimateDispersions, ExonCountSet-method-deprecated  
(estimateDispersions), 10  
estimateDispersions\_BM  
(DEXSeq-deprecated), 4  
estimateDispersions\_BM-deprecated  
(DEXSeq-deprecated), 4  
estimateExonDispersion  
(DEXSeq-deprecated), 4  
estimateExonDispersion-deprecated  
(DEXSeq-deprecated), 4  
estimateExonDispersionsForModelFrame\_BM  
(DEXSeq-deprecated), 4  
estimateExonDispersionsForModelFrame\_BM-deprecated  
(DEXSeq-deprecated), 4  
estimateExonFoldChanges, 11  
estimateLog2FoldChanges  
(DEXSeq-deprecated), 4  
estimateLog2FoldChanges-deprecated  
(DEXSeq-deprecated), 4  
estimateSizeFactors, 12  
estimateSizeFactors, DEXSeqDataSet-method  
(estimateSizeFactors), 12  
estimateSizeFactors, ExonCountSet-method  
(estimateSizeFactors), 12  
estimateSizeFactors, ExonCountSet-method, deprecated  
(estimateSizeFactors), 12  
ExonCountSet (ExonCountSet-class), 12  
ExonCountSet-class, 12  
ExonCountSet-deprecated, methods, 13  
exonIDs (featureCounts), 13

- exonIDs<- (featureCounts), 13
- featureCounts, 13
- featureIDs (featureCounts), 13
- featureIDs<- (featureCounts), 13
- findOverlaps, 14, 15
- findOverlaps,DEXSeqResults,GenomicRanges-method (findOverlaps), 14
- findOverlaps-methods (findOverlaps), 14
- fitDispersionFunction (DEXSeq-deprecated), 4
- fitDispersionFunction-deprecated (DEXSeq-deprecated), 4
- geneCountTable (DEXSeq-deprecated), 4
- geneCountTable-deprecated (DEXSeq-deprecated), 4
- geneIDs (featureCounts), 13
- geneIDs<- (featureCounts), 13
- getCountVector (DEXSeq-deprecated), 4
- getCountVector-deprecated (DEXSeq-deprecated), 4
- groupIDs (featureCounts), 13
- groupIDs<- (featureCounts), 13
- makeCompleteDEUAnalysis\_BM (DEXSeq-deprecated), 4
- makeCompleteDEUAnalysis\_BM-deprecated (DEXSeq-deprecated), 4
- modelFrameForGene (DEXSeq-deprecated), 4
- modelFrameForGene-deprecated (DEXSeq-deprecated), 4
- newExonCountSet (DEXSeq-deprecated), 4
- newExonCountSet-deprecated (DEXSeq-deprecated), 4
- perGeneQValue, 15
- plot, 18
- plotDEXSeq, 16
- plotDispEsts, 17
- plotDispEsts,DEXSeqDataSet-method (plotDispEsts), 17
- plotDispEsts,ExonCountSet-method (ExonCountSet-deprecated,methods), 13
- plotDispEsts,ExonCountSet-method,deprecated (ExonCountSet-deprecated,methods), 13
- plotMA (plotMA-methods), 18
- plotMA,DEXSeqDataSet-method (plotMA-methods), 18
- plotMA,DEXSeqResults-method (plotMA-methods), 18
- plotMA,ExonCountSet (ExonCountSet-deprecated,methods), 13
- plotMA,ExonCountSet-deprecated (ExonCountSet-deprecated,methods), 13
- plotMA,ExonCountSet-method (plotMA-methods), 18
- plotMA,ExonCountSet-method,deprecated (plotMA-methods), 18
- plotMA-methods, 18
- prepareAnnotationForDEXSeq (DEXSeq-defunct), 3
- prepareAnnotationForDEXSeq-defunct (DEXSeq-defunct), 3
- read.HTSeqCounts (DEXSeq-deprecated), 4
- read.HTSeqCounts-deprecated (DEXSeq-deprecated), 4
- sampleAnnotation (featureCounts), 13
- shorth, 12
- sizeFactors,ExonCountSet-method (ExonCountSet-deprecated,methods), 13
- sizeFactors,ExonCountSet-method,deprecated (ExonCountSet-deprecated,methods), 13
- subsetByGenes (DEXSeq-deprecated), 4
- subsetByGenes-deprecated (DEXSeq-deprecated), 4
- subsetByOverlaps (findOverlaps), 14
- subsetByOverlaps,DEXSeqResults,GenomicRanges-method (findOverlaps), 14
- subsetByOverlaps-methods (findOverlaps), 14
- testExonForDEU (DEXSeq-deprecated), 4
- testExonForDEU-deprecated (DEXSeq-deprecated), 4
- testForDEU, 19
- testForDEU\_BM (DEXSeq-deprecated), 4
- testForDEU\_BM-deprecated (DEXSeq-deprecated), 4

testGeneForDEU\_BM (DEXSeq-deprecated), [4](#)  
testGeneForDEU\_BM-deprecated  
(DEXSeq-deprecated), [4](#)