

# arrayMvout

April 19, 2009

---

ArrayOutliers-methods

*ArrayOutliers – wrapper for platform-specific multivariate outlier detection for expression arrays*

---

## Description

wraps functions that perform multivariate outlier detection on dimension-reduced QA statistics of expression arrays

## Methods

**data = "ANY", alpha = "missing", alphaSeq = "missing"** fails; tells user that alpha is obligatory parameter

**data = "AffyBatch", alpha = "numeric", alphaSeq = "ANY"** performs calibrated multivariate outlier detection on an AffyBatch instance using various affy-specific QA parameters

**data = "LumiBatch", alpha = "numeric", alphaSeq = "ANY"** performs calibrated multivariate outlier detection on an LumiBatch instance using various illumina-specific QA parameters

**data = "data.frame", alpha = "numeric", alphaSeq = "ANY"** performs calibrated outlier detection on QA statistics housed in data.frame – all columns of the data entity must be numeric QA statistics for the arrays.

## Examples

```
example(ArrayOutliers)
```

---

ArrayOutliers

*Multivariate outlier detection based on PCA of QA statistics*

---

## Description

Multivariate outlier detection based on PCA of QA statistics

**Usage**

```
ArrayOutliers (data, alpha, alphaSeq = c(0.01, 0.05, 0.1), ... )
#   qcOutput = NULL, plmOutput = NULL, degOutput = NULL, prscale = TRUE,
#   pc2use = 1:3)
```

**Arguments**

<code>data</code>	an (affy) AffyBatch instance with at least 11 samples
<code>alpha</code>	false positive rate for outlier detection, adjusting for multiple comparisons according to Caroni and Prescott's adaptation of Rosner (1983); full report based on this choice of alpha
<code>alphaSeq</code>	vector of alpha candidates to be quickly tried for short report
<code>...</code>	additional parameters, see below

**Details**

Additional parameters may be supplied

**qcOutput** optional result of simpleaffy qc() to speed computations

**plmOutput** optional result of affyPLM fitPLM() to speed computations

**degOutput** optional result of affy AffyRNAdeg() to speed computations

**prscale** scaling option for precomp

**pc2use** selection of principal components to use for outlier detection

Data elements afxsubDEG, afxsubQC, s12cDEG, s12cQC are precomputed RNA degradation and simpleaffy qc() results; s12c is an AffyBatch with digital contamination of some samples.

Data elements maqcQA and itnQA are affymetrix QC statistics on large collections of arrays. Data element ilmQA is a derived from a LumiBatch of the Illumina-submitted MAQC raw data, 19 arrays. (Conveyed by Leming Shi, personal communication). Data element spikQA is a 12x9 matrix of QA parameters obtained for 12 arrays from U133A spikein dataset, with first 2 arrays digitally contaminated as described in Asare et al.

Data element fig3map gives the indices of the points labeled A-H in Figure 3 of the manuscript by Asare et al. associated with this package.

**Value**

an instance of arrOutStruct class, a list with a partition of samples into two data frames (inl and outl) with QA summary statistics

**Author(s)**

Z. Gao et al.

**Examples**

```
library(simpleaffy)
setQCEnvironment("hgu133acdf") # no CDF corresponding to tag array
if ( require("mvoutData") ) {
  data(s12c)
  data(s12cQC)
  data(s12cDEG)
```

```

library(affyPLM)
s12cPset = fitPLM(s12c)
ao = ArrayOutliers(s12c, alpha=0.05, qcOut=s12cQC, plmOut=s12cPset, degOut=s12cDEG)
ao
}
if (require("lumiBarnes")) {
  library(lumiBarnes)
  data(lumiBarnes)
  ArrayOutliers(lumiBarnes, alpha=0.05)
  lb2 = lumiBarnes
  exprs(lb2)[1:20000,1:2] = 10000*exprs(lb2)[1:20000,1:2]
  ArrayOutliers(lb2, alpha=0.05)
}
data(maqcQA) # affy
ArrayOutliers(maqcQA[, -c(1:2)], alpha=.05)
ArrayOutliers(maqcQA[, -c(1:2)], alpha=.01)
data(ilmQA) # illumina
ArrayOutliers(data.frame(ilmQA), alpha=.01)
data(itnQA) # 507 arrays from ITN
ArrayOutliers(itnQA, alpha=.01)

```

---

arrOutStruct-class *Class "arrOutStruct" container for ArrayOutliers output*

---

## Description

Class "arrOutStruct" container for ArrayOutliers output

## Objects from the Class

Objects can be created by calls of the form `new("arrOutStruct", ...)`. This class just extends `list` but has specialized `show` and `plot` methods.

## Extends

Class "`list`", from data part. Class "`vector`", by class "list", distance 2. Class [AssayData](#), by class "list", distance 2.

## Methods

**plot** signature(x = "arrOutStruct", y = "ANY"): a biplot of QA statistics

**show** signature(object = "arrOutStruct"): summary report

## Author(s)

Vince Carey <stvjc@channing.harvard.edu>

## Examples

```

data(maqcQA)
f1 = ArrayOutliers(maqcQA[, -c(1:2)], alpha=0.01)
names(f1)
f1

```

# Index

## \*Topic classes

arrOutStruct-class, 3

## \*Topic methods

ArrayOutliers-methods, 1

## \*Topic models

ArrayOutliers, 1

afxsubDEG (*ArrayOutliers*), 1

afxsubQC (*ArrayOutliers*), 1

ArrayOutliers, 1

ArrayOutliers, AffyBatch, numeric, ANY-method  
(*ArrayOutliers-methods*), 1

ArrayOutliers, ANY, missing, missing-method  
(*ArrayOutliers-methods*), 1

ArrayOutliers, data.frame, numeric, ANY-method  
(*ArrayOutliers-methods*), 1

ArrayOutliers, LumiBatch, numeric, ANY-method  
(*ArrayOutliers-methods*), 1

ArrayOutliers-methods, 1

arrOutStruct-class, 3

AssayData, 3

fig3map (*ArrayOutliers*), 1

ILM1 (*ArrayOutliers*), 1

ilmQA (*ArrayOutliers*), 1

itnQA (*ArrayOutliers*), 1

list, 3

maqQA (*ArrayOutliers*), 1

plot, arrOutStruct, ANY-method  
(*arrOutStruct-class*), 3

s12c (*ArrayOutliers*), 1

s12cDEG (*ArrayOutliers*), 1

s12cQC (*ArrayOutliers*), 1

show, arrOutStruct-method  
(*arrOutStruct-class*), 3

spikQA (*ArrayOutliers*), 1

vector, 3