

quantsmooth

November 11, 2009

R topics documented:

Chromosome14	1
drawSimpleChrom	2
helperFunctions	3
getChangedRegions	3
getLambdaMin	4
grid.chromosome	5
lengthChromosome	6
numericCHR	7
paintCytobands	8
plotChromosome	9
plotSmoothed	10
position2Cytoband	11
prepareGenomePlot	12
quantsmooth.cv	13
quantsmooth	14
quantsmooth.seg	14
scaleto	15
Index	16

Chromosome14 *Example data from several quantitative genomic methods*

Description

A collection of arrays that contains data of chromosome 14 of 3 colorectal tumors. The first tumor shows 1 region of loss, the second tumor shows no aberration, while the third tumor shows loss of 1 copy of the chromosome.

affy.cn Copy number values of 358 probes from Affymetrix 10K genechip. Data was obtained from DChip

affy.pos corresponding probe positions

bac.cn Copy number values of 112 probes from a 1 mb spaced BAC array-CGH

bac.pos corresponding probe positions

ill.cn Copy number values of 207 probes from Illumina GoldenGate Linkage IV data

ill.pos corresponding probe positions

Usage

```
data(chr14)
```

Format

Matrices of copy number values and vectors of chromosomal probe positions

Author(s)

Jan Oosting

```
drawSimpleChrom Draw chromosome-like icons
```

Description

This function paints chromosomal icons on an existing plot

Usage

```
drawSimpleChrom(x, y, len = 3, width = 1, fill, col, orientation = c("h", "v"),
```

Arguments

x	start x-position
y	start y-position
len	total length of the chromosome
width	width of the chromosome
fill	character, {"a","p","q","q[1-3]","p[1-3]"}. Events to a chromosome can be depicted by coloring "a"ll of the chromosome, the complete p or q-arm, or a sub-segment of the arms
col	color(s) of fill
orientation	either "h"orizontal or "v"ertical
centromere.size	The size of the centromere as fraction of the width

Value

This function is executed for its side effects

Author(s)

Jan Oosting

Examples

```
plot(c(0,4),c(0,3),type="n",xaxt="n",yaxt="n",xlab="",ylab="")
drawSimpleChrom(2,3,fill=c("p","q3"),col=c("red","blue"),orientation="v")
```

helperFunctions *arraysmooth Helper functions*

Description

quantsmooth Helper functions

Usage

```
getChangedIdx(changed, up)
```

Arguments

changed

up

Details

Should not be called directly

Value

A data.frame with 3 columns is returned. Each row contains a region with columns `up`, `start` and `end`. `start` and `end` indicate positions in the vector of the first and last position that were up- or downregulated

Author(s)

Jan Oosting

getChangedRegions *getChangedRegions*

Description

retrieve regions of interest in a vector of intensities using quantile smoothing

Usage

```
getChangedRegions(intensities, positions, normalized.to=1, interval, threshold)
```

Arguments

<code>intensities</code>	numeric vector
<code>positions</code>	numeric vector of the same length as <code>intensities</code> . If this argument is not given the results contain the indexes of the <code>intensities</code> vector, else the values in <code>positions</code> are used. Both vectors are sorted in the order of <code>positions</code> .
<code>normalized.to</code>	numeric, reference value. Changes are compared to this value
<code>interval</code>	numeric [0,1], bandwidth around reference. If the smoothed line at the higher quantile drops below the <code>normalized.to</code> value, a deleted region is recognized, and vice versa.
<code>threshold</code>	numeric, if the median smoothed value drops below <code>normalized.to - threshold</code> , or above <code>normalized.to + threshold</code> a changed region is called
<code>minlength</code>	integer, not used currently
<code>...</code>	extra arguments for <code>quantsmooth</code> function

Details

This function uses `quantsmooth` to detect regions in the genome that are abnormal. If `interval` is set then a smoothed line is calculated for $\tau = 0.5 - \text{interval}/2$, and a region is determined as upregulated if this line is above the reference. Down regulation is determined when the smoothed line for $\tau = 0.5 + \text{interval}/2$ is below the reference value. If `threshold` is set then a smoothed line is calculated for $\tau = 0.5$ and up- or down regulation are determined when this line is outside the range `[normalized.t - threshold:normalized.to + threshold]`

Value

A data.frame with 3 columns is returned. Each row contains a region with columns `up`, `start` and `end`. `start` and `end` indicate positions in the vector of the first and last position that were up- or downregulated

Author(s)

Jan Oosting

Examples

```
data(chr14)
getChangedRegions(ill.cn[,1], ill.pos, normalized.to=2, interval=0.5)
```

```
getLambdaMin
```

```
getLambdaMin
```

Description

Test a set of smoothing parameters to find best fit to data

Usage

```
getLambdaMin(intensities, lambdas, ...)
```

Arguments

intensities numeric vector
 lambdas numeric vector; see [quantsmooth](#)
 ... extra parameters for `quantsmooth.cv`; currently only `ridge.kappa`

Details

Cross validation is performed using a set of lambda values in order to find the lambda value that shows the best fit to the data.

Value

This function returns the lambda value that has the lowest cross validation value on this dataset

Author(s)

Jan Oosting

See Also

[quantsmooth.cv](#)

Examples

```
data(chr14)
lambdas<-2^seq(from=-2,to=5,by=0.25)
getLambdaMin(bac.cn[,1],lambdas)
```

grid.chromosome *Draw a chromosome using the grid package*

Description

A chromosome is drawn including the cytobands

Usage

```
grid.chromosome(chrom, side = 1, units = c("cM", "bases", "ISCN"), chrom.width =
  bands = "major", legend = c("chrom", "band", "none"), cex.leg = 0.7
```

Arguments

chrom numeric or character, id of chromosome to plot
 side numeric [1:4], side of rectangle to draw, 4 sides, side 2 and 4 are vertical
 units character, type of unit to use
 chrom.width numeric [0,1], The width relative to the width (sides 2 and 4) or height(sides 1 and 3) of the viewport
 length.out numeric, size of native units of viewport
 bands character, draw either major or minor bands

legend	character, type of legend
cex.leg	numeric, relative size of legend text
bleach	numeric [0,1], proportion by which to bleach the chromosome
...	arguments for viewport(), especially x,y, width, and height

Details

The chromosome is drawn within a rectangle defined by x, y, width, and height, which is pushed as a viewport. The legend is drawn within the same rectangle in the space left over by chrom.width.

Value

This function is executed for its side effects

Author(s)

David L Duffy ,Jan Oosting

References

lodplot package

See Also

[paintCytobands](#)

Examples

```
grid.newpage()
grid.chromosome(1,units="bases",height=0.15)
```

lengthChromosome *Retrieve chromosomal length*

Description

Retrieve human chromosomal length from NCBI data

Usage

```
lengthChromosome(chrom, units = c("cM", "bases", "ISCN"))
```

Arguments

chrom vector of chromosomal id, 1:22,X,Y
units

Value

A vector numeric in the requested units

Author(s)

Jan Oosting

Examples

```
# Show length of chromosome 1 in several types of units
lengthChromosome(1, "cM")
lengthChromosome(1, "bases")
lengthChromosome(1, "ISCN")
```

numericCHR

Conversion of chromosome IDs between numeric and character

Description

The function converts chromosomal ids to their numeric form, and the sex chromosomes to values between 98 and 100. This simplifies sorting on chromosome ID

Usage

```
numericCHR (CHR)
characterCHR (CHR)
```

Arguments

CHR character/numeric vector for both functions the mode of the input is not forced. For numericCHR strings "X","Y" and "XY" are converted to 98,99 and 100 respectively.

Value

numericCHR returns a numeric vector of same length as CHR characterCHR returns a character vector of same length as CHR

Author(s)

Jan Oosting

Examples

```
chroms<-c("3","2","8","X","7","Y","5","1","9","10","11","12","4","6")
sort(chroms)
sort(numericCHR(chroms))
characterCHR(sort(numericCHR(chroms)))
```

paintCytobands *Paint a chromosomal idiogram*

Description

Paints a human chromosomal idiogram in an existing plot Adapted from the paint.chromosome function in the lodplot package by David L Duffy

Usage

```
paintCytobands(chrom, pos = c(0, 0), units = c("cM", "bases", "ISCN"), width = 0,
               length.out, bands = "major", orientation = c("h", "v"), legend = TRUE,
               cex.leg = 0.7, bleach = 0, ...)
```

Arguments

chrom	chromosomal id, chromosome to plot 1:22,X,Y
pos	numeric vector of length 2, position in the plot to start the plot
units	units along which to plot the chromosome
width	numeric, width of the chromosome, the chromosome is plotted between pos[2] and pos[2]-width
length.out	numeric, if given, the chromosome will have this length in the plot
bands	if not equal to "major", then also the minor bands will be plotted
orientation	chromosome is plotted either <i>Horizontally</i> to the right of the starting point or <i>Vertically</i> down from the starting point
legend	logical, if TRUE then the bandnames are plotted next to the chromosome
cex.leg	numeric, relative size of legend text
bleach	numeric [0,1], proportion by which to bleach the chromosome
...	extra parameters for plot

Value

This function is executed for its side effects

Author(s)

David L Duffy , Jan Oosting

References

lodplot package

Examples

```
plot(c(0, lengthChromosome(14, "bases")), c(-2, 2), type="n", xaxt="n", yaxt="n", xlab="", ylab="")
paintCytobands(14, units="bases")
```

plotChromosome	<i>Wrapper for plotSmoothed</i>
----------------	---------------------------------

Description

This function is a wrapper for plotSmoothed, to make data subsetting easier

Usage

```
plotChromosome(gendata, chrompos, chromosome, dataselection = NULL, ylim = NULL,
```

Arguments

gendata	numeric matrix or data.frame
chrompos	chrompos object with same number of rows as gendata
chromosome	numeric, chromosome to show
dataselection	optional, subset of samples/columns in gendata
ylim	limits for plot
normalized.to	y-value(s) for line
grid	x-value(s) for line
smooth.lambda	smoothing parameter, see quantsmooth
interval	position of extra lines besides median, see plotSmoothed
...	extra arguments for plotSmoothed

Value

The function is used for its side effects

Author(s)

Jan Oosting

See Also

[plotSmoothed](#), [quantsmooth](#)

plotSmoothed	<i>plotSmoothed</i>
--------------	---------------------

Description

Plot a smoothed line together with the original data values

Usage

```
plotSmoothed(intensities, position, ylim=NULL, ylab="intensity", xlab="position")
```

Arguments

<code>intensities</code>	numeric vector or matrix, data are plotted by column
<code>position</code>	numeric vector; the length should be the number of rows in <code>intensities</code>
<code>ylim</code>	numeric vector of length 2, limits for plot. If <code>NULL</code> then the minimal and maximal value in <code>intensities</code> is used
<code>ylab</code>	character, label for y-position
<code>xlab</code>	character, label for x-position
<code>normalized.to</code>	numeric, a line(s) is drawn at this horizontal position
<code>grid</code>	numeric, a line(s) is drawn at this vertical position
<code>smooth.lambda</code>	numeric, smoothing parameter see <code>quantsmooth</code>
<code>interval</code>	numeric (0..1), plotting of extra smoothed lines around median. With <code>interval = 0.5</code> the 0.25 and 0.75 quartiles are plotted, with <code>interval = 0.9</code> the 0.05 and 0.95 quartiles are plotted,
<code>plotnew</code>	logical, if <code>TRUE</code> a new plot is created, else the data are plotted into an existing plot
<code>cols</code>	color vector, colors for columns in <code>intensities</code>
<code>cex.pts</code>	size of the dots in the plot. Set to 0 to skip plotting the dots
<code>...</code>	extra parameters for <code>plot</code>

Details

This function plots the raw data values as dots and the median smoothed values as a continuous line. If `interval` is supplied these are plotted as lines in different line types. More than 1 interval can be given.

Value

This function is used for its side effects

Author(s)

Jan Oosting

See Also[quantsmooth](#)**Examples**

```
data(chr14)
plotSmoothed(bac.cn,bac.pos,ylim=c(1,2.5),normalized.to=2,smooth.lambda=2.5)
```

position2Cytoband *Determine cytoband position based on location of probe*

Description

Determine cytoband position based on location of probe

Usage

```
position2Cytoband(chrom, position, units = c("cM", "bases", "ISCN"), bands = c("
```

Arguments

chrom	chromosomal id, chromosome to plot 1:22,X,Y
position	numeric vector
units	character, type of positional unit
bands	character, type of cytoband

Value

Character vector with cytobands, if an illegal position was used, the value "-" is returned. All positions within a single function call should be for a single chromosome

Author(s)

Jan Oosting

See Also[lengthChromosome](#)**Examples**

```
position2Cytoband(1,c(50e6,125e6,200e6),units="bases")
position2Cytoband(1,c(50,125,200),units="cM",bands="minor")
```

```
prepareGenomePlot Set up a full genome plot
```

Description

This function starts up a plot consisting of all chromosomes of a genomen, including axes with chromosome names.

Usage

```
prepareGenomePlot(chrompos, cols = "grey50", paintCytobands = FALSE, bleach = 0,
                  sexChromosomes = FALSE, units = c("bases", "cM", "ISCN"), ...)
```

Arguments

chrompos	chrompos object, data.frame with CHR column identifying the chromosome of probes, and a MapInfo column identifying the position on the chromosome
cols	color(s) for the chromosome lines
paintCytobands	logical, use paintCytoband to plot ideograms for all chromosomes
bleach	numeric [0,1], proportion by which to bleach the ideograms
topspace	numerical, extra space on top of plot, i.e. for legends
organism	character, if given a 2 column plot is created with the chromosomes for the given species. Currently "hsa", "mmu", and "rno" are supported
sexChromosomes	logical, if TRUE then also the sex chromosomes X and Y are plotted
units	character, type of units for genomic data
...	extra arguments for plot function

Details

If organism is not supplied then a single column is plotted of the available chromosomes in chrompos\$CHR. The arguments paintCytobands, bleach, and sexChromosomes are not used in that case.

Value

A matrix with 2 columns that contain the Y and X positions for the probes on the plot

Author(s)

Jan Oosting

quantsmooth.cv *quantsmooth.cv*

Description

Cross validation of smoothing parameters

Usage

```
quantsmooth.cv(intensities, smooth.lambda=2, ridge.kappa=0)
```

Arguments

`intensities` numeric vector
`smooth.lambda`
 numeric; see [quantsmooth](#)
`ridge.kappa` fudge parameter; see [quantsmooth](#)

Details

Cross validation is performed by calculating the fit from the even indices on the odd indices and vice versa.

Value

This function returns the sum of squared differences or NA if the fitting function gave an error

Author(s)

Jan Oosting

See Also

[getLambdaMin](#)

Examples

```
data(chr14)
# A low value is indicative of a better fit to the data
quantsmooth.cv(bac.cn[,1],1)
quantsmooth.cv(bac.cn[,1],2.8)
```

quantsmooth *quantsmooth*

Description

Quantile smoothing of array data

Usage

```
quantsmooth(intensities, smooth.lambda=2, tau=0.5, ridge.kappa=0, smooth.na=TRUE)
```

Arguments

`intensities` numeric vector
`smooth.lambda` numeric
`tau` numeric [0..1], the quantile desired; see [rq.fit](#)
`ridge.kappa` fudge parameter; see details
`smooth.na` logical; handling of NA
`segment` integer, length of overlapping segments

Value

This function returns a vector of the same length as `intensities`, or a matrix if the length of `tau` is greater than 1.

Author(s)

Jan Oosting

Examples

```
data(chr14)
plot(quantsmooth(bac.cn[,1], smooth.lambda=2.8), type="l")
```

quantsmooth.seg *quantsmooth.seg*

Description

segmented Quantile smoothing of array data

Usage

```
quantsmooth.seg(y, x = 1:length(y), lambda = 2, tau = 0.5, kappa = 0, nb = leng
```

Arguments

<code>y</code>	numeric vector
<code>x</code>	numeric vector of same length as <code>y</code> . Position of values
<code>lambda</code>	numeric
<code>tau</code>	numeric [0..1], the quantile desired; see rq.fit
<code>kappa</code>	fudge parameter; see details
<code>nb</code>	integer, basis

Value

This function returns a vector of the same length as `y`

Author(s)

Jan Oosting

Examples

```
data(chr14)
plot(quantsmooth.seg(bac.cn[,1], lambda=2.8, nb=50), type="l")
```

`scaleto`*Scales data within a range to a new range*

Description

This function scales data to a new range while enforcing the boundaries. This can be helpful in preventing overlap between chromosomal plots that display multiple chromosomes in the same plot

Usage

```
scaleto(x, fromlimits = c(0, 50), tolimits = c(0.5, -0.5), adjust = TRUE)
```

Arguments

<code>x</code>	numeric
<code>fromlimits</code>	numeric vector with length 2, original range of data
<code>tolimits</code>	numeric vector with length 2, target range of data
<code>adjust</code>	logical, if TRUE then the target values are clipped to the target range

Value

numeric of same size as `x`

Author(s)

Jan Oosting

Index

- *Topic **aplot**
 - drawSimpleChrom, 2
 - grid.chromosome, 5
 - paintCytobands, 8
- *Topic **attribute**
 - getChangedRegions, 3
- *Topic **datasets**
 - Chromosome14, 1
- *Topic **data**
 - lengthChromosome, 6
- *Topic **hplot**
 - plotChromosome, 9
 - plotSmoothed, 10
 - prepareGenomePlot, 12
- *Topic **htest**
 - quantsmooth.cv, 13
- *Topic **internal**
 - helperFunctions, 3
- *Topic **manip**
 - numericCHR, 7
 - position2Cytoband, 11
 - scaleto, 15
- *Topic **smooth**
 - getLambdaMin, 4
 - quantsmooth, 14
 - quantsmooth.cv, 13
 - quantsmooth.seg, 14

affy.cn (*Chromosome14*), 1
affy.pos (*Chromosome14*), 1

bac.cn (*Chromosome14*), 1
bac.pos (*Chromosome14*), 1

characterCHR (*numericCHR*), 7
chr14 (*Chromosome14*), 1
Chromosome14, 1

drawSimpleChrom, 2

getChangedIdx (*helperFunctions*), 3
getChangedRegions, 3
getLambdaMin, 4, 13
grid.chromosome, 5

helperFunctions, 3

ill.cn (*Chromosome14*), 1
ill.pos (*Chromosome14*), 1

lengthChromosome, 6, 11

numericCHR, 7

paintCytobands, 6, 8
plotChromosome, 9
plotSmoothed, 9, 10
position2Cytoband, 11
prepareGenomePlot, 12

quantsmooth, 5, 9, 11, 13, 14
quantsmooth.cv, 5, 13
quantsmooth.seg, 14

rq.fit, 14, 15

scaleto, 15