

Mfuzz

April 19, 2010

acore

Extraction of alpha cores for soft clusters

Description

This function extracts genes forming the alpha cores of soft clusters

Usage

```
acore(eset, cl, min.acore=0.5)
```

Arguments

eset object of the class *ExpressionSet*.
cl An object of class *flcust* as produced by *mfuzz*.
min.acore minimum membership values of gene belonging to the cluster core.

Value

The function produces an list of alpha cores including genes and their membership values for the corresponding cluster.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

Examples

```
if (interactive()){  
### Data loading and pre-processing  
data(yeast) # data set includes 17 measurements  
yeastF <- filter.NA(yeast)  
yeastF <- fill.NA(yeastF)  
yeastF <- standardise(yeastF)  
  
### Soft clustering and visualisation  
cl <- mfuzz(yeastF, c=20, m=1.25)  
acore.list <- acore(yeastF, cl=cl, min.acore=0.7)  
}
```

`cselection`*Repeated soft clustering for detection of empty clusters*

Description

This function performs repeated soft clustering for a range of cluster numbers `c` and reports the number of empty clusters detected.

Usage

```
cselection(eset, m, crange=seq(4, 32, 4), repeats=5, visu=TRUE, ...)
```

Arguments

<code>eset</code>	object of class <i>ExpressionSet</i> .
<code>m</code>	value of fuzzy c-means parameter <code>m</code> .
<code>crange</code>	range of number of clusters <code>c</code> .
<code>repeats</code>	number of repeated clusterings.
<code>visu</code>	If <code>visu=TRUE</code> plot of number of empty clusters is produced.
<code>...</code>	additional arguments for underlying <code>mfuzz</code> .

Details

A soft cluster is considered as empty, if none of the genes has a corresponding membership value larger than 0.5

Value

A matrix with the number of empty clusters detected is generated.

Note

The `cselection` function may help to determine an accurate cluster number. However, it should be used with care, as the determination remains difficult especially for short time series and overlapping clusters. A better way is likely to perform clustering with a range of cluster numbers and subsequently assess their biological relevance e.g. by GO analyses.

Author(s)

Matthias E. Futschik (http://www.cbme.ualg.pt/mfutschik_cbme.html)

References

- M.E. Futschik and B. Charlisle, Noise robust clustering of gene expression time-course data, *Journal of Bioinformatics and Computational Biology*, 3 (4), 965-988, 2005
- L. Kumar and M. Futschik, *Mfuzz: a software package for soft clustering of microarray data*, *Bioinformatics*, 2(1) 5-7,2007

Examples

```

if (interactive()){
data(yeast)
# Data pre-processing
yeastF <- filter.NA(yeast)
yeastF <- fill.NA(yeastF)
yeastF <- standardise(yeastF)

#### parameter selection
# Empty clusters should not appear
cl <- mfuzz(yeastF, c=20, m=1.25)
mfuzz.plot(yeastF, cl=cl, mfrow=c(4, 5))

# Note: The following calculation might take some time

tmp <- cselection(yeastF, m=1.25, crange=seq(5, 40, 5), repeats=5, visu=TRUE)
# derivation of number of non-empty clusters (crosses) from diagonal
# line indicate appearance of empty clusters

# Empty clusters might appear
cl <- mfuzz(yeastF, c=40, m=1.25)
mfuzz.plot(yeastF, cl=cl, mfrow=c(4, 5))
}

```

fill.NA

*Replacement of missing values***Description**

Methods for replacement of missing values. Missing values should be indicated by NA in the expression matrix.

Usage

```
fill.NA(eset, mode="mean", k=10)
```

Arguments

eset	object of the class <i>ExpressionSet</i> .
mode	method for replacement of missing values: <ul style="list-style-type: none"> • <i>mean</i>- missing values will be replaced by the mean expression value of the gene, • <i>median</i>- missing values will be replaced by the median expression value of the gene, • <i>knn</i>- missing values will be replaced by the averging over the corresponding expression values of the k-nearest neighbours, • <i>knnw</i>-same replacement method as <i>knn</i>, but the expression values averaged are weighted by the distance to the corresponding neighbour
k	Number of neighbours, if one of the knn method for replacement is chosen (<i>knn</i> , <i>knnw</i>).

Value

The function produces an object of the *ExpressionSet* class with missing values replaced.

Note

The replacement methods *knn* and *knnw* can be computationally intensive for large gene expression data sets. It may be a good idea to run these methods as a ‘lunchtime’ or ‘overnight’ job.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>) and Lokesh Kumar

Examples

```
if (interactive()){
  data(yeast) # data set includes 17 measurements
  yeastF <- filter.NA(yeast)
  yeastF <- fill.NA(yeastF)
}
```

filter.NA

Filtering of genes based on number of non-available expression values.

Description

This function can be used to exclude genes with a large number of expression values not available.

Usage

```
filter.NA(eset, thres=0.25)
```

Arguments

eset	object of the class “ExpressionSet”.
thres	threshold for excluding genes. If the percentage of missing values (indicated by NA in the expression matrix) is larger than <code>thres</code> , the corresponding gene will be excluded.

Value

The function produces an object of the *ExpressionSet* class. It is the same as the input `eset` object, except for the genes excluded.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

Examples

```
if (interactive()){  
  data(yeast) # data set includes 17 measurements  
  yeastF <- filter.NA(yeast) # genes are excluded if more than 4 measurements are missing  
}
```

filter.std

Filtering of genes based on their standard deviation.

Description

This function can be used to exclude genes with low standard deviation.

Usage

```
filter.std(eset, min.std, visu=TRUE)
```

Arguments

eset	object of the class <i>ExpressionSet</i> .
min.std	threshold for minimum standard deviation. If the standard deviation of a gene's expression is smaller than <code>min.std</code> the corresponding gene will be excluded.
visu	If <code>visu</code> is set to <code>TRUE</code> , the ordered standard deviations of genes' expression values will be plotted.

Value

The function produces an object of the *ExpressionSet* class. It is the same as the input `eset` object, except for the genes excluded.

Note

As soft clustering is noise robust, pre-filtering can usually be avoided. However, if the number of genes with small expression changes is large, such pre-filtering may be necessary to reduce noise.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

Examples

```
data(yeast) # data set includes 17 measurements  
yeastF <- filter.NA(yeast) # filtering of genes based on missing values  
yeastF <- filter.std(yeastF, min.std=0.3) # filtering of genes based on standard deviation
```

kmeans2.plot *Plotting results for k-means clustering*

Description

This function visualises the clusters produced by kmeans2.

Usage

```
kmeans2.plot (eset, kl, mfrow=c (1, 1) )
```

Arguments

eset	object of the class“ExpressionSet”.
kl	list produced by kmeans2.
mfrow	determines splitting of graphic window.

Value

The function displays the temporal profiles of clusters detected by k-means.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

Examples

```
if (interactive()) {  
  data(yeast)  
  # Data pre-processing  
  yeastF <- filter.NA(yeast)  
  yeastF <- fill.NA(yeastF)  
  yeastF <- standardise(yeastF)  
  
  # K-means clustering and visualisation  
  kl <- kmeans2(yeastF, k=20)  
  kmeans2.plot(yeastF, kl=kl, mfrow=c(2, 2))  
}
```

kmeans2 *K-means clustering for gene expression data*

Description

This function is a wrapper function for `kmeans` of the `e1071` package. It performs hard clustering of genes based on their expression values using the k-means algorithm.

Usage

```
kmeans2(eset, k, iter.max=100)
```

Arguments

eset	object of the class <i>ExpressionSet</i> .
k	number of clusters.
iter.max	maximal number of iterations.

Value

An list of clustering components (see [kmeans](#)).

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

See Also

[kmeans](#)

Examples

```
if (interactive()) {
  data(yeast)
  # Data pre-processing
  yeastF <- filter.NA(yeast)
  yeastF <- fill.NA(yeastF)
  yeastF <- standardise(yeastF)

  # K-means clustering and visualisation
  k1 <- kmeans2(yeastF, k=20)
  kmeans2.plot(yeastF, k1=k1, mfrow=c(2, 2))
}
```

mfuzzColorBar *Plots a colour bar*

Description

This function produces a (separate) colour bar for graphs produced by `mfuzz.plot`

Usage

```
mfuzzColorBar(col, horizontal=FALSE, ...)
```

Arguments

col	vector of colours used. If missing, the same vector as the default vector for <code>mfuzz.plot</code> is used. If <code>col="fancy"</code> , an alternative color palette is used (see <code>mfuzz.plot2</code>).
horizontal	If <code>TRUE</code> , a horizontal colour bar is generated, otherwise a vertical one will be produced.
...	additional parameter passed to <code>maColorBar</code> (see also example in <code>mfuzz.plot2</code>)

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

See Also

[maColorBar](#)

Examples

```
if (interactive()){
  X11(w=1.5,h=5);
  par(mar=c(1,1,1,5))
  mfuzzColorBar()
  mfuzzColorBar(col="fancy",main="Membership value")
}
```

Mfuzzgui

Graphical user interface for Mfuzz package

Description

The function `Mfuzzgui` provides a graphical user interface for clustering of microarray data and visualisation of results. It is based on the functions of the `Mfuzz` package.

Usage

```
Mfuzzgui ()
```

Details

The function `Mfuzzgui` launches a graphical user interface for the *Mfuzz* package. It is based on Tk widgets using the R TclTk interface by Peter Dalgaard. It also employs some pre-made widgets from the `tkWidgets` Bioconductor-package by Jianhua Zhang for the selection of objects/files to be loaded.

`Mfuzzgui` provides a convenient interface to most functions of the `Mfuzz` package without restriction of flexibility. An exception is the batch processes such as `partcoeff` and `cselection` routines which are used for parameter selection in fuzzy c-means clustering of microarray data. These routines are not included in `Mfuzzgui`. To select various parameters, the underlying `Mfuzz` routines may be applied.

Usage of `Mfuzzgui` does not require assumes a pre-built `exprSet` object but can be used with tab-delimited text files containing the gene expression data. Note, however, that the clustering is based on the the ordering of samples (arrays) as of the columns in the expression matrix of the `exprSet` object or in the uploaded table, respectively. Also, replicated arrays in the expression matrix (or table) are treated as independent by the `mfuzz` function and, thus, should be averaged prior to clustering.

For a overview of the functionality of `Mfuzzgui`, please refer to the package vignette. For a description of the underlying functions, please refer to the `Mfuzz` package.

Value

`Mfuzzgui` returns a `tclObj` object.

Note

The newest versions of Mfuzzgui can be found at the Mfuzz webpage (<http://itb.biologie.hu-berlin.de/~futschik/software/R/Mfuzz>).

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>) and Lokesh Kumar

References

1. M.E. Futschik and B. Charlisle, Noise robust clustering of gene expression time-course data, **Journal of Bioinformatics and Computational Biology**, Vol. 3, No. 4, 965-988, 2005.
2. Cho RJ, Campbell MJ, Winzeler EA, Steinmetz L, Conway A, Wodicka L, Wolfsberg TG, Gabrielian AE, Landsman D, Lockhart DJ, Davis RW, A genome-wide transcriptional analysis of the mitotic cell cycle, **Mol Cell**,(2):65-73, 1998.
3. Mfuzz web-page: <http://itb.biologie.hu-berlin.de/~futschik/software/R/Mfuzz>

See Also

[mfuzz](#)

mfuzz.plot2

Plotting results for soft clustering with additional options

Description

This function visualises the clusters produced by mfuzz. it is similar to mfuzz.plot, but offers more options for adjusting the plots.

Usage

```
mfuzz.plot2(eset, cl, mfrow=c(1, 1), colo, min.mem=0, time.labels, x11=TRUE,
            ax.col="black", bg = "white", col.axis="black", col.lab="bl
            col.main="black", col.sub="black", col="black", cex.main=2,
            Xwidth=5, Xheight=5, single=FALSE, ...)
```

Arguments

eset	object of the class <i>ExpressionSet</i> .
cl	object of class <i>fclust</i> .
mfrow	determines splitting of graphic window. Use mfrow=NA if layout is used (see example).
colo	color palette to be used for plotting. If the color argument remains empty, the default palette is used. If the colo = "fancy", an alternative (fancier) palette will be used.
min.mem	Genes with membership values below min.mem will not be displayed.
time.labels	labels can be given for the time axis.

x11	If TRUE, a new window will be open for plotting.
ax.col	Color of axis line.
bg	Background color.
col.axis	Color for axis annotation.
col.lab	Color for axis labels.
col.main	Color for main titles.
col.sub	Color for sub-titles.
col	Default plotting color.
cex.main	Magnification to be used for main titles.
Xwidth	Width of window.
Xheight	Height of window.
single	Integer if a specific cluster is to be plotted, otherwise it should be set to FALSE.
...	Additional, optional plotting arguments passed to plot.default function.

Value

The function generates plots where the membership of genes is color-encoded.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

Examples

```

if (interactive()){
data(yeast)
# Data pre-processing
yeastF <- filter.NA(yeast)
yeastF <- fill.NA(yeastF)
yeastF <- standardise(yeastF)

# Soft clustering and visualisation
cl <- mfuzz(yeastF,c=20,m=1.25)
mfuzz.plot2(yeastF,cl=cl,mfrow=c(2,2)) # same output as mfuzz.plot

# More fancy choice of colors
mfuzz.plot2(yeastF,cl=cl,mfrow=c(2,2),colo="fancy",
ax.col="red",bg = "black",col.axis="red",col.lab="white",
col.main="green",col.sub="blue",col="blue",cex.main=2)

### Single cluster with colorbar (cluster # 3)
X11(width=12)
mat <- matrix(1:2,ncol=2,nrow=1,byrow=TRUE)
l <- layout(mat,width=c(5,1))
mfuzz.plot2(yeastF,cl=cl,mfrow=NA,colo="fancy", ax.col="red",bg = "black",col.axis="red",
col.main="green",col.sub="blue",col="blue",cex.main=2, single=3,x11=FALSE)

mfuzzColorBar(col="fancy",main="Membership",cex.main=1)
}

```

`mfuzz.plot`*Plotting results for soft clustering*

Description

This function visualises the clusters produced by `mfuzz`.

Usage

```
mfuzz.plot(eset, cl, mfrow=c(1, 1), colo, min.mem=0, time.labels, new.window=TRUE)
```

Arguments

<code>eset</code>	object of the class <i>ExpressionSet</i> .
<code>cl</code>	object of class <i>flclust</i> .
<code>mfrow</code>	determines splitting of graphic window.
<code>colo</code>	color palette to be used for plotting. If the color argument remains empty, the default palette is used.
<code>min.mem</code>	Genes with membership values below <code>min.mem</code> will not be displayed.
<code>time.labels</code>	labels can be given for the time axis.
<code>new.window</code>	should a new window be opened for graphics.

Value

The function generates plots where the membership of genes is color-encoded.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

Examples

```
if (interactive()){
  data(yeast)
  # Data pre-processing
  yeastF <- filter.NA(yeast)
  yeastF <- fill.NA(yeastF)
  yeastF <- standardise(yeastF)

  # Soft clustering and visualisation
  cl <- mfuzz(yeastF, c=20, m=1.25)
  mfuzz.plot(yeastF, cl=cl, mfrow=c(2, 2))

  # display of cluster cores with alpha = 0.5
  mfuzz.plot(yeastF, cl=cl, mfrow=c(2, 2), min.mem=0.5)

  # display of cluster cores with alpha = 0.7
  mfuzz.plot(yeastF, cl=cl, mfrow=c(2, 2), min.mem=0.7)
}
```

mfuzz

*Function for soft clustering based on fuzzy c-means.***Description**

This function is a wrapper function for `cmeans` of the `e1071` package. It performs soft clustering of genes based on their expression values using the fuzzy c-means algorithm.

Usage

```
mfuzz(eset, centers, m, ...)
```

Arguments

<code>eset</code>	object of the class “ExpressionSet”.
<code>centers</code>	number of clusters.
<code>m</code>	fuzzification parameter.
<code>...</code>	additional parameters for <code>cmeans</code> .

Details

This function is the core function for soft clustering. It groups genes based on the Euclidean distance and the c-means objective function which is a weighted square error function. Each gene is assigned a membership value between 0 and 1 for each cluster. Hence, genes can be assigned to different clusters in a gradual manner. This contrasts hard clustering where each gene can belong to a single cluster.

Value

An object of class `flcust` (see `cmeans`) which is a list with components:

<code>centers</code>	the final cluster centers.
<code>size</code>	the number of data points in each cluster of the closest hard clustering.
<code>cluster</code>	a vector of integers containing the indices of the clusters where the data points are assigned to for the closest hard clustering, as obtained by assigning points to the (first) class with maximal membership.
<code>iter</code>	the number of iterations performed.
<code>membership</code>	a matrix with the membership values of the data points to the clusters.
<code>withinerror</code>	the value of the objective function.
<code>call</code>	the call used to create the object.

Note

Note that the clustering is based solely on the `exprs` matrix and no information is used from the `phenoData`. In particular, the ordering of samples (arrays) is the same as the ordering of the columns in the `exprs` matrix. Also, replicated arrays in the `exprs` matrix are treated as independent by the `mfuzz` function i.e. they should be averaged prior to clustering or placed into different distinct “ExpressionSet” objects.

Author(s)

Matthias E. Futschik (http://www.cbme.ualg.pt/mfutschik_cbme.html)

References

M.E. Futschik and B. Charlisle, Noise robust clustering of gene expression time-course data, *Journal of Bioinformatics and Computational Biology*, 3 (4), 965-988, 2005

L. Kumar and M. Futschik, Mfuzz: a software package for soft clustering of microarray data, *Bioinformatics*, 2(1) 5-7,2007

See Also

[cmeans](#)

Examples

```
if (interactive()){
  data(yeast)
  # Data pre-processing
  yeastF <- filter.NA(yeast)
  yeastF <- fill.NA(yeastF) # for illustration only; rather use knn method
  yeastF <- standardise(yeastF)

  # Soft clustering and visualisation
  cl <- mfuzz(yeastF, c=20, m=1.25)
  mfuzz.plot(yeastF, cl=cl, mfrow=c(2, 2))

  # Plotting center of cluster 1
  X11(); plot(cl[[1]][1,], type="l", ylab="Expression")

  # Getting the membership values for the first 10 genes in cluster 1
  cl[[4]][1:10, 1]
}
```

overlap.plot

Visualisation of cluster overlap and global clustering structure

Description

This function visualises the cluster overlap produced by `overlap`.

Usage

```
overlap.plot(cl, overlap, thres=0.1, scale=TRUE, magni=30, P=NULL)
```

Arguments

<code>cl</code>	object of class “fclust”
<code>overlap</code>	matrix of cluster overlap produced by <code>overlap</code>
<code>thres</code>	threshold for visualisation. Cluster overlaps below the threshold will not be visualised.

scale	Scale parameter for principal component analysis by prcomp
magni	Factor for increase the line width for cluster overlap.
P	Projection matrix produced by principal component analysis.

Value

A plot is generated based on a principal component analysis of the cluster centers. The overlap is visualised by lines with variable width indicating the strength of the overlap. Additionally, the matrix of principal components is returned. This matrix can be re-used for other projections to compare the overlap and global cluster structure of different clusterings.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

See Also

[prcomp](#)

Examples

```
if (interactive()) {
  data(yeast)
  # Data pre-processing
  yeastF <- filter.NA(yeast)
  yeastF <- fill.NA(yeastF)
  yeastF <- standardise(yeastF)

  # Soft clustering
  cl <- mfuzz(yeastF, c=20, m=1.25)
  X11(); mfuzz.plot(yeastF, cl=cl, mfrow=c(4, 5))
  O <- overlap(cl)
  X11(); Ptmp <- overlap.plot(cl, over=0, thres=0.05)

  # Alternative clustering
  cl <- mfuzz(yeastF, c=10, m=1.25)
  X11(); mfuzz.plot(yeastF, cl=cl, mfrow=c(3, 4))
  O <- overlap(cl)

  X11(); overlap.plot(cl, over=0, P=Ptmp, thres=0.05)
  # visualisation based on principal compents from previous projection
}
```

 overlap

Calculation of the overlap of soft clusters

Description

This function calculates the overlap of clusters produced by `mfuzz`.

Usage

```
overlap(cl)
```

Arguments

cl object of class *fclust*

Value

The function generates a matrix of the normalised overlap of soft clusters. The overlap indicates the extent of “shared” genes between clusters. For a mathematical definition of the overlap, see the vignette of the package or the reference below.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

References

M.E. Futschik and B. Charlise, Noise robust clustering of gene expression time-course data, *Journal of Bioinformatics and Computational Biology*, 3 (4), 965-988, 2005

Examples

```
if (interactive()) {
  data(yeast)
  # Data pre-processing
  yeastF <- filter.NA(yeast)
  yeastF <- fill.NA(yeastF)
  yeastF <- standardise(yeastF)

  # Soft clustering and visualisation
  cl <- mfuzz(yeastF, c=20, m=1.25)
  mfuzz.plot(yeastF, cl=cl, mfrow=c(4, 5))

  # Calculation of cluster overlap and visualisation
  O <- overlap(cl)
  X11()
  Ptmp <- overlap.plot(cl, over=O, thres=0.05)
}
```

partcoef

Calculation of the partition coefficient matrix for soft clustering

Description

This function calculates partition coefficient for clusters within a range of cluster parameters. It can be used to determine the parameters which lead to uniform clustering.

Usage

```
partcoef(eset, crange=seq(4, 32, 4), mrangle=seq(1.05, 2, 0.1), ...)
```

Arguments

eset	object of class "ExpressionSet".
crange	range of number of clusters c .
mrange	range of clustering parameter m .
...	additional arguments for underlying <code>mfuzz</code> .

Details

Introduced by Bezdek (1981), the partition coefficient F is defined as the sum of squares of values of the partition matrix divided by the number of values. It is maximal if the partition is hard and reaches a minimum for $U=1/c$ when every gene is equally assigned to every cluster.

It is well-known that the partition coefficient tends to decrease monotonically with increasing n . To reduce this tendency we defined a normalized partition coefficient where the partition for uniform partitions are subtracted from the actual partition coefficients (Futschik and Kasabov, 2002).

Value

The function generates the matrix of partition coefficients for a range of c and m values. It also produces a matrix of normalised partition coefficients as well as a matrix with partition coefficient for uniform partitions.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

References

1. J.C.Bezdek, Pattern recognition with fuzzy objective function algorithms, Plenum, 1981
2. M.E. Futschik and N.K. Kasabov. Fuzzy clustering of gene expression data, Proceedings of World Congress of Computational Intelligence WCCI 2002, Hawaii, IEEE Press, 2002

Examples

```
if (interactive()) {
  data(yeast)
  # Data pre-processing
  yeastF <- filter.NA(yeast)
  yeastF <- fill.NA(yeastF)
  yeastF <- standardise(yeastF)

  ##### parameter selection
  yeastFR <- randomise(yeastF)
  cl <- mfuzz(yeastFR, c=20, m=1.1)
  mfuzz.plot(yeastFR, cl=cl, mfrow=c(4, 5)) # shows cluster structures (non-uniform partition)

  tmp <- partcoef(yeastFR) # This might take some time.
  F <- tmp[[1]]; F.n <- tmp[[2]]; F.min <- tmp[[3]]

  # Which clustering parameters result in a uniform partition?
  F > 1.01 * F.min

  cl <- mfuzz(yeastFR, c=20, m=1.25) # produces uniform partition
}
```



```
mfuzz.plot(yeastFR, cl=cl, mfrow=c(4, 5))  
# uniform coloring of temporal profiles indicates uniform partition  
}
```

randomise

Randomisation of data

Description

This function randomise the time order for each gene separately.

Usage

```
randomise(eset)
```

Arguments

eset object of the class *ExpressionSet*.

Value

The function produces an object of the *ExpressionSet* class with randomised expression data.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

Examples

```
data(yeast) # data set includes 17 measurements  
yeastR <- randomise(yeast)
```

standardise2

Standardization in regards to selected time-point

Description

Standardisation of the expression values of every gene is performed, so that the expression values at a chosen time point are zero and the standard deviations are one.

Usage

```
standardise2(eset, timepoint=1)
```

Arguments

eset object of the class *ExpressionSet*.
timepoint integer: which time point should have expression values of zero.

Value

The function produces an object of the *ExpressionSet* class with standardised expression values.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

Examples

```
if (interactive()){
  data(yeast)
  # Data pre-processing
  yeastF <- filter.NA(yeast)
  yeastF <- fill.NA(yeastF)
  yeastF <- standardise2(yeastF,timepoint=1)

  # Soft clustering and visualisation
  cl <- mfuzz(yeastF,c=20,m=1.25)
  mfuzz.plot(yeastF,cl=cl,mfrow=c(4,5))
}
```

standardise

Standardization of microarray data for clustering.

Description

Standardisation of the expression values of every gene is performed, so that the average expression value for each gene is zero and the standard deviation is one.

Usage

```
standardise(eset)
```

Arguments

eset object of the classe *ExpressionSet*.

Value

The function produces an object of the *ExpressionSet* class with standardised expression values.

Author(s)

Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

Examples

```
if (interactive()){
  data(yeast)
  # Data pre-processing
  yeastF <- filter.NA(yeast)
  yeastF <- fill.NA(yeastF)
  yeastF <- standardise(yeastF)

  # Soft clustering and visualisation
  cl <- mfuzz(yeastF, c=20, m=1.25)
  mfuzz.plot(yeastF, cl=cl, mfrow=c(4, 5))
}
```

top.count	<i>Determines the number for which each gene has highest membership value in all cluster</i>
-----------	--

Description

This function calculates the number, for which each gene appears to have the top membership score in the partition matrix of clusters produced by `mfuzz`.

Usage

```
top.count(cl)
```

Arguments

`cl` object of class "fclust"

Value

The function generates a vector containing a count for each gene, which is just the number of times that particular gene has acquired the top membership score.

Author(s)

Lokesh Kumar and Matthias E. Futschik (<http://itb.biologie.hu-berlin.de/~futschik>)

Examples

```
if (interactive()){
  data(yeast)
  # Data pre-processing
  yeastF <- filter.NA(yeast)
  yeastF <- fill.NA(yeastF)
  yeastF <- standardise(yeastF)

  # Soft clustering and visualisation
  cl <- mfuzz(yeastF, c=20, m=1.25)
  top.count(cl)
}
```

`yeast`*Gene expression data of the yeast cell cycle*

Description

The data contains gene expression measurements for 3000 randomly chosen genes of the yeast mutant *cdc28* as performed and described by Cho *et al.* For details, see the reference.

Usage

```
data(yeast)
```

Format

An object of class “ExpressionSet”.

Source

The data was downloaded from *Yeast Cell Cycle Analysis Project* website and converted to an *ExpressionSet* object.

References

Cho et al., A genome-wide transcriptional analysis of the mitotic cell cycle, *Mol Cell*. 1998 Jul;2(1):65-73.

`yeast.table2`*Gene expression data of the yeast cell cycle as table*

Description

The data serves as an example for the format required to upload tables with expression data into *Mfuzzgui*. The first row contains the names of the samples and the first column contains unique identifiers for genes. To input measurement time and gene names, refer to [yeast.table](#).

The exemplary tables can be found in the data sub-folder of the *Mfuzzgui* package.

References

Cho et al., A genome-wide transcriptional analysis of the mitotic cell cycle, *Mol Cell*. 1998 Jul;2(1):65-73.

See Also

[yeast.table](#)

`yeast.table`*Gene expression data of the yeast cell cycle as table*

Description

The data serves as an example for the format required for uploading tables with expression data into *Mfuzzgui*. The first row contains the names of the samples, the second row contains the measured time points. Note that “TIME” has to be placed in the first field of the second row.

The first column contains unique identifiers for genes; optionally the second row can contain gene names if “GENE.NAMES” is in the second field in the first row.

An example for a table without optional fields is the dataset `yeast.table2`.

The exemplary tables can be found in the data sub-folder of the *Mfuzzgui* package.

References

Cho et al., A genome-wide transcriptional analysis of the mitotic cell cycle, *Mol Cell*. 1998 Jul;2(1):65-73.

See Also

`yeast.table2`

Index

*Topic **cluster**

- cselection, 2
- kmeans2, 6
- mfuzz, 12
- Mfuzzgui, 8
- overlap, 14
- partcoef, 15
- top.count, 19

*Topic **datasets**

- yeast, 20
- yeast.table, 21
- yeast.table2, 20

*Topic **hplot**

- kmeans2.plot, 6
- mfuzz.plot, 11
- mfuzz.plot2, 9
- overlap.plot, 13

*Topic **misc**

- Mfuzzgui, 8

*Topic **ts**

- Mfuzzgui, 8

*Topic **utilities**

- acore, 1
- fill.NA, 3
- filter.NA, 4
- filter.std, 5
- mfuzzColorBar, 7
- randomise, 17
- standardise, 18
- standardise2, 17

acore, 1

cmeans, 12, 13
cselection, 2

fill.NA, 3
filter.NA, 4
filter.std, 5

kmeans, 6, 7
kmeans2, 6
kmeans2.plot, 6

maColorBar, 8

mfuzz, 9, 12

mfuzz.plot, 11
mfuzz.plot2, 9
mfuzzColorBar, 7
Mfuzzgui, 8

overlap, 14
overlap.plot, 13

partcoef, 15
prcomp, 14

randomise, 17

standardise, 18
standardise2, 17

top.count, 19

yeast, 20
yeast.table, 20, 21
yeast.table2, 20, 21