

# ArrayExpress

October 5, 2010

---

ArrayExpress

*R objects from ArrayExpress database*

---

## Description

ArrayExpress produces an [AffyBatch](#), an [ExpressionSet](#) or a [NChannelSet](#) from a raw dataset from the ArrayExpress database. ArrayExpress needs an Internet connection.

## Usage

```
ArrayExpress(input, path = getwd(), save = FALSE, rawcol = NULL)
```

## Arguments

input	an ArrayExpress identifier. The function currently covers 96% of the raw data sets of the database.
path	the name of the directory in which the files downloaded on the ArrayExpress repository will be extracted. The default is the current directory.
save	if TRUE, the files downloaded from the database will not be deleted from path after executing the function.
rawcol	by default, for the raw data, the columns are automatically selected according to the scanner type. If the scanner is unknown or if the user wants to use different columns than the default, the argument 'rawcol' can be set. For two colour arrays it must be a list with the fields 'R', 'G', 'Rb' and 'Gb' giving the column names to be used for red and green foreground and background. For one colour arrays, it must be a character string with the column name to be used. These column names must correspond to existing column names of the expression files.

## Value

The output is an object of class [AffyBatch](#) or [ExpressionSet](#) or [NChannelSet](#) with the raw expression values in the assayData of the object, the information contained in the .sdrf file in the phenoData, the adf file in the featureData and the idf file content in the experimentData.

If several array designs are used in the data set, the output is a list with an object for each array design.

**Author(s)**

Audrey Kauffmann Maintainer: <kauffmann@bergonie.org>

**See Also**

[queryAE](#), [getAE](#), [magetab2bioc](#), [getcolproc](#), [procset](#)

**Examples**

```
ETABM25.affybatch = ArrayExpress(input = "E-TABM-25")
print(ETABM25.affybatch)
sampleNames(ETABM25.affybatch)
colnames(pData(ETABM25.affybatch))
```

---

extract.zip

*Unzip archives in a specified directory*

---

**Description**

extract.zip extracts the files from a .zip archive in a specific directory.

**Usage**

```
extract.zip(file, extractpath = dirname(file)[1])
```

**Arguments**

file            A file name.

extractpath    A path to define where the files are to be extracted.

**Value**

Success is indicated by returning the directory in which the files have been extracted. If it fails, it returns an empty character string.

**Author(s)**

Audrey Kauffmann Maintainer: <kauffmann@bergonie.org>

---

`getAE`*Download MAGE-TAB files from ArrayExpress in a specified directory*

---

**Description**

`getAE` downloads and extracts the MAGE-TAB files from an ArrayExpress dataset.

**Usage**

```
getAE(input, path = getwd(), type = "full", extract = TRUE)
```

**Arguments**

<code>input</code>	is an ArrayExpress identifier.
<code>path</code>	is the name of the directory in which the files downloaded on the ArrayExpress repository will be extracted.
<code>type</code>	can be 'raw' to download and extract only the raw data, 'processed' to download and extract only the processed data or 'full' to have both raw and processed data.
<code>extract</code>	if FALSE, the files are not extracted from the zip archive.

**Value**

A list with the names of the files that have been downloaded and extracted.

**Author(s)**

Audrey Kauffmann Maintainer: <kauffmann@bergonie.org>

**See Also**

[ArrayExpress](#), [magetab2bioc](#), [getcolproc](#), [procset](#)

**Examples**

```
mexp1422 = getAE("E-MEXP-1422", type = "full")

## Build a an ExpressionSet from the raw data
MEXP1422raw = magetab2bioc(files = mexp1422)

## Build a an ExpressionSet from the processed data
cnames = getcolproc(mexp1422)
MEXP1422proc = procset(mexp1422, cnames[2])
```

---

getcolproc	<i>Return the possible column names from processed MAGE-TAB files</i>
------------	---

---

**Description**

getcolproc extracts the column names from processed MAGE-TAB and return them. The output is needed to call the function procset.

**Usage**

```
getcolproc(files)
```

**Arguments**

files	A list as given from <a href="#">getAE</a> function. Containing the following elements: <b>profile</b> profile is the name of the processed MAGE-TAB file to be read. <b>path</b> is the name of the directory where to find this file.
-------	---

**Author(s)**

Audrey Kauffmann

Maintainer: <kauffmann@bergonie.org>

**See Also**

[ArrayExpress](#), [queryAE](#), [getAE](#), [procset](#)

---

getcolraw	<i>Return the possible column names from raw MAGE-TAB files</i>
-----------	---

---

**Description**

getcolraw extracts the column names from raw MAGE-TAB and return them. The output can be use to set the argument 'rawcol' of the function magetab2bioc.

**Usage**

```
getcolraw(path, rawfiles)
```

**Arguments**

rawfiles	rawfiles are the name of the raw MAGE-TAB files to be read.
path	is the name of the directory where to find these files.

**Author(s)**

Audrey Kauffmann Maintainer: <kauffmann@bergonie.org>

**See Also**

[ArrayExpress](#), [queryAE](#), [getAE](#)

---

`magetab2bioc`*Convert MAGE-TAB files from raw data into a Bioconductor object*

---

## Description

`magetab2bioc` converts local MAGE-TAB files into a `AffyBatch`, an `ExpressionSet` or a `NChannelSet`.

## Usage

```
magetab2bioc(files, rawcol = NULL, save = TRUE)
```

## Arguments

<code>files</code>	A list as given from <code>getAE</code> function. Containing the following elements: <b>rawfiles</b> all the expression files to use to create the object. The content of the raw.zip MAGE-TAB file. <b>sdrf</b> the name of the sdrf file from MAGE-TAB. <b>idf</b> the name of the idf file from MAGE-TAB. <b>adf</b> the name of the adf file from MAGE-TAB. <b>path</b> is the name of the directory containing these files.
<code>rawcol</code>	by default, the columns are automatically selected according to the scanner type. If the scanner is unknown or if the user wants to use different columns than the default, the argument 'rawcol' can be set. For two colour arrays it must be a list with the fields 'R', 'G', 'Rb' and 'Gb' giving the column names to be used for red and green foreground and background. For one colour arrays, it must be a character string with the column name to be used. These column names must correspond to existing column names of the expression files.
<code>save</code>	if TRUE, the files used to create the object will not be deleted from path after executing the function.

## Value

An object of class `AffyBatch`, `ExpressionSet` or `NChannelSet` with the raw expression values in the 'assayData' of the object, the information contained in the sdrf file in the 'phenoData', the adf file content in the 'featureData' and the idf file content in the 'experimentData'.

If several array designs are used in the dataset, the output is a list with an object for each array design.

## Author(s)

Audrey Kauffmann Maintainer: <kauffmann@bergonie.org>

## See Also

[ArrayExpress](#), [queryAE](#), [getAE](#)

## Examples

```
# An example can be found in the help of the getAE function.
```

---

procset	<i>Convert processed MAGE-TAB files into a Bioconductor object</i>
---------	--

---

### Description

procset converts local MAGE-TAB files into an [ExpressionSet](#).

### Usage

```
procset(files, procol)
```

### Arguments

files	is the list with the names of the processed, the sdrf, the adf and the idf files and the path of the data as given by <a href="#">getAE</a> .
procol	the name of the column to be extracted from the file. Obtained using <a href="#">getcolproc</a> .

### Author(s)

Audrey Kauffmann Maintainer: <kauffmann@bergonie.org>

### See Also

[queryAE](#), [getAE](#), [getcolproc](#)

### Examples

```
# An example can be found in the help of the getAE function.
```

---

queryAE	<i>XML query of the ArrayExpress repository</i>
---------	---

---

### Description

queryAE queries the ArrayExpress database with keywords and give a dataframe with ArrayExpress identifiers and related information, as an output.

### Usage

```
queryAE(keywords = NULL, species = NULL)
```

### Arguments

keywords	the keyword(s) of interest. To use several words, they must be separated by a "+" as shown in the examples.
species	the specie(s) of interest.

**Value**

A dataframe with all the ArrayExpress dataset identifiers which correspond to the query in the first column. The following columns contain information about these datasets, such as the number of raw files, the number of data processed, the release date on the database, the pubmed ID, the species, the experiment design and the experimental factors.

**Author(s)**

Audrey Kauffmann

Maintainer: <kauffmann@bergonie.org>

**See Also**

[ArrayExpress](#), [getAE](#)

**Examples**

```
## To retrieve all the identifiers of pneumonia data sets  
pneumo = queryAE(keywords = "pneumonia")
```

```
## To retrieve all the identifiers of pneumonia data sets studied in human  
pneumoHS = queryAE(keywords = "pneumonia", species = "homo+sapiens")
```

# Index

## \*Topic **datasets**

- ArrayExpress, 1
- extract.zip, 2
- getAE, 3
- getcolproc, 4
- getcolraw, 4
- magetab2bioc, 5
- procset, 6
- queryAE, 6

AffyBatch, 1, 5  
ArrayExpress, 1, 3–5, 7

ExpressionSet, 1, 5, 6  
extract.zip, 2

getAE, 2, 3, 4–7  
getcolproc, 2, 3, 4, 6  
getcolraw, 4

magetab2bioc, 2, 3, 5

NChannelSet, 1, 5

procset, 2–4, 6

queryAE, 2, 4, 5, 6, 6