

Mulcom

October 25, 2011

Affy

Affy Dataset

Description

Affy Dataset

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

AffyIlnn

cross mapping table

Description

cross mapping table

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Illumina

Illumina Dataset

Description

Illumina Dataset

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

| | |
|------|---------------------|
| Ilmn | <i>Ilmn Dataset</i> |
|------|---------------------|

Description

Ilmn Dataset

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

| | |
|--------------|---------------------|
| MULCOM-class | <i>Class MulCom</i> |
|--------------|---------------------|

Description

This is a class representation MulCom test scores

Objects from the Class

Objects can be created using the function `mulScores` on `ExpressionSet`.

Slots

FC: Object of class `numeric` representing difference between all experimental groups and the reference groups

HM: Object of class `numeric` representing the harmonic means in all subgroups

MSE_Corrected: Object of class `numeric` representing the MulCom test estimation of mean square error as described in the formula of the Dunnett's t-test

Author(s)

Claudio Isella

Examples

```
data(benchVign)
mulcom_scores <- mulScores(Affy, Affy$Groups)
```

MULCOM_P-class *Class MulCom Permutation*

Description

This is a class representation MulCom test scores permutation

Objects from the Class

Objects can be created using the function `mulScores` on `ExpressionSet`.

Slots

FC: Object of class `numeric` representing delta between all experimental groups and the reference groups

MSE_Corrected: Object of class `numeric` representing the MulCom test estimation of mean square error as described in the formula of the Dunnett's t-test

FCp: Object of class `numeric` representing delta between all experimental groups and the reference groups in permuted data

MSE_Correctedp: Object of class `numeric` representing the MulCom test estimation of mean square error as described in the formula of the Dunnett's t-test in permuted data

Author(s)

Claudio Isella

Examples

```
data(benchVign)
mulcom_scores <- mulScores(Affy, Affy$Groups)
```

harmonicMean *MulCom Harmonic Mean*

Description

Computes harmonic means across groups replicate Should not be called directly

Usage

```
harmonicMean(index)
```

Arguments

`index` a numeric vector with the groups labels of the samples. 0 are the control samples. Number must be progressive

Details

`harmonicMean` calculates harmonic means across groups replicate for the estimation of Mulcom Test

Value

a numeric vector

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

References

<claudio.isella@ircc.it>

limmaAffySymbols *significant gene list with limma in Affymetrix*

Description

significant gene list with limma in Affymetrix

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

limmaIlnnSymbols *significant gene list with limma in Illumina*

Description

significant gene list with limma in Illumina

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

mulCAND

*Identify the Mulcom candidate feature selection***Description**

Identify the Mulcom candidate feature selection by the m and T defined by the user

Usage

```
mulCAND(eset, Mulcom_P, m, t, ese = "T")
```

Arguments

| | |
|----------|---|
| eset | an AffyBatch |
| Mulcom_P | an object of class MULCOM |
| m | m: a numeric vector corresponding to log 2 ratio correction |
| t | t: a numeric vector corresponding to the MulCom T values |
| ese | True or False |

Details

mulCAND Identify the Mulcom candidate feature selection by the m and T defined by the user

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_perm <- mulPerm(Affy, Affy$Groups, 10, 2)
mulcom_cand <- mulCAND(Affy, mulcom_perm, 0.2, 2)
```

mulCalc

*MulCom Calculation***Description**

Calculates MulCom test score for given m and t parameters

Usage

```
mulCalc(Mulcom_P, m, t)
```

Arguments

| | |
|----------|--|
| Mulcom_P | an object of class MULCOM |
| m | m: a numeric value corresponding to log 2 ratio correction for MulCom Test |
| t | t: a numeric value corresponding to T values for MulCom Test |

Details

`mulCalc` Calculate the Mulcom Score with `m` and `t` defined by the user

`Mulcom_P`: an object of class `MULCOM_P`

`m`: a number corresponding to log 2 ratio correction for MulCom Test

`t`: a number corresponding to T values for MulCom Test

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_scores <- mulScores(Affy, Affy$Groups)
mulcom_calc <- mulCalc(mulcom_scores, 0.2, 2)
```

mulDELTA

MulCom Delta

Description

Computes Delta for all the experimental points in the datasets in respect to control Should not be called directly

Usage

```
mulDELTA(vector, index)
```

Arguments

| | |
|---------------------|--|
| <code>vector</code> | vector: numeric vector with data measurements |
| <code>index</code> | a numeric vector with the labels of the samples. 0 are the control samples. number must be progressive |

Details

`mulDELTA` An internal function that should not be called directly. It calculates differential expression in the groups defined in the index class vector, in respect to the 0 groups

Value

| | |
|---------------------|--|
| <code>vector</code> | a numeric vector with data measurements |
| <code>index</code> | a numeric vector with the labels of the samples. 0 are the control samples. number must be progressive |

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_delta <- mulDELTA(exprs(Affy[1,]), Affy$Groups)
```

mulDiff

MulCom Test Differential analysis

Description

Identify the differentially expressed features for a specific comparison with given m and t value

Usage

```
mulDiff(eset, Mulcom_P, m, t, ind)
```

Arguments

| | |
|----------|---|
| eset | An ExpressionSet object from package affy |
| Mulcom_P | An object of class Mulcom_P |
| m | the m values for the analysis |
| t | the t values for the analysis |
| ind | and index refeing to te comparison, should be numeric |

Value

| | |
|----------|---|
| eset | An ExpressionSet object from package affy |
| Mulcom_P | An object of class Mulcom_P |
| m | the m values for the analysis |
| t | the t values for the analysis |
| ind | and index refeing to te comparison, should be numeric |

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_perm <- mulPerm(Affy, Affy$Groups, 10, 7)
mulcom_diff <- mulDiff(Affy, mulcom_perm, 0.2, 2)
```

mulFSG *MulCom False Significant Genes*

Description

Calculate the False Significant Genes for m and t defined by the user

Usage

```
mulFSG(Mulcom_P, m, t)
```

Arguments

| | |
|----------|--|
| Mulcom_P | an object of class MULCOM |
| m | m: a numeric value corresponding to log 2 ratio correction for MulCom Test |
| t | t: a numeric value corresponding to t values for MulCom Test |

Details

mulFDR evaluate the False Significant genes on the Mulcom_P object according to specific m and t parameters. For each permutation it is calculated the number of positive genes. An estimation of the false called genes is evaluated with the median for each experimental subgroups

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_perm <- mulPerm(Affy, Affy$Groups, 10, 7)
mulcom_fsg <- mulFSG(mulcom_perm, 0.2, 2)
```

mulIndex *Mulcom Index for Monte Carlo Simlation*

Description

Random asseby of the groups indices for Monte Carlo Simulation

Usage

```
mulIndex(index, np, seed)
```

Arguments

| | |
|-------|--|
| index | the vector with the groups of analysis, must be numeric and 0 correspond to the reference. |
| np | number of permutation in the simulation |
| seed | seed for permtations |

Details

'mulIndex' generates random index for the function mulPerm. it is not directly called by the user.

Value

A matrix with all indices permutations

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_scores <- mulIndex(Affy$Groups, 5, 7)
```

mulInt

generates a consensus matrix from list of genes

Description

generates a consensus matrix from list of genes

Usage

```
mulInt(...)
```

Arguments

... the function requires vector files as inputs

Details

mulCAND generates a consensus matrix from list of genes

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_perm <- mulPerm(Affy, Affy$Groups, 10,2)
mulcom_opt <- mulOpt(mulcom_perm, vm = seq(0,0.5, 0.1), vt = seq(1,3, 0.1))

h1_opt <- mulParOpt(mulcom_perm, mulcom_opt, ind = 1, th = 0.05)
h2_opt <- mulParOpt(mulcom_perm, mulcom_opt, ind = 1, th = 0.05)

int <- mulInt(h1_opt, h2_opt)
```

| | |
|--------|---------------------------------|
| mulMSE | <i>MulCom Mean Square Error</i> |
|--------|---------------------------------|

Description

Computes Mean Square Error for all the experimental points in the datasets in respect to control
Should not be called directly

Usage

```
mulMSE(vector, index, tmp = vector())
```

Arguments

| | |
|--------|--|
| vector | a numeric vector with data measurements |
| index | a numeric vector with the labels of the samples. 0 are the control samples. number must be progressive |
| tmp | a vector |

Details

mulMSE An internal function that should not be called directly. It calculates within group means square error for the values defined in the x vector according to the index class vector

Value

| | |
|--------|--|
| vector | a numeric vector with data measurements |
| index | a numeric vector with the labels of the samples. 0 are the control samples. number must be progressive |
| tmp | a vector |

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

| | |
|--------|----------------------------|
| mulOpt | <i>MulCom optimization</i> |
|--------|----------------------------|

Description

The function systematically performs the calculation of significant genes and corresponding FDR for all the combination of given list of m and t values.

Usage

```
mulOpt(Mulcom_P, vm, vt)
```

Arguments

Mulcom_P an object of class Mulcom_P
 vm a vector of m values to test
 vt a vector of t values to test

Details

mulOpt The function systematically performs the calculation of significant genes and corresponding FDR for all the combination of given list of m and t values.

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_perm <- mulPerm(Affy, Affy$Groups, 10, 7)
mulcom_opt <- mulOpt(mulcom_perm, seq(0.1, 0.5, 0.1), seq(1, 3, 0.1))
```

mulOptPars

MulCom Parameter Optimization

Description

Function to optimize Mulcom parameter for maximum number of genes with a user defined FDR

Usage

```
mulOptPars(opt, ind, ths)
```

Arguments

opt an MulCom optimization object
 ind index corresponding to the comparison
 ths a threshold for the FDR optimization, default is 0.05

Details

mulOptPars MulCom optimization function to identify best parameters

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_perm <- mulPerm(Affy, Affy$Groups, 10, 7)
#mulcom_opt <- mulOpt(mulcom_perm, seq(0.1, 0.5, 0.1), seq(1, 3, 0.1))
#optThs <- mulOptPars(mulcom_opt, 1, 0.05)
```

mulOptPlot *MulCom optimization Plot*

Description

MulCom optimization Plot to identify best configuration paramters

Usage

```
mulOptPlot(M.Opt, ind, th, smooth = "NO")
```

Arguments

| | |
|--------|---|
| M.Opt | an MulCom optimization object |
| ind | index corresponding to the comparison to plot |
| th | a threshold for the FDR plot |
| smooth | indicates whether the FDR plot will show a significant threshold or will be continuous. |

Details

mulOptPlot MulCom optimization Plot

Value

a numeric vector

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_perm <- mulPerm(Affy, Affy$Groups, 10,2)
mulcom_opt <- mulOpt(mulcom_perm, vm=seq(0.1, 0.5, 0.1), vt=seq(1, 3,1))
mulOptPlot(mulcom_opt, 1, 0.05)
```

mulParOpt *MulCom Parameters Optimization*

Description

MulCom parameter optimization function to identify best combination of t and m providing maximum number of genes at a given FDR

Usage

```
mulParOpt(perm, M.Opt, ind, th, image = "T")
```

Arguments

| | |
|-------|--|
| perm | a object with permuted MulCom Scores |
| M.Opt | an MulCom optimization object |
| ind | index corresponding to the comparison to plot |
| th | a threshold for the FDR plot |
| image | default = "T", indicates is print the MulCom optimization plot |

Details

mulParOpt The function mulParOpt is designed to identify the optimal m and t values combination leading to the maximum number of differentially regulated genes satisfying an user define FDR threshold. In case of equal number of genes, the combination of m and t with the lower FDR will be prioritized. In case of both identical number of genes and FDR, the function will chose the highest t. The function optionally will define a graphical output to visually inspect the performance of the test at given m and t parameters for a certain comparison.

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_perm <- mulPerm(Affy, Affy$Groups, 10,2)
mulcom_opt <- mulOpt(mulcom_perm, vm=seq(0.1, 0.5, 0.1), vt=seq(1, 3,1))
mulParOpt(mulcom_perm, mulcom_opt, 1, 0.05)
```

mulPerm

MulCom Permutation

Description

Reiterate MulCom Test on permuted data to perform Montecarlo simulation

Usage

```
mulPerm(eset, index, np, seed, segm = "F")
```

Arguments

| | |
|-------|--|
| eset | An an AffyBatch object, each row of must correspond to a variable and each column to a sample. |
| index | a numeric vector of length ncol(data) with the labels of the samples. 0 are the reference samples. |
| np | a numeric values indicating the number of permutation to perform. It is set as default to 10 |
| seed | set the seed of the permutaton, default is 1 |
| segm | a default set to F. This parametheres requires to be setted to avoid segmentation fault of C subroutin in the case of very large datasets. |

Details

```
mulPerm
```

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_perm <- mulPerm(Affy, Affy$Groups, 10,2)
```

```
mulPermC
```

```
MulCom Permutation
```

Description

R pipe to C function not called directly by user that reiterate MulCom Test on permuted data to perform Monte Carlo simulation

Usage

```
mulPermC(eset, index, means, mse, n, m, nump, ngroups, reference)
```

Arguments

| | |
|-----------|--|
| eset | An an AffyBatch object, each row of must correspond to a variable and each column to a sample. |
| index | a numeric vector of length ncol(data) with the labels of the samples. 0 are the reference samples. |
| means | entry for the means output. |
| mse | entry for the mean square errors output |
| n | number of rows in obext of class eset |
| m | number of columns |
| nump | number of permutation to perform |
| ngroups | a number corresponding to the number of groups in the analysis. |
| reference | reference for the comparisons. typically it is 0 |

Details

```
mulPerm
```

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
```

mulSSE *MulCom Sum of Square Error*

Description

Computes sum of square errors for all the experimental points in the datasets Should not be called directly

Usage

```
mulSSE(vec, index)
```

Arguments

`vec` a numeric vector with data measurements
`index` a numeric vector with the labels of the samples. 0 are the control samples. number should be progressive

Details

`mulSSE` An internal function that should not be called directly. It calculates sum of square error in the groups defined in the index class vector.

Value

`vec` a numeric vector with data measurements
`index` a numeric vector with the labels of the samples. 0 are the control samples. number must be progressive

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

mulScores *MulCom Score Calculation*

Description

Computes the scores for the MulCom test. The function calculates the numerator and the denominator of the test without the parameters m and t

Usage

```
mulScores(eset, index)
```

Arguments

`eset` An an [AffyBatch](#) object, each row of must correspond to a variable and each column to a sample.
`index` a numeric vector of length `ncol(data)` with the labels of the samples. 0 are the reference samples.

Details

'mulScore' computes the scores for the MulCom test for multiple point profile. The Mulcom test is designed to compare each experimental mean with the control mean and it is derived from the "Dunnett's test". Dunnett's test controls the Experiment-wise Error Rate and is more powerful than tests designed to compare each mean with each other mean. The test is conducted by computing a modified t-test between each experimental group and the control group.

Value

An Object of class MULCOM from Mulcom package

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Examples

```
data(benchVign)
mulcom_scores <- mulScores(Affy, Affy$Groups)
```

mulcomGeneListIilmn *significant gene list with limma in Illumina*

Description

significant gene list with limma in Illumina

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

samAffySymbols *significant gene list with SAM in Affymetrix*

Description

significant gene list with SAM in Affymetrix

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

samIlmnSymbols *significant gene list with SAM in Illumina*

Description

significant gene list with SAM in Illumina

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

samOptPars *sam Parameter Optimization*

Description

Function to optimize Sam parameter for maximim nuber of genes with a user defined FDR

Usage

```
samOptPars(opt, ths)
```

Arguments

| | |
|-----|--------------------------------------|
| opt | an Sam optimization object |
| ths | a threshold for the FDR optimization |

Value

a numeric vector

Author(s)

Claudio Isella, <claudio.isella@ircc.it>

Index

*Topic **MulCom**

- Affy, 1
- AffyIlmn, 1
- harmonicMean, 3
- Illumina, 1
- Ilmn, 2
- limmaAffySymbols, 4
- limmaIlmnSymbols, 4
- mulCalc, 5
- mulCAND, 5
- mulcomGeneListIlmn, 16
- mulDELTA, 6
- mulDiff, 7
- mulFSG, 8
- mulIndex, 8
- mulInt, 9
- mulMSE, 10
- mulOpt, 10
- mulOptPars, 11
- mulOptPlot, 12
- mulParOpt, 12
- mulPerm, 13
- mulPermC, 14
- mulScores, 15
- mulSSE, 15
- samAffySymbols, 16
- samIlmnSymbols, 17
- samOptPars, 17

*Topic **classes**

- MULCOM-class, 2
- MULCOM_P-class, 3

Affy, 1

AffyBatch, 5, 13–15

AffyIlmn, 1

class:MULCOM (*MULCOM-class*), 2

class:MULCOM_P (*MULCOM_P-class*), 3

harmonicMean, 3

Illumina, 1

Ilmn, 2

limmaAffySymbols, 4

limmaIlmnSymbols, 4

mulCalc, 5

mulCAND, 5

MULCOM (*MULCOM-class*), 2

MULCOM-class, 2

MULCOM_P (*MULCOM_P-class*), 3

MULCOM_P-class, 3

mulcomGeneListIlmn, 16

mulDELTA, 6

mulDiff, 7

mulFSG, 8

mulIndex, 8

mulInt, 9

mulMSE, 10

mulOpt, 10

mulOptPars, 11

mulOptPlot, 12

mulParOpt, 12

mulPerm, 13

mulPermC, 14

mulScores, 2, 3, 15

mulSSE, 15

samAffySymbols, 16

samIlmnSymbols, 17

samOptPars, 17