

keggorthology: the KEGG orthology as graph

VJ Carey

April 13, 2011

Contents

| | | |
|---|-------------------------------|---|
| 1 | Introduction | 1 |
| 2 | KOgraph | 1 |
| 3 | Application to gene filtering | 3 |
| 4 | Infrastructure considerations | 4 |
| 5 | Session info | 4 |

1 Introduction

KEGG is the Kyoto Encyclopedia of Genes and Genomes. An important product of the KEGG group is a catalog of pathways. The KEGG Orthology (KO) organizes the pathways into a conceptual hierarchy. This package encodes the hierarchy as a graph, and provides some support for deriving sets of array feature identifiers from the hierarchy.

2 KOgraph

```
> library(keggorthology)
> library(graph)
> data(KOgraph)
> KOgraph
```

```
A graphNEL graph with directed edges
Number of Nodes = 358
Number of Edges = 357
```

```
> nodes(KOgraph)[1:5]
```

```
[1] "KO.Feb10root"           "Metabolism"
[3] "Carbohydrate Metabolism" "Glycolysis / Gluconeogenesis"
[5] "Citrate cycle (TCA cycle)"
```

The upper component of the hierarchy is:

```
> adj(KOgraph, nodes(KOgraph)[1])
```

```
$KO.Feb10root
[1] "Metabolism"
[2] "Genetic Information Processing"
[3] "Environmental Information Processing"
[4] "Cellular Processes"
[5] "Organismal Systems"
[6] "Human Diseases"
```

Graph operations can be used to explore the orthology. For example, the context of the PPAR signaling pathway is found as follows:

```
> library(RBGL)
> sp.between(KOgraph, nodes(KOgraph)[1], "PPAR signaling pathway")
```

```
$`KO.Feb10root:PPAR signaling pathway`
$`KO.Feb10root:PPAR signaling pathway`$length
[1] 3
```

```
$`KO.Feb10root:PPAR signaling pathway`$path_detail
[1] "KO.Feb10root"           "Organismal Systems"     "Endocrine System"
[4] "PPAR signaling pathway"
```

```
$`KO.Feb10root:PPAR signaling pathway`$length_detail
$`KO.Feb10root:PPAR signaling pathway`$length_detail[[1]]
      KO.Feb10root->Organismal Systems
                        1
      Organismal Systems->Endocrine System
                        1
Endocrine System->PPAR signaling pathway
                        1
```

Fixed-length identifiers are used to label pathways. These are available as the 'tag' nodeData attribute.

```
> nodeData(KOgraph, , "tag")[1:5]
```

```
$KO.Feb10root
[1] "NONE"
```

```
$Metabolism
[1] "01100"
```

```
$`Carbohydrate Metabolism`
[1] "01101"
```

```
$`Glycolysis / Gluconeogenesis`
[1] "00010"
```

```
$`Citrate cycle (TCA cycle)`
[1] "00020"
```

The depth of each term is also available.

```
> nodeData(KOgraph, , "depth")[1:5]
```

```
$KO.Feb10root
[1] 0
```

```
$Metabolism
[1] 1
```

```
$`Carbohydrate Metabolism`
[1] 2
```

```
$`Glycolysis / Gluconeogenesis`
[1] 3
```

```
$`Citrate cycle (TCA cycle)`
[1] 3
```

3 Application to gene filtering

Several functions are available for retrieving relevant information from the orthology. If you know a substring of the pathway name of interest, you can obtain the numerical tag(s).

```
> getKOtags("insulin")
```

```
Insulin signaling pathway
      "04910"
```

We can get probe set identifiers corresponding to a term. The default chip annotation package used is hgu95av2.db.

```
> library(hgu95av2.db)
> mp = getK0probes("Methionine")
> library(ALL)
> data(ALL)
> ALL[mp, ]
```

```
ExpressionSet (storageMode: lockedEnvironment)
assayData: 33 features, 128 samples
  element names: exprs
protocolData: none
phenoData
  sampleNames: 01005 01010 ... LAL4 (128 total)
  varLabels: cod diagnosis ... date last seen (21 total)
  varMetadata: labelDescription
featureData: none
experimentData: use 'experimentData(object)'
  pubMedIds: 14684422 16243790
Annotation: hgu95av2
```

4 Infrastructure considerations

Based on keggorthology read of KEGG orthology, March 2 2010. Specifically, we run wget on ftp://ftp.genome.jp/pub/kegg/brite/ko/ko00001.keg and use parsing and modeling code given in inst/keggHTML to generate a data frame respecting the hierarchy, and then keggDF2graph function in keggorthology package to construct the graph.

5 Session info

```
> sessionInfo()
```

```
R version 2.13.0 (2011-04-13)
Platform: x86_64-unknown-linux-gnu (64-bit)
```

```
locale:
 [1] LC_CTYPE=en_US.UTF-8      LC_NUMERIC=C
 [3] LC_TIME=en_US.UTF-8      LC_COLLATE=C
 [5] LC_MONETARY=C             LC_MESSAGES=en_US.UTF-8
 [7] LC_PAPER=en_US.UTF-8     LC_NAME=C
 [9] LC_ADDRESS=C             LC_TELEPHONE=C
```

```
[11] LC_MEASUREMENT=en_US.UTF-8 LC_IDENTIFICATION=C
```

```
attached base packages:
```

```
[1] stats      graphics  grDevices  utils      datasets  methods    base
```

```
other attached packages:
```

```
[1] ALL_1.4.7          RBGL_1.28.0          keggorthology_2.4.0
```

```
[4] hgu95av2.db_2.5.0  org.Hs.eg.db_2.5.0  RSQLite_0.9-4
```

```
[7] DBI_0.2-5          AnnotationDbi_1.14.0 Biobase_2.12.0
```

```
[10] graph_1.30.0
```

```
loaded via a namespace (and not attached):
```

```
[1] tools_2.13.0
```