

# Package ‘Iyer517’

October 7, 2015

**Version** 1.10.0

**Title** exprSets for Iyer, Eisen et al 1999 Science paper

**Author** Vishy Iyer <vishy@cmgm.stanford.edu>

**Maintainer** Vince Carey <stvjc@channing.harvard.edu>

**Description** representation of public Iyer data  
from <http://genome-www.stanford.edu/serum/clusters.html>

**License** Artistic-2.0

**Depends** Biobase (>= 2.5.5)

**biocViews** ExperimentData

**NeedsCompilation** no

## R topics documented:

get.dna2 . . . . .	1
Iyer517 . . . . .	2
IyerAnnotated . . . . .	3

<b>Index</b>	<b>5</b>
--------------	----------

---

get.dna2	<i>query genbank for an EST accession id</i>
----------	--

---

## Description

extends the get.dna function of E Paradis CRAN package "ape"

## Usage

```
get.dna2(access.nb)
```

## Arguments

access.nb      an EST accession id

**Details**

queries ncbi

**Value**

a vector of nucleotide codes

**Note**

try `ape::get.dna` if this fails

**Author(s)**

VJ Carey <stvjc@channing.harvard.edu>

**See Also**

`ape::get.dna`

**Examples**

```
if (interactive())
{
  data(IyerAnnotated)
  get.dna2(IyerAnnotated$GB[1])
}
```

---

Iyer517

*exprSet* instance *Iyer517*, time series on transcriptional response of fibroblasts to serum

---

**Description**

an expression set for timed measurements of transcriptional response of fibroblasts to serum in presence or absence of cycloheximide

**Slots**

`exprs`: Object of class `matrix`, value: 517 x 19 expression levels (normed to 1 at time 0)

`se.exprs`: Object of class `matrix`, value: absent

`description`: Object of class `MIAME`, value: string

`annotation`: Object of class `character`, value: ""

`notes`: Object of class `character`, value: ""

`phenoData`: Object of class `phenoData`, value: data frame with info on timing

`class`: Object of class `character`, value: `'exprSet'`

## References

Iyer et al 1999 Science v283 83-87

## Examples

```
data(Iyer517)
show(Iyer517)
plot(apply(exprs(Iyer517)[1:100,1:13],2,mean),main="Cluster A",
      xlab="index in time seq", ylab="ratio to time 0", log="y")
```

---

IyerAnnotated

*Partly annotated version of Iyer517 data*

---

## Description

GenBank ids, LocusLink ids (where available) and GO tags (where available) for the 517 cDNAs in the dataset.

## Usage

```
data(IyerAnnotated); data(Iyer517GO)
```

## Format

**Iyer517GO**: An environment with keys given by the 'GB' identifiers of probes and values given by vectors of GO tags (named by evidence codes) obtained via locuslink mapping

**IyerAnnotated**: A data frame with 517 observations on the following 9 variables.

**Iclust** a factor with levels N A B ... – the cluster groups A-J of the Iyer paper, with N for those rows that were not clustered

**GB** a factor with levels AA001025 AA001722 ... accession numbers (often genbank) for probes

**seqno** a numeric vector indicating the order of the cDNA in the Iyer report on clustering. (Elements 2:101 formed cluster A, etc.)

**locusid** a numeric vector of locuslink ids, formed using AnnBuilder

**GO1** a character vector of GO tags (there were up to five based on the LL:GO mapping available March 2003 – these should be ignored in favor of the new Iyer517GO environment

**GO2** a character vector

**GO3** a character vector

**GO4** a character vector

**GO5** a character vector

## Details

Annotating this dataset is a good exercise for AnnBuilder. Many of the probes seem to have no annotation.

**Source**

<http://genome-www.stanford.edu/serum/data.html>

**References**

Iyer et al, Science v283: 83-87 (1999)

**Examples**

```
data(IyerAnnotated)
table(is.na(IyerAnnotated$G01))
data(Iyer517G0)
get(ls(env=Iyer517G0)[1],env=Iyer517G0)
```

# Index

\*Topic **datasets**

IyerAnnotated, 3

\*Topic **methods**

Iyer517, 2

\*Topic **models**

get.dna2, 1

get.dna2, 1

Iyer517, 2

Iyer517G0 (IyerAnnotated), 3

IyerAnnotated, 3