

Package ‘EGAD’

April 15, 2020

Type Package

Title Extending guilt by association by degree

Version 1.14.0

Date 2016-04-20

Description The package implements a series of highly efficient tools to calculate functional properties of networks based on guilt by association methods.

License GPL-2

Depends R(>= 3.3)

Imports gplots, Biobase, GEOquery, limma, arrayQualityMetrics, impute, RColorBrewer, zoo, igraph, plyr, Matrix, MASS, RCurl, affy

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

RoxygenNote 5.0.1

LazyData true

biocViews Software, FunctionalGenomics, SystemsBiology, GenePrediction, FunctionalPrediction, NetworkEnrichment, GraphAndNetwork, Network

Author Sara Ballouz [aut, cre], Melanie Weber [aut, ctb], Paul Pavlidis [aut], Jesse Gillis [aut, ctb]

Maintainer Sara Ballouz <sballouz@cshl.edu>

git_url <https://git.bioconductor.org/packages/EGAD>

git_branch RELEASE_3_10

git_last_commit 75ccf2c

git_last_commit_date 2019-10-29

Date/Publication 2020-04-14

R topics documented:

assortativity	3
attr.human	3
attr.mouse	4

auc_multifunc	4
auprc	5
auroc_analytic	6
biogrid	6
build_binary_network	7
build_coexp_expressionSet	7
build_coexp_GEOID	8
build_coexp_network	8
build_semantic_similarity_network	9
build_weighted_network	10
calculate_multifunc	10
conv_smoother	11
example_annotations	11
example_binary_network	12
example_coexpression	12
example_neighbor_voting	12
extend_network	13
filter_network	13
filter_network_cols	14
filter_network_rows	15
filter_orthologs	15
fmeasure	16
genes	17
get_auc	17
get_biogrid	18
get_counts	18
get_density	19
get_expression_data_gemma	19
get_expression_matrix_from_GEO	20
get_phenocarta	20
get_prc	21
get_roc	21
GO.human	22
GO.mouse	22
GO.voc	23
make_annotations	23
make_genelist	24
make_gene_network	24
make_transparent	25
neighbor_voting	25
node_degree	26
ortho	27
pheno	27
plot_densities	28
plot_density_compare	28
plot_distribution	29
plot_network_heatmap	30
plot_prc	30
plot_roc	31
plot_roc_overlay	32
plot_value_compare	32
predictions	33

<i>assortativity</i>	3
repmat	34
run_GBA	34
Index	36

<i>assortativity</i>	<i>Calculating network assortativity</i>
----------------------	--

Description

The function calculates the assortativity of a network, that measures the preference of interactions between similar nodes. As in most literature, 'similarity' is here defined in terms of node degrees.

Usage

```
assortativity(network)
```

Arguments

network matrix indicating network structure (symmetric)

Value

Numeric value

Examples

```
network <- matrix( sample(c(0,1),36, replace=TRUE), nrow=6,byrow=TRUE)
assort_value <- assortativity(network)
```

<i>attr.human</i>	<i>Human GENCODE annotations (v22)</i>
-------------------	--

Description

A dataset containing identifiers for gene transcripts

Format

A data frame with 60483 rows and 10 variables:

- chr** chromosome
- start** chromosomal start position, in base pairs
- end** chromosomal end position, in base pairs
- strand** chromosomal strand, + or -
- un** unknown
- ensemblID** ENSEMBL identifier
- type** type of transcript

stat status of transcript

name HUGO identifier

entrezID Entrez identifier

@source ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_22/

attr.mouse

Mouse GENCODE annotations (M7)

Description

A dataset containing identifiers for gene transcripts

Format

A data frame with 46517 rows and 10 variables:

chr chromosome

start chromosomal start position, in base pairs

end chromosomal end position, in base pairs

strand chromosomal strand, + or -

un unknown

ensemblID ENSEMBL identifier

type type of transcript

stat status of transcript

name HUGO identifier

entrezID Entrez identifier

@source ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M7/

auc_multifunc

Calculating AUC for functional groups from ranked lists

Description

The function calculates the AUC for a functional group analytically using an optimal ranked list of genes that indicates association between genes and groups.

Usage

```
auc_multifunc(annotations, optimallist)
```

Arguments

annotations binary matrix indicating which list elements are in which functional groups.

optimallist Ranked list (multifunctionality analysis, see [calculate_multifunc](#)).

Value

aucs array of aucs for each group in annotations

Examples

```
annotations <- c(rep(0,10))
annotations[c(1,3,5)] <- 1
optimallist <- 10:1
aurocs_mf <- auc_multifunc(annotations, optimallist)
```

auprc	<i>Area under the precision recall curve</i>
-------	--

Description

The function calculates the area under the precision-recall curve

Usage

```
auprc(scores, labels)
```

Arguments

scores	numeric array
labels	binary array

Value

auprc Numeric value

Examples

```
labels <- c(rep(0,10))
labels[c(1,3,5)] <- 1
scores <- 10:1
auprc <- auprc(scores, labels)
```

auroc_analytic *Area under the receiver operating characteristic curve*

Description

The function calculates the area under the receiver operating characteristic (ROC) curve analytically

Usage

```
auroc_analytic(scores, labels)
```

Arguments

scores numeric array
labels binary array

Value

auroc Numeric value

Examples

```
labels <- c(rep(0,10))  
labels[c(1,3,5)] <- 1  
scores <- 10:1  
auroc <- auroc_analytic(scores, labels)
```

biogrid *BIOGRID v3.4.126*

Description

A data frame containing protein-protein interactions

Format

A data frame with 211506 rows and 2 variables:

entrezID_A List of Entrez identifiers, interactor A

entrezID_B List of Entrez identifiers, interactor B

@source <http://thebiogrid.org/>

build_binary_network *Builds a binary network*

Description

The function creates a gene-by-gene matrix with binary entries indicating interaction (1) or no interaction (0) between the genes.

Usage

```
build_binary_network(data, list)
```

Arguments

data	2-column matrix, each row a pair indicating a relationship or interaction
list	string array of genes/labels/ids

Value

net matrix binary characterizing interactions

Examples

```
data <- cbind(edgeA=c('gene1', 'gene2'), edgeB=c('gene3', 'gene3'))
list <- c('gene1', 'gene2', 'gene3')
network <- build_binary_network(data, list)
```

build_coexp_expressionSet

Builds a coexpression network from an expressionSet

Description

The function generates a dense coexpression network from expression data stored in the expressionSet data type. Correlation coefficients are used as to weight the edges of the nodes (genes). Calls [build_coexp_network](#).

Usage

```
build_coexp_expressionSet(exprsSet, gene.list, method = "spearman",
  flag = "rank")
```

Arguments

exprsSet	data class ExpressionSet
gene.list	array of gene labels
method	correlation method to use, default Spearman's rho
flag	string to indicate if the network should be ranked

Value

net Matrix symmetric

Examples

```
exprs <- matrix( rnorm(1000), ncol=10,byrow=TRUE)
gene.list <- paste('gene',1:100, sep='')
sample.list <- paste('sample',1:10, sep='')
rownames(exprs) <- gene.list
colnames(exprs) <- sample.list
network <- build_coexp_expressionSet(exprs, gene.list, method='pearson')
```

build_coexp_GEOID	<i>Builds a coexpression network given a GEO ID</i>
-------------------	---

Description

The function generates a dense coexpression network from expression data stored in GEO. The expression data is downloaded from GEO. Correlation coefficients are used as to weight the edges of the nodes (genes). Calls [get_expression_matrix_from_GEO](#) and [build_coexp_network](#).

Usage

```
build_coexp_GEOID(gseid, gene.list, method = "spearman", flag = "rank")
```

Arguments

gseid	string GEO ID of expression experiment
gene.list	array of gene labels
method	correlation method to use, default Spearman's rho
flag	string to indicate if the network should be ranked

Value

net Matrix symmetric

build_coexp_network	<i>Builds a coexpression network from an expressionSet</i>
---------------------	--

Description

The function generates a dense coexpression network from expression data stored as a matrix, with the genes as row labels, and samples as column labels. Correlation coefficients are used as to weight the edges of the nodes (genes). Calls [cor](#).

Usage

```
build_coexp_network(exprs, gene.list, method = "spearman", flag = "rank")
```


Arguments

exprs	matrix of expression data
gene.list	array of gene labels
method	correlation method to use, default Spearman's rho
flag	string to indicate if the network should be ranked

Value

net Matrix symmetric

Examples

```
exprs <- matrix( rnorm(1000), ncol=10,byrow=TRUE)
gene.list <- paste('gene',1:100, sep='')
sample.list <- paste('sample',1:10, sep='')
rownames(exprs) <- gene.list
colnames(exprs) <- sample.list
network <- build_coexp_network(exprs, gene.list)
```

build_semantic_similarity_network

Builds a semantic similarity network

Description

The function builds a semantic similarity network given a data and labels

Usage

```
build_semantic_similarity_network(genes.labels, genes)
```

Arguments

genes.labels	matrix with rows as genes and columns as a function/label
genes	array of gene IDs

Value

net Numeric value

Examples

```
genes.labels <- matrix( sample(c(0,1), 100, replace=TRUE),ncol=10,nrow=10)
rownames(genes.labels) <- 1:10
genes <- 1:10
net <- build_semantic_similarity_network(genes.labels, genes)
```

```
build_weighted_network
```

Builds a weighted network

Description

The function creates a gene-by-gene matrix with binary entries indicating interaction (1) or no interaction (0) between the genes.

Usage

```
build_weighted_network(data, list)
```

Arguments

data	3-column matrix, each row a pair indicating a relationship or interaction, and the last column the weight
list	string array of genes/labels/ids

Value

net matrix characterizing interactions

Examples

```
data <- cbind(edgeA=c('gene1','gene2'),edgeB=c('gene3','gene3'), weight=c(0.5, 0.9))
list <- c('gene1','gene2','gene3')
network <- build_weighted_network(data,list)
```

```
calculate_multifunc
```

Performing multifunctionality analysis

Description

The function performs multifunctionality analysis ([1]) for a set of annotated genes and creates a rank based optimallist. For annotations use an ontology that is large enough to serve as a prior (e.g. GO, Phenocarta).

Usage

```
calculate_multifunc(genes.labels)
```

Arguments

genes.labels	Annotation matrix
--------------	-------------------

Value

gene.mfs Returns matrix with evaluation of gene function prediction by given labels:

Examples

```
genes.labels <- matrix( sample(c(0,1), 100, replace=TRUE),ncol=10,nrow=10)
rownames(genes.labels) = paste('gene', 1:10, sep='')
colnames(genes.labels) = paste('label', 1:10, sep='')
mf <- calculate_multifunc(genes.labels)
```

conv_smoother	<i>Plot smoothed curve</i>
---------------	----------------------------

Description

The function plots a smoothed curve using the `convolve` function.

Usage

```
conv_smoother(X, Y, window, xlab = "", ylab = "", raw = FALSE)
```

Arguments

X	numeric array
Y	numeric array
window	numeric value indicating size of window to use
xlab	string of x-axis label
ylab	string of y-axis label
raw	boolean

Value

smoothed X,Y and std Y matrix

Examples

```
x <- 1:1000
y <- rnorm(1000)
conv <- conv_smoother(x,y,10)
```

example_annotations	<i>Example of annotations</i>
---------------------	-------------------------------

Description

This dataset includes

example_binary_network

Example of binary network

Description

This dataset includes

Format

Matrices and vectors

example_coexpression *Example of binary network*

Description

This dataset includes

Format

Matrices and vectors

example_neighbor_voting

Example of binary network

Description

This dataset includes

Format

entrezID chromosomal start position, in base pairs

name HUGO gene identifier

species species

disease disease

extend_network	<i>Builds an extended network from a binary network</i>
----------------	---

Description

The function extends a binary network by using the inverse of the path length between nodes as a weighted edge

Usage

```
extend_network(net, max = 6)
```

Arguments

net	matrix binary and symmetric
max	numeric maximum number of jumps

Value

ext_net matrix dense and symmetric

Examples

```
net <- matrix( sample(c(0,1),36, replace=TRUE), nrow=6,byrow=TRUE)
ext_net <- extend_network(net)
```

filter_network	<i>Filter on matrix</i>
----------------	-------------------------

Description

The function filters out the rows or columns of a matrix such that the size of the group is exclusively between given min and max values

Usage

```
filter_network(network, flag = 1, min = 0, max = 1, ids = NA)
```

Arguments

network	numeric matrix
flag	numeric 1 for row filtering, 2 for column filtering
min	numeric value
max	numeric value
ids	array to filter on

Value

network numeric matrix

Examples

```
net <- matrix( rnorm(10000), nrow=100)
filt_net <- filter_network(net,1,10,100)
```

filter_network_cols *Filter on columns*

Description

The function filters out the columns of a matrix such that the size of the group is exclusively between given min and max values

Usage

```
filter_network_cols(network, min = 0, max = 1, ids = NA)
```

Arguments

network	numeric matrix
min	numeric value
max	numeric value
ids	array

Value

network numeric matrix

Examples

```
genes.labels <- matrix( sample( c(0,1), 10000, replace=TRUE), nrow=100)
rownames(genes.labels) = paste('gene', 1:100, sep='')
colnames(genes.labels) = paste('function', 1:100, sep='')
genes.labels <- filter_network_cols(genes.labels,50,200)
```

```
genes.labels <- matrix( sample( c(0,1), 10000, replace=TRUE), nrow=100)
rownames(genes.labels) = paste('gene', 1:100, sep='')
colnames(genes.labels) = paste('function', 1:100, sep='')
genes.labels <- filter_network_cols(genes.labels,ids = paste('function', 1:20, sep=''))
```

filter_network_rows *Filter on rows*

Description

The function filters out the rows of a matrix such that the size of the group is exclusively between given min and max values

Usage

```
filter_network_rows(network, min = 0, max = 1, ids = NA)
```

Arguments

network	numeric matrix
min	numeric value
max	numeric value
ids	array to filter on

Value

network numeric matrix

Examples

```
genes.labels <- matrix( sample( c(0,1), 10000, replace=TRUE), nrow=100)
rownames(genes.labels) = paste('gene', 1:100, sep='')
colnames(genes.labels) = paste('function', 1:100, sep='')
genes.labels <- filter_network_rows(genes.labels,50,200)

genes.labels <- matrix( sample( c(0,1), 10000, replace=TRUE), nrow=100)
rownames(genes.labels) = paste('gene', 1:100, sep='')
colnames(genes.labels) = paste('function', 1:100, sep='')
genes.labels <- filter_network_rows(genes.labels,ids = paste('gene', 1:20, sep=''))
```

filter_orthologs *Filter on orthologs*

Description

The function filters away the labels for the genes that are not in the orthologs list

Usage

```
filter_orthologs(annotations, genelist, orthologs)
```

Arguments

annotations	binary matrix
genelist	array of gene ids
orthologs	array to filter on

Value

annotations_filtered binary matrix

Examples

```
genes.labels <- matrix( sample( c(0,1), 1000, replace=TRUE), nrow=100)
rownames(genes.labels) = paste('gene', 1:100, sep='')
colnames(genes.labels) = paste('function', 1:10, sep='')
gene.list <- paste('gene', 1:100, sep='')
orthologs <- paste('gene', (1:50)*2, sep='')
genes.labels.filt <- filter_orthologs(genes.labels, gene.list, orthologs)
```

fmeasure

Fmeasure of precision-recall

Description

The function calculates fmeasure for a given beta of a precision-recall curve

Usage

```
fmeasure(recall, precis, beta = 1)
```

Arguments

recall	numeric array
precis	numeric array
beta	numeric value, default is 1

Value

fmeasure Numeric value

Examples

```
labels <- c(rep(0,10))
labels[c(1,3,5)] <- 1
scores <- 10:1
prc <- get_prc(scores, labels)
fm <- fmeasure(prc[,1], prc[,2])
```

genes	<i>Genes from BIOGRID v3.4.126</i>
-------	------------------------------------

Description

An array containing identifiers for genes in biogrid

Format

Array

genes List of Entrez identifiers

@source <http://thebiogrid.org/>

get_auc	<i>Calculates the area under a curve</i>
---------	--

Description

The function calculates the area under the curve defined by x and y

Usage

```
get_auc(x, y)
```

Arguments

x numeric array

y numeric array

Value

auc numeric value

Examples

```
x <- 1:100
y <- 1:100
auc <- get_auc(x,y)
```

`get_biogrid`*Downloading and filtering BIOGRID*

Description

The function downloads the specified version of biogrid for a particular taxon

Usage

```
get_biogrid(species = "9606", version = "3.4.131",
            interactions = "physical")
```

Arguments

<code>species</code>	numeric taxon of species
<code>version</code>	string of biogrid version
<code>interactions</code>	string stating either physical or genetic interactions

Value

biogrid data.frame with interactions

`get_counts`*Get counts*

Description

The function formats the count distribution from the histogram function

Usage

```
get_counts(hist)
```

Arguments

<code>hist</code>	histogram
-------------------	-----------

Value

`x,y`

Examples

```
x <- runif(1000)
counts <- get_counts( hist(x, plot=FALSE))
```

get_density	<i>Get density</i>
-------------	--------------------

Description

The function formats the density distribution from the histogram function

Usage

```
get_density(hist)
```

Arguments

hist	histogram
------	-----------

Value

array

Examples

```
x <- runif(1000)
density <- get_density( hist(x, plot=FALSE))
```

get_expression_data_gemma	<i>Obtain expression matrix from the GEMMA database</i>
---------------------------	---

Description

The function downloads and parses the expression matrix from the GEMMA database, specified by the GEO ID

Usage

```
get_expression_data_gemma(gseid, filtered = "true")
```

Arguments

gseid	GEO ID of the expression experiment
filtered	flag to indicate whether or not the data is QC

Value

list of genes and the expression matrix

get_expression_matrix_from_GEO

Obtain expression matrix from GEO database

Description

The function downloads and parses the expression matrix from the GEO file specified by the GEO ID

Usage

```
get_expression_matrix_from_GEO(gseid)
```

Arguments

gseid GEO ID of the expression experiment

Value

list of genes and the expression matrix

get_phenocarta

Downloading and filtering Phenocarta

Description

The function downloads the latest version of phenocarta

Usage

```
get_phenocarta(species = "human", type = "all")
```

Arguments

species string

type string

Value

data data.frame with phenocarta data

get_prc	<i>Build precision-recall curve</i>
---------	-------------------------------------

Description

The function calculates the recall and precision

Usage

```
get_prc(scores, labels)
```

Arguments

scores	numeric array
labels	binary array

Value

recall,precision numeric arrays

Examples

```
labels <- c(rep(0,10))
labels[c(1,3,5)] <- 1
scores <- 10:1
prc <- get_prc(scores, labels)
```

get_roc	<i>Build receiver operating characteristic curve</i>
---------	--

Description

The function calculates the FPR and TRPR for the receiver operating characteristic (ROC)

Usage

```
get_roc(scores, labels)
```

Arguments

scores	numeric array
labels	binary array

Value

FPR,TPR numeric arrays

Examples

```
labels <- c(rep(0,10))
labels[c(1,3,5)] <- 1
scores <- 10:1
roc <- get_roc(scores, labels)
```

GO.human

GO - human

Description

A dataset of the gene GO associations

Format

A data frame with 2511938 rows and 4 variables:

name gene symbol

entrezID entrez identifier

GO gene ontology term ID

evidence evidence code

@source <http://geneontology.org/>

GO.mouse

GO - mouse

Description

A dataset of the gene GO associations

Format

A data frame with 2086086 rows and 4 variables:

name gene symbol

entrezID entrez identifier

GO gene ontology term ID

evidence evidence code

@source <http://geneontology.org/>

GO.voc	<i>Gene ontology vocabulary</i>
--------	---------------------------------

Description

A dataset of the gene ontology vocabulary

Format

A data frame with 42266 rows and 3 variables:

GOID GO identifier

term GO description

domain GO domain

@source <http://geneontology.org/>

make_annotatations	<i>Creating gene annotations</i>
--------------------	----------------------------------

Description

The function annotates a list of genes according to a given ontology. It creates a binary matrix associating genes (rows) with labels (columns).

Usage

```
make_annotatations(data, listA, listB)
```

Arguments

data	2-column matrix, each row a pair indicating a relationship or interaction
listA	string array of genes
listB	string array of labels/functions

Value

net matrix binary

Examples

```
gene.list <- paste('gene', 1:100, sep='')
labels.list <- paste('labels', 1:10, sep='')
data <- matrix(0,nrow=100, ncol=2)
data[,1] <- sample(gene.list, 100, replace=TRUE)
data[,2] <- sample(labels.list, 100, replace=TRUE)
net <- make_annotatations(data, gene.list, labels.list)
```

make_genelist *Creating list of all genes in the data set.*

Description

The function extracts the list of all genes in the data set

Usage

```
make_genelist(gene_data_interacting)
```

Arguments

gene_data_interacting
2-column matrix, each row a pair indicating a relationship or interaction

Value

list array of data labels

Examples

```
gene.list <- paste('gene', 1:100, sep='')  
data <- matrix(0,nrow=100, ncol=2)  
data[,1] <- sample(gene.list, 50, replace=TRUE)  
data[,2] <- sample(gene.list, 50, replace=TRUE)  
genes <- make_genelist(data)
```

make_gene_network *Creating gene-by-gene network*

Description

The function creates a gene-by-gene matrix with binary entries indicating interaction (1) or no interaction (0) between the genes.

Usage

```
make_gene_network(data, list)
```

Arguments

data 2-column matrix, each row a pair indicating a relationship or interaction
list string array of genes

Value

net matrix binary characterizing interactions

Examples

```
gene.list <- paste('gene', 1:100, sep='')
data <- matrix(0,nrow=100, ncol=2)
data[,1] <- sample(gene.list, 100)
data[,2] <- sample(gene.list, 100)
net <- make_gene_network(data, gene.list)
```

make_transparent	<i>Make a color transparent (Taken from an answer on StackOverflow by Nick Sabbe)</i>
------------------	---

Description

Make a color transparent (Taken from an answer on StackOverflow by Nick Sabbe)

Usage

```
make_transparent(someColor, alpha = 100)
```

Arguments

someColor	color number, string or hexadecimal code
alpha	numeric transparency

Value

someColor rgb

neighbor_voting	<i>Evaluating Gene Function Prediction</i>
-----------------	--

Description

The function performs gene function prediction based on 'guilt by association' using cross validation ([1]). Performance and significance are evaluated by calculating the AUROC or AUPRC of each functional group.

Usage

```
neighbor_voting(genes.labels, network, nFold = 3, output = "AUROC",
  FLAG_DRAW = FALSE)
```

Arguments

genes.labels	numeric array
network	numeric array symmetric, gene-by-gene matrix
nFold	numeric value, default is 3
output	string, default is AUROC
FLAG_DRAW	binary flag to draw roc plot

Value

scores numeric matrix

Examples

```
genes.labels <- matrix( sample( c(0,1), 1000, replace=TRUE), nrow=100)
rownames(genes.labels) = paste('gene', 1:100, sep='')
colnames(genes.labels) = paste('function', 1:10, sep='')
net <- cor( matrix( rnorm(10000), ncol=100), method='spearman')
rownames(net) <- paste('gene', 1:100, sep='')
colnames(net) <- paste('gene', 1:100, sep='')

aurocs <- neighbor_voting(genes.labels, net, output = 'AUROC')

auprcs <- neighbor_voting(genes.labels, net, output = 'PR')
```

node_degree

Calculate node degree

Description

The function calculates the node degree of a network

Usage

```
node_degree(net)
```

Arguments

net numeric matrix

Value

node_degree numeric array

Examples

```
net <- cor( matrix(rnorm(1000), ncol=10))
n <- 10
net <- matrix(rank(net, na.last = 'keep', ties.method = 'average'), nrow = n, ncol = n)
net <- net/max(net, na.rm=TRUE)
nd <- node_degree(net)
```

ortho	<i>Gene orthologs</i>
-------	-----------------------

Description

A list containing identifiers for the subsets of gene orthologs

Format

List orthologs for 5 species

dros List of Entrez identifiers, Drosophila

celeg List of Entrez identifiers, C. elegans

yeast List of Entrez identifiers, Yeast

mouse List of Entrez identifiers, Mouse

zf List of Entrez identifiers, Zebrafish

@source <http://useast.ensembl.org/index.html/>

pheno	<i>Phenocarta</i>
-------	-------------------

Description

A dataset of gene disease associations

Format

A data frame with 142272 rows and 4 variables:

entrezID chromosomal start position, in base pairs

name HUGO gene identifier

species species

disease disease

@source <http://www.chibi.ubc.ca/Gemma/phenotypes.html>

plot_densities *Plot densities*

Description

The function plots multiple density curves and compares their modes

Usage

```
plot_densities(hists, id, col = c("lightgrey"), xlab = "",
  ylab = "Density", mode = "hist")
```

Arguments

hists	list of histogram objects or density objects
id	string
col	color for shading
xlab	string x-axis label
ylab	string y-axis label
mode	flag indicating histogram or density

Value

null

Examples

```
aurocsA <- density((runif(1000)+runif(1000)+runif(1000)+runif(1000))/4)
aurocsB <- density((runif(1000)+runif(1000)+runif(1000))/3)
aurocsC <- density(runif(1000))
hists <- list(aurocsA, aurocsB, aurocsC)
temp <- plot_densities(hists, '', mode='density')
```

plot_density_compare *Plot density comparisons*

Description

The function plots two density curves and compares their modes

Usage

```
plot_density_compare(aucA, aucB, col = "lightgrey",
  xlab = "AUROC (neighbor voting)", ylab = "Density", mode = TRUE)
```

Arguments

aucA	numeric array of aurops
aucB	numeric array of aurops
col	color of lines
xlab	string label
ylab	string label
mode	boolean to plot mode or mean

Value

null

Examples

```

auropsA <- (runif(1000)+runif(1000)+runif(1000)+runif(1000))/4
auropsB <- runif(1000)
plot_density_compare(auropsA, auropsB)

```

plot_distribution *Plot distribution histogram*

Description

The function plots a the distribution of AUROCs

Usage

```

plot_distribution(auc, b = 20, col = "lightgrey", xlab = "",
  ylab = "Density", xlim = c(0.4, 1), ylim = c(0, 5), med = TRUE,
  avg = TRUE, density = TRUE, bars = FALSE)

```

Arguments

auc	numeric aucs
b	array of breaks
col	color of line
xlab	string label
ylab	string label
xlim	range of values for xaxis
ylim	range of values for yaxis
med	boolean to plot median auc
avg	boolean to plot average auc
density	boolean
bars	boolean for barplot

Value

auc list and quartiles

Examples

```
aurops <- (runif(1000)+runif(1000)+runif(1000)+runif(1000))/4  
d <- plot_distribution(aurops)
```

plot_network_heatmap *Plot network heatmap*

Description

The function draws a heatmap to visualize a network

Usage

```
plot_network_heatmap(net, colrs)
```

Arguments

net	a numeric matrix of edge weights
colrs	a range of colors to plot the network

Value

null

Examples

```
network <- cor(matrix( rnorm(10000), nrow=100))  
plot_network_heatmap(network)
```

plot_prc *Plot precision recall curve*

Description

The function calculates the precision and recall and plots the curve

Usage

```
plot_prc(scores, labels)
```

Arguments

scores	numeric array
labels	binary array

Value

prc numeric arrays

Examples

```
labels <- c(rep(0,10))
labels[c(1,3,5)] <- 1
scores <- 10:1
roc <- plot_prc(scores, labels)
```

plot_roc

Plot receiver operating characteristic curve

Description

The function calculates the FPR and TRPR for the receiver operating characteristic (ROC) and plots the curve

Usage

```
plot_roc(scores, labels)
```

Arguments

scores	numeric array
labels	binary array

Value

FPR,TPR numeric arrays

Examples

```
labels <- c(rep(0,10))
labels[c(1,3,5)] <- 1
scores <- 10:1
roc <- plot_roc(scores, labels)
```

plot_roc_overlay *Plot ROC overlay*

Description

The function plots a density overlay of ROCs given the scores and labels

Usage

```
plot_roc_overlay(scores.mat, labels.mat, nbins = 100)
```

Arguments

scores.mat	numeric array
labels.mat	numeric array
nbins	numeric value

Value

list of Z(matrix) and roc_sum (average ROC curve)

Examples

```
genes.labels <- matrix( c(rep(1, 1000), rep(0,9000)), nrow=1000, byrow=TRUE)
rownames(genes.labels) = paste('gene', 1:1000, sep='')
colnames(genes.labels) = paste('function', 1:10, sep='')

scores <- matrix( rnorm(10000), nrow=1000)
scores <- apply(scores, 2, rank)
rownames(scores) = paste('gene', 1:1000, sep='')
colnames(scores) = paste('function', 1:10, sep='')

z <- plot_roc_overlay(scores, genes.labels)
```

plot_value_compare *Plot value comparisons*

Description

The function plots a scatter

Usage

```
plot_value_compare(aucA, aucB, xlab = "AUROC", ylab = "AUROC", xlim = c(0,
1), ylim = c(0, 1))
```


Arguments

aucA	numeric array of aucs
aucB	numeric array of aucs
xlab	string label
ylab	string label
xlim	range of values for xaxis
ylim	range of values for yaxis

Value

null

predictions *Performing Gene Function Prediction*

Description

The function performs gene function prediction on the whole data set using the 'guilt by association' principle ([1]).

Usage

```
predictions(genes.labels, network)
```

Arguments

genes.labels	numeric array
network	numeric array symmetric, gene-by-gene matrix

Value

scores numeric matrix

Examples

```
genes.labels <- matrix( sample( c(0,1), 1000, replace=TRUE), nrow=100)
rownames(genes.labels) = paste('gene', 1:100, sep='')
colnames(genes.labels) = paste('function', 1:10, sep='')
net <- cor( matrix( rnorm(10000), ncol=100), method='spearman')
rownames(net) <- paste('gene', 1:100, sep='')
colnames(net) <- paste('gene', 1:100, sep='')

preds <- predictions(genes.labels, net)
```

repmat	<i>Rep function for matrices</i>
--------	----------------------------------

Description

The function generates a matrix by binding the columns and rows

Usage

```
repmat(X, m, n)
```

Arguments

X	numeric matrix
m	numeric value, repeat rows m times
n	numeric value, repeat columns n times

Value

list of genes and the expression matrix

Examples

```
genes.labels <- matrix( sample( c(0,1), 1000, replace=TRUE), nrow=100)
expand <- repmat( genes.labels, 1,2)
```

run_GBA	<i>Performing 'Guilt by Association' Analysis</i>
---------	---

Description

The function runs and evaluates gene function prediction based on the 'guilt by association'-principle using neighbor voting ([neighbor_voting](#)) [1]. As a measure of performance and significance of results, AUCs of all evaluated functional groups are calculated.

Usage

```
run_GBA(network, labels, min = 20, max = 1000, nfold = 3)
```

Arguments

network	numeric array symmetric, gene-by-gene matrix
labels	numeric array
min	numeric value to limit gene function size
max	numeric value to limit gene function size
nfold	numeric value, default is 3

Value

list roc.sub, genes, auroc

Examples

```
genes.labels <- matrix( sample( c(0,1), 1000, replace=TRUE), nrow=100)
rownames(genes.labels) = paste('gene', 1:100, sep='')
colnames(genes.labels) = paste('function', 1:10, sep='')
net <- cor( matrix( rnorm(10000), ncol=100), method='spearman')
rownames(net) <- paste('gene', 1:100, sep='')
colnames(net) <- paste('gene', 1:100, sep='')

gba <- run_GBA(net, genes.labels, min=10)
```

Index

- *Topic **AUC**
 - auc_multifunc, 4
- *Topic **AUROC**
 - plot_distribution, 29
- *Topic **ExpressionSet**
 - build_coexp_expressionSet, 7
 - build_coexp_network, 8
- *Topic **FPR**
 - get_roc, 21
 - plot_roc, 31
- *Topic **GEMMA**
 - get_expression_data_gemma, 19
- *Topic **GEO**
 - build_coexp_GEOID, 8
 - get_expression_data_gemma, 19
 - get_expression_matrix_from_GEO, 20
- *Topic **GSE**
 - build_coexp_GEOID, 8
 - get_expression_data_gemma, 19
 - get_expression_matrix_from_GEO, 20
- *Topic **PRC**
 - plot_prc, 30
- *Topic **ROC**
 - auroc_analytic, 6
 - get_roc, 21
 - plot_distribution, 29
 - plot_roc, 31
 - plot_roc_overlay, 32
- *Topic **TPR**
 - get_roc, 21
 - plot_roc, 31
- *Topic **analytic**
 - auroc_analytic, 6
- *Topic **annotations**
 - filter_orthologs, 15
 - make_annotations, 23
- *Topic **area**
 - auprc, 5
 - auroc_analytic, 6
 - get_auc, 17
- *Topic **association**
 - neighbor_voting, 25
 - predictions, 33
 - run_GBA, 34
- *Topic **assortativity**
 - assortativity, 3
- *Topic **a**
 - get_auc, 17
- *Topic **biogrid**
 - get_biogrid, 18
- *Topic **by**
 - neighbor_voting, 25
 - predictions, 33
 - run_GBA, 34
- *Topic **characteristic**
 - auroc_analytic, 6
 - get_roc, 21
 - plot_roc, 31
- *Topic **coexpression**
 - build_coexp_expressionSet, 7
 - build_coexp_GEOID, 8
 - build_coexp_network, 8
- *Topic **cross**
 - neighbor_voting, 25
 - run_GBA, 34
- *Topic **curve**
 - get_auc, 17
- *Topic **degree**
 - node_degree, 26
- *Topic **dense**
 - build_coexp_expressionSet, 7
 - build_coexp_GEOID, 8
 - build_coexp_network, 8
- *Topic **density**
 - plot_densities, 28
- *Topic **distribution**
 - plot_distribution, 29
- *Topic **download**
 - get_biogrid, 18
 - get_phenocarta, 20
- *Topic **evaluation**
 - calculate_multifunc, 10
 - neighbor_voting, 25
 - run_GBA, 34
- *Topic **evaluation**
 - auc_multifunc, 4

- *Topic **experiment**
 - get_expression_data_gemma, 19
 - get_expression_matrix_from_GEO, 20
- *Topic **expressionSet**
 - build_coexp_expressionSet, 7
 - build_coexp_network, 8
- *Topic **expression**
 - get_expression_data_gemma, 19
 - get_expression_matrix_from_GEO, 20
- *Topic **extended**
 - extend_network, 13
- *Topic **extract**
 - make_genelist, 24
- *Topic **filter**
 - filter_network, 13
 - filter_network_cols, 14
 - filter_network_rows, 15
 - filter_orthologs, 15
- *Topic **fmeasure**
 - fmeasure, 16
- *Topic **function**
 - calculate_multifunc, 10
 - make_annotations, 23
 - neighbor_voting, 25
 - predictions, 33
 - run_GBA, 34
- *Topic **gene-by-gene**
 - build_binary_network, 7
 - build_weighted_network, 10
 - make_gene_network, 24
- *Topic **gene**
 - calculate_multifunc, 10
 - make_annotations, 23
 - make_genelist, 24
 - neighbor_voting, 25
 - predictions, 33
 - run_GBA, 34
- *Topic **guilt**
 - neighbor_voting, 25
 - predictions, 33
 - run_GBA, 34
- *Topic **heatmap**
 - plot_network_heatmap, 30
- *Topic **histogram**
 - get_counts, 18
 - get_density, 19
- *Topic **igraph**
 - extend_network, 13
- *Topic **image**
 - plot_network_heatmap, 30
- *Topic **interaction**
 - build_binary_network, 7
 - build_weighted_network, 10
 - make_gene_network, 24
- *Topic **jaccard**
 - build_semantic_similarity_network, 9
- *Topic **labels**
 - make_annotations, 23
- *Topic **length**
 - extend_network, 13
- *Topic **list**
 - make_genelist, 24
- *Topic **matrix**
 - repmat, 34
- *Topic **mean**
 - get_auc, 17
- *Topic **metric**
 - auprc, 5
 - auroc_analytic, 6
 - get_roc, 21
 - node_degree, 26
 - plot_prc, 30
 - plot_roc, 31
- *Topic **multifunctionality**
 - auc_multifunc, 4
- *Topic **neighbor**
 - neighbor_voting, 25
 - predictions, 33
 - run_GBA, 34
- *Topic **network**
 - assortativity, 3
 - build_binary_network, 7
 - build_coexp_expressionSet, 7
 - build_coexp_GEOID, 8
 - build_coexp_network, 8
 - build_semantic_similarity_network, 9
 - build_weighted_network, 10
 - extend_network, 13
 - filter_network, 13
 - filter_network_cols, 14
 - filter_network_rows, 15
 - make_gene_network, 24
 - node_degree, 26
 - plot_network_heatmap, 30
- *Topic **node**
 - node_degree, 26
- *Topic **ontology**
 - calculate_multifunc, 10
 - make_annotations, 23
- *Topic **operating**
 - auroc_analytic, 6
 - get_roc, 21

- plot_roc, 31
- *Topic **orthologs**
 - filter_orthologs, 15
- *Topic **overlay**
 - plot_roc_overlay, 32
- *Topic **path**
 - extend_network, 13
- *Topic **phenocarta**
 - get_phenocarta, 20
- *Topic **plot**
 - conv_smoother, 11
 - get_density, 19
 - plot_densities, 28
 - plot_density_compare, 28
 - plot_distribution, 29
 - plot_network_heatmap, 30
 - plot_prc, 30
 - plot_roc_overlay, 32
 - plot_value_compare, 32
- *Topic **precision-recall**
 - auprc, 5
 - fmeasure, 16
- *Topic **precision**
 - get_prc, 21
 - plot_prc, 30
- *Topic **precsion-recall**
 - get_prc, 21
- *Topic **prediction**
 - calculate_multifunc, 10
 - neighbor_voting, 25
 - predictions, 33
 - run_GBA, 34
- *Topic **properties**
 - assortativity, 3
- *Topic **recall**
 - get_prc, 21
 - plot_prc, 30
- *Topic **receiver**
 - auroc_analytic, 6
 - get_roc, 21
 - plot_roc, 31
- *Topic **repeat**
 - repmat, 34
- *Topic **repmat**
 - repmat, 34
- *Topic **rolling**
 - get_auc, 17
- *Topic **rows**
 - filter_network, 13
 - filter_network_cols, 14
 - filter_network_rows, 15
- *Topic **semantic**
 - build_semantic_similarity_network, 9
- *Topic **shortest**
 - extend_network, 13
- *Topic **similarity**
 - build_semantic_similarity_network, 9
- *Topic **smooth**
 - conv_smoother, 11
- *Topic **topology**
 - assortativity, 3
 - node_degree, 26
- *Topic **to**
 - make_annotations, 23
- *Topic **under**
 - get_auc, 17
- *Topic **validation**
 - neighbor_voting, 25
 - run_GBA, 34
- *Topic **voting**
 - neighbor_voting, 25
 - predictions, 33
 - run_GBA, 34
- assortativity, 3
- attr.human, 3
- attr.mouse, 4
- auc_multifunc, 4
- auprc, 5
- auroc_analytic, 6
- biogrid, 6
- build_binary_network, 7
- build_coexp_expressionSet, 7
- build_coexp_GEOID, 8
- build_coexp_network, 7, 8, 8
- build_semantic_similarity_network, 9
- build_weighted_network, 10
- calculate_multifunc, 4, 10
- conv_smoother, 11
- convolve, 11
- cor, 8
- example_annotations, 11
- example_binary_network, 12
- example_coexpression, 12
- example_neighbor_voting, 12
- extend_network, 13
- filter_network, 13
- filter_network_cols, 14
- filter_network_rows, 15

filter_orthologs, 15
fmeasure, 16

genes, 17
get_auc, 17
get_biogrid, 18
get_counts, 18
get_density, 19
get_expression_data_gemma, 19
get_expression_matrix_from_GEO, 8, 20
get_phenocarta, 20
get_prc, 21
get_roc, 21
GO.human, 22
GO.mouse, 22
GO.voc, 23

make_annotations, 23
make_gene_network, 24
make_genelist, 24
make_transparent, 25

neighbor_voting, 25, 34
node_degree, 26

ortho, 27

pheno, 27
plot_densities, 28
plot_density_compare, 28
plot_distribution, 29
plot_network_heatmap, 30
plot_prc, 30
plot_roc, 31
plot_roc_overlay, 32
plot_value_compare, 32
predictions, 33

repmat, 34
run_GBA, 34