

Package ‘MotIV’

April 15, 2020

Type Package

Title Motif Identification and Validation

Version 1.42.0

Date 2014-04-09

Author Eloi Mercier, Raphael Gottardo

Maintainer Eloi Mercier <emercier@bcgsc.ca>, Raphael Gottardo
<rgottard@fhcrc.org>

Depends R (>= 2.10), graphics, BiocGenerics, GenomicRanges

Imports methods, stats, grid, S4Vectors, IRanges (>= 1.13.5),
Biostrings, lattice, rGADEM, utils

Suggests rtracklayer

SystemRequirements GNU Scientific Library >= 1.6
(<http://www.gnu.org/software/gsl/>)

Description This package makes use of STAMP for comparing a set of motifs to a given database (e.g. JASPAR). It can also be used to visualize motifs, motif distributions, modules and filter motifs.

License GPL-2

biocViews Microarray, ChIPchip, ChIPSeq, GenomicSequence,
MotifAnnotation

git_url <https://git.bioconductor.org/packages/MotIV>

git_branch RELEASE_3_10

git_last_commit 8c9b4d3

git_last_commit_date 2019-10-29

Date/Publication 2020-04-14

R topics documented:

alignments-class	2
as.data.frame	3
combineMotifs	4
exportAsGRanges	5
exportAsRangedData	6
exportAsTransfacFile	7

filter	8
filter-class	10
filters-methods	10
FOXA1_rGADEM	11
generateDBScores	12
getGademPWM	13
getPWM	14
jaspar2010	14
makePWM	15
matches-class	16
motifDistances	17
motifMatch	18
motiv-class	19
motiv-methods	20
occurrences	21
plot-methods	21
readGademPWMFile	23
readPWMfile	24
seqLogo2	25
setFilter	26
split-methods	27
transcriptionFactor-class	28
trimPWMedge	29
viewAlignments	29
viewMotifs-methods	30

Index 32

alignments-class	<i>Class "alignments"</i>
------------------	---------------------------

Description

This object contains the alignments found by a MotIV analysis.

Objects from the Class

Objects can be created by calls of the form `new("alignments", TF, evalue, sequence, match, strand)`.

Slots

TF Object of class "TF"
evalue The e-value of the alignment.
sequence The input sequence aligned.
match The TF sequence wick as been matched.
strand The strand of the alignment.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

motiv, matches, transcriptionFactor

as.data.frame *Coerce to a Data Frame*

Description

This function coerces a MotIV object into a data frame.

Usage

```
## S4 method for signature 'motiv'  
as.data.frame(x)
```

Arguments

x An object of class motiv.

Details

'as.data.frame' returns a data frame.

This object regroups all the TF identified by MotIV with the corresponding evaluate and alignments.

Value

A data.frame object.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

data.frame, viewAlignments

Examples

```
#####Database and Scores#####  
path <- system.file(package="MotIV")  
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))  
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))  
  
#####Input#####  
data(FOXA1_rGADEM)  
motifs <- getPWM(gadem)  
motifs.trimed <- lapply(motifs, trimPWMedge, threshold=1)  
  
#####Analysis#####  
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs, align="SWU", cc="PCC", database=jaspar, DBscores=jaspar.scores)  
foxa1.analysis.jaspar.df = as.data.frame(foxa1.analysis.jaspar)  
head(foxa1.analysis.jaspar.df)
```

`combineMotifs`*Combine Motifs*

Description

This function combines motifs according to a set of filters.

Usage

```
## S4 method for signature 'motif, filters'  
combineMotifs(x, y, name=NULL, exact=TRUE, verbose=TRUE)
```

Arguments

<code>x</code>	An object of class <code>motif</code> .
<code>y</code>	A filter or a set of filter.
<code>name</code>	Name(s) to be given for similar motifs.
<code>verbose</code>	If <code>FALSE</code> , no output will be print.
<code>exact</code>	If <code>TRUE</code> , search only for perfect name match.

Details

This function is used to consider some motifs as a unique motif or similar motifs.

Many filters could be pass in argument separated by coma. They will be considered independently (coma is considered as OR).

If a name or a vector of name is provided, it will be used to assign new name for similar motif to the corresponding filter. Else, a generic name is used.

Value

A `motif` object.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

`setFilter`, `filter`, `split`

Examples

```
#####Database and Scores#####  
path <- system.file(package="MotIV")  
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))  
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))  
  
#####Input#####  
data(FOXA1_rGADEM)  
motifs <- getPWM(gadem)  
motifs.trimed <- lapply(motifs, trimPWMedge, threshold=1)
```

```
#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs,align="SWU",cc="PCC",database=jaspar,DBscores=jaspar.summary(foxa1.analysis.jaspar ))

#####Filters#####
f.foxa1<-setFilter(name="", tfname="FOXA1", top=3, evaluateMax=10^-5)
f.ap1 <- setFilter (tfname="AP1", top=3)
f.foxa1.ap1 <- f.foxa1 | f.ap1
foxa1.filter <- filter(foxa1.analysis.jaspar, f.foxa1.ap1, exact=FALSE, verbose=TRUE)
foxa1.filter.combine <- combineMotifs(foxa1.filter, c(f.foxa1, f.ap1), exact=FALSE, name=c("FOXA1", "AP1"), v
```

 exportAsGRanges

Export MotIV Results

Description

Export your

Usage

```
exportAsGRanges(x, y, correction=TRUE)
```

Arguments

x	An object of class <code>motiv</code> .
y	The <code>rGADEM</code> type object associated with the <code>motiv</code> object.
correction	If <code>TRUE</code> , corrects the position according to the alignment.

Details

Use this function to export the results into a `GRanges` object.

Value

An object of type `GRanges`.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path,"/extdata/jaspar2010.txt",sep=""))
jaspar.scores <- readDBScores(paste(path,"/extdata/jaspar2010_PCC_SWU.scores",sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs,trimPWMedge, threshold=1)
```

```
#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs,align="SWU",cc="PCC",database=jaspar,DBscores=jaspar.summary(foxa1.analysis.jaspar ))

#####Filters#####
f.foxa1<-setFilter(name="", tfname="FOXA1", top=3, evaluateMax=10^-5)
f.ap1 <- setFilter (tfname="AP1", top=3)
f.foxa1.ap1 <- f.foxa1 | f.ap1
foxa1.filter <- filter(foxa1.analysis.jaspar, f.foxa1.ap1, exact=FALSE, verbose=TRUE)
foxa1.split <- split(foxa1.analysis.jaspar, c(f.foxa1, f.ap1) , drop=FALSE, exact=FALSE, verbose=TRUE)
foxa1.filter.combine <- combineMotifs(foxa1.filter, c(f.foxa1, f.ap1), exact=FALSE, name=c("FOXA1", "AP1"), v

#####Plots#####
#plot(foxa1.filter.combine, ncol=2,top=5, rev=FALSE, main="FOXA1", bysim=TRUE)
#plot(foxa1.filter.combine ,gadem,ncol=2, type="distribution", correction=TRUE, group=FALSE, bysim=TRUE, str
#plot(foxa1.filter.combine ,gadem,type="distance", correction=TRUE, group=TRUE, bysim=TRUE, main="FOXA1", str

#####GRanges#####
foxa1.gr <- exportAsGRanges(foxa1.filter.combine["FOXA1"], gadem)
ap1.gr <- exportAsGRanges(foxa1.filter.combine["AP1"], gadem)
```

exportAsRangedData *Export MotIV Results*

Description

IMPORTANT NOTE: The `exportAsRangedData()` function is deprecated in favor of `exportAsGRanges()`.
Export your

Usage

```
exportAsRangedData(x, y, correction=TRUE)
```

Arguments

<code>x</code>	An object of class <code>motiv</code> .
<code>y</code>	The <code>rGADEM</code> type object associated with the <code>motiv</code> object.
<code>correction</code>	If <code>TRUE</code> , corrects the position according to the alignment.

Details

Use this function to export the results into a `RangedData` object.

Value

An object of type `RangedData`.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs, trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs, align="SWU", cc="PCC", database=jaspar, DBscores=jaspar.scores)
summary(foxa1.analysis.jaspar)

#####Filters#####
f.foxa1 <- setFilter(name="", tfname="FOXA1", top=3, evaluateMax=10^-5)
f.ap1 <- setFilter(tfname="AP1", top=3)
f.foxa1.ap1 <- f.foxa1 | f.ap1
foxa1.filter <- filter(foxa1.analysis.jaspar, f.foxa1.ap1, exact=FALSE, verbose=TRUE)
foxa1.split <- split(foxa1.analysis.jaspar, c(f.foxa1, f.ap1), drop=FALSE, exact=FALSE, verbose=TRUE)
foxa1.filter.combine <- combineMotifs(foxa1.filter, c(f.foxa1, f.ap1), exact=FALSE, name=c("FOXA1", "AP1"), verbose=TRUE)

#####Plots#####
#plot(foxa1.filter.combine, ncol=2, top=5, rev=FALSE, main="FOXA1", bysim=TRUE)
#plot(foxa1.filter.combine, gadem, ncol=2, type="distribution", correction=TRUE, group=FALSE, bysim=TRUE, str=TRUE)
#plot(foxa1.filter.combine, gadem, type="distance", correction=TRUE, group=TRUE, bysim=TRUE, main="FOXA1", str=TRUE)

#####RangedData#####
## Not run:
foxa1.rd <- exportAsRangedData(foxa1.filter.combine["FOXA1"], gadem)
ap1.rd <- exportAsRangedData(foxa1.filter.combine["AP1"], gadem)

## End(Not run)
```

exportAsTransfacFile *Write Transfac Files*

Description

Export an object of class `motiv` as a Transfac file type.

Usage

```
## S4 method for signature 'motiv'
exportAsTransfacFile(x, file)
## S4 method for signature 'list'
exportAsTransfacFile(x, file)
```

Arguments

`x` An object of class `motiv` to be export.

`file` A character string naming a file.

Details

This function is made to provide standard output file used by STAMP. It take an object of class `motiv` and write two files named `*_matched.txt` and `*_match_pairs.txt` containing alignments and identified PWMs.

For more information about the Transfac file format, please refer to <http://www.benoslab.pitt.edu/stamp/help.html>.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs, trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs, align="SWU", cc="PCC", database=jaspar, DBscores=jaspar.scores)
summary(foxa1.analysis.jaspar )

#####Filters#####
f.foxa1 <- setFilter(name="", tfname="FOXA1", top=3, evaluateMax=10^5)
f.ap1 <- setFilter(tfname="AP1", top=3)
f.foxa1.ap1 <- f.foxa1 | f.ap1
foxa1.filter <- filter(foxa1.analysis.jaspar, f.foxa1.ap1, exact=FALSE, verbose=TRUE)
foxa1.split <- split(foxa1.analysis.jaspar, c(f.foxa1, f.ap1), drop=FALSE, exact=FALSE, verbose=TRUE)
foxa1.filter.combine <- combineMotifs(foxa1.filter, c(f.foxa1, f.ap1), exact=FALSE, name=c("FOXA1", "AP1"), v

#####Export#####
#exportAsTransfacFile(foxa1.filter.combine, file="foxa1_analysis")
```

filter

Filter Motifs

Description

This function selects motifs according to a set of filters.

Usage

```
## S4 method for signature 'motiv, filters'
filter(x, f, exact=FALSE, verbose=TRUE)
```


Arguments

x	An object of class <code>motiv</code> .
f	A filter or a set of filter for <code>motiv</code> object.
verbose	If FALSE, no output will be print.
exact	If TRUE, search only for perfect name match.

Details

This function is used to select motifs that correspond to the filters.

Many filter could be pass in argument separated by coma. They will be considered independently.

Value

A `motiv` object.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

`setFilter`, `split`, `combine`

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path,"/extdata/jaspar2010.txt",sep=""))
jaspar.scores <- readDBScores(paste(path,"/extdata/jaspar2010_PCC_SWU.scores",sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs,trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs,align="SWU",cc="PCC",database=jaspar,DBscores=jaspar.scores)
summary(foxa1.analysis.jaspar )

#####Filters#####
f.foxa1<-setFilter(name="", tfname="FOXA1", top=3, evaluateMax=10^-5)
f.ap1 <- setFilter (tfname="AP1", top=3)
f.foxa1.ap1 <- f.foxa1 | f.ap1
foxa1.filter <- filter(foxa1.analysis.jaspar, f.foxa1.ap1, exact=FALSE, verbose=TRUE)
foxa1.split <- split(foxa1.analysis.jaspar, c(f.foxa1, f.ap1) , drop=FALSE, exact=FALSE, verbose=TRUE)
foxa1.filter.combine <- combineMotifs(foxa1.filter, c(f.foxa1, f.ap1), exact=FALSE, name=c("FOXA1", "AP1"), v
```

filter-class	<i>Class "filter"</i>
--------------	-----------------------

Description

This object information to be apply as filter.

Details

This class `filter` is used to selected motif objects according the filter's arguments.

Objects from the Class

Objects can be created by calls of the form `new("filter", name, tfname, top, evaluateMax, lengthMax, valid)`.

Slots

name A name or a list of names.

tfname A transcription factor name or a list of TF names.

evaluateMax An e-value between 0 and 1.

top Defined the depth of the filter.

lengthMax The maximum motif length.

valid The alignment that should be considered as valid.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

`setFilter`, `filter`, `split`, `combine`

Examples

```
showClass("filter")
```

filters-methods	<i>Filters Methods</i>
-----------------	------------------------

Description

Methods for filters object

Usage

```
## S4 method for signature 'filter'  
summary(object)  
## S4 method for signature 'filters'  
summary(object)  
## S4 method for signature 'filter'  
names(x)  
## S4 method for signature 'filters'  
names(x)
```

Arguments

```
object      An object of class filter.  
x           An object of class filter.
```

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

setFilter , filter, split, combine

Examples

```
showClass("filter")
```

FOXA1_rGADEM

Dataset for FOXA1

Description

This dataset contains results obtained by rGADEM for the FOXA1 transcription factor.

Usage

```
gadem
```

References

<http://genomebiology.com/2008/9/9/R137>

Examples

```
#####Database and Scores#####  
path <- system.file(package="MotIV")  
data(jaspar2010)  
data(jaspar2010_scores)  
  
#####Input#####  
data(FOXA1_rGADEM)  
motifs <- getPWM(gadem)
```

```

motifs.trimed <- lapply(motifs,trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs,align="SWU",cc="PCC",database=jaspar,DBscores=jaspar.sc
summary(foxa1.analysis.jaspar )

```

generateDBScores *Database Scores Functions*

Description

This functions are used to generate scores of a PWM database.

Usage

```

generateDBScores(inputDB,cc="PCC",align="SWU",nRand=1000,go=1,ge=0.5)
readDBScores(file)
writeDBScores(x, file)

```

Arguments

inputDB	A list of PWM corresponding to the database.
cc	The metric name to be used :
align	The Alignment method to be used.
go	Gap open penalty.
ge	Gap extension penalty.
nRand	The number of random PWM to be generated. The more higer it is, the more accurate score will be.
file	A character string naming a file.
x	A numeric matrix corresponding to a score.

Details

The score reflects the biais of the database. It is used to compute more precisely e-value alignments. generateDBScores : Based on database properties (suchs as length, zero rate, invariant columns), nRand matrix are generated. A score is calculated for each matrix length with the specified alignment method and metric.

The score is associated to a database and a alignment method and metric so you don't have to generate it each time you use the same database. Use the writeDBScores and readDBScores instead. readDBScores : Read a score file. writeDBScores : Write a score file.

Value

A numeric matrix. Columns correspond respectively to the first matrix length, second matrix length, variance, mean, matrix number, distance min and max.

Warning

Because of each matrix is compare to each other, computing time is exponential. You should be aware of this fact before provided a high nRand. 5000 is a good time/accuracy rate choice.

Author(s)

Shaun Mahony, modified by Eloi Mercier <<emercier@chibi.ubc.ca>>

References

Sandelin, A. and Wasserman, W.W. (2004) Constrained binding site diversity within families of transcription factors enhances pattern discovery bioinformatics. *J. Mol. Biol.*, 338, 207/215.

See Also

'readDBScores', 'writeDBScores'

Examples

```
#####Database and Scores#####  
path <- system.file(package="MotIV")  
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))  
#jaspar.scores <- generateDBScores(inputDB=jaspar, cc="PCC", align="SWU", nRand=1000)  
#writeDBScores(jaspar.scores, paste(path, "/extdata/jaspar_PCC_SWU.scores", sep=""))  
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))
```

getGademPWM

Recover PWM

Description

This function selects the PWMs contained in an object of type gadem.

Usage

```
getGademPWM(y)
```

Arguments

y A gadem object.

Value

A list of PWM.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
# motifs <- getGademPWM(gadem) #deprecated
motifs <- getPWM(gadem)
motifs.trimmed <- lapply(motifs, trimPWMedge, threshold=1)
```

getPWM	<i>Get PWMs from a motiv object</i>
--------	-------------------------------------

Description

Get PWMs from a motiv object.

Usage

```
## S4 method for signature 'motiv'
getPWM(x)
```

Arguments

x An object of class motiv.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

jaspar2010	<i>Jaspar 2010 Database</i>
------------	-----------------------------

Description

Jaspar database and Jaspar score.

Usage

```
jaspar
jaspar.scores
```

Details

Jaspar is a well-known transcription factor database. Version 2010 contents 130 non-redundant matrix of TF binding sites.

The jaspar scores have been computed with Pearson Correlation Coefficient and Smith-Waterman Ungapped alignments.

Source

<http://jaspar.genereg.net/>

References

Albin Sandelin, Wynand Alkema, Pär Engström, Wyeth W. Wasserman and Boris Lenhard, JASPAR: an open-access database for eukaryotic transcription factor binding profiles, *Nucleic Acids Research*(2003)

See Also

generateDBscores, motifMatch

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
data(jaspar2010)
data(jaspar2010_scores)

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs,trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs,align="SWU",cc="PCC",database=jaspar,DBscores=jaspar_scores)
summary(foxa1.analysis.jaspar )
```

makePWM

Constructing a pwm object

Description

This function constructs an object of class `pwm` from a matrix. It checks that the matrix has correct dimensions and that columns add up to 1.0.

Usage

```
makePWM(pwm, alphabet="DNA")
```

Arguments

<code>pwm</code>	Matrix representing the position weight matrix
<code>alphabet</code>	Character the alphabet making up the sequence. Currently, only "DNA" is supported.

Value

An object of class `pwm`.

Author(s)

Oliver Bembom, <bembom@berkeley.edu>

Examples

```
#mFile <- system.file("Exfiles/pwm1", package="seqLogo")
#m <- read.table(mFile)
#pwm <- makePWM(m)
```

matches-class

Class "matches"

Description

This object contains the name of the input motif and all the matches found.

Objects from the Class

Objects can be created by calls of the form `new("matches", name, aligns, similarity, valid)`.

Slots

name Motif name.

aligns Alignments found by `motifMatch`.

similarity The optional name given to the motif.

valid The alignment that should be considered as valid.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

`motiv`, `alignments`, `tf`

Examples

```
showClass("matches")
```

motifDistances *Clustering PWMs Computation*

Description

Set of functions to perform clustering of PWMs.

Usage

```
motifDistances(inputPWM, DBscores=jaspar.scores, cc="PCC", align="SWU", top=5, go=1, ge=0.5)
motifHclust(x,...)
motifCutree(tree,k=NULL, h=NULL)
```

Arguments

```
inputPWM, DBscores, cc, align, top, go, ge
                                Option for the PWMs distances computation. Refere to motifMatch.
x, ...                           Arguments to pass to the hclust function. See hclust.
tree, k, h                       Arguments to pass to the cutree function. See cutree.
```

Details

This function are made to perform motifs clustering.

The ‘motifDistances’ function computes the distances between each pair of motifs using the specified alignment.

The ‘motifHclust’ and ‘motifCutree’ functions are simple redefinition of ‘hclust’ and ‘cutree’.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs, trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs, align="SWU", cc="PCC", database=jaspar, DBscores=jaspar.scores)

#####Clustering#####
d <- motifDistances(getPWM(foxa1.analysis.jaspar))
hc <- motifHclust(d)
plot(hc)
f <- motifCutree(hc, k=2)
foxa1.combine <- combineMotifs(foxa1.analysis.jaspar, f, exact=FALSE, name=c("Group1", "Group2"), verbose=TRUE)
```

`motifMatch`*Motifs Matches Analysis*

Description

Search for motifs matches corresponding to PWM.

Usage

```
motifMatch(inputPWM, database=jaspar, DBscores=jaspar.scores, cc="PCC", align="SWU", top=5, go=1,
```

Arguments

<code>inputPWM</code>	A list of PWM.
<code>database</code>	A list of PWM corresponding to the database.
<code>DBscores</code>	A matrix object containing the scores associated to the database.
<code>cc</code>	The metric name to be used
<code>align</code>	The Alignment method to be used.
<code>top</code>	The number of identified transcription factors per motif.
<code>go</code>	Gap open penalty.
<code>ge</code>	Gap extension penalty.

Details

For a set of PWMs given by `inputPWM`, this function realizes alignments with each motif of the database and returns the top best motifs. If no database is provided, the function will use `jaspar` by loading `data(jaspar2010)`. If no `DBscores` is given, `jaspar.scores` from `data(jaspar2010_scores)` will be used.

The e-value is computed according the metric name `cc` and is corrected by the `DBscores`.

Value

A `motif` object.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

References

S Mahony, PE Auron, PV Benos, DNA familial binding profiles made easy: comparison of various motif alignment and clustering strategies, *PLoS Computational Biology* (2007) 3(3):e61

See Also

`generateDBScores`

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs, trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs, align="SWU", cc="PCC", database=jaspar, DBscores=jaspar.scores)
summary(foxa1.analysis.jaspar )
```

motiv-class

Class "motiv"

Description

This object contains all informations about the motiv analysis.

Objects from the Class

Objects can be created by calls of the form `new("motiv", input, bestMatch, argv)`.

Slots

input List of input PWM.

bestMatch Object of class "matches".

argv List of arguments used.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

matches, alignments, transcriptionFactor

Examples

```
showClass("motiv")
```

motiv-methods

Motiv methods

Description

Methods for motiv objects.

Usage

```
## S4 method for signature 'motiv'
summary(object)
## S4 method for signature 'motiv'
names(x)
## S4 method for signature 'motiv'
length(x)
## S4 method for signature 'motiv'
similarity(x)
## S4 method for signature 'motiv'
x[i,j=ANY, bysim=TRUE, ...,exact=TRUE, ignore.case=FALSE, drop=FALSE]
```

Arguments

object	An object of class <code>motiv</code> .
x	An object of class <code>motiv</code> .
i	A string representing a motif name.
j	NOT USED.
bysim	If TRUE, select by similarity name.
...	Further potential arguments passed to methods.
ignore.case	if FALSE, the pattern matching is case sensitive and if TRUE, case is ignored during matching
exact	If TRUE, search only for perfect name match.
drop	If TRUE, no match motifs will be dropped.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

`matches`, `alignments`, `tf`

Examples

```
showClass("motiv")
```

 occurrences

Motifs Occurrences and Co-occurrences

Description

Get the number of motifs occurrences and co-occurrences from a rGADEM object.

Usage

```
occurrences(gadem)
cooccurrences(x)
```

Arguments

gadem	An object of type rGADEM.
x	A contingency table.

Value

occurrences returns the contingency table of the number of motifs per sequences.

This object can be put in cooccurrences to return the number of sequences where two motifs appear together.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
data("FOXA1_rGADEM")
oc <- occurrences(gadem)
coc <- cooccurrences(oc)
coc
```

 plot-methods

Plot Motiv

Description

This functions are used to visualize and validate motif analysis.

Usage

```
## S4 method for signature 'motiv,ANY'
plot(x, y=NULL, main=NULL, sub=NULL, ncol=0, nrow=0, top=3, bysim=TRUE, rev=FALSE, trim=0.05, cex)

## S4 method for signature 'motiv,gadem'
plot(x, y, sort=FALSE, group=FALSE, main=NULL, sub=NULL, ncol=0, nrow=0, xlim=NULL, correction=TRUE)
```

Arguments

<code>x</code>	An object of class <code>motiv</code> .
<code>y</code>	The GADDEM type object associated with the <code>motiv</code> object.
<code>ncol, nrow</code>	A numeric value giving the the number of columns and rows to plot.
<code>top</code>	A numeric value giving the number of best matches per motif to display.
<code>rev</code>	A logical value. If TRUE, print reverse motif for negatif strand.
<code>main</code>	An overall title for the plot: see <code>title</code> .
<code>sub</code>	A sub title for the plot: see <code>'title'</code>
<code>type</code>	What type of plot should be drawn. Possible values are : distribution to display the binding sites distribution within the peaks or distance to show the pairwise distance between motifs.
<code>strand</code>	If TRUE, distribution will be plot for both forward and reverse strand.
<code>group</code>	If TRUE, similar motifs will be grouped.
<code>sort</code>	If TRUE, motifs will be plot according their computed variance.
<code>bysim</code>	If TRUE, the <code>'similar'</code> field (defined with the <code>combine</code> function) will be print instead of the original name.
<code>xlim</code>	A numeric vectors of length 2, giving the x coordinates ranges.
<code>correction</code>	If TRUE, corrects the position according to the alignment.
<code>trim</code>	A numeric value. Define the mimimun information content value for which the logo letters are shown.
<code>col, border, lwd, lty</code>	Define respectively the color, the border, the line wide and the line type of both curve and histogram. See <code>'par'</code> .
<code>nclass</code>	A numerical value giving the number of class for the histogram.
<code>bw</code>	he smoothing bandwidth to be used to calculate the density. See <code>density</code> .
<code>cex, vcol</code>	A numerical value giving the amount by which plotting text should be magnified relative to the default.

Details

A `motiv` object (usualy provied by `motifMatch`) will plot the list of identified transcription factors for each motif. With `rev=TRUE`, the transcription factor logo will be print to correspond to the real alignment instead of original TF PWM.

Giving a `motiv` object and a `gadem` object with `type="distribution"` will show the motif repartition within `gadem` peaks. If `strand=TRUE`, a distinct distribution is made for forward and reverse strand.

A `var.test` is automatically made to help to distinguish centered distribution. The distribution with lowest variance is assign as "reference" distribution to compute the `var.test` statistic. With `sort=TRUE`, distribution are plot according decreasing statistic.

`type="distance"` indicates to compute and plot the distance between each pair of motif. It also provied Venn diagramm that returns the proportion of common sequences per pair of motif.

The `group` argument indicates to consider similar motif as a single motif.

With `correction=TRUE` the motif position is corrected accoring to the alignment. It means that the `gap/"N"` contained in the alignments are removed to give a corrected start and end position.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs, trimPWMedge, threshold=1)
#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs, align="SWU", cc="PCC", database=jaspar, DBscores=jaspar.scores)
summary(foxa1.analysis.jaspar )

#####Filters#####
f.foxa1 <- setFilter(name="", tfname="FOXA1", top=3, evaluateMax=10^-5)
f.ap1 <- setFilter (tfname="AP1", top=3)
f.foxa1.ap1 <- f.foxa1 | f.ap1
foxa1.filter <- filter(foxa1.analysis.jaspar, f.foxa1.ap1, exact=FALSE, verbose=TRUE)
foxa1.split <- split(foxa1.analysis.jaspar, c(f.foxa1, f.ap1) , drop=FALSE, exact=FALSE, verbose=TRUE)
foxa1.filter.combine <- combineMotifs(foxa1.filter, c(f.foxa1, f.ap1), exact=FALSE, name=c("FOXA1", "AP1"), v

#####Plots#####
plot(foxa1.filter.combine, ncol=2, top=5, rev=FALSE, main="FOXA", bysim=TRUE)
plot(foxa1.filter.combine , gadem, ncol=2, type="distribution", correction=TRUE, group=FALSE, bysim=TRUE, str
plot(foxa1.filter.combine , gadem, type="distance", correction=TRUE, group=TRUE, bysim=TRUE, main="FOXA", str
```

readGademPWMFile

Read Gadem File

Description

This function is use to read a gadem file containing PWM.

Usage

```
readGademPWMFile(file)
```

Arguments

file File's name.

Details

This function is made to read typically output file from Gadem (v1.2). Standard name is 'observed-PWMs.txt'.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs, trimPWMedge, threshold=1)
```

readPWMfile	<i>Read Transfac File</i>
-------------	---------------------------

Description

This function is use to read standard Transfac type file.

Usage

```
readPWMfile(file)
```

Arguments

file Transfac file's name.

Details

This function is designed to read standard Transfac type file. For more information about the format, please refer to <http://mcast.sdsc.edu/doc/transfac-format.html>

Value

A list of matrix.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))
```


seqLogo2

*Plot a sequence logo for a given position weight matrix***Description**

This function takes the 4xW position weight matrix of a DNA sequence motif and plots the corresponding sequence logo.

Usage

```
seqLogo2(pwm, ic.scale=TRUE, xaxis=TRUE, yaxis=TRUE, xfontsize=15, yfontsize=15, vmargins=c(0,0),
```

Arguments

pwm	numeric	The 4xW position weight matrix.
ic.scale	logical	If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height.
xaxis	logical	If TRUE, an X-axis will be plotted.
yaxis	logical	If TRUE, a Y-axis will be plotted.
xfontsize	numeric	Font size to be used for the X-axis.
yfontsize	numeric	Font size to be used for the Y-axis.
vmargins	numeric	Vertical margins.
hmargins	numeric	Horizontal margins.
size	numeric	Graphic size.
trim	numeric	Print nucleotide only if the information content is superior to this trim threshold.

Details

Within each column, the height of a given letter is proportional to its frequency at that position. If `ic.scale` is TRUE, the height of each column in the plot indicates the information content at that position of the motif. Otherwise, the height of all columns are identical.

This is an internal function for the package MotIV. User should prefer the `seqLogo` function from the package `seqLogo` to visualize individual motif.

Value

None.

Author(s)

Oliver Bembom, <bembom@berkeley.edu>, modified by Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
#mFile <- system.file("Exfiles/pwm1", package="seqLogo")
#m <- read.table(mFile)
#pwm <- makePWM(m)
#seqLogo2(pwm)
```

setFilter *Set Motif Filter*

Description

This function is use to set a motif filter.

Usage

```
setFilter(name="", tfname="", evaluateMax=1, top=10, lengthMax=100, valid=NULL)
```

Arguments

name	A name or a list of names.
tfname	A transcription factor name or a list of TF names.
evaluateMax	An evalue between 0 and 1.
top	Defines the depth of the filter.
lengthMax	The maximum motif length.
valid	The alignment that should be considered as valid.

Value

A filter object.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

filter , split, combine

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimmed <- lapply(motifs, trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs, align="SWU", cc="PCC", database=jaspar, DBscores=jaspar.scores)
summary(foxa1.analysis.jaspar )

#####Filters#####
f.foxa1 <- setFilter(name="", tfname="FOXA1", top=3, evaluateMax=10^-5)
f.ap1 <- setFilter (tfname="AP1", top=3)
f.foxa1.ap1 <- f.foxa1 | f.ap1
```

```
foxa1.filter <- filter(foxa1.analysis.jaspar, f.foxa1.ap1, exact=FALSE, verbose=TRUE)
foxa1.split <- split(foxa1.analysis.jaspar, c(f.foxa1, f.ap1) , drop=FALSE, exact=FALSE, verbose=TRUE)
foxa1.filter.combine <- combineMotifs(foxa1.filter, c(f.foxa1, f.ap1), exact=FALSE, name=c("FOXA1", "AP1"), v
```

split-methods

Split Motiv Object

Description

This function splits a 'motiv' object according filters.

Usage

```
## S4 method for signature 'motiv,filters'
split(x, f, exact=TRUE, drop=FALSE, verbose=TRUE, ...)
```

Arguments

x	An object of class motiv (usually provided by motifMatch).
f	A filter or a set of filter for motiv object.
drop	If TRUE, no match motifs will be dropped.
verbose	If FALSE, no output will be printed.
exact	If TRUE, search only for perfect name match.
...	Further potential arguments passed to methods.

Details

This function is used to split motifs that correspond to the filters.

Many filters could be passed in argument separated by comma. They will be considered independently (comma is considered as OR).

Value

A list of motiv objects.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

setFilter, filter, combine

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path,"/extdata/jaspar2010.txt",sep=""))
jaspar.scores <- readDBScores(paste(path,"/extdata/jaspar2010_PCC_SWU.scores",sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs,trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs,align="SWU",cc="PCC",database=jaspar,DBscores=jaspar.scores)
summary(foxa1.analysis.jaspar )

#####Filters#####
f.foxa1<-setFilter(name="", tfname="FOXA1", top=3, evaluateMax=10^-5)
f.ap1 <- setFilter (tfname="AP1", top=3)
f.foxa1.ap1 <- f.foxa1 | f.ap1
foxa1.filter <- filter(foxa1.analysis.jaspar, f.foxa1.ap1, exact=FALSE, verbose=TRUE)
foxa1.split <- split(foxa1.analysis.jaspar, c(f.foxa1, f.ap1) , drop=FALSE, exact=FALSE, verbose=TRUE)
foxa1.filter.combine <- combineMotifs(foxa1.filter, c(f.foxa1, f.ap1), exact=FALSE, name=c("FOXA1", "AP1"), v
```

transcriptionFactor-class

Transcription Factor Class

Description

This object contains the Transcription Factor name and PWM.

Objects from the Class

Objects can be created by calls of the form `new("transcriptionFactor", name, pwm)`.

Slots

name TF name.

pwm TF PWM.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

`motiv`, `matches`, `alignments`

Examples

```
showClass("transcriptionFactor")
```

trimPwMedge	<i>Trim PWM edge</i>
-------------	----------------------

Description

This function is use to cut edges with low information content.

Usage

```
trimPwMedge(x, threshold=1)
```

Arguments

x	A matrix representing a PWM.
threshold	A transcription factor name or a list of TF names.

Value

A PWM.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

makePWM

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs, trimPwMedge, threshold=1)
```

viewAlignments	<i>Print Motifs Alignments</i>
----------------	--------------------------------

Description

This function return a list of the alignments of a motif object for each motif.

Usage

```
viewAlignments(x)
```

Arguments

x An object of class `motiv` (usually provided by `motifMatch`).

Details

This function shows the alignments for each motif.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

See Also

`as.data.frame`

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs, trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs, align="SWU", cc="PCC", database=jaspar, DBscores=jaspar.scores)
summary(foxa1.analysis.jaspar )
viewAlignments(foxa1.analysis.jaspar )
```

viewMotifs-methods *Print Identified Motifs*

Description

This function return a list of the identified motifs contained in a `motiv` object.

Usage

```
## S4 method for signature 'motiv'
viewMotifs(x, n=100)
```

Arguments

x An object of class `motiv` (usually provided by `motifMatch`).

n The number of motifs shown.

Details

This function shows the number of identified motif.

Value

A list of motifs names.

Author(s)

Eloi Mercier <<emercier@chibi.ubc.ca>>

Examples

```
#####Database and Scores#####
path <- system.file(package="MotIV")
jaspar <- readPWMfile(paste(path, "/extdata/jaspar2010.txt", sep=""))
jaspar.scores <- readDBScores(paste(path, "/extdata/jaspar2010_PCC_SWU.scores", sep=""))

#####Input#####
data(FOXA1_rGADEM)
motifs <- getPWM(gadem)
motifs.trimed <- lapply(motifs, trimPWMedge, threshold=1)

#####Analysis#####
foxa1.analysis.jaspar <- motifMatch(inputPWM=motifs, align="SWU", cc="PCC", database=jaspar, DBscores=jaspar.scores)
viewMotifs(foxa1.analysis.jaspar, 5)
```

Index

*Topic **classes**

- alignments-class, 2
- filter-class, 10
- filters-methods, 10
- matches-class, 16
- motiv-class, 19
- transcriptionFactor-class, 28

*Topic **methods**

- as.data.frame, 3
- combineMotifs, 4
- filter, 8
- motiv-methods, 20
- plot-methods, 21
- split-methods, 27

*Topic **misc**

- exportAsGRanges, 5
- exportAsRangedData, 6
- exportAsTransfacFile, 7
- FOXA1_rGADEM, 11
- generateDBScores, 12
- getGademPWM, 13
- getPWM, 14
- jaspar2010, 14
- makePWM, 15
- motifDistances, 17
- motifMatch, 18
- occurrences, 21
- readGademPWMFile, 23
- readPWMfile, 24
- seqLogo2, 25
- setFilter, 26
- trimPWMedge, 29
- viewAlignments, 29
- viewMotifs-methods, 30
- [,motiv,ANY,ANY,ANY-method (motiv-methods), 20
- [,motiv,ANY,ANY-method (motiv-methods), 20
- [,motiv-method (motiv-methods), 20
- &,filters,filters-method (filters-methods), 10

alignments-class, 2

as.data.frame, 3

as.data.frame,motiv-method (as.data.frame), 3

as.data.frame-methods (as.data.frame), 3

combineMotifs, 4

combineMotifs,motiv,filters-method (combineMotifs), 4

combineMotifs,motiv,list-method (combineMotifs), 4

combineMotifs-method (combineMotifs), 4

cooccurrences (occurrences), 21

exportAsGRanges, 5

exportAsRangedData, 6

exportAsTransfacFile, 7

exportAsTransfacFile,list-method (exportAsTransfacFile), 7

exportAsTransfacFile,motiv-method (exportAsTransfacFile), 7

exportAsTransfacFile-methods (exportAsTransfacFile), 7

filter, 8

filter,motiv,filters-method (filter), 8

filter,motiv,list-method (filter), 8

filter-class, 10

filter-methods (filter), 8

filters-methods, 10

FOXA (FOXA1_rGADEM), 11

FOXA1_rGADEM, 11

gadem (FOXA1_rGADEM), 11

generateDBScores, 12

getGademPWM, 13

getPWM, 14

getPWM,motiv-method (getPWM), 14

getPWM-methods (getPWM), 14

jaspar (jaspar2010), 14

jaspar2010, 14

length,motiv-method (motiv-methods), 20

makePWM, 15

matches-class, 16

motifCutree (motifDistances), 17
motifDistances, 17
motifHclust (motifDistances), 17
motifMatch, 18
motiv (motiv-methods), 20
motiv-class, 19
motiv-methods, 20

names, filter-method (filters-methods),
10
names, filters-method (filters-methods),
10
names, motiv-method (motiv-methods), 20
names<- ,motiv-method (motiv-methods), 20

occurrences, 21

plot (plot-methods), 21
plot, motiv, ANY-method (plot-methods), 21
plot, motiv, gadem-method (plot-methods),
21
plot, motiv-method (plot-methods), 21
plot-methods, 21

readDBScores (generateDBScores), 12
readGademPWMFile, 23
readPWMfile, 24

seqLogo2, 25
setFilter, 26
show, filter-method (filters-methods), 10
show, motiv-method (motiv-methods), 20
similarity (motiv-methods), 20
similarity, list-method (motiv-methods),
20
similarity, motiv-method
(motiv-methods), 20
split, motiv, filters-method
(split-methods), 27
split, motiv, list-method
(split-methods), 27
split-methods, 27
summary, filter-method
(filters-methods), 10
summary, filters-method
(filters-methods), 10
summary, list-method (motiv-methods), 20
summary, motiv-method (motiv-methods), 20

transcriptionFactor-class, 28
trimPWMedge, 29

viewAlignments, 29
viewMotifs (viewMotifs-methods), 30
viewMotifs, motiv-method
(viewMotifs-methods), 30
viewMotifs-methods, 30
writeDBScores (generateDBScores), 12