

Package ‘PharmacoGx’

April 15, 2020

Type Package

Title Analysis of Large-Scale Pharmacogenomic Data

Version 1.17.1

Date 2020-01-28

Author Petr Smirnov, Zhaleh Safikhani, Mark Freeman, Benjamin Haibe-Kains

Maintainer Benjamin Haibe-Kains <benjamin.haibe.kains@utoronto.ca>

Description Contains a set of functions to perform large-scale analysis of pharmacogenomic data.

License Artistic-2.0

Suggests xtable, testthat

Encoding UTF-8

Imports Biobase, piano, magicaxis, RColorBrewer, parallel, caTools,
methods, downloader, stats, utils, graphics, grDevices, lsa,
reshape2

Depends R (>= 3.6)

RoxygenNote 7.0.2

biocViews GeneExpression, Pharmacogenetics, Pharmacogenomics,
Software, Classification

BugReports <https://github.com/bhklab/PharmacoGx/issues>

git_url <https://git.bioconductor.org/packages/PharmacoGx>

git_branch RELEASE_3_10

git_last_commit e34f5b8

git_last_commit_date 2020-01-29

Date/Publication 2020-04-14

R topics documented:

| | |
|--------------------------|---|
| amcc | 3 |
| availablePSETS | 4 |
| CCLsmall | 5 |
| cellInfo | 5 |
| cellInfo<- | 6 |
| cellNames | 6 |
| cellNames<- | 7 |

| | |
|-------------------------|----|
| checkPSetStructure | 7 |
| CMAPsmall | 8 |
| computeABC | 8 |
| computeAmax | 9 |
| computeAUC | 10 |
| computeIC50 | 11 |
| computeSlope | 13 |
| connectivityScore | 14 |
| cosinePerm | 15 |
| dateCreated | 16 |
| dim,PharmacoSet-method | 16 |
| downloadPertSig | 17 |
| downloadPSet | 17 |
| drugDoseResponseCurve | 18 |
| drugInfo | 20 |
| drugInfo<- | 21 |
| drugNames | 21 |
| drugNames<- | 22 |
| drugPerturbationSig | 22 |
| drugSensitivitySig | 23 |
| featureInfo | 25 |
| featureInfo<- | 26 |
| filterNoisyCurves | 26 |
| fNames | 27 |
| GDSCsmall | 28 |
| gwc | 28 |
| HDAC_genes | 29 |
| intersectList | 30 |
| intersectPSet | 30 |
| logLogisticRegression | 31 |
| mcc | 33 |
| mDataNames | 34 |
| molecularProfiles | 34 |
| molecularProfiles<- | 35 |
| pertNumber | 35 |
| pertNumber<- | 36 |
| PharmacoSet | 36 |
| PharmacoSet-class | 38 |
| phenoInfo | 41 |
| phenoInfo<- | 42 |
| pSetName | 42 |
| sensitivityInfo | 43 |
| sensitivityInfo<- | 43 |
| sensitivityMeasures | 44 |
| sensitivityProfiles | 44 |
| sensitivityProfiles<- | 45 |
| sensNumber | 45 |
| sensNumber<- | 46 |
| show,PharmacoSet-method | 46 |
| show,PharmacoSig-method | 47 |
| showSigAnnot | 47 |
| subsetTo | 48 |

| | |
|--|----|
| <i>amcc</i> | 3 |
| summarizeMolecularProfiles | 49 |
| summarizeSensitivityProfiles | 50 |
| symSetDiffList | 51 |
| unionList | 52 |
| [,PharmacoSet,ANY,ANY,ANY-method | 52 |

Index **54**

amcc *Calculate an Adaptive Matthews Correlation Coefficient*

Description

This function calculates an Adaptive Matthews Correlation Coefficient (AMCC) for two vectors of values identical length. It assumes the entries in the two vectors are paired. The Adaptive Matthews Correlation Coefficient for two vectors of values is defined as the Maximum Matthews Coefficient over all possible binary splits of the ranks of the two vectors. In this way, it calculates the best possible agreement of a binary classifier on the two vectors of data. #If the AMCC is low, then it is impossible to find any binary classification of the two vectors with a high degree of concordance.

Usage

```
amcc(
  x,
  y,
  step.prct = 0,
  min.cat = 3,
  nperm = 1000,
  setseed = 12345,
  nthread = 1
)
```

Arguments

- x, y* Two paired vectors of values. Could be replicates of observations for the same experiments for example.
- step.prct* Instead of testing all possible splits of the data, it is possible to test steps of a percentage size of the total number of ranks in *x/y*. If this variable is 0, function defaults to testing all possible splits.
- min.cat* The minimum number of members per category. Classifications with less members fitting into both categories will not be considered.
- nperm* The number of perumatation to use for estimating significance. If 0, then no p-value is calculated.
- setseed* Allows setting a consitent seed for reproducibility of permutation testing results. Defaults to 12345.
- nthread* Number of threads to parallize over. Both the AMCC calculation and the permutation testing is done in parallel.

Value

Returns a list with two elements. *\$amcc* contains the highest "mcc" value over all the splits, the p value, as well as the rank at which the split was done.

Examples

```
x <- c(1,2,3,4,5,6,7)
y <- c(1,3,5,4,2,7,6)
amcc(x,y, min.cat=2)
```

availablePSets

Return a table of PharmacoSets available for download

Description

The function fetches a table of all PharmacoSets available for download from the PharmacoGx server. The table includes the names of the PharamcoSet, the types of data available in the object, and the date of last update.

Usage

```
availablePSets(
  saveDir = file.path(".", "PSets"),
  myfn = "PSets.csv",
  verbose = TRUE
)
```

Arguments

| | | |
|---------|-----------|--|
| saveDir | character | Directory to save the table of PSets |
| myfn | character | The filename for the table of PSets |
| verbose | bool | Should status messages be printed during download. |

Value

A data.frame with details about the available PharmacoSet objects

Examples

```
if (interactive()){
  availablePSets()
}
```

`CCEsmall`*Cancer Cell Line Encyclopedia (CCLE) Example PharmacoSet*

Description

A small example version of the CCLE PharmacoSet, used in the documentation examples. All credit for the data goes to the CCLE group at the Broad Institute. This is not a full version of the dataset, most of the dataset was removed to make runnable example code. For the full dataset, please download using the `downloadPSet` function.

Usage

```
data(CCEsmall)
```

Format

PharmacoSet object

References

Barretina et al. The Cancer Cell Line Encyclopedia enables predictive modelling of anticancer drug sensitivity. *Nature*, 2012

`cellInfo`*cellInfo Generic*

Description

Generic for `cellInfo` method

Usage

```
cellInfo(pSet)
```

Arguments

`pSet` The PharmacoSet to retrieve cell info from

Value

a `data.frame` with the cell annotations

Examples

```
data(CCEsmall)
cellInfo(CCEsmall)
```

| | |
|------------|------------------------------|
| cellInfo<- | <i>cellInfo<- Generic</i> |
|------------|------------------------------|

Description

Generic for cellInfo replace method

Usage

```
cellInfo(object) <- value
```

Arguments

| | |
|--------|--|
| object | The PharmacoS _e t to replace cell info in |
| value | A data.frame with the new cell annotations |

Value

Updated PharmacoS_et

Examples

```
data(CCLEsmall)
cellInfo(CCLEsmall) <- cellInfo(CCLEsmall)
```

| | |
|-----------|--------------------------|
| cellNames | <i>cellNames Generic</i> |
|-----------|--------------------------|

Description

A generic for the cellNames method

Usage

```
cellNames(pSet)
```

Arguments

| | |
|------|--|
| pSet | The PharmacoS _e t to return cell names from |
|------|--|

Value

A vector of the cell names used in the PharmacoS_et

Examples

```
data(CCLEsmall)
cellNames(CCLEsmall)
```

| | |
|-------------|-------------------------------|
| cellNames<- | <i>cellNames<- Generic</i> |
|-------------|-------------------------------|

Description

A generic for the cellNames replacement method

Usage

```
cellNames(object) <- value
```

Arguments

| | |
|--------|--|
| object | The PharmacoS e t to update |
| value | A character vector of the new cell names |

Value

Updated PharmacoS**e**t

Examples

```
data(CCLEsmall)
cellNames(CCLEsmall) <- cellNames(CCLEsmall)
```

| | |
|--------------------|---|
| checkPSetStructure | <i>A function to verify the structure of a PharmacoSet</i> |
|--------------------|---|

Description

This function checks the structure of a PharamcoSet, ensuring that the correct annotations are in place and all the required slots are filled so that matching of cells and drugs can be properly done across different types of data and with other studies.

Usage

```
checkPSetStructure(pSet, plotDist = FALSE, result.dir = ".")
```

Arguments

| | |
|------------|---|
| pSet | A PharmacoS e t to be verified |
| plotDist | Should the function also plot the distribution of molecular data? |
| result.dir | The path to the directory for saving the plots as a string |

Value

Prints out messages whenever describing the errors found in the structure of the pset object passed in.

Examples

```
data(CCLEsmall)

checkPSetStructure(CCLEsmall)
```

CMAPsmall

Connectivity Map Example PharmacoSet

Description

A small example version of the Connectivity Map PharmacoSet, used in the documentation examples. All credit for the data goes to the Connectivity Map group at the Broad Institute. This is not a full version of the dataset, most of the dataset was removed to make runnable example code. For the full dataset, please download using the downloadPSet function.

Usage

```
data(CMAPsmall)
```

Format

PharmacoSet object

References

Lamb et al. The Connectivity Map: using gene-expression signatures to connect small molecules, genes, and disease. *Science*, 2006.

computeABC

Fits dose-response curves to data given by the user and returns the ABC of the fitted curves.

Description

Fits dose-response curves to data given by the user and returns the ABC of the fitted curves.

Usage

```
computeABC(
  conc1,
  conc2,
  viability1,
  viability2,
  Hill_fit1,
  Hill_fit2,
  conc_as_log = FALSE,
  viability_as_pct = TRUE,
  trunc = TRUE,
  verbose = TRUE
)
```


Arguments

| | |
|------------------|--|
| conc1 | [vector] is a vector of drug concentrations. |
| conc2 | [vector] is a vector of drug concentrations. |
| viability1 | [vector] is a vector whose entries are the viability values observed in the presence of the drug concentrations whose logarithms are in the corresponding entries of conc1, expressed as percentages of viability in the absence of any drug. |
| viability2 | [vector] is a vector whose entries are the viability values observed in the presence of the drug concentrations whose logarithms are in the corresponding entries of conc2, expressed as percentages of viability in the absence of any drug. |
| Hill_fit1 | [list or vector] In the order: c("Hill Slope", "E_inf", "EC50"), the parameters of a Hill Slope as returned by logLogisticRegression. If conc_as_log is set then the function assumes logEC50 is passed in, and if viability_as_pct flag is set, it assumes E_inf is passed in as a percent. Otherwise, E_inf is assumed to be a decimal, and EC50 as a concentration. |
| Hill_fit2 | [list or vector] In the order: c("Hill Slope", "E_inf", "EC50"), the parameters of a Hill Slope as returned by logLogisticRegression. If conc_as_log is set then the function assumes logEC50 is passed in, and if viability_as_pct flag is set, it assumes E_inf is passed in as a percent. Otherwise, E_inf is assumed to be a decimal, and EC50 as a concentration. |
| conc_as_log | [logical], if true, assumes that log10-concentration data has been given rather than concentration data. |
| viability_as_pct | [logical], if false, assumes that viability is given as a decimal rather than a percentage, and returns ABC as a decimal. Otherwise, viability is interpreted as percent, and AUC is returned 0-100. |
| trunc | [logical], if true, causes viability data to be truncated to lie between 0 and 1 before curve-fitting is performed. |
| verbose | [logical], if true, causes warnings thrown by the function to be printed. |

Value

The numeric area of the absolute difference between the two hill slopes

Examples

```
dose1 <- c("0.0025", "0.008", "0.025", "0.08", "0.25", "0.8", "2.53", "8")
viability1 <- c("108.67", "111", "102.16", "100.27", "90", "87", "74", "57")
dose2 <- c("0.0025", "0.008", "0.025", "0.08", "0.25", "0.8", "2.53", "8")
viability2 <- c("100.94", "112.5", "86", "104.16", "75", "68", "48", "29")
computeABC(dose1, dose2, viability1, viability2)
```

computeAmax

Fits dose-response curves to data given by the user and returns the Amax of the fitted curve. Amax: 100 - viability at maximum concentration (in fitted curve)

Description

Fits dose-response curves to data given by the user and returns the Amax of the fitted curve. Amax: 100 - viability at maximum concentration (in fitted curve)

Usage

```
computeAmax(concentration, viability, trunc = TRUE, verbose = FALSE)
```

Arguments

`concentration` [vector] is a vector of drug concentrations.

`viability` [vector] is a vector whose entries are the viability values observed in the presence of the drug concentrations whose logarithms are in the corresponding entries of the `log_conc`, expressed as percentages of viability in the absence of any drug.

`trunc` [logical], if true, causes viability data to be truncated to lie between 0 and 1 before curve-fitting is performed.

`verbose` [logical] should warnings be printed

Value

The numerical Amax

Examples

```
dose <- c("0.0025", "0.008", "0.025", "0.08", "0.25", "0.8", "2.53", "8")
viability <- c("108.67", "111", "102.16", "100.27", "90", "87", "74", "57")
computeAmax(dose, viability)
```

computeAUC

Computes the AUC for a Drug Dose Viability Curve

Description

Returns the AUC (Area Under the drug response Curve) given concentration and viability as input, normalized by the concentration range of the experiment. The area returned is the response (1-Viability) area, i.e. area under the curve when the response curve is plotted on a log₁₀ concentration scale, with high AUC implying high sensitivity to the drug. The function can calculate both the area under a fitted Hill Curve to the data, and a trapz numeric integral of the actual data provided. Alternatively, the parameters of a Hill Slope returned by `logLogisticRegression` can be passed in if they already known.

Usage

```
computeAUC(
  concentration,
  viability,
  Hill_fit,
  conc_as_log = FALSE,
  viability_as_pct = TRUE,
```

```

trunc = TRUE,
area.type = c("Fitted", "Actual"),
verbose = TRUE
)

```

Arguments

concentration [vector] is a vector of drug concentrations.

viability [vector] is a vector whose entries are the viability values observed in the presence of the drug concentrations whose logarithms are in the corresponding entries of conc, where viability 0 indicates that all cells died, and viability 1 indicates that the drug had no effect on the cells.

Hill_fit [list or vector] In the order: c("Hill Slope", "E_inf", "EC50"), the parameters of a Hill Slope as returned by logLogisticRegression. If conc_as_log is set then the function assumes logEC50 is passed in, and if viability_as_pct flag is set, it assumes E_inf is passed in as a percent. Otherwise, E_inf is assumed to be a decimal, and EC50 as a concentration.

conc_as_log [logical], if true, assumes that log10-concentration data has been given rather than concentration data.

viability_as_pct [logical], if false, assumes that viability is given as a decimal rather than a percentage, and returns AUC as a decimal. Otherwise, viability is interpreted as percent, and AUC is returned 0-100.

trunc [logical], if true, causes viability data to be truncated to lie between 0 and 1 before curve-fitting is performed.

area.type Should the area be computed using the actual data ("Actual"), or a fitted curve ("Fitted")

verbose [logical], if true, causes warnings thrown by the function to be printed.

Value

Numeric AUC value

Examples

```

dose <- c("0.0025", "0.008", "0.025", "0.08", "0.25", "0.8", "2.53", "8")
viability <- c("108.67", "111", "102.16", "100.27", "90", "87", "74", "57")
computeAUC(dose, viability)

```

computeIC50

Computes the IC_n for any n in 0-100 for a Drug Dose Viability Curve

Description

Returns the IC_n for any given nth percentile when given concentration and viability as input, normalized by the concentration range of the experiment. A Hill Slope is first fit to the data, and the IC_n is inferred from the fitted curve. Alternatively, the parameters of a Hill Slope returned by logLogisticRegression can be passed in if they already known.

Usage

```

computeIC50(
  concentration,
  viability,
  Hill_fit,
  conc_as_log = FALSE,
  viability_as_pct = TRUE,
  verbose = TRUE,
  trunc = TRUE
)

computeICn(
  concentration,
  viability,
  Hill_fit,
  n,
  conc_as_log = FALSE,
  viability_as_pct = TRUE,
  verbose = TRUE,
  trunc = TRUE
)

```

Arguments

| | |
|------------------|--|
| concentration | [vector] is a vector of drug concentrations. |
| viability | [vector] is a vector whose entries are the viability values observed in the presence of the drug concentrations whose logarithms are in the corresponding entries of conc, where viability 0 indicates that all cells died, and viability 1 indicates that the drug had no effect on the cells. |
| Hill_fit | [list or vector] In the order: c("Hill Slope", "E_inf", "EC50"), the parameters of a Hill Slope as returned by logLogisticRegression. If conc_as_log is set then the function assumes logEC50 is passed in, and if viability_as_pct flag is set, it assumes E_inf is passed in as a percent. Otherwise, E_inf is assumed to be a decimal, and EC50 as a concentration. |
| conc_as_log | [logical], if true, assumes that log10-concentration data has been given rather than concentration data, and that log10(ICn) should be returned instead of ICn. |
| viability_as_pct | [logical], if false, assumes that viability is given as a decimal rather than a percentage, and that E_inf passed in as decimal. |
| verbose | [logical], if true, causes warnings thrown by the function to be printed. |
| trunc | [logical], if true, causes viability data to be truncated to lie between 0 and 1 before curve-fitting is performed. |
| n | [numeric] The percentile concentration to compute. If viability_as_pct set, assumed to be percentage, otherwise assumed to be a decimal value. |

Value

a numeric value for the concentration of the nth percentile viability reduction

Functions

- computeIC50: Returns the IC50 of a Drug Dose response curve

Examples

```
dose <- c("0.0025", "0.008", "0.025", "0.08", "0.25", "0.8", "2.53", "8")
viability <- c("108.67", "111", "102.16", "100.27", "90", "87", "74", "57")
computeIC50(dose, viability)
computeICn(dose, viability, n=10)
```

| | |
|--------------|---|
| computeSlope | <i>Return Slope (normalized slope of the drug response curve) for an experiment of a pSet by taking its concentration and viability as input.</i> |
|--------------|---|

Description

Return Slope (normalized slope of the drug response curve) for an experiment of a pSet by taking its concentration and viability as input.

Usage

```
computeSlope(concentration, viability, trunc = TRUE, verbose = TRUE)
```

Arguments

| | |
|---------------|--|
| concentration | [vector] A concentration range that the AUC should be computed for that range. Concentration range by default considered as not logarithmic scaled. Converted to numeric by function if necessary. |
| viability | [vector] Viabilities corresponding to the concentration range passed as first parameter. The range of viability values by definition should be between 0 and 100. But the viabilities greater than 100 and lower than 0 are also accepted. |
| trunc | [binary] A flag that identify if the viability values should be truncated to be in the range of (0,100) |
| verbose | [boolean] If 'TRUE' the function will retrun warnings and other infomrative messages. |

Value

Returns the normalized linear slope of the drug response curve

Examples

```
dose <- c("0.0025", "0.008", "0.025", "0.08", "0.25", "0.8", "2.53", "8")
viability <- c("108.67", "111", "102.16", "100.27", "90", "87", "74", "57")
computeSlope(dose, viability)
```

connectivityScore *Function computing connectivity scores between two signatures*

Description

A function for finding the connectivity between two signatures, using either the GSEA method based on the KS statistic, or the gwc method based on a weighted spearman statistic. The GSEA analysis is implemented in the piano package.

Usage

```
connectivityScore(
  x,
  y,
  method = c("gsea", "fgsea", "gwc"),
  nperm = 10000,
  nthread = 1,
  gwc.method = c("spearman", "pearson"),
  ...
)
```

Arguments

| | |
|------------|--|
| x | A matrix with the first gene signature. In the case of GSEA the vector of values per gene for GSEA in which we are looking for an enrichment. In the case of gwc, this should be a matrix, with the per gene responses in the first column, and the significance values in the second. |
| y | A matrix with the second signature. In the case of GSEA, this is the vector of up and down regulated genes we are looking for in our signature, with the direction being determined from the sign. In the case of gwc, this should be a matrix of identical size to x, once again with the per gene responses in the first column, and their significance in the second. |
| method | character string identifying which method to use, out of 'gsea' and 'gwc' |
| nperm | numeric, how many permutations should be done to determine significance through permutation testing? The minimum is 100, default is 1e4. |
| nthread | numeric, how many cores to run parallel processing on. |
| gwc.method | character, should gwc use a weighted spearman or pearson statistic? |
| ... | Additional arguments passed down to gsea and gwc functions |

Value

numeric a numeric vector with the score and the p-value associated with it

References

F. Pozzi, T. Di Matteo, T. Aste, "Exponential smoothing weighted correlations", The European Physical Journal B, Vol. 85, No 6, 2012. DOI: 10.1140/epjb/e2012-20697-x

Varemo, L., Nielsen, J. and Nookaew, I. (2013) Enriching the gene set analysis of genome-wide data by incorporating directionality of gene expression and combining statistical hypotheses and methods. Nucleic Acids Research. 41 (8), 4378-4391. doi: 10.1093/nar/gkt111

Examples

```
xValue <- c(1,5,23,4,8,9,2,19,11,12,13)
xSig <- c(0.01, 0.001, .97, 0.01,0.01,0.28,0.7,0.01,0.01,0.01,0.01)
yValue <- c(1,5,10,4,8,19,22,19,11,12,13)
ySig <- c(0.01, 0.001, .97,0.01, 0.01,0.78,0.9,0.01,0.01,0.01,0.01)
xx <- cbind(xValue, xSig)
yy <- cbind(yValue, ySig)
rownames(xx) <- rownames(yy) <- c('1','2','3','4','5','6','7','8','9','10','11')
data.cor <- connectivityScore(xx,yy,method="gwc", gwc.method="spearman", nperm=300)
```

cosinePerm

*Computes the cosine similarity and significance using permutation test***Description**

Computes the cosine similarity and significance using permutation test

Usage

```
cosinePerm(
  x,
  y,
  nperm = 1000,
  alternative = c("two.sided", "less", "greater"),
  include.perm = FALSE,
  setseed = 12345,
  nthread = 1
)
```

Arguments

| | |
|--------------|--|
| x | [factor] is the factors for the first variable |
| y | [factor] is the factors for the second variable |
| nperm | [integer] is the number of permutations to compute the null distribution of MCC estimates |
| alternative | [string] indicates the alternative hypothesis and must be one of "two.sided", "greater" or "less". You can specify just the initial letter. "greater" corresponds to positive association, "less" to negative association. Options are "two.sided", "less", or "greater" |
| include.perm | [boolean] indicates whether the estimates for the null distribution should be returned. Default set to 'FALSE' |
| setseed | [integer] is the seed specified by the user. Defaults is '12345' |
| nthread | [integer] is the number of threads to be used to perform the permutations in parallel |

Value

list estimate of the cosine similarity, p-value and estimates after random permutations (null distribution) in include.perm is set to 'TRUE'

Examples

```
x <- factor(c(1,2,1,2,1))
y <- factor(c(2,2,1,1,1))
cosinePerm(x, y)
```

| | |
|-------------|----------------------------|
| dateCreated | <i>dateCreated Generic</i> |
|-------------|----------------------------|

Description

A generic for the dateCreated method

Usage

```
dateCreated(pSet)
```

Arguments

pSet A PharmacoSet

Value

The date the PharmacoSet was created

Examples

```
data(CCLEsmall)
dateCreated(CCLEsmall)
```

| | |
|------------------------|--|
| dim,PharmacoSet-method | <i>Get the dimensions of a PharmacoSet</i> |
|------------------------|--|

Description

Get the dimensions of a PharmacoSet

Usage

```
## S4 method for signature 'PharmacoSet'
dim(x)
```

Arguments

x PharmacoSet

Value

A named vector with the number of Cells and Drugs in the PharmacoSet

| | |
|-----------------|--|
| downloadPertSig | <i>Download Drug Perturbation Signatures</i> |
|-----------------|--|

Description

This function allows you to download an array of drug perturbation signatures, as would be computed by the `drugPerturbationSig` function, for the available perturbation `PharmacoSets`. This function allows the user to skip these very lengthy calculation steps for the datasets available, and start their analysis from the already computed signatures

Usage

```
downloadPertSig(  
  name,  
  saveDir = file.path(".", "PSETS", "Sigs"),  
  myfn = NULL,  
  verbose = TRUE  
)
```

Arguments

| | |
|---------|---|
| name | Character string, the name of the <code>PharmacoSet</code> for which to download signatures. The name should match the names returned in the <code>availablePSETS</code> table. |
| saveDir | Character string with the folder path where the <code>PharmacoSet</code> should be saved. Defaults to <code>"/PSETS/Sigs/"</code> . Will create directory if it does not exist. |
| myfn | character string, the file name to save the dataset under |
| verbose | bool Should status messages be printed during download. Defaults to <code>TRUE</code> . |

Value

An array type object containing the signatures

Examples

```
if (interactive()){  
  downloadPertSig("CMAP")  
}
```

| | |
|--------------|--------------------------------------|
| downloadPSet | <i>Download a PharmacoSet object</i> |
|--------------|--------------------------------------|

Description

This function allows you to download a `PharmacoSet` object for use with this package. The `PharmacoSets` have been extensively curated and organised within a `PharmacoSet` class, enabling use with all the analysis tools provided in `PharmacoGx`.

Usage

```
downloadPSet(
  name,
  saveDir = file.path(".", "Psets"),
  pSetFileName = NULL,
  verbose = TRUE
)
```

Arguments

| | |
|--------------|--|
| name | Character string, the name of the PharmacoSet to download. |
| saveDir | Character string with the folder path where the PharmacoSet should be saved. Defaults to './Psets/'. Will create directory if it does not exist. |
| pSetFileName | character string, the file name to save the dataset under |
| verbose | bool Should status messages be printed during download. Defaults to TRUE. |

Value

A PSet object with the dataset, downloaded from our server

Examples

```
if (interactive()){
  downloadPSet("CMAP")
}
```

drugDoseResponseCurve *Plot drug response curve of a given drug and a given cell for a list of pSets (objects of the PharmacoSet class).*

Description

Given a list of PharmacoSets, the function will plot the drug_response curve, for a given drug/cell pair. The y axis of the plot is the viability percentage and x axis is the log transformed concentrations. If more than one pSet is provided, a light gray area would show the common concentration range between pSets. User can ask for type of sensitivity measurement to be shown in the plot legend. The user can also provide a list of their own concentrations and viability values, as in the examples below, and it will be treated as experiments equivalent to values coming from a pset. The names of the concentration list determine the legend labels.

Usage

```
drugDoseResponseCurve(
  drug,
  cellline,
  pSets = list(),
  concentrations = list(),
  viabilities = list(),
  conc_as_log = FALSE,
```

```

viability_as_pct = TRUE,
trunc = TRUE,
legends.label = c("ic50_published", "gi50_published", "auc_published",
  "auc_recomputed", "ic50_recomputed"),
ylim = c(0, 100),
xlim,
mycol,
title,
plot.type = c("Fitted", "Actual", "Both"),
summarize.replicates = TRUE,
lwd = 0.5,
cex = 0.7,
cex.main = 0.9,
legend.loc = "topright",
verbose = TRUE
)

```

Arguments

| | |
|-----------------------------|---|
| drug | [string] A drug name for which the drug response curve should be plotted. If the plot is desirable for more than one pharmaco set, A unique drug id should be provided. |
| cellline | [string] A cell line name for which the drug response curve should be plotted. If the plot is desirable for more than one pharmaco set, A unique cell id should be provided. |
| pSets | [list] a list of PharmacoSet objects, for which the function should plot the curves. |
| concentrations, viabilities | [list] A list of concentrations and viabilities to plot, the function assumes that concentrations[[i]] is plotted against viabilities[[i]]. The names of the concentration list are used to create the legend labels |
| conc_as_log | [logical], if true, assumes that log10-concentration data has been given rather than concentration data, and that log10(ICn) should be returned instead of ICn. Applies only to the concentrations parameter. |
| viability_as_pct | [logical], if false, assumes that viability is given as a decimal rather than a percentage, and that E_inf passed in as decimal. Applies only to the viabilities parameter. |
| trunc | [bool] Should the viability values be truncated to lie in [0-100] before doing the fitting |
| legends.label | [vector] A vector of sensitivity measurement types which could be any combination of ic50_published, auc_published, auc_recomputed and auc_recomputed_star. A legend will be displayed on the top right of the plot which each line of the legend is the values of requested sensitivity measurements for one of the requested pSets. If this parameter is missed no legend would be provided for the plot. |
| ylim | [vector] A vector of two numerical values to be used as ylim of the plot. If this parameter would be missed c(0,100) would be used as the ylim of the plot. |
| xlim | [vector] A vector of two numerical values to be used as xlim of the plot. If this parameter would be missed the minimum and maximum concentrations between all the pSets would be used as plot xlim. |

| | |
|----------------------|--|
| mycol | [vector] A vector with the same length of the pSets parameter which will determine the color of the curve for the pharmac sets. If this parameter is missed default colors from Rcolorbrewer package will be used as curves color. |
| title | [character] The title of the graph. If no title is provided, then it defaults to 'Drug':'Cell Line'. |
| plot.type | [character] Plot type which can be the actual one ("Actual") or the one fitted by logl logistic regression ("Fitted") or both of them ("Both"). If this parameter is missed by default actual curve is plotted. |
| summarize.replicates | [character] If this parameter is set to true replicates are summarized and replicates are plotted individually otherwise |
| lwd | [numeric] The line width to plot with |
| cex | [numeric] The cex parameter passed to plot |
| cex.main | [numeric] The cex.main parameter passed to plot, controls the size of the titles |
| legend.loc | And argument passable to xy.coords for the position to place the legend. |
| verbose | [boolean] Should warning messages about the data passed in be printed? |

Value

Plots to the active graphics device and returns and invisible NULL.

Examples

```
if (interactive()) {
  drugDoseResponseCurve(concentrations=list("Experiment 1"=c(.008, .04, .2, 1)),
    viabilities=list(c(100,50,30,1)), plot.type="Both")
}
```

 drugInfo

drugInfo Generic

Description

Generic for drugInfo method

Usage

```
drugInfo(pSet)
```

Arguments

pSet The Pharmacoset to retrieve drug info from

Value

a data.frame with the drug annotations

Examples

```
data(CCLEsmall)
drugInfo(CCLEsmall)
```

| | |
|------------|------------------------------|
| drugInfo<- | <i>drugInfo<- Generic</i> |
|------------|------------------------------|

Description

Generic for drugInfo replace method

Usage

```
drugInfo(object) <- value
```

Arguments

| | |
|--------|--|
| object | The PharmacoSet to replace drug info in |
| value | A data.frame with the new drug annotations |

Value

Updated PharmacoSet

Examples

```
data(CCLEsmall)
drugInfo(CCLEsmall) <- drugInfo(CCLEsmall)
```

| | |
|-----------|--------------------------|
| drugNames | <i>drugNames Generic</i> |
|-----------|--------------------------|

Description

A generic for the drugNames method

Usage

```
drugNames(pSet)
```

Arguments

| | |
|------|---|
| pSet | The PharmacoSet to return drug names from |
|------|---|

Value

A vector of the drug names used in the PharmacoSet

Examples

```
data(CCLEsmall)
drugNames(CCLEsmall)
```

```
drugNames<-          drugNames<- Generic
```

Description

A generic for the drugNames replacement method

Usage

```
drugNames(object) <- value
```

Arguments

| | |
|--------|--|
| object | The PharmacoSet to update |
| value | A character vector of the new drug names |

Value

Updated PharmacoSet

Examples

```
data(CCLEsmall)
drugNames(CCLEsmall) <- drugNames(CCLEsmall)
```

```
drugPerturbationSig  Creates a signature representing gene expression (or other molecular profile) change induced by administering a drug, for use in drug effect analysis.
```

Description

Given a PharmacoSet of the perturbation experiment type, and a list of drugs, the function will compute a signature for the effect of drug concentration on the molecular profile of a cell. The algorithm uses a regression model which corrects for experimental batch effects, cell specific differences, and duration of experiment to isolate the effect of the concentration of the drug applied. The function returns the estimated coefficient for concentration, the t-stat, the p-value and the false discovery rate associated with that coefficient, in a 3 dimensional array, with genes in the first direction, drugs in the second, and the selected return values in the third.

Usage

```
drugPerturbationSig(
  pSet,
  mDataType,
  drugs,
  cells,
  features,
  nthread = 1,
```

```

returnValues = c("estimate", "tstat", "pvalue", "fdr"),
verbose = FALSE
)

```

Arguments

| | |
|--------------|---|
| pSet | [PharmacoSet] a PharmacoSet of the perturbation experiment type |
| mDataType | [character] which one of the molecular data types to use in the analysis, out of dna, rna, rnaseq, snp, cnv |
| drugs | [character] a vector of drug names for which to compute the signatures. Should match the names used in the PharmacoSet. |
| cells | [character] a vector of cell names to use in computing the signatures. Should match the names used in the PharmacoSet. |
| features | [character] a vector of features for which to compute the signatures. Should match the names used in correspondent molecular data in PharmacoSet. |
| nthread | [numeric] if multiple cores are available, how many cores should the computation be parallelized over? |
| returnValues | [character] Which of estimate, t-stat, p-value and fdr should the function return for each gene drug pair? |
| verbose | [bool] Should diagnostic messages be printed? (default false) |

Value

list a 3D array with genes in the first dimension, drugs in the second, and return values in the third.

Examples

```

data(CMAPsmall)
drug.perturbation <- drugPerturbationSig(CMAPsmall, mDataType="rna", nthread=1)
print(drug.perturbation)

```

| | |
|--------------------|--|
| drugSensitivitySig | <i>Creates a signature representing the association between gene expression (or other molecular profile) and drug dose response, for use in drug sensitivity analysis.</i> |
|--------------------|--|

Description

Given a PharmacoSet of the sensitivity experiment type, and a list of drugs, the function will compute a signature for the effect gene expression on the molecular profile of a cell. The function returns the estimated coefficient, the t-stat, the p-value and the false discovery rate associated with that coefficient, in a 3 dimensional array, with genes in the first direction, drugs in the second, and the selected return values in the third.

Usage

```

drugSensitivitySig(
  pSet,
  mDataType,
  drugs,
  features,
  cells,
  tissues,
  sensitivity.measure = "auc_recomputed",
  molecular.summary.stat = c("mean", "median", "first", "last", "or", "and"),
  sensitivity.summary.stat = c("mean", "median", "first", "last"),
  returnValues = c("estimate", "pvalue", "fdr"),
  sensitivity.cutoff,
  standardize = c("SD", "rescale", "none"),
  molecular.cutoff = NA,
  molecular.cutoff.direction = c("less", "greater"),
  nthread = 1,
  verbose = TRUE,
  ...
)

```

Arguments

| | |
|--------------------------|--|
| pSet | [PharmacoSet] a PharmacoSet of the perturbation experiment type |
| mDataType | [character] which one of the molecular data types to use in the analysis, out of dna, rna, rnaseq, snp, cnv |
| drugs | [character] a vector of drug names for which to compute the signatures. Should match the names used in the PharmacoSet. |
| features | [character] a vector of features for which to compute the signatures. Should match the names used in correspondant molecular data in PharmacoSet. |
| cells | [character] allows choosing exactly which cell lines to include for the signature fitting. Should be a subset of cellNames(pSet) |
| tissues | [character] a vector of which tissue types to include in the signature fitting. Should be a subset of cellInfo(pSet)\$tissueid |
| sensitivity.measure | [character] which measure of the drug dose sensitivity should the function use for its computations? Use the sensitivityMeasures function to find out what measures are available for each PSet. |
| molecular.summary.stat | What summary statistic should be used to summarize duplicates for cell line molecular profile measurements? |
| sensitivity.summary.stat | What summary statistic should be used to summarize duplicates for cell line sensitivity measurements? |
| returnValues | [character] Which of estimate, t-stat, p-value and fdr should the function return for each gene drug pair? |
| sensitivity.cutoff | [numeric] Allows the user to binarize the sensitivity data using this threshold. |

| | |
|----------------------------|--|
| standardize | [character] One of "SD", "rescale", or "none", for the form of standardization of the data to use. If "SD", the the data is scaled so that SD = 1. If rescale, then the data is scaled so that the 95 interquantile range lies in [0,1]. If none no rescaling is done. |
| molecular.cutoff | Allows the user to binarize the sensitivity data using this threshold. |
| molecular.cutoff.direction | [character] One of "less" or "greater", allows to set direction of binarization. |
| nthread | [numeric] if multiple cores are available, how many cores should the computation be parallelized over? |
| verbose | [boolean] 'TRUE' if the warnings and other infomrative message should be displayed |
| ... | additional arguments not currently fully supported by the function |

Value

list a 3D array with genes in the first dimension, drugs in the second, and return values in the third.

Examples

```
data(GDSCsmall)
drug.sensitivity <- drugSensitivitySig(GDSCsmall, mDataType="rna",
                                     nthread=1, features = fName(GDSCsmall, "rna")[1])
print(drug.sensitivity)
```

| | |
|-------------|----------------------------|
| featureInfo | <i>featureInfo Generic</i> |
|-------------|----------------------------|

Description

Generic for featureInfo method

Usage

```
featureInfo(pSet, mDataType)
```

Arguments

| | |
|-----------|--|
| pSet | The PharmacoSet to retrieve feature annotations from |
| mDataType | the type of molecular data |

Value

a data.frame with the experiment info

Examples

```
data(CCLEsmall)
featureInfo(CCLEsmall, "rna")
```

```
featureInfo<-          featureInfo<- Generic
```

Description

Generic for featureInfo replace method

Usage

```
featureInfo(object, mDataType) <- value
```

Arguments

| | |
|-----------|--|
| object | The PharmacoS _{et} to replace gene annotations in |
| mDataType | The type of molecular data to be updated |
| value | A data.frame with the new feature annotations |

Value

Updated PharmacoS_{et}

Examples

```
data(CCLEsmall)
featureInfo(CCLEsmall, "rna") <- featureInfo(CCLEsmall, "rna")
```

| | |
|-------------------|---|
| filterNoisyCurves | <i>Viability measurements in dose-reponse curves must remain stable or decrease monotonically reflecting response to the drug being tested. filterNoisyCurves flags dose-response curves that strongly violate these assumptions.</i> |
|-------------------|---|

Description

Viability measurements in dose-reponse curves must remain stable or decrease monotonically reflecting response to the drug being tested. filterNoisyCurves flags dose-response curves that strongly violate these assumptions.

Usage

```
filterNoisyCurves(
  pSet,
  epsilon = 25,
  positive.cutoff.percent = 0.8,
  mean.viability = 200,
  nthread = 1
)
```

Arguments

| | |
|-------------------------|--|
| pSet | [PharmacoSet] a PharmacoSet object |
| epsilon | [numeric] a value indicates assumed threshold for the distance between to consecutive viability values on the drug-response curve in the analysis, out of dna, rna, rnaseq, snp, cnv |
| positive.cutoff.percent | [numeric] This value indicates that function may violate epsilon rule for how many points on drug-response curve |
| mean.viability | [numeric] average expected viability value |
| nthread | [numeric] if multiple cores are available, how many cores should the computation be parallelized over? |

Value

a list with two elements 'noisy' containing the rownames of the noisy curves, and 'ok' containing the rownames of the non-noisy curves

Examples

```
data(GDSCsmall)
filterNoisyCurves(GDSCsmall)
```

| | |
|--------|-----------------------|
| fNames | <i>fNames Generic</i> |
|--------|-----------------------|

Description

A generic for the fNames method

Usage

```
fNames(pSet, mDataType)
```

Arguments

| | |
|-----------|---|
| pSet | The PharmacoSet |
| mDataType | The molecular data type to return feature names for |

Value

A character vector of the feature names

Examples

```
data(CCLEsmall)
fNames(CCLEsmall, "rna")
```

`GDSCsmall`*Genomics of Drug Sensitivity in Cancer Example PharmacoSet*

Description

A small example version of the Genomics of Drug Sensitivity in Cancer Project PharmacoSet, used in the documentation examples. All credit for the data goes to the Genomics of Drug Sensitivity in Cancer Project group at the Sanger. This is not a full version of the dataset, most of the dataset was removed to make runnable example code. For the full dataset, please download using the `downloadPSet` function.

Usage

```
data(GDSCsmall)
```

Format

PharmacoSet object

References

Garnett et al. Systematic identification of genomic markers of drug sensitivity in cancer cells. *Nature*, 2012.

`gwc`*Calculate the gwc score between two vectors, using either a weighted spearman or pearson correlation*

Description

Calculate the gwc score between two vectors, using either a weighted spearman or pearson correlation

Usage

```
gwc(  
  x1,  
  p1,  
  x2,  
  p2,  
  method.cor = c("pearson", "spearman"),  
  nperm = 10000,  
  truncate.p = 1e-16,  
  ...  
)
```

Arguments

| | |
|------------|---|
| x1 | numeric vector of effect sizes (e.g., fold change or t statistics) for the first experiment |
| p1 | numeric vector of p-values for each corresponding effect size for the first experiment |
| x2 | numeric effect size (e.g., fold change or t statistics) for the second experiment |
| p2 | numeric vector of p-values for each corresponding effect size for the second experiment |
| method.cor | character string identifying if a pearson or spearman correlation should be used |
| nperm | numeric how many permutations should be done to determine |
| truncate.p | numeric Truncation value for extremely low p-values |
| ... | Other passed down to internal functions |

Value

numeric a vector of two values, the correlation and associated p-value.

Examples

```
data(CCLEsmall)
x <- molecularProfiles(CCLEsmall,"rna")[,1]
y <- molecularProfiles(CCLEsmall,"rna")[,2]
x_p <- rep(0.05, times=length(x))
y_p <- rep(0.05, times=length(y))
names(x_p) <- names(x)
names(y_p) <- names(y)
gwc(x,x_p,y,y_p, nperm=100)
```

HDAC_genes

HDAC Gene Signature

Description

A gene signature for HDAC inhibitors, as detailed by Glaser et al. The signature is mapped from the probe to gene level using probeGeneMapping

Usage

```
data(HDAC_genes)
```

Format

a 13x2 data.frame with gene identifiers in the first column and direction change in the second

References

Glaser et al. Gene expression profiling of multiple histone deacetylase (HDAC) inhibitors: defining a common gene set produced by HDAC inhibition in T24 and MDA carcinoma cell lines. *Molecular cancer therapeutics*, 2003.

| | |
|---------------|--|
| intersectList | <i>Utility to find the intersection between a list of more than two vectors or lists</i> |
|---------------|--|

Description

This function extends the native intersect function to work on two or more arguments.

Usage

```
intersectList(...)
```

Arguments

... A list of or any number of vector like objects of the same mode, which could also be operated on by the native R set operations

Value

A vector like object of the same mode as the first argument, containing only the intersection common to all arguments to the function

Examples

```
list1 <- list('a', 'b', 'c')
list2 <- list('a', 'c')
list3 <- list('a', 'c', 'd')
listAll <- intersectList(list1, list2, list3)
listAll
```

| | |
|---------------|--|
| intersectPSet | <i>Intersects objects of the PharmacoSet class, subsetting them to the common drugs and/or cell lines as selected by the user.</i> |
|---------------|--|

Description

Given a list of PharmacoSets, the function will find the common drugs, and/or cell lines, and return PharmacoSets that contain data only pertaining to the common drugs, and/or cell lines. The mapping between dataset drug and cell names is done using annotations found in the PharmacoSet object's internal curation slot

Usage

```
intersectPSet(
  pSets,
  intersectOn = c("drugs", "cell.lines", "concentrations"),
  cells,
  drugs,
  strictIntersect = FALSE,
  verbose = TRUE,
  nthread = 1
)
```

Arguments

| | |
|-----------------|--|
| pSets | [list] a list of PharmacoSet objects, of which the function should find the intersection |
| intersectOn | [character] which identifiers to intersect on, drugs, cell lines, or concentrations |
| cells | a vector of common cell lines between pSets. In case user is interested on getting intersection on certain cell lines, they can provide their list of cell lines |
| drugs | a vector of common drugs between pSets. In case user is interested on getting intersection on certain drugs, they can provide their list of drugs. |
| strictIntersect | [boolean] Should the intersection keep only the drugs and cell lines that have been tested on together? |
| verbose | [boolean] Should the function announce its key steps? |
| nthread | [numeric] The number of cores to use to run intersection on concentrations |

Value

list a list of pSets, containing only the intersection

Examples

```
data(GDSCsmall)
data(CCLEsmall)
common <- intersectPSet(list('GDSC'=GDSCsmall,
  'CCLE'=CCLEsmall), intersectOn = c("drugs", "cell.lines"))
common$CGP
common$CCLE
```

logLogisticRegression *Fits curves of the form $E = E_{inf} + (1 - E_{inf})/(1 + (c/EC50)^{HS})$ to dose-response data points (c, E) given by the user and returns a vector containing estimates for HS , E_{inf} , and $EC50$.*

Description

By default, logLogisticRegression uses an L-BFGS algorithm to generate the fit. However, if this fails to converge to solution, logLogisticRegression samples lattice points throughout the parameter space. It then uses the lattice point with minimal least-squares residual as an initial guess for the optimal parameters, passes this guess to drm, and re-attempts the optimization. If this still fails, logLogisticRegression uses the PatternSearch algorithm to fit a log-logistic curve to the data.

Usage

```
logLogisticRegression(
  conc,
  viability,
  density = c(2, 10, 2),
  step = 0.5/density,
  precision = 0.05,
```

```

lower_bounds = c(0, 0, -6),
upper_bounds = c(4, 1, 6),
scale = 0.07,
family = c("normal", "Cauchy"),
median_n = 1,
conc_as_log = FALSE,
viability_as_pct = TRUE,
trunc = TRUE,
verbose = FALSE
)

```

Arguments

| | |
|------------------|--|
| conc | [vector] is a vector of drug concentrations. |
| viability | [vector] is a vector whose entries are the viability values observed in the presence of the drug concentrations whose logarithms are in the corresponding entries of the log_conc, where viability 0 indicates that all cells died, and viability 1 indicates that the drug had no effect on the cells. |
| density | [vector] is a vector of length 3 whose components are the numbers of lattice points per unit length along the HS-, E_inf-, and base-10 logarithm of the EC50-dimensions of the parameter space, respectively. |
| step | [vector] is a vector of length 3 whose entries are the initial step sizes in the HS, E_inf, and base-10 logarithm of the EC50 dimensions, respectively, for the PatternSearch algorithm. |
| precision | is a positive real number such that when the ratio of current step size to initial step size falls below it, the PatternSearch algorithm terminates. A smaller value will cause LogisticPatternSearch to take longer to complete optimization, but will produce a more accurate estimate for the fitted parameters. |
| lower_bounds | [vector] is a vector of length 3 whose entries are the lower bounds on the HS, E_inf, and base-10 logarithm of the EC50 parameters, respectively. |
| upper_bounds | [vector] is a vector of length 3 whose entries are the upper bounds on the HS, E_inf, and base-10 logarithm of the EC50 parameters, respectively. |
| scale | is a positive real number specifying the shape parameter of the Cauchy distribution. |
| family | [character], if "cauchy", uses MLE under an assumption of Cauchy-distributed errors instead of sum-of-squared-residuals as the objective function for assessing goodness-of-fit of dose-response curves to the data. Otherwise, if "normal", uses MLE with a gaussian assumption of errors |
| median_n | If the viability points being fit were medians of measurements, they are expected to follow a median of family distribution, which is in general quite different from the case of one measurement. Median_n is the number of measurements the median was taken of. If the measurements are means of values, then both the Normal and the Cauchy distributions are stable, so means of Cauchy or Normal distributed variables are still Cauchy and normal respectively. |
| conc_as_log | [logical], if true, assumes that log10-concentration data has been given rather than concentration data, and that log10(EC50) should be returned instead of EC50. |
| viability_as_pct | [logical], if false, assumes that viability is given as a decimal rather than a percentage, and that E_inf should be returned as a decimal rather than a percentage. |

trunc [logical], if true, causes viability data to be truncated to lie between 0 and 1 before curve-fitting is performed.

verbose [logical], if true, causes warnings thrown by the function to be printed.

Value

A vector containing estimates for HS, E_inf, and EC50

Examples

```
dose <- c("0.0025", "0.008", "0.025", "0.08", "0.25", "0.8", "2.53", "8")
viability <- c("108.67", "111", "102.16", "100.27", "90", "87", "74", "57")
computeAUC(dose, viability)
```

mcc

*Compute a Mathews Correlation Coefficient***Description**

The function computes a Matthews correlation coefficient for two factors provided to the function. It assumes each factor is a factor of class labels, and the entries are paired in order of the vectors.

Usage

```
mcc(x, y, nperm = 1000, setseed = 12345, nthread = 1)
```

Arguments

x, y factor of the same length with the same number of levels

nperm number of permutations for significance estimation. If 0, no permutation testing is done

setseed seed for permutation testing

nthread can parallelize permutation testing using parallel's mclapply

Value

A list with the MCC as the \$estimate, and p value as \$p.value

Examples

```
x <- factor(c(1,2,1,2,3,1))
y <- factor(c(2,1,1,1,2,2))
mcc(x,y)
```

| | |
|------------|-------------------|
| mDataNames | <i>mDataNames</i> |
|------------|-------------------|

Description

Returns the molecular data names for the PharmacoSet.

Usage

```
mDataNames(pSet)
```

Arguments

| | |
|------|--------------------|
| pSet | PharmacoSet object |
|------|--------------------|

Value

Vector of names of the molecular data types

Examples

```
data(CCLEsmall)
mDataNames(CCLEsmall)
```

| | |
|-------------------|----------------------------------|
| molecularProfiles | <i>molecularProfiles Generic</i> |
|-------------------|----------------------------------|

Description

Generic for molecularProfiles method

Usage

```
molecularProfiles(pSet, mDataType)
```

Arguments

| | |
|-----------|---|
| pSet | The PharmacoSet to retrieve molecular profiles from |
| mDataType | the type of molecular data |

Value

a data.frame with the experiment info

Examples

```
data(CCLEsmall)
molecularProfiles(CCLEsmall, "rna")
```

molecularProfiles<- *molecularProfiles<- Generic*

Description

Generic for molecularProfiles replace method

Usage

```
molecularProfiles(object, mDataType) <- value
```

Arguments

| | |
|-----------|--|
| object | The PharmacoSet to replace molecular profiles in |
| mDataType | The type of molecular data to be updated |
| value | A matrix with the new profiles |

Value

Updated PharmacoSet

Examples

```
data(CCLEsmall)
molecularProfiles(CCLEsmall, "rna") <- molecularProfiles(CCLEsmall, "rna")
```

pertNumber *pertNumber Generic*

Description

A generic for the pertNumber method

Usage

```
pertNumber(pSet)
```

Arguments

| | |
|------|---------------|
| pSet | A PharmacoSet |
|------|---------------|

Value

A 3D array with the number of perturbation experiments per drug and cell line, and data type

Examples

```
data(CCLEsmall)
pertNumber(CCLEsmall)
```

pertNumber<- *pertNumber<- Generic*

Description

A generic for the pertNumber method

Usage

```
pertNumber(object) <- value
```

Arguments

| | |
|--------|--|
| object | A PharmacoSet |
| value | A new 3D array with the number of perturbation experiments per drug and cell line, and data type |

Value

The updated PharmacoSet

Examples

```
data(CCLEsmall)
pertNumber(CCLEsmall) <- pertNumber(CCLEsmall)
```

PharmacoSet *PharmacoSet constructor*

Description

A constructor that simplifies the process of creating PharmacoSets, as well as creates empty objects for data not provided to the constructor. Only objects returned by this constructor are expected to work with the PharmacoSet methods. For a much more detailed instruction on creating PharmacoSets, please see the "CreatingPharmacoSet" vignette.

Usage

```
PharmacoSet(
  name,
  molecularProfiles = list(),
  cell = data.frame(),
  drug = data.frame(),
  sensitivityInfo = data.frame(),
  sensitivityRaw = array(dim = c(0, 0, 0)),
  sensitivityProfiles = matrix(),
  sensitivityN = matrix(nrow = 0, ncol = 0),
  perturbationN = array(NA, dim = c(0, 0, 0)),
  curationDrug = data.frame(),
```

```

    curationCell = data.frame(),
    curationTissue = data.frame(),
    datasetType = c("sensitivity", "perturbation", "both"),
    verify = TRUE
  )

```

Arguments

| | |
|---|---|
| <code>name</code> | A character string detailing the name of the dataset |
| <code>molecularProfiles</code> | A list of ExpressionSet objects containing molecular profiles |
| <code>cell</code> | A data.frame containing the annotations for all the cell lines profiled in the data set, across all data types |
| <code>drug</code> | A data.frame containing the annotations for all the drugs profiled in the data set, across all data types |
| <code>sensitivityInfo</code> | A data.frame containing the information for the sensitivity experiments |
| <code>sensitivityRaw</code> | A 3 Dimensional array containing the raw drug dose response data for the sensitivity experiments |
| <code>sensitivityProfiles</code> | data.frame containing drug sensitivity profile statistics such as IC50 and AUC |
| <code>sensitivityN, perturbationN</code> | A data.frame summarizing the available sensitivity/perturbation data |
| <code>curationDrug, curationCell, curationTissue</code> | A data.frame mapping the names for drugs, cells and tissues used in the data set to universal identifiers used between different PharmacoSet objects |
| <code>datasetType</code> | A character string of 'sensitivity', 'preturbation', or both detailing what type of data can be found in the PharmacoSet, for proper processing of the data |
| <code>verify</code> | boolean Should the function verify the PharmacoSet and print out any errors it finds after construction? |

Value

An object of class PharmacoSet

Examples

```

## For help creating a PharmacoSet object, please see the following vignette:
browseVignettes("PharmacoGx")

```

| | |
|-------------------|--|
| PharmacoSet-class | <i>A Class to Contain PharmacoGenomic datasets together with their curations</i> |
|-------------------|--|

Description

The PharmacoSet (PSet) class was developed to contain and organise large PharmacoGenomic datasets, and aid in their metanalysis. It was designed primarily to allow bioinformaticians and biologists to work with data at the level of genes, drugs and cell lines, providing a more naturally intuitive interface and simplifying analyses between several datasets. As such, it was designed to be flexible enough to hold datasets of two different natures while providing a common interface. The class can accomodate datasets containing both drug dose response data, as well as datasets containing genetic profiles of cell lines pre and post treatment with compounds, known respectively as sensitivity and perturbation datasets.

Usage

```
## S4 method for signature 'PharmacoSet'
cellInfo(pSet)

## S4 replacement method for signature 'PharmacoSet,data.frame'
cellInfo(object) <- value

## S4 method for signature 'PharmacoSet'
drugInfo(pSet)

## S4 replacement method for signature 'PharmacoSet,data.frame'
drugInfo(object) <- value

## S4 method for signature 'PharmacoSet'
phenoInfo(pSet, mDataType)

## S4 replacement method for signature 'PharmacoSet,character,data.frame'
phenoInfo(object, mDataType) <- value

## S4 method for signature 'PharmacoSet'
molecularProfiles(pSet, mDataType)

## S4 replacement method for signature 'PharmacoSet,character,matrix'
molecularProfiles(object, mDataType) <- value

## S4 method for signature 'PharmacoSet'
featureInfo(pSet, mDataType)

## S4 replacement method for signature 'PharmacoSet,character,data.frame'
featureInfo(object, mDataType) <- value

## S4 method for signature 'PharmacoSet'
sensitivityInfo(pSet)

## S4 replacement method for signature 'PharmacoSet,data.frame'
```

```
sensitivityInfo(object) <- value

## S4 method for signature 'PharmacoSet'
sensitivityProfiles(pSet)

## S4 replacement method for signature 'PharmacoSet,data.frame'
sensitivityProfiles(object) <- value

## S4 replacement method for signature 'PharmacoSet,matrix'
sensitivityProfiles(object) <- value

## S4 method for signature 'PharmacoSet'
sensitivityMeasures(pSet)

## S4 method for signature 'PharmacoSet'
drugNames(pSet)

## S4 replacement method for signature 'PharmacoSet,character'
drugNames(object) <- value

## S4 method for signature 'PharmacoSet'
cellNames(pSet)

## S4 replacement method for signature 'PharmacoSet,character'
cellNames(object) <- value

## S4 method for signature 'PharmacoSet'
fNames(pSet, mDataType)

## S4 method for signature 'PharmacoSet'
dateCreated(pSet)

## S4 method for signature 'PharmacoSet'
pSetName(pSet)

## S4 method for signature 'PharmacoSet'
pertNumber(pSet)

## S4 method for signature 'PharmacoSet'
sensNumber(pSet)

## S4 replacement method for signature 'PharmacoSet,array'
pertNumber(object) <- value

## S4 replacement method for signature 'PharmacoSet,matrix'
sensNumber(object) <- value
```

Arguments

| | |
|--------|----------------------|
| pSet | A PharmacoSet object |
| object | A PharmacoSet object |
| value | A replacement value |

mDataType A character with the type of molecular data to return/update

Value

An object of the PharmacoSet class

Methods (by generic)

- cellInfo: Returns the annotations for all the cell lines tested on in the PharmacoSet
- cellInfo<-: Update the cell line annotations
- drugInfo: Returns the annotations for all the drugs tested in the PharmacoSet
- drugInfo<-: Update the drug annotations
- phenoInfo: Return the experiment info from the given type of molecular data in PharmacoSet
- phenoInfo<-: Update the the given type of molecular data experiment info in the PharmacoSet
- molecularProfiles: Return the given type of molecular data from the PharmacoSet
- molecularProfiles<-: Update the given type of molecular data from the PharmacoSet
- featureInfo: Return the feature info for the given molecular data
- featureInfo<-: Replace the gene info for the molecular data
- sensitivityInfo: Return the drug dose sensitivity experiment info
- sensitivityInfo<-: Update the sensitivity experiment info
- sensitivityProfiles: Return the phenotypic data for the drug dose sensitivity
- sensitivityProfiles<-: Update the phenotypic data for the drug dose sensitivity
- sensitivityProfiles<-: Update the phenotypic data for the drug dose sensitivity
- sensitivityMeasures: Returns the available sensitivity profile summaries, for example, whether there are IC50 values available
- drugNames: Return the names of the drugs used in the PharmacoSet
- drugNames<-: Update the drug names used in the dataset
- cellNames: Return the cell names used in the dataset
- cellNames<-: Update the cell names used in the dataset
- fName: Return the feature names used in the dataset
- dateCreated: Return the date the PharmacoSet was created
- pSetName: Return the name of the PharmacoSet
- pertNumber: Return the summary of available perturbation experiments
- sensNumber: Return the summary of available sensitivity experiments
- pertNumber<-: Update the summary of available perturbation experiments
- sensNumber<-: Update the summary of available sensitivity experiments

Slots

annotation A list of annotation data about the PharmacoSet, including the \$name and the session information for how the object was creating, detailing the exact versions of R and all the packages used

molecularProfiles A list containing 4 Biobase::ExpressionSet type object for holding data for RNA, DNA, SNP and Copy Number Variation measurements respectively, with associated fData and pData containing the row and column metadata

- `cell` A `data.frame` containing the annotations for all the cell lines profiled in the data set, across all data types
- `drug` A `data.frame` containing the annotations for all the drugs profiled in the data set, across all data types
- `sensitivity` A list containing all the data for the sensitivity experiments, including `$info`, a `data.frame` containing the experimental info, `$raw` a 3D array containing raw data, `$profiles`, a `data.frame` containing sensitivity profiles statistics, and `$n`, a `data.frame` detailing the number of experiments for each cell-drug pair
- `perturbation` A list containing `$n`, a `data.frame` summarizing the available perturbation data,
- `curation` A list containing mappings for `$drug`, `cell`, `tissue` names used in the data set to universal identifiers used between different `PharmacoSet` objects
- `datasetType` A character string of 'sensitivity', 'perturbation', or both detailing what type of data can be found in the `PharmacoSet`, for proper processing of the data

 phenoInfo

phenoInfo Generic

Description

Generic for `phenoInfo` method

Usage

```
phenoInfo(pSet, mDataType)
```

Arguments

| | |
|------------------------|---|
| <code>pSet</code> | The <code>PharmacoSet</code> to retrieve rna annotations from |
| <code>mDataType</code> | the type of molecular data |

Value

a `data.frame` with the experiment info

Examples

```
data(CCLEsmall)
phenoInfo(CCLEsmall, mDataType="rna")
```

phenoInfo<- *phenoInfo<- Generic*

Description

Generic for phenoInfo replace method

Usage

```
phenoInfo(object, mDataType) <- value
```

Arguments

| | |
|-----------|---|
| object | The PharmacoSet to retrieve molecular experiment annotations from |
| mDataType | the type of molecular data |
| value | a data.frame with the new experiment annotations |

Value

The updated PharmacoSet

Examples

```
data(CCLEsmall)
phenoInfo(CCLEsmall, mDataType="rna") <- phenoInfo(CCLEsmall, mDataType="rna")
```

pSetName *pSetName Generic*

Description

A generic for the pSetName method

Usage

```
pSetName(pSet)
```

Arguments

| | |
|------|---------------|
| pSet | A PharmacoSet |
|------|---------------|

Value

The name of the PharmacoSet

Examples

```
data(CCLEsmall)
pSetName(CCLEsmall)
```

| | |
|-----------------|--------------------------------|
| sensitivityInfo | <i>sensitivityInfo Generic</i> |
|-----------------|--------------------------------|

Description

Generic for sensitivityInfo method

Usage

```
sensitivityInfo(pSet)
```

Arguments

pSet The PharmacoSet to retrieve sensitivity experiment annotations from

Value

a data.frame with the experiment info

Examples

```
data(CCLEsmall)
sensitivityInfo(CCLEsmall)
```

| | |
|-------------------|-------------------------------------|
| sensitivityInfo<- | <i>sensitivityInfo<- Generic</i> |
|-------------------|-------------------------------------|

Description

A generic for the sensitivityInfo replacement method

Usage

```
sensitivityInfo(object) <- value
```

Arguments

object The PharmacoSet to update
value A data.frame with the new sensitivity annotations

Value

Updated PharmacoSet

Examples

```
data(CCLEsmall)
sensitivityInfo(CCLEsmall) <- sensitivityInfo(CCLEsmall)
```

sensitivityMeasures *sensitivityMeasures Generic*

Description

A generic for the sensitivityMeasures method

Usage

```
sensitivityMeasures(pSet)
```

Arguments

pSet The PharmacoS

Value

A character vector of all the available sensitivity measures

Examples

```
data(CCLEsmall)
sensitivityMeasures(CCLEsmall)
```

sensitivityProfiles *sensitivityProfiles Generic*

Description

Generic for sensitivityProfiles method

Usage

```
sensitivityProfiles(pSet)
```

Arguments

pSet The PharmacoS to retrieve sensitivity experiment data from

Value

a data.frame with the experiment info

Examples

```
data(CCLEsmall)
sensitivityProfiles(CCLEsmall)
```

sensitivityProfiles<- *sensitivityProfiles<- Generic*

Description

A generic for the sensitivityProfiles replacement method

Usage

```
sensitivityProfiles(object) <- value
```

Arguments

| | |
|--------|--|
| object | The PharmacoS e t to update |
| value | A data.frame with the new sensitivity profiles. If a matrix object is passed in, converted to data.frame before assignment |

Value

Updated PharmacoS**e**t

Examples

```
data(CCLEsmall)
sensitivityProfiles(CCLEsmall) <- sensitivityProfiles(CCLEsmall)
```

sensNumber *sensNumber Generic*

Description

A generic for the sensNumber method

Usage

```
sensNumber(pSet)
```

Arguments

| | |
|------|------------------------|
| pSet | A PharmacoS e t |
|------|------------------------|

Value

A data.frame with the number of sensitivity experiments per drug and cell line

Examples

```
data(CCLEsmall)
sensNumber(CCLEsmall)
```

```
sensNumber<-          sensNumber<- Generic
```

Description

A generic for the sensNumber method

Usage

```
sensNumber(object) <- value
```

Arguments

| | |
|--------|--|
| object | A PharmacoSet |
| value | A new data.frame with the number of sensitivity experiments per drug and cell line |

Value

The updated PharmacoSet

Examples

```
data(CCLEsmall)
sensNumber(CCLEsmall) <- sensNumber(CCLEsmall)
```

```
show,PharmacoSet-method
          Show a PharamcoSet
```

Description

Show a PharamcoSet

Usage

```
## S4 method for signature 'PharmacoSet'
show(object)
```

Arguments

| | |
|--------|-------------|
| object | PharmacoSet |
|--------|-------------|

Value

Prints the PharmacoSet object to the output stream, and returns invisible NULL.

Examples

```
data(CCLEsmall)
CCLEsmall
```

show,PharmacoSig-method
Show PharmacoGx Signatures

Description

Show PharmacoGx Signatures

Usage

```
## S4 method for signature 'PharmacoSig'  
show(object)
```

Arguments

object PharmacoSig

Value

Prints the PharmacoGx Signatures object to the output stream, and returns invisible NULL.

Examples

```
data(GDSCsmall)  
drug.sensitivity <- drugSensitivitySig(GDSCsmall, mDataType="rna",  
                                      nthread=1, features = fNames(GDSCsmall, "rna")[1])  
drug.sensitivity
```

showSigAnnot *Show the Annotations of a signature object*

Description

This function prints out the information about the call used to compute the drug signatures, and the session info for the session in which the computation was done. Useful for determining the exact conditions used to generate signatures.

Usage

```
showSigAnnot(Sigs)
```

Arguments

Sigs An object of the PharmacoSig Class, as returned by drugPerturbationSig or drugSensitivitySig

Value

Prints the PharmacoGx Signatures annotations to the output stream, and returns invisible NULL.

Examples

```
data(GDSCsmall)
drug.sensitivity <- drugSensitivitySig(GDSCsmall, mDataType="rna",
                                     nthread=1, features = fNames(GDSCsmall, "rna")[1])
showSigAnnot(drug.sensitivity)
```

| | |
|----------|--|
| subsetTo | <i>A function to subset a PharmacoSet to data containing only specified drugs, cells and genes</i> |
|----------|--|

Description

This is the preferred method of subsetting a PharmacoSet. This function allows abstraction of the data to the level of biologically relevant objects: drugs and cells. The function will automatically go through all of the combined data in the PharmacoSet and ensure only the requested drugs and cell lines are found in any of the slots. This allows quickly picking out all the experiments for a drug or cell of interest, as well removes the need to keep track of all the metadata conventions between different datasets.

Usage

```
subsetTo(
  pSet,
  cells = NULL,
  drugs = NULL,
  molecular.data.cells = NULL,
  keep.controls = TRUE,
  ...
)
```

Arguments

| | |
|----------------------|---|
| pSet | A PharmacoSet to be subsetted |
| cells | A list or vector of cell names as used in the dataset to which the object will be subsetted. If left blank, then all cells will be left in the dataset. |
| drugs | A list or vector of drug names as used in the dataset to which the object will be subsetted. If left blank, then all drugs will be left in the dataset. |
| molecular.data.cells | A list or vector of cell names to keep in the molecular data |
| keep.controls | If the dataset has perturbation type experiments, should the controls be kept in the dataset? Defaults to true. |
| ... | Other arguments passed by other function within the package |

Value

A PharmacoSet with only the selected drugs and cells

Examples

```
data(CCLEsmall)
CCLEdrugs <- drugNames(CCLEsmall)
CCLEcells <- cellNames(CCLEsmall)
PSet <- subsetTo(CCLEsmall, drugs = CCLEdrugs[1], cells = CCLEcells[1])
PSet
```

```
summarizeMolecularProfiles
```

Takes molecular data from a PharmacoSet, and summarises them into one entry per drug

Description

Given a PharmacoSet with molecular data, this function will summarize the data into one profile per cell line, using the chosen summary.stat. Note that this does not really make sense with perturbation type data, and will combine experiments and controls when doing the summary if run on a perturbation dataset.

Usage

```
summarizeMolecularProfiles(
  pSet,
  mDataType,
  cell.lines,
  features,
  summary.stat = c("mean", "median", "first", "last", "and", "or"),
  fill.missing = TRUE,
  summarize = TRUE,
  verbose = TRUE,
  binarize.threshold = NA,
  binarize.direction = c("less", "greater")
)
```

Arguments

| | |
|--------------|---|
| pSet | PharmacoSet The PharmacoSet to summarize |
| mDataType | character which one of the molecular data types to use in the analysis, out of all the molecular data types available for the pset for example: rna, rnaseq, snp |
| cell.lines | character The cell lines to be summarized. If any cell.line has no data, missing values will be created |
| features | character A vector of the feature names to include in the summary |
| summary.stat | character which summary method to use if there are repeated cell.lines? Choices are "mean", "median", "first", or "last" In case molecular data type is mutation or fusion "and" and "or" choices are available |
| fill.missing | boolean should the missing cell lines not in the molecular data object be filled in with missing values? |
| summarize | A flag which when set to FALSE (defaults to TRUE) disables summarizing and returns the data unchanged as a ExpressionSet |

verbose boolean should messages be printed
binarize.threshold numeric A value on which the molecular data is binarized. If NA, no binarization is done.
binarize.direction character One of "less" or "greater", the direction of binarization on binarize.threshold, if it is not NA.

Value

matrix An updated PharmacoSet with the molecular data summarized per cell line.

Examples

```

data(GDSCsmall)
GDSCsmall <- summarizeMolecularProfiles(GDSCsmall,
                                       mDataType = "rna", cell.lines=cellNames(GDSCsmall),
                                       summary.stat = 'median', fill.missing = TRUE, verbose=TRUE)
GDSCsmall
  
```

summarizeSensitivityProfiles

Takes the sensitivity data from a PharmacoSet, and summarises them into a drug vs cell line table

Description

This function creates a table with cell lines as rows and drugs as columns, summarising the drug sensitivity data of a PharmacoSet into drug-cell line pairs

Usage

```

summarizeSensitivityProfiles(
  pSet,
  sensitivity.measure = "auc_recomputed",
  cell.lines,
  drugs,
  summary.stat = c("mean", "median", "first", "last", "max", "min"),
  fill.missing = TRUE,
  verbose = TRUE
)
  
```

Arguments

pSet [PharmacoSet] The PharmacoSet from which to extract the data
sensitivity.measure [character] which sensitivity measure to use? Use the `sensitivityMeasures` function to find out what measures are available for each PSet.
cell.lines character The cell lines to be summarized. If any cell lines has no data, it will be filled with missing values

| | |
|--------------|--|
| drugs | character The drugs to be summarized. If any drugs has no data, it will be filled with missing values |
| summary.stat | character which summary method to use if there are repeated cell line-drug experiments? Choices are "mean", "median", "first", or "last" |
| fill.missing | boolean should the missing cell lines not in the molecular data object be filled in with missing values? |
| verbose | Should the function print progress messages? |

Value

matrix A matrix with cell lines going down the rows, drugs across the columns, with the selected sensitivity statistic for each pair.

Examples

```
data(GDSCsmall)
GDSCauc <- summarizeSensitivityProfiles(GDSCsmall, sensitivity.measure='auc_published')
```

| | |
|----------------|---|
| symSetDiffList | <i>Utility to find the symmetric set difference of a list of two or more vectors or lists</i> |
|----------------|---|

Description

The function finds the symmetric set differences between all the arguments, defined as Union(args)-Intersection(args)

Usage

```
symSetDiffList(...)
```

Arguments

... A list of or any number of vector like objects of the same mode, which could also be operated on by the native R set operations

Value

A vector like object of the same mode as the first argument, containing only the symmetric set difference

Examples

```
list1 <- list('a', 'b', 'c')
list2 <- list('a', 'c')
list3 <- list('a', 'c', 'd')
listAll <- symSetDiffList(list1, list2, list3)
listAll
```

 unionList

Utility to find the union between a list of more than two vectors or lists

Description

This function extends the native union function to work on two or more arguments.

Usage

```
unionList(...)
```

Arguments

... A list of or any number of vector like objects of the same mode, which could also be operated on by the native R set operations

Value

A vector like object of the same mode as the first argument, containing all the elements of all arguments passed to the function

Examples

```
list1 <- list('a', 'b')
list2 <- list('a', 'c')
list3 <- list('c', 'd')
listAll <- unionList(list1, list2, list3)
listAll
```

 [,PharmacoSet,ANY,ANY,ANY-method

 ‘[‘

Description

‘[‘

Usage

```
## S4 method for signature 'PharmacoSet,ANY,ANY,ANY'
x[i, j, ..., drop = FALSE]
```

Arguments

| | |
|------|--|
| x | PSet |
| i | Cell lines to keep in PSet |
| j | Drugs to keep in PSet |
| ... | further arguments |
| drop | A boolean flag of whether to drop single dimensions or not |

Value

Returns the subsetted PSet

Index

*Topic **datasets**

- CCLEsmall, [5](#)
- CMAPsmall, [8](#)
- GDSCsmall, [28](#)
- HDAC_genes, [29](#)
- .PharmacoSet (PharmacoSet-class), [38](#)
- [, PharmacoSet, ANY, ANY, ANY-method, [52](#)

- amcc, [3](#)
- availablePSets, [4](#)

- CCLEsmall, [5](#)
- cellInfo, [5](#)
- cellInfo, PharmacoSet-method
(PharmacoSet-class), [38](#)
- cellInfo<-, [6](#)
- cellInfo<-, PharmacoSet, data.frame-method
(PharmacoSet-class), [38](#)
- cellNames, [6](#)
- cellNames, PharmacoSet-method
(PharmacoSet-class), [38](#)
- cellNames<-, [7](#)
- cellNames<-, PharmacoSet, character-method
(PharmacoSet-class), [38](#)
- checkPSetStructure, [7](#)
- CMAPsmall, [8](#)
- computeABC, [8](#)
- computeAmax, [9](#)
- computeAUC, [10](#)
- computeIC50, [11](#)
- computeICn (computeIC50), [11](#)
- computeSlope, [13](#)
- connectivityScore, [14](#)
- cosinePerm, [15](#)

- dateCreated, [16](#)
- dateCreated, PharmacoSet-method
(PharmacoSet-class), [38](#)
- dim, PharmacoSet-method, [16](#)
- downloadPertSig, [17](#)
- downloadPSet, [17](#)
- drugDoseResponseCurve, [18](#)
- drugInfo, [20](#)

- drugInfo, PharmacoSet-method
(PharmacoSet-class), [38](#)
- drugInfo<-, [21](#)
- drugInfo<-, PharmacoSet, data.frame-method
(PharmacoSet-class), [38](#)
- drugNames, [21](#)
- drugNames, PharmacoSet-method
(PharmacoSet-class), [38](#)
- drugNames<-, [22](#)
- drugNames<-, PharmacoSet, character-method
(PharmacoSet-class), [38](#)
- drugPerturbationSig, [22](#)
- drugSensitivitySig, [23](#)

- featureInfo, [25](#)
- featureInfo, PharmacoSet-method
(PharmacoSet-class), [38](#)
- featureInfo<-, [26](#)
- featureInfo<-, PharmacoSet, character, data.frame-method
(PharmacoSet-class), [38](#)
- filterNoisyCurves, [26](#)
- fNames, [27](#)
- fNames, PharmacoSet-method
(PharmacoSet-class), [38](#)

- GDSCsmall, [28](#)
- gwc, [28](#)

- HDAC_genes, [29](#)

- intersectList, [30](#)
- intersectPSet, [30](#)

- logLogisticRegression, [31](#)

- mcc, [33](#)
- mDataNames, [34](#)
- molecularProfiles, [34](#)
- molecularProfiles, PharmacoSet-method
(PharmacoSet-class), [38](#)
- molecularProfiles<-, [35](#)
- molecularProfiles<-, PharmacoSet, character, matrix-method
(PharmacoSet-class), [38](#)

- pertNumber, [35](#)

pertNumber, PharmacoSet-method
(PharmacoSet-class), 38

pertNumber<-, 36

pertNumber<-, PharmacoSet, array-method
(PharmacoSet-class), 38

PharmacoSet, 36

PharmacoSet-class, 38

phenoInfo, 41

phenoInfo, PharmacoSet-method
(PharmacoSet-class), 38

phenoInfo<-, 42

phenoInfo<-, PharmacoSet, character, data.frame-method
(PharmacoSet-class), 38

pSetName, 42

pSetName, PharmacoSet-method
(PharmacoSet-class), 38

sensitivityInfo, 43

sensitivityInfo, PharmacoSet-method
(PharmacoSet-class), 38

sensitivityInfo<-, 43

sensitivityInfo<-, PharmacoSet, data.frame-method
(PharmacoSet-class), 38

sensitivityMeasures, 44

sensitivityMeasures, PharmacoSet-method
(PharmacoSet-class), 38

sensitivityProfiles, 44

sensitivityProfiles, PharmacoSet-method
(PharmacoSet-class), 38

sensitivityProfiles<-, 45

sensitivityProfiles<-, PharmacoSet, data.frame-method
(PharmacoSet-class), 38

sensitivityProfiles<-, PharmacoSet, matrix-method
(PharmacoSet-class), 38

sensNumber, 45

sensNumber, PharmacoSet-method
(PharmacoSet-class), 38

sensNumber<-, 46

sensNumber<-, PharmacoSet, matrix-method
(PharmacoSet-class), 38

show, PharmacoSet-method, 46

show, PharmacoSig-method, 47

showSigAnnot, 47

subsetTo, 48

summarizeMolecularProfiles, 49

summarizeSensitivityProfiles, 50

symSetDiffList, 51

unionList, 52