

Package ‘pcaExplorer’

April 15, 2020

Type Package

Title Interactive Visualization of RNA-seq Data Using a Principal Components Approach

Version 2.12.0

Date 2019-10-14

Description This package provides functionality for interactive visualization of RNA-seq datasets based on Principal Components Analysis. The methods provided allow for quick information extraction and effective data exploration. A Shiny application encapsulates the whole analysis.

License MIT + file LICENSE

LazyData TRUE

Imports DESeq2, SummarizedExperiment, GenomicRanges, IRanges, S4Vectors, genefilter, ggplot2 (>= 2.0.0), d3heatmap, scales, NMF, plyr, topGO, limma, GOstats, GO.db, AnnotationDbi, shiny (>= 0.12.0), shinydashboard, shinyBS, ggrepel, DT, shinyAce, threejs, biomaRt, pheatmap, knitr, rmarkdown, base64enc, tidyr, grDevices, methods

Suggests testthat, BiocStyle, airway, org.Hs.eg.db, htmltools

URL <https://github.com/federicomarini/pcaExplorer>,
<https://federicomarini.github.io/pcaExplorer/>

BugReports <https://github.com/federicomarini/pcaExplorer/issues>

biocViews ImmunoOncology, Visualization, RNASeq, DimensionReduction, PrincipalComponent, QualityControl, GUI, ReportWriting

VignetteBuilder knitr

RoxygenNote 6.1.1

Encoding UTF-8

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/pcaExplorer>

git_branch RELEASE_3_10

git_last_commit 832d95f

git_last_commit_date 2019-10-29

Date/Publication 2020-04-14

Author Federico Marini [aut, cre] (<<https://orcid.org/0000-0003-3252-7758>>)

Maintainer Federico Marini <marinif@uni-mainz.de>

R topics documented:

| | |
|--|-----------|
| correlatePCs | 2 |
| distro_expr | 3 |
| geneprofiler | 3 |
| genespca | 4 |
| get_annotation | 6 |
| get_annotation_orgdb | 7 |
| hi_loadings | 7 |
| limmaquickpca2go | 8 |
| makeExampleDESeqDataSet_multifac | 9 |
| pair_corr | 10 |
| pca2go | 11 |
| pcaExplorer | 12 |
| pcaExplorer-pkg | 13 |
| pcaplot | 14 |
| pcaplot3d | 15 |
| pcasree | 16 |
| plotPCcorrs | 16 |
| topGOTable | 17 |
| Index | 20 |

| | |
|--------------|--|
| correlatePCs | <i>Principal components (cor)relation with experimental covariates</i> |
|--------------|--|

Description

Computes the significance of (cor)relations between PCA scores and the sample experimental covariates, using Kruskal-Wallis test for categorial variables and the `cor.test` based on Spearman's correlation for continuous variables

Usage

```
correlatePCs(pcaobj, coldata, pcs = 1:4)
```

Arguments

| | |
|----------------------|---|
| <code>pcaobj</code> | A <code>prcomp</code> object |
| <code>coldata</code> | A <code>data.frame</code> object containing the experimental covariates |
| <code>pcs</code> | A numeric vector, containing the corresponding PC number |

Value

A `data.frame` object with computed p values for each covariate and for each principal component

Examples

```
library(DESeq2)
dds <- makeExampleDESeqDataSet_multifac(betaSD_condition = 3,betaSD_tissue = 1)
r1t <- DESeq2::rlogTransformation(dds)
pcaobj <- prcomp(t(assay(r1t)))
correlatePCs(pcaobj,colData(dds))
```

distro_expr

Plot distribution of expression values

Description

Plot distribution of expression values

Usage

```
distro_expr(rld, plot_type = "density")
```

Arguments

rld A [DESeqTransform](#) object.

plot_type Character, choose one of boxplot, violin or density. Defaults to density

Value

A plot with the distribution of the expression values

Examples

```
dds <- makeExampleDESeqDataSet_multifac(betaSD_condition = 3,betaSD_tissue = 1)
r1t <- DESeq2::rlogTransformation(dds)
distro_expr(r1t)
```

geneprofiler

Extract and plot the expression profile of genes

Description

Extract and plot the expression profile of genes

Usage

```
geneprofiler(se, genelist = NULL, intgroup = "condition",
             plotZ = FALSE)
```

Arguments

| | |
|----------|--|
| se | A DESeqDataSet object, or a DESeqTransform object. |
| genelist | An array of characters, including the names of the genes of interest of which the profile is to be plotted |
| intgroup | A factor, needs to be in the colnames of colData(se) |
| plotZ | Logical, whether to plot the scaled expression values. Defaults to FALSE |

Value

A plot of the expression profile for the genes

Examples

```
dds <- makeExampleDESeqDataSet_multifac(betaSD_condition = 3, betaSD_tissue = 1)
r1t <- DESeq2::rlogTransformation(dds)
geneprofiler(r1t, paste0("gene", sample(1:1000, 20)))
geneprofiler(r1t, paste0("gene", sample(1:1000, 20)), plotZ=TRUE)
```

genespca

Principal components analysis on the genes

Description

Computes and plots the principal components of the genes, eventually displaying the samples as in a typical biplot visualization.

Usage

```
genespca(x, ntop, choices = c(1, 2), arrowColors = "steelblue",
  groupNames = "group", biplot = TRUE, scale = 1, pc.biplot = TRUE,
  obs.scale = 1 - scale, var.scale = scale, groups = NULL,
  ellipse = FALSE, ellipse.prob = 0.68, labels = NULL,
  labels.size = 3, alpha = 1, var.axes = TRUE, circle = FALSE,
  circle.prob = 0.69, varname.size = 4, varname.adjust = 1.5,
  varname.abbrev = FALSE, returnData = FALSE, coordEqual = FALSE,
  scaleArrow = 1, useRownamesAsLabels = TRUE, point_size = 2,
  annotation = NULL)
```

Arguments

| | |
|-------------|--|
| x | A DESeqTransform object, with data in <code>assay(x)</code> , produced for example by either rlog or varianceStabilizingTransformation |
| ntop | Number of top genes to use for principal components, selected by highest row variance |
| choices | Vector of two numeric values, to select on which principal components to plot |
| arrowColors | Vector of character, either as long as the number of the samples, or one single value |
| groupNames | Factor containing the groupings for the input data. Is efficiently chosen as the (interaction of more) factors in the colData for the object provided |

| | |
|---------------------|--|
| biplot | Logical, whether to additionally draw the samples labels as in a biplot representation |
| scale | Covariance biplot (scale = 1), form biplot (scale = 0). When scale = 1, the inner product between the variables approximates the covariance and the distance between the points approximates the Mahalanobis distance. |
| pc.biplot | Logical, for compatibility with biplot.princomp() |
| obs.scale | Scale factor to apply to observations |
| var.scale | Scale factor to apply to variables |
| groups | Optional factor variable indicating the groups that the observations belong to. If provided the points will be colored according to groups |
| ellipse | Logical, draw a normal data ellipse for each group |
| ellipse.prob | Size of the ellipse in Normal probability |
| labels | optional Vector of labels for the observations |
| labels.size | Size of the text used for the labels |
| alpha | Alpha transparency value for the points (0 = transparent, 1 = opaque) |
| var.axes | Logical, draw arrows for the variables? |
| circle | Logical, draw a correlation circle? (only applies when prcomp was called with scale = TRUE and when var.scale = 1) |
| circle.prob | Size of the correlation circle in Normal probability |
| varname.size | Size of the text for variable names |
| varname.adjust | Adjustment factor the placement of the variable names, >= 1 means farther from the arrow |
| varname.abbrev | Logical, whether or not to abbreviate the variable names |
| returnData | Logical, if TRUE returns a data.frame for further use, containing the selected principal components for custom plotting |
| coordEqual | Logical, default FALSE, for allowing brushing. If TRUE, plot using equal scale cartesian coordinates |
| scaleArrow | Multiplicative factor, usually >=1, only for visualization purposes, to allow for distinguishing where the variables are plotted |
| useRownamesAsLabels | Logical, if TRUE uses the row names as labels for plotting |
| point_size | Size of the points to be plotted for the observations (genes) |
| annotation | A data.frame object, with row.names as gene identifiers (e.g. ENSEMBL ids) and a column, gene_name, containing e.g. HGNC-based gene symbols |

Details

The implementation of this function is based on the beautiful ggbiplot package developed by Vince Vu, available at <https://github.com/vqv/ggbiplot>. The adaptation and additional parameters are tailored to display typical genomics data such as the transformed counts of RNA-seq experiments

Value

An object created by ggplot, which can be assigned and further customized.

Examples

```

library(DESeq2)
dds <- makeExampleDESeqDataSet_multifac(betaSD_condition = 3,betaSD_tissue = 1)
rlt <- rlogTransformation(dds)
groups <- colData(dds)$condition
groups <- factor(groups,levels=unique(groups))
cols <- scales::hue_pal()(2)[groups]
genespca(rlt,ntop=100,arrowColors=cols,groupNames=groups)

groups_multi <- interaction(as.data.frame(colData(rlt)[,c("condition","tissue")]))
groups_multi <- factor(groups_multi,levels=unique(groups_multi))
cols_multi <- scales::hue_pal()(length(levels(groups_multi)))[factor(groups_multi)]
genespca(rlt,ntop=100,arrowColors=cols_multi,groupNames=groups_multi)

```

get_annotation

Get an annotation data frame from biomaRt

Description

Get an annotation data frame from biomaRt

Usage

```
get_annotation(dds, biomaRt_dataset, idtype)
```

Arguments

dds A [DESeqDataSet](#) object

biomaRt_dataset A biomaRt dataset to use. To see the list, type `mart = useMart('ensembl')`, followed by `listDatasets(mart)`.

idtype Character, the ID type of the genes as in the row names of dds, to be used for the call to [getBM](#)

Value

A data frame for ready use in `pcaExplorer`, retrieved from biomaRt.

Examples

```

library(airway)
data(airway)
airway
dds_airway <- DESeq2::DESeqDataSetFromMatrix(assay(airway),
                                             colData = colData(airway),
                                             design=~dex+cell)

## Not run:
get_annotation(dds_airway,"hsapiens_gene_ensembl","ensembl_gene_id")

## End(Not run)

```

get_annotation_orgdb *Get an annotation data frame from org db packages*

Description

Get an annotation data frame from org db packages

Usage

```
get_annotation_orgdb(dds, orgdb_species, idtype)
```

Arguments

| | |
|---------------|---|
| dds | A DESeqDataSet object |
| orgdb_species | Character string, named as the org.XX.eg.db package which should be available in Bioconductor |
| idtype | Character, the ID type of the genes as in the row names of dds, to be used for the call to mapIds |

Value

A data frame for ready use in `pcaExplorer`, retrieved from the org db packages

Examples

```
library(airway)
data(airway)
airway
dds_airway <- DESeq2::DESeqDataSetFromMatrix(assay(airway),
                                             colData = colData(airway),
                                             design=~dex+cell)

## Not run:
get_annotation_orgdb(dds_airway,"org.Hs.eg.db", "ENSEMBL")

## End(Not run)
```

hi_loadings *Extract genes with highest loadings*

Description

Extract genes with highest loadings

Usage

```
hi_loadings(pcaobj, whichpc = 1, topN = 10, exprTable = NULL,
            annotation = NULL, title = "Top/bottom loadings")
```

Arguments

| | |
|------------|---|
| pcaobj | A prcomp object |
| whichpc | An integer number, corresponding to the principal component of interest |
| topN | Integer, number of genes with top and bottom loadings |
| exprTable | A matrix object, e.g. the counts of a DESeqDataSet . If not NULL, returns the counts matrix for the selected genes |
| annotation | A data.frame object, with row.names as gene identifiers (e.g. ENSEMBL ids) and a column, gene_name, containing e.g. HGNC-based gene symbols |
| title | The title of the plot |

Value

A ggplot2 object, or a matrix, if exprTable is not null

Examples

```
dds <- makeExampleDESeqDataSet_multifac(betaSD = 3, betaSD_tissue = 1)
r1t <- DESeq2::rlogTransformation(dds)
pcaobj <- prcomp(t(SummarizedExperiment::assay(r1t)))
hi_loadings(pcaobj, topN = 20)
hi_loadings(pcaobj, topN = 10, exprTable=dds)
hi_loadings(pcaobj, topN = 10, exprTable=counts(dds))
```

| | |
|------------------|---|
| limmaquickpca2go | <i>Functional interpretation of the principal components, based on simple overrepresentation analysis</i> |
|------------------|---|

Description

Extracts the genes with the highest loadings for each principal component, and performs functional enrichment analysis on them using the simple and quick routine provided by the limma package

Usage

```
limmaquickpca2go(se, pca_ngenes = 10000, inputType = "ENSEMBL",
  organism = "Mm", loadings_ngenes = 500, background_genes = NULL,
  scale = FALSE, ...)
```

Arguments

| | |
|------------|---|
| se | A DESeqTransform object, with data in assay(se), produced for example by either rlog or varianceStabilizingTransformation |
| pca_ngenes | Number of genes to use for the PCA |
| inputType | Input format type of the gene identifiers. Defaults to ENSEMBL, that then will be converted to ENTREZ ids. Can assume values such as ENTREZID, GENENAME or SYMBOL, like it is normally used with the select function of AnnotationDbi |
| organism | Character abbreviation for the species, using org.XX.eg.db for annotation |


```

loadings_ngenes      Number of genes to extract the loadings (in each direction)
background_genes     Which genes to consider as background.
scale                Logical, defaults to FALSE, scale values for the PCA
...                 Further parameters to be passed to the topGO routine

```

Value

A nested list object containing for each principal component the terms enriched in each direction. This object is to be thought in combination with the displaying feature of the main [pcaExplorer](#) function

Examples

```

library(airway)
library(DESeq2)
library(limma)
data(airway)
airway
dds_airway <- DESeqDataSet(airway, design= ~ cell + dex)
## Not run:
rld_airway <- rlogTransformation(dds_airway)
goquick_airway <- limmaquickpca2go(rld_airway,
                                   pca_ngenes = 10000,
                                   inputType = "ENSEMBL",
                                   organism = "Hs")

## End(Not run)

```

```
makeExampleDESeqDataSet_multifac
```

Make a simulated DESeqDataSet for two or more experimental factors

Description

Constructs a simulated dataset of Negative Binomial data from different conditions. The fold changes between the conditions can be adjusted with the `betaSD_condition` and the `betaSD_tissue` arguments.

Usage

```

makeExampleDESeqDataSet_multifac(n = 1000, m = 12,
  betaSD_condition = 1, betaSD_tissue = 3, interceptMean = 4,
  interceptSD = 2, dispMeanRel = function(x) 4/x + 0.1,
  sizeFactors = rep(1, m))

```

Arguments

| | |
|------------------|---|
| n | number of rows (genes) |
| m | number of columns (samples) |
| betaSD_condition | the standard deviation for condition betas, i.e. $\beta \sim N(0, \text{betaSD})$ |
| betaSD_tissue | the standard deviation for tissue betas, i.e. $\beta \sim N(0, \text{betaSD})$ |
| interceptMean | the mean of the intercept betas (log2 scale) |
| interceptSD | the standard deviation of the intercept betas (log2 scale) |
| dispMeanRel | a function specifying the relationship of the dispersions on $2^{\text{trueIntercept}}$ |
| sizeFactors | multiplicative factors for each sample |

Details

This function is designed and inspired following the proposal of [makeExampleDESeqDataSet](#) from the DESeq2 package. Credits are given to Mike Love for the nice initial implementation

Value

a [DESeqDataSet](#) with true dispersion, intercept for two factors (condition and tissue) and beta values in the metadata columns. Note that the true betas are provided on the log2 scale.

Examples

```
dds <- makeExampleDESeqDataSet_multifac(betaSD_condition = 3, betaSD_tissue = 1)
dds
dds2 <- makeExampleDESeqDataSet_multifac(betaSD_condition = 1, betaSD_tissue = 4)
dds2
```

pair_corr

Pairwise scatter and correlation plot of counts

Description

Pairwise scatter and correlation plot of counts

Usage

```
pair_corr(df, log = FALSE, method = "pearson", use_subset = TRUE)
```

Arguments

| | |
|------------|--|
| df | A data frame, containing the (raw/normalized/transformed) counts |
| log | Logical, whether to convert the input values to log2 (with addition of a pseudo-count). Defaults to FALSE. |
| method | Character string, one of pearson (default), kendall, or spearman as in cor |
| use_subset | Logical value. If TRUE, only 1000 values per sample will be used to speed up the plotting operations. |

Value

A plot with pairwise scatter plots and correlation coefficients

Examples

```
library(airway)
data(airway)
airway
dds_airway <- DESeq2::DESeqDataSetFromMatrix(assay(airway),
                                             colData = colData(airway),
                                             design=~dex+cell)
pair_corr(counts(dds_airway)[1:100,]) # use just a subset for the example
```

pca2go

*Functional interpretation of the principal components***Description**

Extracts the genes with the highest loadings for each principal component, and performs functional enrichment analysis on them using routines and algorithms from the topGO package

Usage

```
pca2go(se, pca_ngenes = 10000, annotation = NULL,
       inputType = "geneSymbol", organism = "Mm", ensToGeneSymbol = FALSE,
       loadings_ngenes = 500, background_genes = NULL, scale = FALSE,
       return_ranked_gene_loadings = FALSE, annopkg = NULL, ...)
```

Arguments

| | |
|-----------------------------|---|
| se | A DESeqTransform object, with data in <code>assay(se)</code> , produced for example by either rlog or varianceStabilizingTransformation |
| pca_ngenes | Number of genes to use for the PCA |
| annotation | A <code>data.frame</code> object, with <code>row.names</code> as gene identifiers (e.g. ENSEMBL ids) and a column, <code>gene_name</code> , containing e.g. HGNC-based gene symbols |
| inputType | Input format type of the gene identifiers. Will be used by the routines of topGO |
| organism | Character abbreviation for the species, using <code>org.XX.eg.db</code> for annotation |
| ensToGeneSymbol | Logical, whether to expect ENSEMBL gene identifiers, to convert to gene symbols with the annotation provided |
| loadings_ngenes | Number of genes to extract the loadings (in each direction) |
| background_genes | Which genes to consider as background. |
| scale | Logical, defaults to FALSE, scale values for the PCA |
| return_ranked_gene_loadings | Logical, defaults to FALSE. If TRUE, simply returns a list containing the top ranked genes with hi loadings in each PC and in each direction |

annopkg String containing the name of the organism annotation package. Can be used to override the organism parameter, e.g. in case of alternative identifiers used in the annotation package (Arabidopsis with TAIR)

... Further parameters to be passed to the topGO routine

Value

A nested list object containing for each principal component the terms enriched in each direction. This object is to be thought in combination with the displaying feature of the main [pcaExplorer](#) function

Examples

```
library(airway)
library(DESeq2)
data(airway)
airway
dds_airway <- DESeqDataSet(airway, design= ~ cell + dex)
## Not run:
rld_airway <- rlogTransformation(dds_airway)
# constructing the annotation object
anno_df <- data.frame(gene_id = rownames(dds_airway),
                      stringsAsFactors=FALSE)
library("AnnotationDbi")
library("org.Hs.eg.db")
anno_df$gene_name <- mapIds(org.Hs.eg.db,
                           keys=anno_df$gene_id,
                           column="SYMBOL",
                           keytype="ENSEMBL",
                           multiVals="first")
rownames(anno_df) <- anno_df$gene_id
bg_ids <- rownames(dds_airway)[rowSums(counts(dds_airway)) > 0]
library(topGO)
pca2go_airway <- pca2go(rld_airway,
                       annotation = anno_df,
                       organism = "Hs",
                       ensToGeneSymbol = TRUE,
                       background_genes = bg_ids)

## End(Not run)
```

pcaExplorer

Explore a dataset from a PCA perspective

Description

Launch a Shiny App for interactive exploration of a dataset from the perspective of Principal Components Analysis

Usage

```
pcaExplorer(dds = NULL, dst = NULL, countmatrix = NULL,
            coldata = NULL, pca2go = NULL, annotation = NULL,
            runLocal = TRUE)
```

Arguments

| | |
|-------------|---|
| dds | A <code>DESeqDataSet</code> object. If not provided, then a <code>countmatrix</code> and a <code>coldata</code> need to be provided. If none of the above is provided, it is possible to upload the data during the execution of the Shiny App |
| dst | A <code>DESeqTransform</code> object. Can be computed from the <code>dds</code> object if left <code>NULL</code> . If none is provided, then a <code>countmatrix</code> and a <code>coldata</code> need to be provided. If none of the above is provided, it is possible to upload the data during the execution of the Shiny App |
| countmatrix | A count matrix, with genes as rows and samples as columns. If not provided, it is possible to upload the data during the execution of the Shiny App |
| coldata | A <code>data.frame</code> containing the info on the covariates of each sample. If not provided, it is possible to upload the data during the execution of the Shiny App |
| pca2go | An object generated by the <code>pca2go</code> function, which contains the information on enriched functional categories in the genes that show the top or bottom loadings in each principal component of interest. If not provided, it is possible to compute live during the execution of the Shiny App |
| annotation | A <code>data.frame</code> object, with <code>row.names</code> as gene identifiers (e.g. ENSEMBL ids) and a column, <code>gene_name</code> , containing e.g. HGNC-based gene symbols |
| runLocal | A logical indicating whether the app is to be run locally or remotely on a server, which determines how documentation will be accessed. |

Value

A Shiny App is launched for interactive data exploration

Examples

```
library(airway)
data(airway)
airway
dds_airway <- DESeq2::DESeqDataSetFromMatrix(assay(airway),
                                             colData = colData(airway),
                                             design=~dex+cell)

## Not run:
rld_airway <- DESeq2::rlogTransformation(dds_airway)

pcaExplorer(dds_airway,rld_airway)

pcaExplorer(countmatrix = counts(dds_airway), coldata = colData(dds_airway))

pcaExplorer() # and then upload count matrix, covariate matrix (and eventual annotation)

## End(Not run)
```

Description

pcaExplorer provides functionality for interactive visualization of RNA-seq datasets based on Principal Components Analysis. The methods provided allow for quick information extraction and effective data exploration. A Shiny application encapsulates the whole analysis.

Details

pcaExplorer provides functionality for interactive visualization of RNA-seq datasets based on Principal Components Analysis. The methods provided allow for quick information extraction and effective data exploration. A Shiny application encapsulates the whole analysis.

Author(s)

Federico Marini <marinif@uni-mainz.de>, 2016

Maintainer: Federico Marini <marinif@uni-mainz.de>

pcaplot

Sample PCA plot for transformed data

Description

Plots the results of PCA on a 2-dimensional space

Usage

```
pcaplot(x, intgroup = "condition", ntop = 500, returnData = FALSE,
        title = NULL, pcX = 1, pcY = 2, text_labels = TRUE,
        point_size = 3, ellipse = TRUE, ellipse.prob = 0.95)
```

Arguments

| | |
|--------------|--|
| x | A DESeqTransform object, with data in <code>assay(x)</code> , produced for example by either rlog or varianceStabilizingTransformation |
| intgroup | Interesting groups: a character vector of names in <code>colData(x)</code> to use for grouping |
| ntop | Number of top genes to use for principal components, selected by highest row variance |
| returnData | logical, if TRUE returns a data.frame for further use, containing the selected principal components and intgroup covariates for custom plotting |
| title | The plot title |
| pcX | The principal component to display on the x axis |
| pcY | The principal component to display on the y axis |
| text_labels | Logical, whether to display the labels with the sample identifiers |
| point_size | Integer, the size of the points for the samples |
| ellipse | Logical, whether to display the confidence ellipse for the selected groups |
| ellipse.prob | Numeric, a value in the interval [0;1) |

Value

An object created by ggplot, which can be assigned and further customized.

Examples

```
dds <- makeExampleDESeqDataSet_multifac(betaSD_condition = 3,betaSD_tissue = 1)
rlt <- DESeq2::rlogTransformation(dds)
pcaplot(rlt, ntop=200)
```

pcaplot3d

Sample PCA plot for transformed data

Description

Plots the results of PCA on a 3-dimensional space, interactively

Usage

```
pcaplot3d(x, intgroup = "condition", ntop = 500, returnData = FALSE,
  title = NULL, pcX = 1, pcY = 2, pcZ = 3, text_labels = TRUE,
  point_size = 3)
```

Arguments

| | |
|-------------|--|
| x | A DESeqTransform object, with data in assay(x), produced for example by either rlog or varianceStabilizingTransformation |
| intgroup | Interesting groups: a character vector of names in colData(x) to use for grouping |
| ntop | Number of top genes to use for principal components, selected by highest row variance |
| returnData | logical, if TRUE returns a data.frame for further use, containing the selected principal components and intgroup covariates for custom plotting |
| title | The plot title |
| pcX | The principal component to display on the x axis |
| pcY | The principal component to display on the y axis |
| pcZ | The principal component to display on the z axis |
| text_labels | Logical, whether to display the labels with the sample identifiers |
| point_size | Integer, the size of the points for the samples |

Value

A html-based visualization of the 3d PCA plot

Examples

```
dds <- makeExampleDESeqDataSet_multifac(betaSD_condition = 3,betaSD_tissue = 1)
rlt <- DESeq2::rlogTransformation(dds)
pcaplot3d(rlt, ntop=200)
```

pcascree *Scree plot of the PCA on the samples*

Description

Produces a scree plot for investigating the proportion of explained variance, or alternatively the cumulative value

Usage

```
pcascree(obj, type = c("pev", "cev"), pc_nr = NULL, title = NULL)
```

Arguments

| | |
|-------|--|
| obj | A prcomp object |
| type | Display absolute proportions or cumulative proportion. Possible values: "pev" or "cev" |
| pc_nr | How many principal components to display max |
| title | Title of the plot |

Value

An object created by ggplot, which can be assigned and further customized.

Examples

```
dds <- makeExampleDESeqDataSet_multifac(betaSD_condition = 3, betaSD_tissue = 1)
rlt <- DESeq2::rlogTransformation(dds)
pcaobj <- prcomp(t(SummarizedExperiment::assay(rlt)))
pcascree(pcaobj, type="pev")
pcascree(pcaobj, type="cev", title="Cumulative explained proportion of variance - Test dataset")
```

plotPCcorr *Plot significance of (cor)relations of covariates VS principal components*

Description

Plots the significance of the (cor)relation of each covariate vs a principal component

Usage

```
plotPCcorr(pccorr, pc = 1, logp = TRUE)
```

Arguments

| | |
|--------|--|
| pccorr | A data.frame object generated by correlatePCs |
| pc | An integer number, corresponding to the principal component of interest |
| logp | Logical, defaults to TRUE, displays the $-\log_{10}$ of the pvalue instead of the p value itself |

Value

A base plot object

Examples

```
library(DESeq2)
dds <- makeExampleDESeqDataSet_multifac(betaSD_condition = 3, betaSD_tissue = 1)
r1t <- rlogTransformation(dds)
pcaobj <- prcomp(t(assay(r1t)))
res <- correlatePCs(pcaobj, colData(dds))
plotPCcorrs(res)
```

topGOTable

Extract functional terms enriched in the DE genes, based on topGO

Description

A wrapper for extracting functional GO terms enriched in the DE genes, based on the algorithm and the implementation in the topGO package

Usage

```
topGOTable(DEgenes, BGgenes, ontology = "BP", annot = annFUN.org,
  mapping = "org.Mm.eg.db", geneID = "symbol", topTablerows = 200,
  fullNamesInRows = TRUE, addGeneToTerms = TRUE, plotGraph = FALSE,
  plotNodes = 10, writeOutput = FALSE, outputFile = "",
  topGO_method2 = "elim", do_padj = FALSE)
```

Arguments

| | |
|-----------------|---|
| DEgenes | A vector of (differentially expressed) genes |
| BGgenes | A vector of background genes, e.g. all (expressed) genes in the assays |
| ontology | Which Gene Ontology domain to analyze: BP (Biological Process), MF (Molecular Function), or CC (Cellular Component) |
| annot | Which function to use for annotating genes to GO terms. Defaults to annFUN.org |
| mapping | Which org.XX.eg.db to use for annotation - select according to the species |
| geneID | Which format the genes are provided. Defaults to symbol, could also be entrez or ENSEMBL |
| topTablerows | How many rows to report before any filtering |
| fullNamesInRows | Logical, whether to display or not the full names for the GO terms |
| addGeneToTerms | Logical, whether to add a column with all genes annotated to each GO term |
| plotGraph | Logical, if TRUE additionally plots a graph on the identified GO terms |
| plotNodes | Number of nodes to plot |
| writeOutput | Logical, if TRUE additionally writes out the result to a file |
| outputFile | Name of the file the result should be written into |

| | |
|---------------|--|
| topGO_method2 | Character, specifying which of the methods implemented by topGO should be used, in addition to the classic algorithm. Defaults to elim |
| do_padj | Logical, whether to perform the adjustment on the p-values from the specific topGO method, based on the FDR correction. Defaults to FALSE, since the assumption of independent hypotheses is somewhat violated by the intrinsic DAG-structure of the Gene Ontology Terms |

Details

Allowed values assumed by the topGO_method2 parameter are one of the following: elim, weight, weight01, lea, parentchild. For more details on this, please refer to the original documentation of the topGO package itself

Value

A table containing the computed GO Terms and related enrichment scores

Examples

```
library(airway)
library(DESeq2)
data(airway)
airway
dds_airway <- DESeqDataSet(airway, design= ~ cell + dex)
# Example, performing extraction of enriched functional categories in
# detected significantly expressed genes
## Not run:
dds_airway <- DESeq(dds_airway)
res_airway <- results(dds_airway)
library("AnnotationDbi")
library("org.Hs.eg.db")
res_airway$symbol <- mapIds(org.Hs.eg.db,
                           keys=row.names(res_airway),
                           column="SYMBOL",
                           keytype="ENSEMBL",
                           multiVals="first")
res_airway$entrez <- mapIds(org.Hs.eg.db,
                           keys=row.names(res_airway),
                           column="ENTREZID",
                           keytype="ENSEMBL",
                           multiVals="first")
resOrdered <- as.data.frame(res_airway[order(res_airway$padj),])
de_df <- resOrdered[resOrdered$padj < .05 & !is.na(resOrdered$padj),]
de_symbols <- de_df$symbol
bg_ids <- rownames(dds_airway)[rowSums(counts(dds_airway)) > 0]
bg_symbols <- mapIds(org.Hs.eg.db,
                    keys=bg_ids,
                    column="SYMBOL",
                    keytype="ENSEMBL",
                    multiVals="first")

library(topGO)
topgoDE_airway <- topGOtable(de_symbols, bg_symbols,
                            ontology = "BP",
                            mapping = "org.Hs.eg.db",
                            geneID = "symbol")
```

topGOTable

19

End(Not run)

Index

correlatePCs, [2](#), [16](#)

DESeqDataSet, [4](#), [6–8](#), [10](#), [13](#)
DESeqTransform, [3](#), [4](#), [8](#), [11](#), [13–15](#)
distro_expr, [3](#)

geneprofiler, [3](#)
genespca, [4](#)
get_annotation, [6](#)
get_annotation_orgdb, [7](#)
getBM, [6](#)

hi_loadings, [7](#)

limmaquickpca2go, [8](#)

makeExampleDESeqDataSet, [10](#)
makeExampleDESeqDataSet_multifac, [9](#)
mapIds, [7](#)

pair_corr, [10](#)
pca2go, [11](#), [13](#)
pcaExplorer, [9](#), [12](#), [12](#)
pcaExplorer-pkg, [13](#)
pcaExplorer-pkg-package
 (pcaExplorer-pkg), [13](#)
pcaplot, [14](#)
pcaplot3d, [15](#)
pcasree, [16](#)
plotPCcorrs, [16](#)

rlog, [4](#), [8](#), [11](#), [14](#), [15](#)

topG0table, [17](#)

varianceStabilizingTransformation, [4](#), [8](#),
 [11](#), [14](#), [15](#)