

Package ‘phantasus’

April 15, 2020

Title Visual and interactive gene expression analysis

Version 1.6.0

Description Phantasus is a web-application for visual and interactive gene expression analysis. Phantasus is based on Morpheus – a web-based software for heatmap visualisation and analysis, which was integrated with an R environment via OpenCPU API. Aside from basic visualization and filtering methods, R-based methods such as k-means clustering, principal component analysis or differential expression analysis with limma package are supported.

URL <https://genome.ifmo.ru/phantasus>,
<https://artyomovlab.wustl.edu/phantasus>

BugReports <https://github.com/ctlab/phantasus/issues>

Depends R (>= 3.5)

biocViews GeneExpression, GUI, Visualization, DataRepresentation, Transcriptomics, RNASeq, Microarray, Normalization, Clustering, DifferentialExpression, PrincipalComponent, ImmunoOncology

Imports ggplot2, protolite, Biobase, GEOquery, Rook, htmltools, httpuv, jsonlite, limma, opencpu, assertthat, methods, httr, rhdf5, utils, parallel, stringr, fgsea (>= 1.9.4), svglite, gtable, stats, Matrix, Matrix.utils, pheatmap, scales, ccaPP, grid, grDevices, AnnotationDbi

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Suggests testthat, BiocStyle, knitr, rmarkdown, data.table

VignetteBuilder knitr

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/phantasus>

git_branch RELEASE_3_10

git_last_commit 80c7b42

git_last_commit_date 2019-10-29

Date/Publication 2020-04-14

Author Daria Zenkova [aut],
 Vladislav Kamenev [aut],
 Rita Sablina [ctb],
 Maxim Artyomov [aut],
 Alexey Sergushichev [aut, cre]

Maintainer Alexey Sergushichev <alsergbox@gmail.com>

R topics documented:

adjustDataset	2
annotationDBMeta	3
calcPCA	4
calculatedAnnotation	4
checkGPLs	5
collapseDataset	6
convertByAnnotationDB	6
createES	7
es	8
getArchs4Files	8
getES	9
getGDS	9
getGSE	10
gseaPlot	11
limmaAnalysis	11
loadFromARCHS4	12
loadGEO	12
loadPreloaded	13
performKmeans	14
queryAnnotationDBMeta	14
read.gct	15
reparseCachedESs	15
servePhantasia	16
shinyGAMAnalysis	16
subsetES	17
write.gct	17
Index	19

adjustDataset	<i>Adjust dataset</i>
---------------	-----------------------

Description

Adjust dataset

Usage

```
adjustDataset(es, scaleColumnSum = NULL, log2 = FALSE,
  onePlusLog2 = FALSE, inverseLog2 = FALSE,
  quantileNormalize = FALSE, zScore = FALSE, robustZScore = FALSE,
  sweep = NULL)
```

Arguments

es	Expression set to perform adjustment on
scaleColumnSum	perform sum scaling of columns (default FALSE)
log2	perform logarithm2 adjustment (default FALSE)
onePlusLog2	perform $\log_2(1+x)$ adjustment (default FALSE)
inverseLog2	perform 2^x adjustment (default FALSE)
quantileNormalize	perform quantile normalization (default FALSE)
zScore	perform zScore adjustment: subtract mean, divide by std (default FALSE)
robustZScore	perform robustZScore adjustment: subtract median, divide by MAD (default FALSE)
sweep	perform sweep adjustment on rows/columns (default FALSE)

Value

Nothing. Adjusted dataset will be assigned as ES in global environment

Examples

```
## Not run:
es <- gseGSE('GSE53986')[[1]]
adjustDataset(es, log2 = T, quantileNormalize = T)

## End(Not run)
```

annotationDBMeta	<i>Create meta file for AnnotationDB</i>
------------------	--

Description

createES function creates an rds file containing meta information of provided sqlite files for AnnotationDB

Usage

```
annotationDBMeta(cacheDir)
```

Arguments

cacheDir	cacheDir for phantastus
----------	-------------------------

Value

nothing

Examples

```
## Not run:
annotationDBMeta('/var/phantasus/cache')

## End(Not run)
```

calcPCA	<i>Principal Component Analysis.</i>
---------	--------------------------------------

Description

calcPCA calculates PCA-matrix for the given ExpressionSet and returns this matrix encoded to JSON.

Usage

```
calcPCA(es, replacena = "mean")
```

Arguments

es	an ExpressionSet object, should be normalized
replacena	method for replacing NA values (mean by default)

Value

json with full description of the plot for plotly.js

Examples

```
## Not run:
data(es)
calcPCA(es)

## End(Not run)
```

calculatedAnnotation	<i>Create calculated annotation</i>
----------------------	-------------------------------------

Description

calculatedAnnotation adds a column calculated by operation

Usage

```
calculatedAnnotation(es, operation, rows = c(), columns = c(),
  isColumns = FALSE, name = NULL)
```

Arguments

es	ExpressionSet object.
operation	Name of the operation to perform calculation
rows	List of specified rows' indices (optional), indices start from 0
columns	List of specified columns' indices (optional), indices start from 0#'
isColumns	Apply fn to columns
name	Name of the new annotation

Value

Nothing. Annotated dataset will be assigned to es in environment

checkGPLs	<i>Check possible annotations for GEO Dataset.</i>
-----------	--

Description

checkGPLs returns GPL-names for the specified GEO identifier.

Usage

```
checkGPLs(name)
```

Arguments

name	String, containing GEO identifier of the dataset.
------	---

Value

Vector of filenames serialized in JSON format. If there is only one GPL for that dataset, the function will return name.

Examples

```
## Not run:  
checkGPLs('GSE27112')  
checkGPLs('GSE14308')  
  
## End(Not run)
```

collapseDataset	<i>Collapse dataset</i>
-----------------	-------------------------

Description

collapseDataset performs a collapse action on expression set

Usage

```
collapseDataset(es, isRows = TRUE, selectOne = FALSE, fn, fields,
  removeEmpty = TRUE)
```

Arguments

es	Expression set
isRows	Work with rows. False if columns (default True - row mode)
selectOne	select best match or merge duplicates
fn	select/merge function
fields	fields to unique on
removeEmpty	remove unannotated genes

Value

Nothing. Collapsed dataset will be assigned to es in environment

Examples

```
## Not run:
es <- getGSE('GSE53986')[[1]]
collapseDataset(es, isRows = TRUE, selectOne = TRUE,
  fn = mean, fields = c('Gene ID', 'Gene symbol'))

## End(Not run)
```

convertByAnnotationDB	<i>Map indexes using Annotation DB</i>
-----------------------	--

Description

createES function creates an rds file containing meta information of provided sqlite files for AnnotationDB

Usage

```
convertByAnnotationDB(es, dbName, columnName, columnType, keyType)
```

Arguments

es	source ExpressionSet
dbName	name of AnnotationDB file
columnName	name of column in featureData of source ExpressionSet
columnType	Type of indexes in columnName
keyType	Type of mapped indexes

Value

JSON object with a vector of converted IDs

createES	<i>Create ExpressionSet.</i>
----------	------------------------------

Description

createES function produces an ExpressionSet object from given data, and exports it to global scope.

Usage

```
createES(data, pData, varLabels, fData, fvarLabels, eData)
```

Arguments

data	Gene expression matrix.
pData	Matrix with phenotypical data.
varLabels	Names of phenoData columns.
fData	Matrix with feature data.
fvarLabels	Names of featureData columns.
eData	List with experimentData

Value

produced ExpressionSet object

Examples

```
## Not run:
data <- matrix(1:15, 5, 3)
pData <- c("A", "B", "C")
varLabels <- "cat"
fData <- c("p", "r", "s", "t", "u")
fvarLabels <- "id"
eData <- list(name="", lab="", contact="", title="", url="", other=list(), pubMedIds="")
createES(data, pData, varLabels, fData, fvarLabels, eData)

## End(Not run)
```

es	<i>Example dataset</i>
----	------------------------

Description

Small slice from GSE27112-GPL6103 for runnable examples.

Usage

```
data(es)
```

Format

An object of class ExpressionSet with 20 rows and 5 columns.

Examples

```
## Not run:  
data(es)  
performKmeans(es, k = 2)  
  
## End(Not run)
```

getArchs4Files	<i>Returns list of ARCHS4 hdf5 files with expression data</i>
----------------	---

Description

Returns list of ARCHS4 hdf5 files with expression data

Usage

```
getArchs4Files(cacheDir)
```

Arguments

cacheDir base directory for cache

Value

list of .h5 files

getES *Load ExpressionSet by GEO identifier*

Description

getES return the ExpressionSet object(s) corresponding to GEO identifier.

Usage

```
getES(name, type = NA, destdir = tempdir(),  
      mirrorPath = "https://ftp.ncbi.nlm.nih.gov")
```

Arguments

name	String, containing GEO identifier of the dataset. It should start with 'GSE' or 'GDS' and can include exact GPL to annotate dataset, separated with dash ('-') from the identifier.
type	Type of the dataset: 'GSE' or 'GDS'. If not specified, the function will take first three letters of name variable as type.
destdir	Directory for caching loaded Series and GPL files from GEO database.
mirrorPath	URL string which specifies the source of matrices.

Value

List of ExpressionSet objects, that were available by given in name variable GEO identifier.

Examples

```
## Not run:  
  getES('GSE14308', type = 'GSE', destdir = 'cache')  
  getES('GSE27112')  
  
## End(Not run)  
  getES('GDS4922')
```

getGDS *Load ExpressionSet from GEO Datasets*

Description

getGDS return the ExpressionSet object corresponding to GEO Dataset identifier.

Usage

```
getGDS(name, destdir = tempdir(),  
      mirrorPath = "https://ftp.ncbi.nlm.nih.gov")
```

Arguments

name	String, containing GEO identifier of the dataset. It should start with 'GSE' or 'GDS' and can include exact GPL to annotate dataset, separated with dash ('-') from the identifier.
destdir	Directory for caching loaded Series and GPL files from GEO database.
mirrorPath	URL string which specifies the source of matrices.

Value

ExpressionSet object wrapped in list, that was available by given in name variable GEO identifier.

Examples

```
getGDS('GDS4922')
```

getGSE	<i>Load ExpressionSet from GEO Series</i>
--------	---

Description

getGSE return the ExpressionSet object(s) corresponding to GEO Series Identifier.

Usage

```
getGSE(name, destdir = tempdir(),
        mirrorPath = "https://ftp.ncbi.nlm.nih.gov")
```

Arguments

name	String, containing GEO identifier of the dataset. It should start with 'GSE' or 'GDS' and can include exact GPL to annotate dataset, separated with dash ('-') from the identifier.
destdir	Directory for caching loaded Series and GPL files from GEO database.
mirrorPath	URL string which specifies the source of matrices.

Value

List of ExpressionSet objects, that were available by given in name variable GEO identifier.

Examples

```
## Not run:
  getGSE('GSE14308', destdir = 'cache')
  getGSE('GSE27112')

## End(Not run)
getGSE('GSE53986')
```

gseaPlot	<i>Returns path to an svg file with enrichment plot</i>
----------	---

Description

Returns path to an svg file with enrichment plot

Usage

```
gseaPlot(es, rankBy, selectedGenes, width, height, vertical = FALSE,
         addHeatmap = FALSE, showAnnotation = NULL, annotationColors = NULL,
         pallete = c("blue", "white", "red"))
```

Arguments

es	ExpressionSet object.
rankBy	name of the numeric column used for gene ranking
selectedGenes	indexes of selected genes (starting from one, in the order of fData)
width	width of the image (in inches)
height	height of the image (in inches)
vertical	whether to use vertical orientation (default: FALSE)
addHeatmap	whether to add an expression heatmap, sorted by rankBy (default: FALSE)
showAnnotation	a name of column annotation to add to the heatmap, default: NULL (no annotation)
annotationColors	a list of colors to use in annotation
pallete	a vector of colors to draw heatmap

Value

path to an svg file

limmaAnalysis	<i>Differential Expression analysis.</i>
---------------	--

Description

limmaAnalysis performs differential expression analysis from limma package and returns a ProtoBuf-serialized resulting de-matrix.

Usage

```
limmaAnalysis(es, fieldValues)
```

Arguments

es	ExpressionSet object. It should be normalized for more accurate analysis.
fieldValues	Vector of comparison values, mapping categories' names to columns/samples

Value

Name of the file containing serialized de-matrix.

Examples

```
## Not run:
data(es)
limmaAnalysis(es, fieldValues = c("A", "A", "A", "B", "B"))

## End(Not run)
```

loadFromARCHS4	<i>Loads expression data from ARCHS4 count files. Only samples with counted expression are kept. If es already contains expression data it is returned as is.</i>
----------------	---

Description

Loads expression data from ARCHS4 count files. Only samples with counted expression are kept. If es already contains expression data it is returned as is.

Usage

```
loadFromARCHS4(es, archs4_files)
```

Arguments

es	ExpressionSet from GEO to check for expression in ARCHS4
archs4_files	list of available .h5 files from ARCHS4 project

Value

either original es or an ExpressionSet with loaded count data from ARCHS4

loadGEO	<i>Load GEO Dataset.</i>
---------	--------------------------

Description

loadGEO returns the file with serialized ExpressionSet using ProtoBuf, parsed from data downloaded from GEO by identifier.

Usage

```
loadGEO(name, type = NA)
```

Arguments

name	String, containing GEO identifier of the dataset. It should start with 'GSE' or 'GDS' and can include exact GPL to annotate dataset, separated with dash ('-') from the identifier.
type	Type of the dataset: 'GSE' or 'GDS'. If not specified, the function will take first three letters of name variable as type.

Value

File with ProtoBuf-serialized ExpressionSet-s that were downloaded by this identifier. For GSE-datasets there can be multiple annotations, so in file will be a list mapping name with GPL to ExpressionSet.

Examples

```
## Not run:
  loadGEO("GSE27112")
  loadGEO("GDS4922")

## End(Not run)
```

loadPreloaded	<i>Load GEO Dataset.</i>
---------------	--------------------------

Description

loadPreloaded returns the file with serialized ExpressionSets using ProtoBuf, that were preloaded on server.

Usage

```
loadPreloaded(name)
```

Arguments

name	String, containing filename. Assuming that in the directory with preloaded files preloadedDir exists file filename.rda with list of ExpressionSets ess.
------	---

Value

File with ProtoBuf-serialized ExpressionSet-s that were loaded from specified file.

performKmeans *K-means clusterisation.*

Description

performKmeans returns a vector of corresponding clusters for each gene from a given Expression-Set.

Usage

```
performKmeans(es, k, replacena = "mean")
```

Arguments

es	ExpressionSet object.
k	Expected number of clusters.
replacena	Method for replacing NA values in series matrix (mean by default)

Value

Vector of corresponding clusters, serialized to JSON.

Examples

```
## Not run:
data(es)
performKmeans(es, k = 2)

## End(Not run)
```

queryAnnotationDBMeta *Get meta list for annotationDB files*

Description

createES Function reads an rds file containing meta information of provided sqlite files for AnnotationDB

Usage

```
queryAnnotationDBMeta()
```

Value

meta info in JSON

Examples

```
## Not run:
queryAnnotationDBMeta()

## End(Not run)
```

read.gct	<i>Reads ExpressionSet from a GCT file.</i>
----------	---

Description

Only versions 1.2 and 1.3 are supported.

Usage

```
read.gct(gct, ...)
```

Arguments

gct	Path to gct file
...	additional options for read.csv

Value

ExpressionSet object

Examples

```
read.gct(system.file("extdata", "centers.gct", package = "phantasus"))
```

reparseCachedESs	<i>Reparse cached expression sets from GEO.</i>
------------------	---

Description

The function should be used on phantasus version updates that change behavior of loading datasets from GEO. It finds all the datasets that were cached and runs 'getES' for them again. The function uses cached Series and other files from GEO.

Usage

```
reparseCachedESs(destdir, mirrorPath = "https://ftp.ncbi.nlm.nih.gov")
```

Arguments

destdir	Directory used for caching loaded Series files from GEO database.
mirrorPath	URL string which specifies the source of matrices.

Value

vector of previously cached GSE IDs

Examples

```
reparseCachedESs(destdir=tempdir())
```

servePhantasus	<i>Serve phantasus.</i>
----------------	-------------------------

Description

servePhantasus starts http server handling phantasus static files and opencpu server.

Usage

```
servePhantasus(host = "0.0.0.0", port = 8000,
  staticRoot = system.file("www/phantasus.js", package = "phantasus"),
  cacheDir = tempdir(), preloadedDir = NULL, openInBrowser = TRUE,
  quiet = TRUE)
```

Arguments

host	Host to listen.
port	Port to listen.
staticRoot	Path to static files with phantasus.js (on local file system).
cacheDir	Full path to cache directory.
preloadedDir	Full path to directory with preloaded files.
openInBrowser	Boolean value which states if application will be automatically loaded in default browser.
quiet	Boolean value which states whether the connection log should be hidden (default: TRUE)

Value

Running instance of phantasus application.

Examples

```
## Not run:
servePhantasus()

## End(Not run)
```

shinyGAMAnalysis	<i>Constructs data frame with gene annotations and submits it into Shiny GAM web-server</i>
------------------	---

Description

Constructs data frame with gene annotations and submits it into Shiny GAM web-server

Usage

```
shinyGAMAnalysis(es)
```


Arguments

es Expression set object

Value

URL for Shiny GAM

subsetES	<i>Subsets es, if rows or columns are not specified, all are retained</i>
----------	---

Description

Subsets es, if rows or columns are not specified, all are retained

Usage

```
subsetES(es, columns = c(), rows = c())
```

Arguments

es ExpressionSet object.#'
columns List of specified columns' indices (optional), indices start from 0#'
rows List of specified rows' indices (optional), indices start from 0

Value

new expression set 'es'

write.gct	<i>Saves ExpressionSet to a GCT file (version 1.3).</i>
-----------	---

Description

Saves ExpressionSet to a GCT file (version 1.3).

Usage

```
write.gct(es, file, gzip = FALSE)
```

Arguments

es ExpressionSet object to save
file Path to output gct file
gzip Whether to gzip apply gzip-compression for the output file#'
... additional options for read.csv

Value

Result of the closing file (as in 'close()' function')

Examples

```
es <- read.gct(system.file("extdata", "centers.gct", package = "phantasus"))
out <- tempfile(fileext = ".gct.gz")
write.gct(es, out, gzip=TRUE)
```

Index

*Topic **datasets**

es, [8](#)

[adjustDataset](#), [2](#)

[annotationDBMeta](#), [3](#)

[calcPCA](#), [4](#)

[calculatedAnnotation](#), [4](#)

[checkGPLs](#), [5](#)

[collapseDataset](#), [6](#)

[convertByAnnotationDB](#), [6](#)

[createES](#), [7](#)

es, [8](#)

[getArchs4Files](#), [8](#)

[getES](#), [9](#)

[getGDS](#), [9](#)

[getGSE](#), [10](#)

[gseaPlot](#), [11](#)

[limmaAnalysis](#), [11](#)

[loadFromARCHS4](#), [12](#)

[loadGEO](#), [12](#)

[loadPreloaded](#), [13](#)

[performKmeans](#), [14](#)

[queryAnnotationDBMeta](#), [14](#)

[read.gct](#), [15](#)

[reparseCachedESs](#), [15](#)

[servePhantastus](#), [16](#)

[shinyGAMAnalysis](#), [16](#)

[subsetES](#), [17](#)

[write.gct](#), [17](#)