

Package ‘psychomics’

April 15, 2020

Title Graphical Interface for Alternative Splicing Quantification,
Analysis and Visualisation

Version 1.12.1

Encoding UTF-8

Description Interactive R package with an intuitive Shiny-based graphical interface for alternative splicing quantification and integrative analyses of alternative splicing and gene expression based on The Cancer Genome Atlas (TCGA), the Genotype-Tissue Expression project (GTEx), Sequence Read Archive (SRA) and user-provided data. The tool interactively performs survival, dimensionality reduction and median- and variance-based differential splicing and gene expression analyses that benefit from the incorporation of clinical and molecular sample-associated features (such as tumour stage or survival). Interactive visual access to genomic mapping and functional annotation of selected alternative splicing events is also included.

Depends R (>= 3.6), shiny (>= 1.0.3), shinyBS

License MIT + file LICENSE

LazyData true

RoxygenNote 7.0.2

Imports AnnotationDbi, AnnotationHub, BiocFileCache, cluster, colourpicker, data.table, digest, dplyr, DT (>= 0.2), edgeR, fastICA, fastmatch, ggplot2, ggrepel, graphics, grDevices, highcharter (>= 0.5.0), htmltools, httr, jsonlite, limma, miscTools, pairsD3, plyr, Rcpp (>= 0.12.14), recount, R.utils, reshape2, shinyjs, stringr, stats, SummarizedExperiment, survival, tools, utils, XML, xtable, methods, org.Hs.eg.db

Suggests testthat, knitr, parallel, devtools, rmarkdown, gplots, covr, car, rstudioapi, spelling

LinkingTo Rcpp

VignetteBuilder knitr

Collate 'RcppExports.R' 'utils.R' 'globalAccess.R' 'app.R'
'analysis.R' 'analysis_correlation.R'
'analysis_diffExpression.R' 'analysis_diffExpression_event.R'
'analysis_diffExpression_table.R' 'analysis_diffSplicing.R'
'analysis_diffSplicing_event.R' 'analysis_diffSplicing_table.R'
'analysis_dimReduction.R' 'analysis_dimReduction_ica.R'
'analysis_dimReduction_pca.R' 'analysis_information.R'

'analysis_survival.R' 'analysis_template.R' 'data.R'
 'formats.R' 'data_firebrowse.R'
 'data_geNormalisationFiltering.R' 'data_gtex.R'
 'data_inclusionLevels.R' 'data_local.R' 'data_recount.R'
 'events_suppa.R' 'events_vastTools.R' 'events_miso.R'
 'events_mats.R' 'events.R' 'formats_firebrowseGeneExpression.R'
 'formats_firebrowseJunctionReads.R'
 'formats_firebrowseMergeClinical.R'
 'formats_firebrowseNormalizedGeneExpression.R'
 'formats_genericClinical.R' 'formats_genericGeneExpression.R'
 'formats_genericInclusionLevels.R'
 'formats_genericJunctionReads.R' 'formats_genericSampleInfo.R'
 'formats_gtexClinical.R' 'formats_gtexGeneReadsFormat.R'
 'formats_gtexJunctionReads.R' 'formats_gtexSampleInfo.R'
 'formats_gtexV7Clinical.R' 'formats_gtexV7JunctionReads.R'
 'formats_psichomicsGeneExpression.R'
 'formats_psichomicsInclusionLevels.R'
 'formats_recountSampleInfo.R' 'groups.R' 'help.R'
 'utils_drawSplicingEvent.R' 'utils_fileBrowserDialog.R'
 'utils_interactiveGgplot.R' 'utils_interface.R'

biocViews Sequencing, RNASeq, AlternativeSplicing,
 DifferentialSplicing, Transcription, GUI, PrincipalComponent,
 Survival, BiomedicalInformatics, Transcriptomics,
 ImmunoOncology, Visualization, MultipleComparison,
 GeneExpression, DifferentialExpression

URL <https://nuno-agostinho.github.io/psichomics/>

BugReports <https://github.com/nuno-agostinho/psichomics/issues>

Language en-GB

git_url <https://git.bioconductor.org/packages/psichomics>

git_branch RELEASE_3_10

git_last_commit fac011f

git_last_commit_date 2020-01-29

Date/Publication 2020-04-14

Author Nuno Saraiva-Agostinho [aut, cre]
 (<<https://orcid.org/0000-0002-5549-105X>>),
 Nuno Luís Barbosa-Morais [aut, led, ths]
 (<<https://orcid.org/0000-0002-1215-0538>>),
 André Falcão [ths],
 Lina Gallego Paez [ctb],
 Marie Bordone [ctb],
 Teresa Maia [ctb],
 Mariana Ferreira [ctb],
 Ana Carolina Leote [ctb],
 Bernardo de Almeida [ctb]

Maintainer Nuno Saraiva-Agostinho <nunodanielagostinho@gmail.com>

R topics documented:

assignValuePerSubject	4
calculateLoadingsContribution	5
colSums,EList-method	6
convertGeneIdentifiers	6
correlateGEandAS	7
createGroupByAttribute	8
diffAnalyses	9
ensemblToUniprot	10
filterGeneExpr	11
filterGroups	12
filterPSI	13
getAttributesTime	14
getDownloadsFolder	15
getGeneList	15
getGtexDataTypes	16
getGtexTissues	16
getMatchingSamples	17
getSplicingEventFromGenes	18
getSplicingEventTypes	19
getSubjectFromSample	19
getTCGAdataTypes	20
groupPerElem	21
isFirebrowseUp	21
labelBasedOnCutoff	22
listSplicingAnnotations	23
loadAnnotation	23
loadGtexData	24
loadLocalFiles	25
loadSRAProject	26
loadTCGAdata	26
normaliseGeneExpression	28
optimalSurvivalCutoff	29
parseCategoricalGroups	30
parseSplicingEvent	31
parseSuppaAnnotation	31
parseTCGAsampleTypes	33
performICA	34
performPCA	35
plotDistribution	36
plotGeneExprPerSample	38
plotGroupIndependence	39
plotICA	40
plotPCA	41
plotProtein	42
plotRowStats	43
plotSplicingEvent	44
plotSurvivalCurves	46
plotSurvivalPvaluesByCutoff	47
plotTranscripts	48
plotVariance	49

prepareAnnotationFromEvents	50
prepareSRAMetadata	51
processSurvTerms	52
psychomics	54
quantifySplicing	55
queryEnsemblByGene	56
readFile	56
rowMeans	57
survdiffTerms	57
survfit.survTerms	59
testGroupIndependence	60
testSurvival	61
[.GEandAScorrelation	63

Index	66
--------------	-----------

assignValuePerSubject *Assign average sample values to their corresponding subjects*

Description

Assign average sample values to their corresponding subjects

Usage

```
assignValuePerSubject(
  data,
  match,
  clinical = NULL,
  patients = NULL,
  samples = NULL
)
```

Arguments

data	One-row data frame/matrix or vector: values per sample for a single gene
match	Matrix: match between samples and subjects
clinical	Data frame or matrix: clinical dataset (only required if the subjects argument is not handed)
patients	Character: subject identifiers (only required if the clinical argument is not handed)
samples	Character: samples to use when assigning values per subject (if NULL, all samples will be used)

Value

Values per subject

See Also

Other functions to analyse survival: [getAttributesTime\(\)](#), [labelBasedOnCutoff\(\)](#), [optimalSurvivalCutoff\(\)](#), [plotSurvivalCurves\(\)](#), [plotSurvivalPvaluesByCutoff\(\)](#), [processSurvTerms\(\)](#), [survdiffTerms\(\)](#), [survfit.survTerms\(\)](#), [testSurvival\(\)](#)

Examples

```
# Calculate PSI for skipped exon (SE) and mutually exclusive (MXE) events
annot <- readfile("ex_splicing_annotation.RDS")
junctionQuant <- readfile("ex_junctionQuant.RDS")

psi <- quantifySplicing(annot, junctionQuant, eventType=c("SE", "MXE"))

# Match between subjects and samples
match <- rep(paste("Subject", 1:3), 2)
names(match) <- colnames(psi)

# Assign PSI values to each subject based on the PSI of their samples
assignValuePerSubject(psi[,3, ], match)
```

calculateLoadingsContribution

Calculate the contribution of PCA loadings to the selected principal components

Description

Total contribution of a variable is calculated as per $((C_x * E_x) + (C_y * E_y)) / (E_x + E_y)$, where:

- C_x and C_y are the contributions of a variable to principal components x and y
- E_x and E_y are the eigenvalues of principal components x and y

Usage

```
calculateLoadingsContribution(pca, pcX = 1, pcY = 2)
```

Arguments

pca	prcomp object
pcX	Character: name of the X axis of interest from the PCA
pcY	Character: name of the Y axis of interest from the PCA

Value

Data frame containing the correlation between variables and selected principal components and the contribution of variables to the selected principal components (both individual and total contribution)

Source

<http://www.sthda.com/english/articles/31-principal-component-methods-in-r-practical-guide/112-pca-principal-component-analysis-essentials/>

See Also

Other functions to analyse principal components: [performPCA\(\)](#), [plotPCA\(\)](#), [plotVariance\(\)](#)

Examples

```
pca <- performPCA(USArrests)
calculateLoadingsContribution(pca)
```

`colSums, EList-method` *Sum columns using an [EList-class](#) object*

Description

Sum columns using an [EList-class](#) object

Usage

```
## S4 method for signature 'EList'
colSums(x, na.rm = FALSE, dims = 1)
```

Arguments

<code>x</code>	an array of two or more dimensions, containing numeric, complex, integer or logical values, or a numeric data frame. For <code>.colSums()</code> etc, a numeric, integer or logical matrix (or vector of length $m * n$).
<code>na.rm</code>	logical. Should missing values (including NaN) be omitted from the calculations?
<code>dims</code>	integer: Which dimensions are regarded as ‘rows’ or ‘columns’ to sum over. For <code>row*</code> , the sum or mean is over dimensions <code>dims+1, . . .</code> ; for <code>col*</code> it is over dimensions <code>1:dims</code> .

Value

Numeric vector with the sum of the columns

`convertGeneIdentifiers`
Convert gene identifiers

Description

Convert gene identifiers

Usage

```
convertGeneIdentifiers(
  annotation,
  genes,
  key = "ENSEMBL",
  target = "SYMBOL",
  ignoreDuplicatedTargets = TRUE
)
```

Arguments

annotation	OrgDb: genome wide annotation for an organism, e.g. org.Hs.eg.db
genes	Character: genes to be converted
key	Character: type of identifier used, e.g. ENSEMBL; read ?AnnotationDbi::columns
target	Character: type of identifier to convert to; read ?AnnotationDbi::columns
ignoreDuplicatedTargets	Boolean: if TRUE, identifiers that share targets with other identifiers will not be converted

Value

Character vector of the respective targets of gene identifiers. The previous identifiers remain other identifiers have the same target (in case `ignoreDuplicatedTargets = TRUE`) or if no target was found.

See Also

Other functions for gene expression pre-processing: [filterGeneExpr\(\)](#), [normaliseGeneExpression\(\)](#), [plotGeneExprPerSample\(\)](#), [plotRowStats\(\)](#)

Examples

```
if ( require("org.Hs.eg.db") ) {
  columns(org.Hs.eg.db)

  genes <- c("ENSG0000012048", "ENSG0000083093", "ENSG0000141510",
            "ENSG0000051180")
  convertGeneIdentifiers(org.Hs.eg.db, genes,
                        key="ENSEMBL", target="SYMBOL")
}
```

correlateGEandAS	<i>Correlate gene expression data against alternative splicing quantification</i>
------------------	---

Description

Test for association between paired samples' gene expression (for any genes of interest) and alternative splicing quantification.

Usage

```
correlateGEandAS(geneExpr, psi, gene, ASevents = NULL, ...)
```

Arguments

geneExpr	Matrix or data frame: gene expression data
psi	Matrix or data frame: alternative splicing quantification data
gene	Character: gene symbol for genes of interest
ASevents	Character: alternative splicing events to correlate with gene expression of a gene (if NULL, the events will be automatically retrieved from the given gene)
...	Extra parameters passed to cor.test

Value

List of correlations where each element contains:

eventID	Alternative splicing event identifier
cor	Correlation between gene expression and alternative splicing quantification of one alternative splicing event
geneExpr	Gene expression for the selected gene
psi	Alternative splicing quantification for the alternative splicing event

See Also

Other functions to correlate gene expression and alternative splicing: [\[.GEandAScorrelation\(\)\]](#)

Examples

```
annot <- readfile("ex_splicing_annotation.RDS")
junctionQuant <- readfile("ex_junctionQuant.RDS")
psi <- quantifySplicing(annot, junctionQuant, eventType=c("SE", "MXE"))

geneExpr <- readfile("ex_gene_expression.RDS")
correlateGEandAS(geneExpr, psi, "ALDOA")
```

createGroupByAttribute

Split elements into groups based on a given column of a dataset

Description

Elements are identified by their respective row name.

Usage

```
createGroupByAttribute(col, dataset)
```

Arguments

col	Character: column name
dataset	Matrix or data frame: dataset

Value

Named list with each unique value from a given column and respective elements

See Also

Other functions for data grouping: [getGeneList\(\)](#), [getMatchingSamples\(\)](#), [getSubjectFromSample\(\)](#), [groupPerElem\(\)](#), [plotGroupIndependence\(\)](#), [testGroupIndependence\(\)](#)

Examples

```
df <- data.frame(gender=c("male", "female"),
                 stage=paste("stage", c(1, 3, 1, 4, 2, 3, 2, 2)))
rownames(df) <- paste0("subject-", LETTERS[1:8])
createGroupByAttribute(col="stage", dataset=df)
```

diffAnalyses

*Perform statistical analyses***Description**

Perform statistical analyses

Usage

```
diffAnalyses(
  data,
  groups = NULL,
  analyses = c("wilcoxRankSum", "ttest", "kruskal", "levene", "fligner"),
  pvalueAdjust = "BH",
  geneExpr = NULL,
  psi = NULL
)
```

Arguments

<code>data</code>	Data frame or matrix: gene expression or alternative splicing quantification
<code>groups</code>	Named list of characters (containing elements belonging to each group) or character vector (containing the group of each individual sample); if NULL, sample types are used instead when available, e.g. normal, tumour and metastasis
<code>analyses</code>	Character: statistical tests to perform (see Details)
<code>pvalueAdjust</code>	Character: method used to adjust p-values (see Details)
<code>geneExpr</code>	Character: name of the gene expression dataset (only required for density sparklines available in the interactive mode)
<code>psi</code>	Data frame or matrix: alternative splicing quantification (defunct argument, use <code>data</code> instead)

Details

The following statistical analyses may be performed by including the respective string in the `analysis` argument:

- `ttest` - Unpaired t-test (2 groups)
- `wilcoxRankSum` - Wilcoxon Rank Sum test (2 groups)
- `kruskal` - Kruskal test (2 or more groups)
- `levene` - Levene's test (2 or more groups)
- `fligner` - Fligner-Killeen test (2 or more groups)
- `density` - Sample distribution per group (only usable through the visual interface)

The following methods for p-value adjustment are supported by using the respective string in the `pvalueAdjust` argument:

- none: do not adjust p-values
- BH: Benjamini-Hochberg's method (false discovery rate)
- BY: Benjamini-Yekutieli's method (false discovery rate)
- bonferroni: Bonferroni correction (family-wise error rate)
- holm: Holm's method (family-wise error rate)
- hochberg: Hochberg's method (family-wise error rate)
- hommel: Hommel's method (family-wise error rate)

Value

Table of statistical analyses

See Also

Other functions to perform and plot differential analyses: [plotDistribution\(\)](#)

Examples

```
# Calculate PSI for skipped exon (SE) and mutually exclusive (MXE) events
eventType <- c("SE", "MXE")
annot <- readfile("ex_splicing_annotation.RDS")
junctionQuant <- readfile("ex_junctionQuant.RDS")

psi <- quantifySplicing(annot, junctionQuant, eventType=c("SE", "MXE"))
group <- c(rep("Normal", 3), rep("Tumour", 3))
diffAnalyses(psi, group)
```

ensemblToUniprot

Convert from Ensembl to UniProt identifier

Description

Convert from Ensembl to UniProt identifier

Usage

```
ensemblToUniprot(protein)
```

Arguments

`protein` Character: Ensembl identifier

Value

UniProt protein identifier

See Also

Other functions to retrieve external information: [plotProtein\(\)](#), [plotTranscripts\(\)](#), [queryEnsemblByGene\(\)](#)

Examples

```
gene <- "ENSG00000173262"
ensemblToUniprot(gene)

protein <- "ENSP00000445929"
ensemblToUniprot(protein)
```

filterGeneExpr

Filter genes based on their expression

Description

Filter genes based on their expression

Usage

```
filterGeneExpr(  
  geneExpr,  
  minMean = 0,  
  maxMean = Inf,  
  minVar = 0,  
  maxVar = Inf,  
  minCounts = 10,  
  minTotalCounts = 15  
)
```

Arguments

geneExpr	Data frame or matrix: gene expression
minMean	Numeric: minimum of read count mean per gene
maxMean	Numeric: maximum of read count mean per gene
minVar	Numeric: minimum of read count variance per gene
maxVar	Numeric: maximum of read count variance per gene
minCounts	Numeric: minimum number of read counts per gene for at least some samples
minTotalCounts	Numeric: minimum total number of read counts per gene

Value

Boolean vector indicating which genes have sufficiently large counts

See Also

Other functions for gene expression pre-processing: [convertGeneIdentifiers\(\)](#), [normaliseGeneExpression\(\)](#), [plotGeneExprPerSample\(\)](#), [plotRowStats\(\)](#)

Examples

```

geneExpr <- readRDS("ex_gene_expression.RDS")

# Add some genes with low expression
geneExpr <- rbind(geneExpr,
                 lowReadGene1=c(rep(4:5, 10)),
                 lowReadGene2=c(rep(5:1, 10)),
                 lowReadGene3=c(rep(10:1, 10)),
                 lowReadGene4=c(rep(7:8, 10)))

# Filter out genes with low reads across samples
geneExpr[filterGeneExpr(geneExpr), ]

```

filterGroups

Filter groups with less data points than the threshold

Description

Groups containing a number of non-missing values less than the threshold are discarded.

Usage

```
filterGroups(vector, group, threshold = 1)
```

Arguments

vector	Unnamed elements
group	Character: group of the elements
threshold	Integer: number of valid non-missing values by group

Value

Named vector with filtered elements from valid groups. The group of the respective element is given in the name.

Examples

```

# Removes groups with less than two elements
filterGroups(1:4, c("A", "B", "B", "D"), threshold=2)

```

`filterPSI`*Filter alternative splicing quantification*

Description

Filter alternative splicing quantification

Usage

```
filterPSI(  
  psi,  
  minMedian = -Inf,  
  maxMedian = Inf,  
  minLogVar = -Inf,  
  maxLogVar = Inf,  
  minRange = -Inf,  
  maxRange = Inf  
)
```

Arguments

<code>psi</code>	Data frame or matrix: alternative splicing quantification
<code>minMedian</code>	Numeric: minimum of read count median per splicing event
<code>maxMedian</code>	Numeric: maximum of read count median per splicing event
<code>minLogVar</code>	Numeric: minimum log10(read count variance) per splicing event
<code>maxLogVar</code>	Numeric: maximum log10(read count variance) per splicing event
<code>minRange</code>	Numeric: minimum range of read counts across samples per splicing event
<code>maxRange</code>	Numeric: maximum range of read counts across samples per splicing event

Value

Boolean vector indicating which splicing events pass the thresholds

See Also

Other functions for PSI quantification: [getSplicingEventTypes\(\)](#), [listSplicingAnnotations\(\)](#), [loadAnnotation\(\)](#), [plotRowStats\(\)](#), [quantifySplicing\(\)](#)

Examples

```
# Calculate PSI for skipped exon (SE) and mutually exclusive (MXE) events  
annot <- readfile("ex_splicing_annotation.RDS")  
junctionQuant <- readfile("ex_junctionQuant.RDS")  
  
psi <- quantifySplicing(annot, junctionQuant, eventType=c("SE", "MXE"))  
psi[filterPSI(psi, minMedian=0.05, maxMedian=0.95, minRange=0.15), ]
```

getAttributesTime *Get time values for given columns in a clinical dataset*

Description

Get time values for given columns in a clinical dataset

Usage

```
getAttributesTime(  
  clinical,  
  event,  
  timeStart,  
  timeStop = NULL,  
  followup = "days_to_last_followup"  
)
```

Arguments

clinical	Data frame: clinical data
event	Character: name of column containing time of the event of interest
timeStart	Character: name of column containing starting time of the interval or follow up time
timeStop	Character: name of column containing ending time of the interval (only relevant for interval censoring)
followup	Character: name of column containing follow up time

Value

Data frame containing the time for the given columns

See Also

Other functions to analyse survival: [assignValuePerSubject\(\)](#), [labelBasedOnCutoff\(\)](#), [optimalSurvivalCutoff\(\)](#), [plotSurvivalCurves\(\)](#), [plotSurvivalPvaluesByCutoff\(\)](#), [processSurvTerms\(\)](#), [survdiffTerms\(\)](#), [survfit.survTerms\(\)](#), [testSurvival\(\)](#)

Examples

```
df <- data.frame(followup=c(200, 300, 400), death=c(NA, 300, NA))  
rownames(df) <- paste("subject", 1:3)  
getAttributesTime(df, event="death", timeStart="death", followup="followup")
```

getDownloadsFolder *Get the path to the Downloads folder*

Description

Get the path to the Downloads folder

Usage

```
getDownloadsFolder()
```

Value

Path to Downloads folder

See Also

Other functions associated with TCGA data retrieval: [getTCGAdataTypes\(\)](#), [isFirebrowseUp\(\)](#), [loadTCGAdata\(\)](#), [parseTCGAsampleTypes\(\)](#)

Other functions associated with GTEx data retrieval: [getGtexDataTypes\(\)](#), [getGtexTissues\(\)](#), [loadGtexData\(\)](#)

Other functions associated with SRA data retrieval: [loadSRaproject\(\)](#)

Examples

```
getDownloadsFolder()
```

getGeneList *Get curated, literature-based gene lists*

Description

Available gene lists:

- **Sebestyen et al., 2016:** 1350 genes encoding RNA-binding proteins, 167 of which are splicing factors

Usage

```
getGeneList()
```

Value

List of genes

See Also

Other functions for data grouping: [createGroupByAttribute\(\)](#), [getMatchingSamples\(\)](#), [getSubjectFromSample\(\)](#), [groupPerElem\(\)](#), [plotGroupIndependence\(\)](#), [testGroupIndependence\(\)](#)

Examples

```
getGeneList()
```

```
getGtexDataTypes
```

Get GTEX data types

Description

Get GTEX data types

Usage

```
getGtexDataTypes()
```

Value

GTEX data types

See Also

Other functions associated with GTEX data retrieval: [getDownloadsFolder\(\)](#), [getGtexTissues\(\)](#), [loadGtexData\(\)](#)

Examples

```
getGtexDataTypes()
```

```
getGtexTissues
```

Get GTEX tissues from given GTEX sample attributes

Description

Get GTEX tissues from given GTEX sample attributes

Usage

```
getGtexTissues(folder = getDownloadsFolder())
```

Arguments

folder Character: folder containing data

Value

Character: available tissues

See Also

Other functions associated with GTEX data retrieval: [getDownloadsFolder\(\)](#), [getGtexDataTypes\(\)](#), [loadGtexData\(\)](#)

Examples

```
## Not run:  
getGtexTissues()  
  
## End(Not run)
```

getMatchingSamples *Get samples matching the given subjects*

Description

Get samples matching the given subjects

Usage

```
getMatchingSamples(  
  patients,  
  samples,  
  clinical = NULL,  
  rm.NA = TRUE,  
  match = NULL,  
  showMatch = FALSE  
)
```

Arguments

patients	Character or list of characters: subject identifiers
samples	Character: sample identifiers
clinical	Data frame or matrix: clinical dataset
rm.NA	Boolean: remove missing values?
match	Integer: vector of subject index with the sample identifiers as name to save time (optional)
showMatch	Boolean: show matching subject index?

Value

Names of the matching samples (if showMatch = TRUE, a character with the subjects as values and their respective samples as names is returned)

See Also

Other functions for data grouping: [createGroupByAttribute\(\)](#), [getGeneList\(\)](#), [getSubjectFromSample\(\)](#), [groupPerElem\(\)](#), [plotGroupIndependence\(\)](#), [testGroupIndependence\(\)](#)

Examples

```
subjects <- c("GTEX-ABC", "GTEX-DEF", "GTEX-GHI", "GTEX-JKL", "GTEX-MNO")  
samples <- paste0(subjects, "-sample")  
clinical <- data.frame(samples=samples)  
rownames(clinical) <- subjects  
getMatchingSamples(subjects[c(1, 4)], samples, clinical)
```

```
getSplicingEventFromGenes
```

Get alternative splicing events from genes or vice-versa

Description

Get alternative splicing events from genes or vice-versa

Usage

```
getSplicingEventFromGenes(genes, ASevents)
```

```
getGenesFromSplicingEvents(ASevents)
```

Arguments

genes	Character: gene symbols (or TCGA-styled gene symbols)
ASevents	Character: alternative splicing events

Details

A list of alternative splicing events is required to run `getSplicingEventFromGenes`

Value

Named character containing alternative splicing events or genes and their respective genes or alternative splicing events as names (depending on the function in use)

Examples

```
ASevents <- c("SE_1+_201763003_201763300_201763374_201763594_NAV1",
             "SE_1+_183515472_183516238_183516387_183518343_SMG7",
             "SE_1+_183441784_183471388_183471526_183481972_SMG7",
             "SE_1+_181019422_181022709_181022813_181024361_MR1",
             "SE_1+_181695298_181700311_181700367_181701520_CACNA1E")
genes <- c("NAV1", "SMG7", "MR1", "HELLO")

# Get splicing events from genes
matchedASevents <- getSplicingEventFromGenes(genes, ASevents)

# Names of matched events are the matching input genes
names(matchedASevents)
matchedASevents

# Get genes from splicing events
matchedGenes <- getGenesFromSplicingEvents(ASevents)

# Names of matched genes are the matching input alternative splicing events
names(matchedGenes)
matchedGenes
```

getSplicingEventTypes *Get supported splicing event types*

Description

Get supported splicing event types

Usage

```
getSplicingEventTypes(acronymsAsNames = FALSE)
```

Arguments

acronymsAsNames
 Boolean: return acronyms as names?

Value

Named character vector with splicing event types

See Also

Other functions for PSI quantification: [filterPSI\(\)](#), [listSplicingAnnotations\(\)](#), [loadAnnotation\(\)](#), [plotRowStats\(\)](#), [quantifySplicing\(\)](#)

Examples

```
getSplicingEventTypes()
```

getSubjectFromSample *Get subjects from given samples*

Description

Get subjects from given samples

Usage

```
getSubjectFromSample(sampleId, patientId = NULL, na = FALSE, sampleInfo = NULL)
```

Arguments

sampleId Character: sample identifiers
 patientId Character: subject identifiers to filter by (optional; if a matrix or data frame is given, its rownames will be used to infer the subject identifiers)
 na Boolean: return NA for samples with no matching subjects
 sampleInfo Data frame or matrix: sample information containing the sample identifiers as rownames and a column named "Subject ID" with the respective subject identifiers

Value

Character: subject identifiers corresponding to the given samples

See Also

Other functions for data grouping: [createGroupByAttribute\(\)](#), [getGeneList\(\)](#), [getMatchingSamples\(\)](#), [groupPerElem\(\)](#), [plotGroupIndependence\(\)](#), [testGroupIndependence\(\)](#)

Examples

```
samples <- paste0("GTEX-", c("ABC", "DEF", "GHI", "JKL", "MNO"), "-sample")
getSubjectFromSample(samples)

# Filter returned samples based on available subjects
subjects <- paste0("GTEX-", c("DEF", "MNO"))
getSubjectFromSample(samples, subjects)
```

getTCGAdataTypes	<i>Get available parameters for TCGA data</i>
------------------	---

Description

Parameters obtained via [Firebrowse](#)

Usage

```
getTCGAdataTypes()

getTCGAdates()

getTCGAcohorts(cohort = NULL)
```

Arguments

cohort Character: filter results by cohorts (optional)

Value

Parsed response

See Also

Other functions associated with TCGA data retrieval: [getDownloadsFolder\(\)](#), [isFirebrowseUp\(\)](#), [loadTCGAdata\(\)](#), [parseTCGAsampleTypes\(\)](#)

Examples

```
getTCGAdataTypes()
if (isFirebrowseUp()) getFirebrowseDates()
if (isFirebrowseUp()) getTCGAcohorts()
```

groupPerElem	<i>Assign one group to each element</i>
--------------	---

Description

Assign one group to each element

Usage

```
groupPerElem(groups, elem = NULL, outerGroupName = NA)
```

Arguments

groups	List of integers: groups of elements
elem	Character: all elements available
outerGroupName	Character: name to give to outer group (if NULL, only show elements matched to their respective groups)

Value

Character vector where each element corresponds to the group of the respective element

See Also

Other functions for data grouping: [createGroupByAttribute\(\)](#), [getGeneList\(\)](#), [getMatchingSamples\(\)](#), [getSubjectFromSample\(\)](#), [plotGroupIndependence\(\)](#), [testGroupIndependence\(\)](#)

Examples

```
groups <- list(1:3, 4:7, 8:10)
names(groups) <- paste("Stage", 1:3)
groupPerElem(groups)
```

isFirebrowseUp	<i>Check if Rhrefhttp://firebrowse.org/api-docs/Firebrowse API is running</i>
----------------	---

Description

Check if **Firebrowse API** is running

Usage

```
isFirebrowseUp()
```

Value

Invisible TRUE if the **Firebrowse API** is working; otherwise, raises a warning with the status code and a brief explanation.

See Also

Other functions associated with TCGA data retrieval: [getDownloadsFolder\(\)](#), [getTCGAdataTypes\(\)](#), [loadTCGAdata\(\)](#), [parseTCGAsampleTypes\(\)](#)

Examples

```
isFirebrowseUp()
```

labelBasedOnCutoff *Label groups based on a given cutoff*

Description

Label groups based on a given cutoff

Usage

```
labelBasedOnCutoff(data, cutoff, label = NULL, gte = TRUE)
```

Arguments

data	Numeric: test data
cutoff	Numeric: test cutoff
label	Character: label to prefix group names
gte	Boolean: test using greater than or equal than cutoff (TRUE) or less than or equal than cutoff (FALSE)?

Value

Labelled groups

See Also

Other functions to analyse survival: [assignValuePerSubject\(\)](#), [getAttributesTime\(\)](#), [optimalSurvivalCutoff\(\)](#), [plotSurvivalCurves\(\)](#), [plotSurvivalPvaluesByCutoff\(\)](#), [processSurvTerms\(\)](#), [survdiffTerms\(\)](#), [survfit.survTerms\(\)](#), [testSurvival\(\)](#)

Examples

```
labelBasedOnCutoff(data=c(1, 0, 0, 1, 0, 1), cutoff=0.5)

labelBasedOnCutoff(data=c(1, 0, 0, 1, 0, 1), cutoff=0.5, "Ratio")

# Use "greater than" instead of "greater than or equal to"
labelBasedOnCutoff(data=c(1, 0, 0, 0.5, 0, 1), cutoff=0.5, gte=FALSE)
```

```
listSplicingAnnotations
```

List alternative splicing annotations

Description

List alternative splicing annotations

Usage

```
listSplicingAnnotations(species = NULL, assembly = NULL, date = NULL)
```

Arguments

species	Character: filter results by species (regular expression)
assembly	Character: filter results by assembly (regular expression)
date	Character: filter results by date (regular expression)

Value

Named character vector with splicing annotation names

See Also

Other functions for PSI quantification: [filterPSI\(\)](#), [getSplicingEventTypes\(\)](#), [loadAnnotation\(\)](#), [plotRowStats\(\)](#), [quantifySplicing\(\)](#)

Examples

```
listSplicingAnnotations() # Return all alternative splicing annotations
listSplicingAnnotations(assembly="hg19") # Search for hg19 annotation
listSplicingAnnotations(assembly="hg38") # Search for hg38 annotation
listSplicingAnnotations(date="201(7|8)") # Search for 2017 or 2018 annotation
```

```
loadAnnotation
```

Load alternative splicing annotation from AnnotationHub

Description

Load alternative splicing annotation from AnnotationHub

Usage

```
loadAnnotation(annotation, cache = NULL)
```

Arguments

annotation	Character: annotation to load
cache	Character: directory path of cache (if NULL, default location is AnnotationHub::getAnnotationHubCacheDir())

Value

List of data frames containing the alternative splicing annotation per event type

See Also

Other functions for PSI quantification: [filterPSI\(\)](#), [getSplicingEventTypes\(\)](#), [listSplicingAnnotations\(\)](#), [plotRowStats\(\)](#), [quantifySplicing\(\)](#)

Examples

```
human <- listSplicingAnnotations()[[1]]
## Not run:
annot <- loadAnnotation(human)

## End(Not run)
```

loadGtexData

Load GTEx data

Description

Load GTEx data

Usage

```
loadGtexData(
  folder = getDownloadsFolder(),
  data = getGtexDataTypes(),
  tissue = NULL
)
```

Arguments

folder	Character: folder containing data
data	Character: data types to load (see getGtexDataTypes())
tissue	Character: tissues to load (if NULL, load all); tissue selection may speed up data loading

Value

List with loaded data

See Also

Other functions associated with GTEx data retrieval: [getDownloadsFolder\(\)](#), [getGtexDataTypes\(\)](#), [getGtexTissues\(\)](#)

Examples

```
## Not run:
# Download and load all available GTEx data
data <- loadGtexData()

# Download and load only junction quantification and sample info from GTEx
getGtexDataTypes()
data <- loadGtexData(data=c("sampleInfo", "junctionQuant"))

# Download and load only data for specific tissues
getGtexTissues()
data <- loadGtexData(tissue=c("Stomach", "Small Intestine"))

## End(Not run)
```

loadLocalFiles	<i>Load local files</i>
----------------	-------------------------

Description

Load local files

Usage

```
loadLocalFiles(folder, ignore = c(".aux.", ".mage-tab."), name = "Data")
```

Arguments

folder	Character: path to folder containing files of interest
ignore	Character: skip folders and filenames that match the expression
name	Character: name of the category containing all loaded datasets

Value

List of data frames from valid files

See Also

Other functions to load local files: [prepareSRAMetadata\(\)](#)

Examples

```
## Not run:
folder <- "~/Downloads/ACC 2016"
data <- loadLocalFiles(folder)

ignore <- c(".aux.", ".mage-tab.", "junction quantification")
loadLocalFiles(folder, ignore)

## End(Not run)
```

loadSRaproject	<i>Download and load SRA projects via Rhrefhttps://jhubiostatistics.shinyapps.io/recount/recount2</i>
----------------	--

Description

Download and load SRA projects via [recount2](#)

Usage

```
loadSRaproject(project, outdir = getDownloadsFolder())
```

Arguments

project	Character: SRA project identifiers (check recount_abstract)
outdir	Character: directory to store the downloaded files

Value

List with loaded projects

See Also

Other functions associated with SRA data retrieval: [getDownloadsFolder\(\)](#)

loadTCGAdata	<i>Download and process TCGA data</i>
--------------	---------------------------------------

Description

TCGA data obtained via [Firebrowse](#)

Usage

```
loadTCGAdata(  
  folder = getDownloadsFolder(),  
  data = c("clinical", "junction_quantification", "RSEM_genes"),  
  exclude = c(".aux.", ".mage-tab.", "MANIFEST.txt"),  
  ...,  
  download = TRUE  
)
```

Arguments

folder	Character: directory to store the downloaded archives (by default, saves to getDownloadsFolder())
data	Character: data to load (see getTCGAdataTypes())
exclude	Character: files and folders to exclude from downloading and from loading into R (by default, exclude files containing .aux., .mage-tab. and MANIFEST.TXT)
...	Arguments passed on to queryFirebrowseData
format	Character: response format as JSON, CSV or TSV
date	Character: dates of the data retrieval by Firebrowse (by default, it uses the most recent data available)
cohort	Character: abbreviation of the cohorts (by default, returns data for all cohorts)
data_type	Character: data types (optional)
tool	Character: data produced by the selected Firebrowse tools (optional)
platform	Character: data generation platforms (optional)
center	Character: data generation centres (optional)
level	Integer: data levels (optional)
protocol	Character: sample characterization protocols (optional)
page	Integer: page of the results to return (optional)
page_size	Integer: number of records per page of results (optional)
sort_by	String: column used to sort the data (by default, sort by cohort)
download	Boolean: download missing files

Value

A list with the loaded data, unless required files are unavailable and `download = FALSE` (if so, it returns the URL of files to download)

See Also

Other functions associated with TCGA data retrieval: [getDownloadsFolder\(\)](#), [getTCGAdataTypes\(\)](#), [isFirebrowseUp\(\)](#), [parseTCGAsampleTypes\(\)](#)

Examples

```
getFirebrowseDataTypes()
## Not run:
loadFirebrowseData(cohort = "ACC", data_type = "Clinical")

## End(Not run)
```

`normaliseGeneExpression`*Filter and normalise gene expression*

Description

Filter and normalise gene expression

Usage

```
normaliseGeneExpression(  
  geneExpr,  
  geneFilter = NULL,  
  method = "TMM",  
  p = 0.75,  
  log2transform = TRUE,  
  priorCount = 0.25,  
  performVoom = FALSE  
)
```

Arguments

<code>geneExpr</code>	Matrix or data frame: gene expression
<code>geneFilter</code>	Boolean: filtered genes
<code>method</code>	Character: normalisation method, including TMM, RLE, upperquartile, none or quantile (see Details)
<code>p</code>	percentile (between 0 and 1) of the counts that is aligned when method="upperquartile"
<code>log2transform</code>	Boolean: perform log2-transformation?
<code>priorCount</code>	Average count to add to each observation to avoid zeroes after log-transformation
<code>performVoom</code>	Boolean: perform mean-variance modelling (voom)?

Details

`edgeR::calcNormFactors` will be used to normalise gene expression if one of the following methods is set: TMM, RLE, upperquartile or none. However, [voom](#) will be used for normalisation if `performVoom = TRUE` and the selected method is quantile.

Value

Filtered and normalised gene expression

See Also

Other functions for gene expression pre-processing: [convertGeneIdentifiers\(\)](#), [filterGeneExpr\(\)](#), [plotGeneExprPerSample\(\)](#), [plotRowStats\(\)](#)

Examples

```
geneExpr <- readfile("ex_gene_expression.RDS")  
normaliseGeneExpression(geneExpr)
```

optimalSurvivalCutoff *Calculate optimal data cutoff that best separates survival curves*

Description

Uses `stats::optim` with the Brent method to test multiple cutoffs and to find the minimum log-rank p-value.

Usage

```
optimalSurvivalCutoff(
  clinical,
  data,
  censoring,
  event,
  timeStart,
  timeStop = NULL,
  followup = "days_to_last_followup",
  session = NULL,
  filter = TRUE,
  survTime = NULL,
  lower = NULL,
  upper = NULL
)
```

Arguments

<code>clinical</code>	Data frame: clinical data
<code>data</code>	Numeric: data values
<code>censoring</code>	Character: censor using left, right, interval or interval2
<code>event</code>	Character: name of column containing time of the event of interest
<code>timeStart</code>	Character: name of column containing starting time of the interval or follow up time
<code>timeStop</code>	Character: name of column containing ending time of the interval (only relevant for interval censoring)
<code>followup</code>	Character: name of column containing follow up time
<code>session</code>	Shiny session (only used for the visual interface)
<code>filter</code>	Boolean or numeric: elements to use (all are used by default)
<code>survTime</code>	<code>survTime</code> object: times to follow up, time start, time stop and event (optional)
<code>lower, upper</code>	Bounds in which to search (if NULL, bounds are set to <code>lower = 0</code> and <code>upper = 1</code> if all data values are within that interval; otherwise, <code>lower = min(data, na.rm = TRUE)</code> and <code>upper = max(data, na.rm = TRUE)</code>)

Value

List containing the optimal cutoff (`par`) and the corresponding p-value (`value`)

See Also

Other functions to analyse survival: [assignValuePerSubject\(\)](#), [getAttributesTime\(\)](#), [labelBasedOnCutoff\(\)](#), [plotSurvivalCurves\(\)](#), [plotSurvivalPvaluesByCutoff\(\)](#), [processSurvTerms\(\)](#), [survdiffTerms\(\)](#), [survfit.survTerms\(\)](#), [testSurvival\(\)](#)

Examples

```
clinical <- read.table(text = "2549  NA ii  female
                             840  NA i   female
                             NA 1204 iv  male
                             NA  383 iv  female
                             1293  NA iii male
                             NA 1355 ii  male")
names(clinical) <- c("patient.days_to_last_followup",
                    "patient.days_to_death",
                    "patient.stage_event.pathologic_stage",
                    "patient.gender")
timeStart <- "days_to_death"
event     <- "days_to_death"

psi <- c(0.1, 0.2, 0.9, 1, 0.2, 0.6)
opt <- optimalSurvivalCutoff(clinical, psi, "right", event, timeStart)
```

parseCategoricalGroups

Parse categorical columns in a data frame

Description

Retrieve elements grouped by their unique group based on each categorical column

Usage

```
parseCategoricalGroups(df)
```

Arguments

df Data frame

Value

List of lists containing values based on rownames of df

See Also

[testGroupIndependence\(\)](#) and [plotGroupIndependence\(\)](#)

Examples

```
df <- data.frame("race"=c("caucasian", "caucasian", "asian"),
                 "gender"=c("male", "female", "male"))
rownames(df) <- paste("subject", 1:3)
parseCategoricalGroups(df)
```

parseSplicingEvent *Parse alternative splicing event identifier*

Description

Parse alternative splicing event identifier

Usage

```
parseSplicingEvent(  
  event,  
  char = FALSE,  
  pretty = FALSE,  
  extra = NULL,  
  coords = FALSE  
)
```

Arguments

event	Character: event identifier
char	Boolean: return character vector instead of list with parsed values?
pretty	Boolean: return a prettier name of the event identifier?
extra	Character: extra information to add (such as species and assembly version); only used if pretty = TRUE and char = TRUE
coords	Boolean: display extra coordinates regarding the alternative and constitutive regions of alternative splicing events? If char = FALSE, all coordinates are always displayed

Value

Parsed event

Examples

```
events <- c("SE_1_-_123_456_789_1024_TST",  
           "MXE_3+_473_578_686_736_834_937_HEY/YOU")  
parseSplicingEvent(events)
```

parseSuppaAnnotation *Get events from alternative splicing annotation*

Description

Get events from alternative splicing annotation

Usage

```

parseSuppaAnnotation(
  folder,
  types = c("SE", "AF", "AL", "MX", "A5", "A3", "RI"),
  genome = "hg19"
)

parseVastToolsAnnotation(
  folder,
  types = c("ALT3", "ALT5", "COMBI", "IR", "MERGE3m", "MIC", "EXSK", "MULTI"),
  genome = "Hsa",
  complexEvents = FALSE
)

parseMisoAnnotation(
  folder,
  types = c("SE", "AFE", "ALE", "MXE", "A5SS", "A3SS", "RI", "TandemUTR"),
  genome = "hg19"
)

parseMatsAnnotation(
  folder,
  types = c("SE", "AFE", "ALE", "MXE", "A5SS", "A3SS", "RI"),
  genome = "fromGTF",
  novelEvents = TRUE
)

```

Arguments

folder	Character: path to folder
types	Character: type of events to retrieve (depends on the program of origin; see details)
genome	Character: genome of interest (for instance, hg19; depends on the program of origin)
complexEvents	Boolean: should complex events in A3SS and A5SS be parsed?
novelEvents	Boolean: parse events detected due to novel splice sites

Details

Type of parsable events:

- Alternative 3' splice site
- Alternative 5' splice site
- Alternative first exon
- Alternative last exon
- Skipped exon (may include skipped micro-exons)
- Mutually exclusive exon
- Retained intron
- Tandem UTR

Value

Retrieve data frame with events based on a given alternative splicing annotation

See Also

Other functions to prepare alternative splicing annotations: [prepareAnnotationFromEvents\(\)](#)

Examples

```
# Load sample files
folder <- "extdata/eventsAnnotSample/suppa_output/suppaEvents"
suppaOutput <- system.file(folder, package="psychomics")

suppa <- parseSuppaAnnotation(suppaOutput)
# Load sample files
folder <- "extdata/eventsAnnotSample/VASTDB/Hsa/TEMPLATES"
vastToolsOutput <- system.file(folder, package="psychomics")

vast <- parseVastToolsAnnotation(vastToolsOutput)
# Load sample files
folder <- "extdata/eventsAnnotSample/miso_annotation"
misoOutput <- system.file(folder, package="psychomics")

miso <- parseMisoAnnotation(misoOutput)
# Load sample files
folder <- "extdata/eventsAnnotSample/mats_output/ASEvents"
matsOutput <- system.file(folder, package="psychomics")

mats <- parseMatsAnnotation(matsOutput)

# Do not parse novel events
mats <- parseMatsAnnotation(matsOutput, novelEvents=FALSE)
```

parseTCGAsampleTypes *Parse sample information from TCGA sample identifiers*

Description

Parse sample information from TCGA sample identifiers

Usage

```
parseTCGAsampleTypes(
  samples,
  filename = system.file("extdata", "TCGAsampleType.RDS", package = "psychomics")
)

parseTCGAsampleInfo(samples, match = NULL)
```

Arguments

samples	Character: sample identifiers
filename	Character: path to RDS file containing corresponding types
match	Integer: match between samples and subjects (NULL by default; performs the match)

Value

Metadata associated with each TCGA sample

See Also

Other functions associated with TCGA data retrieval: [getDownloadsFolder\(\)](#), [getTCGAdataTypes\(\)](#), [isFirebrowseUp\(\)](#), [loadTCGAdata\(\)](#)

Examples

```

parseTCGAsampleTypes(c("TCGA-01A-Tumour", "TCGA-10B-Normal"))
samples <- c("TCGA-3C-AAAU-01A-11R-A41B-07", "TCGA-3C-AALI-01A-11R-A41B-07",
            "TCGA-3C-AALJ-01A-31R-A41B-07", "TCGA-3C-AALK-01A-11R-A41B-07",
            "TCGA-4H-AAAK-01A-12R-A41B-07", "TCGA-5L-AAT0-01A-12R-A41B-07")

parseTCGAsampleInfo(samples)

```

performICA	<i>Perform independent component analysis after processing missing values</i>
------------	---

Description

Perform independent component analysis after processing missing values

Usage

```

performICA(
  data,
  n.comp = min(5, ncol(data)),
  center = TRUE,
  scale. = FALSE,
  missingValues = round(0.05 * nrow(data)),
  alg.typ = c("parallel", "defaltion"),
  fun = c("logcosh", "exp"),
  alpha = 1,
  ...
)

```

Arguments

<code>data</code>	an optional data frame (or similar: see model.frame) containing the variables in the formula <code>formula</code> . By default the variables are taken from <code>environment(formula)</code> .
<code>n.comp</code>	number of components to be extracted
<code>center</code>	a logical value indicating whether the variables should be shifted to be zero centered. Alternately, a vector of length equal the number of columns of <code>x</code> can be supplied. The value is passed to <code>scale</code> .
<code>scale.</code>	a logical value indicating whether the variables should be scaled to have unit variance before the analysis takes place. The default is <code>FALSE</code> for consistency with <code>S</code> , but in general scaling is advisable. Alternatively, a vector of length equal the number of columns of <code>x</code> can be supplied. The value is passed to scale .
<code>missingValues</code>	Integer: number of tolerated missing values per column to be replaced with the mean of the values of that same column
<code>alg.typ</code>	if <code>alg.typ == "parallel"</code> the components are extracted simultaneously (the default). if <code>alg.typ == "deflation"</code> the components are extracted one at a time.
<code>fun</code>	the functional form of the G function used in the approximation to neg-entropy (see 'details').
<code>alpha</code>	constant in range <code>[1, 2]</code> used in approximation to neg-entropy when <code>fun == "logcosh"</code>
<code>...</code>	Arguments passed on to <code>fastICA::fastICA</code>

Value

ICA result in a `prcomp` object

See Also

Other functions to analyse independent components: [plotICA\(\)](#)

Examples

```
performICA(USArrests)
```

```
performPCA
```

Perform principal component analysis after processing missing values

Description

Perform principal component analysis after processing missing values

Usage

```
performPCA(
  data,
  center = TRUE,
  scale. = FALSE,
  missingValues = round(0.05 * nrow(data)),
  ...
)
```

Arguments

data	an optional data frame (or similar: see model.frame) containing the variables in the formula formula. By default the variables are taken from <code>environment(formula)</code> .
center	a logical value indicating whether the variables should be shifted to be zero centered. Alternately, a vector of length equal the number of columns of x can be supplied. The value is passed to <code>scale</code> .
scale.	a logical value indicating whether the variables should be scaled to have unit variance before the analysis takes place. The default is FALSE for consistency with S, but in general scaling is advisable. Alternatively, a vector of length equal the number of columns of x can be supplied. The value is passed to scale .
missingValues	Integer: number of tolerated missing values per column to be replaced with the mean of the values of that same column
...	Arguments passed on to <code>stats::prcomp</code>

Value

PCA result in a `prcomp` object

See Also

Other functions to analyse principal components: [calculateLoadingsContribution\(\)](#), [plotPCA\(\)](#), [plotVariance\(\)](#)

Examples

```
performPCA(USArrests)
```

plotDistribution	<i>Plot distribution through a density plot</i>
------------------	---

Description

The tooltip shows the median, variance, max, min and number of non-NA samples of each data series (if data contains names or column names, those will be used as sample names and also appear in the tooltip).

Usage

```
plotDistribution(
  data,
  groups = NULL,
  rug = TRUE,
  vLine = TRUE,
  ...,
  title = NULL,
  psi = NULL,
  rugLabels = FALSE,
  rugLabelsRotation = 0
)
```

Arguments

data	Numeric, data frame or matrix: gene expression data or alternative splicing event quantification values (sample names are based on their names or colnames)
groups	List of sample names or vector containing the group name per data value (read Details); if NULL or a character vector of length 1, data values are considered from the same group
rug	Boolean: show rug plot?
vLine	Boolean: plot vertical lines (including descriptive statistics for each group)?
...	Arguments passed on to <code>stats::density.default</code>
bw	<p>the smoothing bandwidth to be used. The kernels are scaled such that this is the standard deviation of the smoothing kernel. (Note this differs from the reference books cited below, and from S-PLUS.)</p> <p>bw can also be a character string giving a rule to choose the bandwidth. See <code>bw.nrd</code>.</p> <p>The default, "nrd0", has remained the default for historical and compatibility reasons, rather than as a general recommendation, where e.g., "SJ" would rather fit, see also Venables and Ripley (2002).</p> <p>The specified (or computed) value of bw is multiplied by adjust.</p>
adjust	the bandwidth used is actually <code>adjust*bw</code> . This makes it easy to specify values like 'half the default' bandwidth.
kernel	<p>a character string giving the smoothing kernel to be used. This must partially match one of "gaussian", "rectangular", "triangular", "epanechnikov", "biweight", "cosine" or "optcosine", with default "gaussian", and may be abbreviated to a unique prefix (single letter).</p> <p>"cosine" is smoother than "optcosine", which is the usual 'cosine' kernel in the literature and almost MSE-efficient. However, "cosine" is the version used by S.</p>
window	<p>a character string giving the smoothing kernel to be used. This must partially match one of "gaussian", "rectangular", "triangular", "epanechnikov", "biweight", "cosine" or "optcosine", with default "gaussian", and may be abbreviated to a unique prefix (single letter).</p> <p>"cosine" is smoother than "optcosine", which is the usual 'cosine' kernel in the literature and almost MSE-efficient. However, "cosine" is the version used by S.</p>
weights	numeric vector of non-negative observation weights, hence of same length as x. The default NULL is equivalent to <code>weights = rep(1/nx, nx)</code> where nx is the length of (the finite entries of) <code>x[]</code> .
width	this exists for compatibility with S; if given, and bw is not, will set bw to width if this is a character string, or to a kernel-dependent multiple of width if this is numeric.
give.Rkern	logical; if true, <i>no</i> density is estimated, and the 'canonical bandwidth' of the chosen kernel is returned instead.
n	<p>the number of equally spaced points at which the density is to be estimated.</p> <p>When $n > 512$, it is rounded up to a power of 2 during the calculations (as <code>fft</code> is used) and the final result is interpolated by <code>approx</code>. So it almost always makes sense to specify n as a power of two.</p>
from	the left and right-most points of the grid at which the density is to be estimated; the defaults are <code>cut * bw</code> outside of <code>range(x)</code> .
to	the left and right-most points of the grid at which the density is to be estimated; the defaults are <code>cut * bw</code> outside of <code>range(x)</code> .

	cut	by default, the values of from and to are cut bandwidths beyond the extremes of the data. This allows the estimated density to drop to approximately zero at the extremes.
title	Character:	plot title
psi	Boolean:	are data composed of PSI values? If NULL, psi = TRUE if all data values are between 0 and 1
rugLabels	Boolean:	plot sample names in the rug?
rugLabelsRotation	Numeric:	rotation (in degrees) of rug labels; this may present issues at different zoom levels and depending on the proximity of data values

Details

Argument groups can be either:

- a list of sample names, e.g. `list("Group 1"=c("Sample A", "Sample B"), "Group 2"=c("Sample C"))`
- a character vector with the same length as data, e.g. `c("Sample A", "Sample C", "Sample B")`.

Value

highchart object with density plot

See Also

Other functions to perform and plot differential analyses: [diffAnalyses\(\)](#)

Examples

```
data <- sample(20, rep=TRUE)/20
groups <- paste("Group", c(rep("A", 10), rep("B", 10)))
names(data) <- paste("Sample", 1:20)
plotDistribution(data, groups)

# Using colours
attr(groups, "Colour") <- c("Group A"="pink", "Group B"="orange")
plotDistribution(data, groups)
```

plotGeneExprPerSample *Plot distribution of gene expression per sample*

Description

Plot distribution of gene expression per sample

Usage

```
plotGeneExprPerSample(geneExpr, ...)
```

Arguments

geneExpr Data frame or matrix: gene expression
 ... Arguments passed on to [renderBoxplot](#)
 data Data frame or matrix
 outliers Boolean: draw outliers?
 sortByMedian Boolean: sort box plots based on ascending median?
 showXlabels Boolean: show labels in X axis?

Value

Gene expression distribution plots

See Also

Other functions for gene expression pre-processing: [convertGeneIdentifiers\(\)](#), [filterGeneExpr\(\)](#), [normaliseGeneExpression\(\)](#), [plotRowStats\(\)](#)

Examples

```
df <- data.frame(geneA=c(2, 4, 5),
                 geneB=c(20, 3, 5),
                 geneC=c(5, 10, 21))
colnames(df) <- paste("Sample", 1:3)
plotGeneExprPerSample(df)
```

plotGroupIndependence *Plot $-\log_{10}$ (p-values) of the results obtained after multiple group independence testing*

Description

Plot $-\log_{10}$ (p-values) of the results obtained after multiple group independence testing

Usage

```
plotGroupIndependence(
  groups,
  top = 50,
  textSize = 10,
  colourLow = "lightgrey",
  colourMid = "blue",
  colourHigh = "orange",
  colourMidpoint = 150
)
```

Arguments

groups	multiGroupIndependenceTest object (obtained after running testGroupIndependence())
top	Integer: number of attributes to render
textSize	Integer: size of the text
colourLow	Character: name or HEX code of colour for lower values
colourMid	Character: name or HEX code of colour for middle values
colourHigh	Character: name or HEX code of colour for higher values
colourMidpoint	Numeric: midpoint to identify middle values

Value

ggplot object

See Also

[parseCategoricalGroups\(\)](#) and [testGroupIndependence\(\)](#)

Other functions for data grouping: [createGroupByAttribute\(\)](#), [getGeneList\(\)](#), [getMatchingSamples\(\)](#), [getSubjectFromSample\(\)](#), [groupPerElem\(\)](#), [testGroupIndependence\(\)](#)

Examples

```
elements <- paste("subjects", 1:50)
ref       <- elements[10:50]
groups   <- list(race=list(asian=elements[1:3],
                          white=elements[4:7],
                          black=elements[8:10]),
                region=list(european=elements[c(4, 5, 9)],
                            african=elements[c(6:8, 10:50)]))
groupTesting <- testGroupIndependence(ref, groups, elements)
plotGroupIndependence(groupTesting)
```

plotICA

Create multiple scatterplots from ICA

Description

Create multiple scatterplots from ICA

Usage

```
plotICA(ica, components = seq(10), groups = NULL, ...)
```

Arguments

ica	Object resulting from performICA()
components	Numeric: independent components to plot
groups	Matrix: groups to plot indicating the index of interest of the samples (use clinical or sample groups)
...	Arguments passed on to pairsD3::pairsD3

group a optional vector specifying the group each observation belongs to. Used for tooltips and colouring the observations.

subset an optional vector specifying a subset of observations to be used for plotting. Useful when you have a large number of observations, you can specify a random subset.

labels the names of the variables (column names of x used by default).

cex the magnification of the plotting symbol (default=3)

width the width (and height) of the plot when viewed externally.

col an optional (hex) colour for each of the levels in the group vector.

big a logical parameter. Prevents inadvertent plotting of huge data sets. Default limit is 10 variables, to plot more than 10 set big=TRUE.

theme a character parameter specifying whether the theme should be colour colour (default) or black and white bw.

opacity numeric between 0 and 1. The opacity of the plotting symbols (default 0.9).

tooltip an optional vector with the tool tip to be displayed when hovering over an observation. You can include basic html.

leftmar space on the left margin

topmar space on the bottom margin

Value

Multiple scatterplots as a pairsD3 object

See Also

Other functions to analyse independent components: [performICA\(\)](#)

Examples

```
data <- scale(USArrests)
ica <- fastICA::fastICA(data, n.comp=4)
plotICA(ica)

# Colour by groups
groups <- NULL
groups$sunny <- c("California", "Hawaii", "Florida")
groups$ozEntrance <- c("Kansas")
groups$novel <- c("New Mexico", "New York", "New Hampshire", "New Jersey")
plotICA(ica, groups=groups)
```

plotPCA

Create a scatterplot from a PCA object

Description

Create a scatterplot from a PCA object

Usage

```
plotPCA(
  pca,
  pcX = 1,
  pcY = 2,
  groups = NULL,
  individuals = TRUE,
  loadings = FALSE,
  nLoadings = NULL
)
```

Arguments

pca	prcomp object
pcX	Character: name of the X axis of interest from the PCA
pcY	Character: name of the Y axis of interest from the PCA
groups	Matrix: groups to plot indicating the index of interest of the samples (use clinical or sample groups)
individuals	Boolean: plot PCA individuals
loadings	Boolean: plot PCA loadings/rotations
nLoadings	Integer: Number of variables to plot, ordered by those that most contribute to selected principal components (this allows for faster performance as only the most contributing variables are rendered); if NULL, all variables are plotted

Value

Scatterplot as an highchart object

See Also

Other functions to analyse principal components: [calculateLoadingsContribution\(\)](#), [performPCA\(\)](#), [plotVariance\(\)](#)

Examples

```
pca <- prcomp(USArrests, scale=TRUE)
plotPCA(pca)
plotPCA(pca, pcX=2, pcY=3)

# Plot both individuals and loadings
plotPCA(pca, pcX=2, pcY=3, loadings=TRUE)
```

plotProtein

Plot protein features

Description

Plot protein features

Usage

```
plotProtein(molecule)
```

Arguments

molecule Character: UniProt protein or Ensembl transcript identifier

Value

highcharter object

See Also

Other functions to retrieve external information: [ensemblToUniprot\(\)](#), [plotTranscripts\(\)](#), [queryEnsemblByGene\(\)](#)

Examples

```
protein <- "P38398"
plotProtein(protein)

transcript <- "ENST00000488540"
plotProtein(transcript)
```

plotRowStats	<i>Plot sample statistics per row</i>
--------------	---------------------------------------

Description

Plot sample statistics per row

Usage

```
plotRowStats(
  data,
  x,
  y,
  subset = NULL,
  xmin = NULL,
  xmax = NULL,
  ymin = NULL,
  ymax = NULL,
  xlim = NULL,
  ylim = NULL
)
```

Arguments

data Data frame or matrix

x, y Character: statistic to calculate and display in the plot per row; choose between mean, median, var or range (or transformations of those variables, e.g. $\log_{10}(\text{var})$)

subset Boolean or integer: data points to highlight (if NULL, all points are highlighted)
 xmin, xmax, ymin, ymax Numeric: minimum and maximum X and Y values to draw in the plot
 xlim, ylim Numeric: X and Y axis range

Value

Plot of data

See Also

Other functions for gene expression pre-processing: [convertGeneIdentifiers\(\)](#), [filterGeneExpr\(\)](#), [normaliseGeneExpression\(\)](#), [plotGeneExprPerSample\(\)](#)

Other functions for PSI quantification: [filterPSI\(\)](#), [getSplicingEventTypes\(\)](#), [listSplicingAnnotations\(\)](#), [loadAnnotation\(\)](#), [quantifySplicing\(\)](#)

Examples

```
library(ggplot2)

# Plotting gene expression data
geneExpr <- readRDS("ex_gene_expression.RDS")
plotRowStats(geneExpr, "mean", "var^(1/4)") +
  ggtitle("Mean-variance plot") +
  labs(y="Square Root of the Standard Deviation")

# Plotting alternative splicing quantification
annot <- readRDS("ex_splicing_annotation.RDS")
junctionQuant <- readRDS("ex_junctionQuant.RDS")
psi <- quantifySplicing(annot, junctionQuant, eventType=c("SE", "MXE"))

medianVar <- plotRowStats(psi, x="median", y="var", xlim=c(0, 1)) +
  labs(x="Median PSI", y="PSI variance")
medianVar

rangeVar <- plotRowStats(psi, x="range", y="log10(var)", xlim=c(0, 1)) +
  labs(x="PSI range", y="log10(PSI variance)")
rangeVar
```

plotSplicingEvent *Plot diagram of alternative splicing events*

Description

Plot diagram of alternative splicing events

Usage

```
plotSplicingEvent(
  ASevent,
  class = NULL,
  style = NULL,
```

```

    showText = TRUE,
    showPath = TRUE,
    showAlternative1 = TRUE,
    showAlternative2 = TRUE,
    constitutiveWidth = 60,
    alternativeWidth = NULL,
    intronWidth = 15,
    constitutiveFill = "lightgray",
    constitutiveStroke = "darkgray",
    alternative1Fill = "#ffb153",
    alternative1Stroke = "#faa000",
    alternative2Fill = "#caa06c",
    alternative2Stroke = "#9d7039"
)

```

Arguments

ASevent	Character: alternative splicing event identifiers
class	Character: class of SVG parent tag
style	Character: style of SVG parent tag
showText	Boolean: display coordinates and length (if available)
showPath	Boolean: display alternative splicing junctions
showAlternative1	Boolean: show alternative exon 1 and respective splicing junctions and text?
showAlternative2	Boolean: show alternative exon 2 and respective splicing junctions and text? (only related with mutually exclusive exons)
constitutiveWidth	Numeric: width of constitutive exon(s)
alternativeWidth	Numeric: width of alternative exon(s)
intronWidth	Numeric: width of intron's representation
constitutiveFill	Character: fill colour of constitutive exons
constitutiveStroke	Character: stroke colour of constitutive exons
alternative1Fill	Character: fill colour of alternative exon 1
alternative1Stroke	Character: stroke colour of alternative exon 1
alternative2Fill	Character: fill colour of alternative exon 2
alternative2Stroke	Character: stroke colour of alternative exon 2

Value

List of SVG (one for each alternative splicing event)

Examples

```

ASevent <- c(
  "SE_9+_6486925_6492303_6492401_6493826_UHRF2",
  "SE_11+_86925_92303_92401_93826_TESTING/MHG2",
  "A5SS_15+_63353472_63353987_63354414_TPM1",
  "A3SS_3-_145796903_145794682_145795711_PLOD2",
  "AFE_17-_15165746_15168471_15164078_PMP22",
  "ALE_18-_5395066_5394792_5393477_EPB41L3",
  "MXE_15+_63335142_63335905_63336030_63336226_63336351_63349184_TPM1")
diagram <- plotSplicingEvent(ASevent)

diagram[["A3SS_3-_145796903_145794682_145795711_PLOD2"]]
diagram[[6]]
diagram

```

plotSurvivalCurves *Plot survival curves*

Description

Plot survival curves

Usage

```

plotSurvivalCurves(
  surv,
  mark = TRUE,
  interval = FALSE,
  pvalue = NULL,
  title = "Survival analysis",
  scale = NULL,
  auto = TRUE
)

```

Arguments

surv	Survival object
mark	Boolean: mark times?
interval	Boolean: show interval ranges?
pvalue	Numeric: p-value of the survival curves
title	Character: plot title
scale	Character: time scale (default is days)
auto	Boolean: return the plot automatically prepared (TRUE) or only the bare minimum (FALSE)?

Value

Plot of survival curves

See Also

Other functions to analyse survival: [assignValuePerSubject\(\)](#), [getAttributesTime\(\)](#), [labelBasedOnCutoff\(\)](#), [optimalSurvivalCutoff\(\)](#), [plotSurvivalPvaluesByCutoff\(\)](#), [processSurvTerms\(\)](#), [survdiffTerms\(\)](#), [survfit.survTerms\(\)](#), [testSurvival\(\)](#)

Examples

```
require("survival")
fit <- survfit(Surv(time, status) ~ x, data = aml)
plotSurvivalCurves(fit)
```

plotSurvivalPvaluesByCutoff

Plot p-values of survival difference between groups based on multiple cutoffs

Description

Plot p-values of survival difference between groups based on multiple cutoffs

Usage

```
plotSurvivalPvaluesByCutoff(
  clinical,
  data,
  censoring,
  event,
  timeStart,
  timeStop = NULL,
  followup = "days_to_last_followup",
  significance = 0.05,
  cutoffs = seq(0, 0.99, 0.01)
)
```

Arguments

clinical	Data frame: clinical data
data	Numeric: elements of interest to test against the cutoff
censoring	Character: censor using left, right, interval or interval2
event	Character: name of column containing time of the event of interest
timeStart	Character: name of column containing starting time of the interval or follow up time
timeStop	Character: name of column containing ending time of the interval (only relevant for interval censoring)
followup	Character: name of column containing follow up time
significance	Numeric: significance threshold
cutoffs	Numeric: cutoffs to test

Value

p-value plot

See Also

Other functions to analyse survival: [assignValuePerSubject\(\)](#), [getAttributesTime\(\)](#), [labelBasedOnCutoff\(\)](#), [optimalSurvivalCutoff\(\)](#), [plotSurvivalCurves\(\)](#), [processSurvTerms\(\)](#), [survdiffTerms\(\)](#), [survfit.survTerms\(\)](#), [testSurvival\(\)](#)

Examples

```
clinical <- read.table(text = "2549  NA ii  female
                             840  NA i   female
                             NA 1204 iv  male
                             NA  383 iv  female
                             1293  NA iii male")
names(clinical) <- c("patient.days_to_last_followup",
                    "patient.days_to_death",
                    "patient.stage_event.pathologic_stage",
                    "patient.gender")
clinical <- do.call(rbind, rep(list(clinical), 5))

psi <- data.frame(t(c(rep(0.1, 9), rep(0.2, 13), rep(0.3, 3))))
colnames(psi) <- paste0("sample", seq(psi))

# Match between subjects and samples
match <- paste0("subject", seq(psi))
names(match) <- colnames(psi)
rownames(clinical) <- match

eventData <- assignValuePerSubject(psi[1, ], match)

event      <- "days_to_death"
timeStart  <- "days_to_death"
plotSurvivalPvaluesByCutoff(clinical, eventData, censoring="right",
                             event=event, timeStart=timeStart)
```

plotTranscripts

Plot transcripts

Description

Plot transcripts

Usage

```
plotTranscripts(info, eventPosition = NULL, event = NULL, shiny = FALSE)
```

Arguments

info	Information retrieved from Ensembl
eventPosition	Numeric: coordinates of the alternative splicing event (ignored if event is set)
event	Character: identifier of the alternative splicing event to plot
shiny	Boolean: is the function running in a Shiny session?

Value

NULL (function is only used to modify the Shiny session's state or internal variables)

See Also

Other functions to retrieve external information: [ensemblToUniprot\(\)](#), [plotProtein\(\)](#), [queryEnsemblByGene\(\)](#)

Examples

```
event <- "SE_12_-_7985318_7984360_7984200_7982602_SLC2A14"
info <- queryEnsemblByEvent(event, species="human", assembly="hg19")
## Not run:
plotTranscripts(info, event=event)

## End(Not run)
```

plotVariance

Create the explained variance plot from a PCA

Description

Create the explained variance plot from a PCA

Usage

```
plotVariance(pca)
```

Arguments

pca prcomp object

Value

Plot variance as an highchart object

See Also

Other functions to analyse principal components: [calculateLoadingsContribution\(\)](#), [performPCA\(\)](#), [plotPCA\(\)](#)

Examples

```
pca <- prcomp(USArrests)
plotVariance(pca)
```

`prepareAnnotationFromEvents`*Prepare annotation from alternative splicing events*

Description

In case more than one data frame with alternative splicing events is given, the events are cross-referenced according to the chromosome, strand and relevant coordinates per event type (see details).

Usage

```
prepareAnnotationFromEvents(...)
```

Arguments

... Data frame(s) of alternative splicing events to include in the annotation

Details

Events from two or more data frames are cross-referenced based on each event's chromosome, strand and specific coordinates relevant for each event type:

- Skipped exon: constitutive exon 1 end, alternative exon (start and end) and constitutive exon 2 start
- Mutually exclusive exon: constitutive exon 1 end, alternative exon 1 and 2 (start and end) and constitutive exon 2 start
- Alternative 5' splice site: constitutive exon 1 end, alternative exon 1 end and constitutive exon 2 start
- Alternative first exon: same as alternative 5' splice site
- Alternative 3' splice site: constitutive exon 1 end, alternative exon 1 start and constitutive exon 2 start
- Alternative last exon: same as alternative 3' splice site

Value

List of data frames with the annotation from different data frames joined by event type

Note

When cross-referencing events, gene information is discarded.

See Also

Other functions to prepare alternative splicing annotations: [parseSuppaAnnotation\(\)](#)

Examples

```
# Load sample files (SUPPA annotation)
folder <- "extdata/eventsAnnotSample/suppa_output/suppaEvents"
suppaOutput <- system.file(folder, package="psychomics")

# Parse and prepare SUPPA annotation
suppa <- parseSuppaAnnotation(suppaOutput)
annot <- prepareAnnotationFromEvents(suppa)

# Load sample files (rMATS annotation)
folder <- "extdata/eventsAnnotSample/mats_output/ASEvents/"
matsOutput <- system.file(folder, package="psychomics")

# Parse rMATS annotation and prepare combined annotation from rMATS and SUPPA
mats <- parseMatsAnnotation(matsOutput)
annot <- prepareAnnotationFromEvents(suppa, mats)
```

```
prepareSRAMetadata    Prepare user-provided files to be loaded into psychomics
```

Description

Prepare user-provided files to be loaded into psychomics

Usage

```
prepareSRAMetadata(file, output = "psychomics_metadata.txt")

prepareJunctionQuant(
  ...,
  output = "psychomics_junctions.txt",
  startOffset = NULL,
  endOffset = NULL
)

prepareGeneQuant(
  ...,
  output = "psychomics_gene_counts.txt",
  strandedness = c("unstranded", "stranded", "stranded (reverse)")
)
```

Arguments

file	Character: path to file
output	Character: path of output file (if NULL, only returns the data without saving it to a file)
...	Character: path of (optionally named) input files (see Examples)
startOffset	Numeric: value to offset start position
endOffset	Numeric: value to offset end position
strandedness	Character: strandedness of RNA-seq protocol; may be one of the following: unstranded, stranded or stranded (reverse)

Value

Prepared file (if output != NULL) and object

See Also

Other functions to load local files: [loadLocalFiles\(\)](#)

Examples

```
## Not run:
prepareJunctionQuant("Control rep1"=junctionFile1,
                    "Control rep2"=junctionFile2,
                    "KD rep1"=junctionFile3,
                    "KD rep2"=junctionFile4)

## End(Not run)
## Not run:
prepareGeneQuant("Control rep1"=geneCountFile1,
                "Control rep2"=geneCountFile2,
                "KD rep1"=geneCountFile3,
                "KD rep2"=geneCountFile4)

## End(Not run)
```

processSurvTerms

Process survival curves terms to calculate survival curves

Description

Process survival curves terms to calculate survival curves

Usage

```
processSurvTerms(
  clinical,
  censoring,
  event,
  timeStart,
  timeStop = NULL,
  group = NULL,
  formulaStr = NULL,
  coxph = FALSE,
  scale = "days",
  followup = "days_to_last_followup",
  survTime = NULL
)
```

Arguments

clinical	Data frame: clinical data
censoring	Character: censor using left, right, interval or interval2
event	Character: name of column containing time of the event of interest


```

    survTime=survTime)
}

```

psychomics *Start graphical interface of psychomics*

Description

Start graphical interface of psychomics

Usage

```
psychomics(..., launch.browser = TRUE, reset = FALSE, testData = FALSE)
```

Arguments

...	Arguments passed on to shiny::runApp
port	The TCP port that the application should listen on. If the port is not specified, and the <code>shiny.port</code> option is set (with <code>options(shiny.port = XX)</code>), then that port will be used. Otherwise, use a random port.
host	The IPv4 address that the application should listen on. Defaults to the <code>shiny.host</code> option, if set, or "127.0.0.1" if not. See Details.
workerId	Can generally be ignored. Exists to help some editions of Shiny Server Pro route requests to the correct process.
quiet	Should Shiny status messages be shown? Defaults to FALSE.
display.mode	The mode in which to display the application. If set to the value "showcase", shows application code and metadata from a DESCRIPTION file in the application directory alongside the application. If set to "normal", displays the application normally. Defaults to "auto", which displays the application in the mode given in its DESCRIPTION file, if any.
test.mode	Should the application be launched in test mode? This is only used for recording or running automated tests. Defaults to the <code>shiny.testmode</code> option, or FALSE if the option is not set.
launch.browser	If true, the system's default web browser will be launched automatically after the app is started. Defaults to true in interactive sessions only. This value of this parameter can also be a function to call with the application's URL.
reset	Boolean: reset Shiny session? Requires package devtools
testData	Boolean: load with test data

Value

NULL (function is only used to modify the Shiny session's state or internal variables)

Examples

```

## Not run:
psychomics()

## End(Not run)

```

quantifySplicing *Quantify alternative splicing events*

Description

Quantify alternative splicing events

Usage

```
quantifySplicing(  
  annotation,  
  junctionQuant,  
  eventType = c("SE", "MXE", "ALE", "AFE", "A3SS", "A5SS"),  
  minReads = 10,  
  genes = NULL  
)
```

Arguments

annotation	List of data frames: annotation for each alternative splicing event type
junctionQuant	Data frame: junction quantification
eventType	Character: splicing event types to quantify
minReads	Integer: discard alternative splicing quantified using a number of reads below this threshold
genes	Character: gene symbols for which the splicing quantification of associated splicing events is performed (by default, splicing events from all genes are selected)

Value

Data frame with the quantification of the alternative splicing events

See Also

Other functions for PSI quantification: [filterPSI\(\)](#), [getSplicingEventTypes\(\)](#), [listSplicingAnnotations\(\)](#), [loadAnnotation\(\)](#), [plotRowStats\(\)](#)

Examples

```
# Calculate PSI for skipped exon (SE) and mutually exclusive (MXE) events  
annot <- readfile("ex_splicing_annotation.RDS")  
junctionQuant <- readfile("ex_junctionQuant.RDS")  
  
quantifySplicing(annot, junctionQuant, eventType=c("SE", "MXE"))
```

queryEnsemblByGene *Query information from Ensembl*

Description

Query information from Ensembl

Usage

```
queryEnsemblByGene(gene, species = NULL, assembly = NULL)
```

```
queryEnsemblByEvent(event, species, assembly)
```

Arguments

gene	Character: gene
species	Character: species (may be NULL for an Ensembl identifier)
assembly	Character: assembly version (may be NULL for an Ensembl identifier)
event	Character: alternative splicing event

Value

Information from Ensembl

See Also

Other functions to retrieve external information: [ensemblToUniprot\(\)](#), [plotProtein\(\)](#), [plotTranscripts\(\)](#)

Examples

```
queryEnsemblByGene("BRCA1", "human", "hg19")
queryEnsemblByGene("ENSG00000139618")
event <- "SE_17_-_41251792_41249306_41249261_41246877_BRCA1"
queryEnsemblByEvent(event, species="human", assembly="hg19")
```

readFile *Load psychomics-specific file*

Description

Load psychomics-specific file

Usage

```
readFile(file)
```

Arguments

file	Character: path to the file
------	-----------------------------

Value

Loaded file

Examples

```
junctionQuant <- readRDS("ex_junctionQuant.RDS")
```

rowMeans

Calculate mean or variance for each row of a matrix

Description

Calculate mean or variance for each row of a matrix

Usage

```
rowMeans(mat, na.rm = FALSE)
```

```
rowVars(mat, na.rm = FALSE)
```

Arguments

mat Matrix

na.rm Boolean: remove missing values (NA)?

Value

Vector of means or variances

Examples

```
df <- rbind("Gene 1"=c(3, 5, 7), "Gene 2"=c(8, 2, 4), "Gene 3"=c(9:11))
rowMeans(df)
rowVars(df)
```

survdiffTerms

Test Survival Curve Differences

Description

Tests if there is a difference between two or more survival curves using the G^p family of tests, or for a single curve against a known alternative.

Usage

```
survdiffTerms(survTerms, ...)
```

Arguments

survTerms survTerms object: survival terms obtained after running processSurvTerms (see examples)

... Arguments passed on to [survival::survdiff](#)

subset expression indicating which subset of the rows of data should be used in the fit. This can be a logical vector (which is replicated to have length equal to the number of observations), a numeric vector indicating which observation numbers are to be included (or excluded if negative), or a character vector of row names to be included. All observations are included by default.

na.action a missing-data filter function. This is applied to the model.frame after any subset argument has been used. Default is options()\$na.action.

rho a scalar parameter that controls the type of test.

timefix process times through the aeqSurv function to eliminate potential roundoff issues.

Value

survfit object. See survfit.object for details. Methods defined for survfit objects are print, plot, lines, and points.

METHOD

This function implements the G-rho family of Harrington and Fleming (1982), with weights on each death of $S(t)^{\rho}$, where $S(t)$ is the Kaplan-Meier estimate of survival. With $\rho = 0$ this is the log-rank or Mantel-Haenszel test, and with $\rho = 1$ it is equivalent to the Peto & Peto modification of the Gehan-Wilcoxon test.

If the right hand side of the formula consists only of an offset term, then a one sample test is done. To cause missing values in the predictors to be treated as a separate group, rather than being omitted, use the factor function with its exclude argument.

References

Harrington, D. P. and Fleming, T. R. (1982). A class of rank test procedures for censored survival data. *Biometrika* **69**, 553-566.

See Also

Other functions to analyse survival: [assignValuePerSubject\(\)](#), [getAttributesTime\(\)](#), [labelBasedOnCutoff\(\)](#), [optimalSurvivalCutoff\(\)](#), [plotSurvivalCurves\(\)](#), [plotSurvivalPvaluesByCutoff\(\)](#), [processSurvTerms\(\)](#), [survfit.survTerms\(\)](#), [testSurvival\(\)](#)

Examples

```
clinical <- read.table(text = "2549 NA ii female
                             840 NA i female
                             NA 1204 iv male
                             NA 383 iv female
                             1293 NA iii male
                             NA 1355 ii male")
names(clinical) <- c("patient.days_to_last_followup",
                   "patient.days_to_death",
```

```

                "patient.stage_event.pathologic_stage",
                "patient.gender")
timeStart <- "days_to_death"
event     <- "days_to_death"
formulaStr <- "patient.stage_event.pathologic_stage + patient.gender"
survTerms <- processSurvTerms(clinical, censoring="right", event, timeStart,
                             formulaStr=formulaStr)
survdiffTerms(survTerms)

```

survfit.survTerms *Create survival curves*

Description

Create survival curves

Usage

```
## S3 method for class 'survTerms'
survfit(survTerms, ...)
```

Arguments

survTerms	survTerms object: survival terms obtained after running processSurvTerms (see examples)
...	Arguments passed on to survival::survdiff
subset	expression indicating which subset of the rows of data should be used in the fit. This can be a logical vector (which is replicated to have length equal to the number of observations), a numeric vector indicating which observation numbers are to be included (or excluded if negative), or a character vector of row names to be included. All observations are included by default.
na.action	a missing-data filter function. This is applied to the model.frame after any subset argument has been used. Default is options()\$na.action.
rho	a scalar parameter that controls the type of test.
timefix	process times through the aeqSurv function to eliminate potential roundoff issues.

Details

A survival curve is based on a tabulation of the number at risk and number of events at each unique death time. When time is a floating point number the definition of "unique" is subject to interpretation. The code uses factor() to define the set. For further details see the documentation for the appropriate method, i.e., ?survfit.formula or ?survfit.coxph.

A survfit object may contain a single curve, a set of curves, or a matrix curves. Predicted curves from a coxph model have one row for each stratum in the Cox model fit and one column for each specified covariate set. Curves from a multi-state model have one row for each stratum and a column for each state, the strata correspond to predictors on the right hand side of the equation. The default printing and plotting order for curves is by column, as with other matrices.

Curves can be subscripted using either a single or double subscript. If the set of curves is a matrix, as in the above, and one of the dimensions is 1 then the code allows a single subscript to be used. (That is, it is not quite as general as using a single subscript for a numeric matrix.)

Value

survfit object. See `survfit.object` for details. Methods defined for `survfit` objects are `print`, `plot`, `lines`, and `points`.

See Also

Other functions to analyse survival: `assignValuePerSubject()`, `getAttributesTime()`, `labelBasedOnCutoff()`, `optimalSurvivalCutoff()`, `plotSurvivalCurves()`, `plotSurvivalPvaluesByCutoff()`, `processSurvTerms()`, `survdiffTerms()`, `testSurvival()`

Examples

```
library("survival")
clinical <- read.table(text = "2549  NA ii  female
                             840  NA i   female
                             NA 1204 iv  male
                             NA  383 iv  female
                             1293  NA iii male
                             NA 1355 ii  male")
names(clinical) <- c("patient.days_to_last_followup",
                    "patient.days_to_death",
                    "patient.stage_event.pathologic_stage",
                    "patient.gender")
timeStart <- "days_to_death"
event <- "days_to_death"
formulaStr <- "patient.stage_event.pathologic_stage + patient.gender"
survTerms <- processSurvTerms(clinical, censoring="right", event, timeStart,
                              formulaStr=formulaStr)

survfit(survTerms)
```

testGroupIndependence *Multiple independence tests between reference groups and list of groups*

Description

Test multiple contingency tables comprised by two groups (one reference group and another containing remaining elements) and provided groups.

Usage

```
testGroupIndependence(ref, groups, elements, pvalueAdjust = "BH")
```

Arguments

ref	List of character: list of groups where each element contains the identifiers of respective elements
groups	List of characters: list of groups where each element contains the identifiers of respective elements
elements	Character: all available elements (if a data frame is given, its rownames will be used)
pvalueAdjust	Character: method used to adjust p-values (see Details)

Details

The following methods for p-value adjustment are supported by using the respective string in the `pvalueAdjust` argument:

- `none`: Do not adjust p-values
- `BH`: Benjamini-Hochberg's method (false discovery rate)
- `BY`: Benjamini-Yekutieli's method (false discovery rate)
- `bonferroni`: Bonferroni correction (family-wise error rate)
- `holm`: Holm's method (family-wise error rate)
- `hochberg`: Hochberg's method (family-wise error rate)
- `hommel`: Hommel's method (family-wise error rate)

Value

`multiGroupIndependenceTest` object, a data frame containing:

<code>attribute</code>	Name of the original groups compared against the reference groups
<code>table</code>	Contingency table used for testing
<code>pvalue</code>	Fisher's exact test's p-value

See Also

[parseCategoricalGroups\(\)](#) and [plotGroupIndependence\(\)](#)

Other functions for data grouping: [createGroupByAttribute\(\)](#), [getGeneList\(\)](#), [getMatchingSamples\(\)](#), [getSubjectFromSample\(\)](#), [groupPerElem\(\)](#), [plotGroupIndependence\(\)](#)

Examples

```
elements <- paste("subjects", 1:10)
ref       <- elements[5:10]
groups   <- list(race=list(asian=elements[1:3],
                          white=elements[4:7],
                          black=elements[8:10]),
                region=list(european=elements[c(4, 5, 9)],
                            african=elements[c(6:8, 10)]))
groupTesting <- testGroupIndependence(ref, groups, elements)
# View(groupTesting)
```

testSurvival

Test the survival difference between groups of subjects

Description

Test the survival difference between groups of subjects

Usage

```
testSurvival(survTerms, ...)
```

Arguments

survTerms survTerms object: survival terms obtained after running processSurvTerms (see examples)

... Arguments passed on to [survival::survdiff](#)

subset expression indicating which subset of the rows of data should be used in the fit. This can be a logical vector (which is replicated to have length equal to the number of observations), a numeric vector indicating which observation numbers are to be included (or excluded if negative), or a character vector of row names to be included. All observations are included by default.

na.action a missing-data filter function. This is applied to the model.frame after any subset argument has been used. Default is options()\$na.action.

rho a scalar parameter that controls the type of test.

timefix process times through the aeqSurv function to eliminate potential roundoff issues.

Value

p-value of the survival difference or NA

Note

Instead of raising errors, returns NA

See Also

Other functions to analyse survival: [assignValuePerSubject\(\)](#), [getAttributesTime\(\)](#), [labelBasedOnCutoff\(\)](#), [optimalSurvivalCutoff\(\)](#), [plotSurvivalCurves\(\)](#), [plotSurvivalPvaluesByCutoff\(\)](#), [processSurvTerms\(\)](#), [survdiffTerms\(\)](#), [survfit.survTerms\(\)](#)

Examples

```
require("survival")
data <- aml
timeStart <- "event"
event <- "event"
followup <- "time"
data$event <- NA
data$event[aml$status == 1] <- aml$time[aml$status == 1]
censoring <- "right"
formulaStr <- "x"
survTerms <- processSurvTerms(data, censoring=censoring, event=event,
                             timeStart=timeStart, followup=followup,
                             formulaStr=formulaStr)

testSurvival(survTerms)
```

[.GEandAScorrelation *Display results of correlation analyses*

Description

Plot, print and display as table the results of gene expression and alternative splicing

Usage

```
## S3 method for class 'GEandAScorrelation'
x[genes = NULL, ASevents = NULL]
```

```
## S3 method for class 'GEandAScorrelation'
plot(
  x,
  autoZoom = FALSE,
  loessSmooth = TRUE,
  loessFamily = c("gaussian", "symmetric"),
  colour = "black",
  alpha = 0.2,
  size = 1.5,
  loessColour = "red",
  loessAlpha = 1,
  loessWidth = 0.5,
  fontSize = 12,
  ...,
  colourGroups = NULL,
  legend = FALSE,
  showAllData = TRUE,
  density = FALSE,
  densityColour = "blue",
  densityWidth = 0.5
)
```

```
## S3 method for class 'GEandAScorrelation'
print(x, ...)
```

```
## S3 method for class 'GEandAScorrelation'
as.table(x, pvalueAdjust = "BH", ...)
```

Arguments

x	GEandAScorrelation object obtained after running correlateGEandAS()
genes	Character: genes
ASevents	Character: AS events
autoZoom	Boolean: automatically set the range of PSI values based on available data? If FALSE, the axis relative to PSI values will range from 0 to 1
loessSmooth	Boolean: plot a smooth curve computed by <code>stats::loess.smooth?</code>
loessFamily	Character: if gaussian, loess fitting is by least-squares, and if symmetric, a re-descending M estimator is used

colour	Character: points' colour
alpha	Numeric: points' alpha
size	Numeric: points' size
loessColour	Character: loess line's colour
loessAlpha	Numeric: loess line's opacity
loessWidth	Numeric: loess line's width
fontSize	Numeric: plot font size
...	Arguments passed on to <code>stats::loess.smooth</code> span smoothness parameter for loess. degree degree of local polynomial used. evaluation number of points at which to evaluate the smooth curve.
colourGroups	List of characters: sample colouring by group
legend	Boolean: show legend for sample colouring?
showAllData	Boolean: show data outside selected groups as a single group (coloured based on the colour argument)
density	Boolean: contour plot of a density estimate
densityColour	Character: line colour of contours
densityWidth	Numeric: line width of contours
pvalueAdjust	Character: method used to adjust p-values (see Details)

Details

The following methods for p-value adjustment are supported by using the respective string in the `pvalueAdjust` argument:

- none: do not adjust p-values
- BH: Benjamini-Hochberg's method (false discovery rate)
- BY: Benjamini-Yekutieli's method (false discovery rate)
- bonferroni: Bonferroni correction (family-wise error rate)
- holm: Holm's method (family-wise error rate)
- hochberg: Hochberg's method (family-wise error rate)
- hommel: Hommel's method (family-wise error rate)

Value

Plots, summary tables or results of correlation analyses

See Also

Other functions to correlate gene expression and alternative splicing: [correlateGEandAS\(\)](#)

Other functions to correlate gene expression and alternative splicing: [correlateGEandAS\(\)](#)

Examples

```
annot <- readfile("ex_splicing_annotation.RDS")
junctionQuant <- readfile("ex_junctionQuant.RDS")
psi <- quantifySplicing(annot, junctionQuant, eventType=c("SE", "MXE"))

geneExpr <- readfile("ex_gene_expression.RDS")
corr <- correlateGEandAS(geneExpr, psi, "ALDOA")

# Quick display of the correlation results per splicing event and gene
print(corr)

# Table summarising the correlation analysis results
as.table(corr)

# Correlation analysis plots
colourGroups <- list(Normal=paste("Normal", 1:3),
                    Tumour=paste("Cancer", 1:3))
attr(colourGroups, "Colour") <- c(Normal="#00C65A", Tumour="#EEE273")
plot(corr, colourGroups=colourGroups, alpha=1)
```

Index

- [.GEandAScorrelation, 8, 63
- approx, 37
- as.table.GEandAScorrelation
([.GEandAScorrelation), 63
- assignValuePerPatient
(assignValuePerSubject), 4
- assignValuePerSubject, 4, 14, 22, 30, 47,
48, 53, 58, 60, 62
- bw.nrd, 37
- calculateLoadingsContribution, 5, 36, 42,
49
- colSums, EList-method, 6
- convertGeneIdentifiers, 6, 11, 28, 39, 44
- cor.test, 7
- correlateGEandAS, 7, 63, 64
- createGroupByAttribute, 8, 15, 17, 20, 21,
40, 61
- diffAnalyses, 9, 38
- EList-class, 6
- ensemblToUniprot, 10, 43, 49, 56
- fft, 37
- filterGeneExpr, 7, 11, 28, 39, 44
- filterGroups, 12
- filterPSI, 13, 19, 23, 24, 44, 55
- getAttributesTime, 5, 14, 22, 30, 47, 48, 53,
58, 60, 62
- getDownloadsFolder, 15, 16, 20, 22, 24, 26,
27, 34
- getFirebrowseCohorts
(getTCGAdataTypes), 20
- getFirebrowseDataTypes
(getTCGAdataTypes), 20
- getFirebrowseDates (getTCGAdataTypes),
20
- getGenelist, 8, 15, 17, 20, 21, 40, 61
- getGenesFromSplicingEvents
(getSplicingEventFromGenes), 18
- getGtexDataTypes, 15, 16, 16, 24
- getGtexTissues, 15, 16, 16, 24
- getMatchingSamples, 8, 15, 17, 20, 21, 40, 61
- getPatientFromSample
(getSubjectFromSample), 19
- getSampleFromPatient
(getMatchingSamples), 17
- getSampleFromSubject
(getMatchingSamples), 17
- getSplicingEventFromGenes, 18
- getSplicingEventTypes, 13, 19, 23, 24, 44,
55
- getSubjectFromSample, 8, 15, 17, 19, 21, 40,
61
- getTCGAcohorts (getTCGAdataTypes), 20
- getTCGAdataTypes, 15, 20, 22, 27, 34
- getTCGAdates (getTCGAdataTypes), 20
- getValuePerPatient
(assignValuePerSubject), 4
- getValuePerSubject
(assignValuePerSubject), 4
- groupPerElem, 8, 15, 17, 20, 21, 40, 61
- isFirebrowseUp, 15, 20, 21, 27, 34
- labelBasedOnCutoff, 5, 14, 22, 30, 47, 48,
53, 58, 60, 62
- listSplicingAnnotations, 13, 19, 23, 24,
44, 55
- loadAnnotation, 13, 19, 23, 23, 44, 55
- loadFirebrowseData (loadTCGAdata), 26
- loadGtexData, 15, 16, 24
- loadLocalFiles, 25, 52
- loadSRaproject, 15, 26
- loadTCGAdata, 15, 20, 22, 26, 34
- model.frame, 35, 36
- normaliseGeneExpression, 7, 11, 28, 39, 44
- optimalSurvivalCutoff, 5, 14, 22, 29, 47,
48, 53, 58, 60, 62
- pairsD3::pairsD3, 40
- parseCategoricalGroups, 30, 40, 61

- parseMatsAnnotation
 - (parseSuppaAnnotation), 31
- parseMisoAnnotation
 - (parseSuppaAnnotation), 31
- parseSampleGroups
 - (parseTCGAsampleTypes), 33
- parseSplicingEvent, 31
- parseSuppaAnnotation, 31, 50
- parseTCGAsampleInfo
 - (parseTCGAsampleTypes), 33
- parseTcgaSampleInfo
 - (parseTCGAsampleTypes), 33
- parseTCGAsampleTypes, 15, 20, 22, 27, 33
- parseVastToolsAnnotation
 - (parseSuppaAnnotation), 31
- performICA, 34, 40, 41
- performPCA, 6, 35, 42, 49
- plot.GEandAScorrelation
 - ([.GEandAScorrelation]), 63
- plotCorrelation ([.GEandAScorrelation), 63
- plotDistribution, 10, 36
- plotGeneExprPerSample, 7, 11, 28, 38, 44
- plotGroupIndependence, 8, 15, 17, 20, 21, 30, 39, 61
- plotICA, 35, 40
- plotPCA, 6, 36, 41, 49
- plotProtein, 10, 42, 49, 56
- plotRowStats, 7, 11, 13, 19, 23, 24, 28, 39, 43, 55
- plotSplicingEvent, 44
- plotSurvivalCurves, 5, 14, 22, 30, 46, 48, 53, 58, 60, 62
- plotSurvivalPvaluesByCutoff, 5, 14, 22, 30, 47, 47, 53, 58, 60, 62
- plotTranscripts, 10, 43, 48, 56
- plotVariance, 6, 36, 42, 49
- prepareAnnotationFromEvents, 33, 50
- prepareGeneQuant (prepareSRAMetadata), 51
- prepareJunctionQuant
 - (prepareSRAMetadata), 51
- prepareSRAMetadata, 25, 51
- print.GEandAScorrelation
 - ([.GEandAScorrelation]), 63
- processSurvTerms, 5, 14, 22, 30, 47, 48, 52, 58, 60, 62
- psychomics, 54
- quantifySplicing, 13, 19, 23, 24, 44, 55
- queryEnsemblByEvent
 - (queryEnsemblByGene), 56
- queryEnsemblByGene, 10, 43, 49, 56
- queryFirebrowseData, 27
- readFile, 56
- recount_abstract, 26
- renderBoxplot, 39
- rowMeans, 57
- rowVars (rowMeans), 57
- scale, 35, 36
- shiny::runApp, 54
- stats::density.default, 37
- stats::loess.smooth, 64
- survdiffTerms, 5, 14, 22, 30, 47, 48, 53, 57, 60, 62
- survfit.survTerms, 5, 14, 22, 30, 47, 48, 53, 58, 59, 62
- survival::survdiff, 58, 59, 62
- testGroupIndependence, 8, 15, 17, 20, 21, 30, 40, 60
- testSurvival, 5, 14, 22, 30, 47, 48, 53, 58, 60, 61
- voom, 28