

# Package ‘tximport’

April 15, 2020

**Version** 1.14.2

**Title** Import and summarize transcript-level estimates for transcript- and gene-level analysis

**Description** Imports transcript-level abundance, estimated counts and transcript lengths, and summarizes into matrices for use with downstream gene-level analysis packages. Average transcript length, weighted by sample-specific transcript abundance estimates, is provided as a matrix which can be used as an offset for different expression of gene-level counts.

**Author** Michael Love [cre,aut], Charlotte Soneson [aut], Mark Robinson [aut], Rob Patro [ctb], Andrew Parker Morgan [ctb], Ryan C. Thompson [ctb], Matt Shirley [ctb], Avi Srivastava [ctb]

**Maintainer** Michael Love <michaelisaiahlove@gmail.com>

**License** GPL (>=2)

**VignetteBuilder** knitr

**Imports** utils, stats, methods

**Suggests** knitr, rmarkdown, testthat, tximportData, TxDb.Hsapiens.UCSC.hg19.knownGene, readr (>= 0.2.2), limma, edgeR, csaw, DESeq2 (>= 1.11.6), rhdf5, jsonlite, matrixStats, Matrix, fishpond

**URL** <https://github.com/mikelove/tximport>

**biocViews** DataImport, Preprocessing, RNASeq, Transcriptomics, Transcription, GeneExpression, ImmunoOncology

**RoxygenNote** 6.1.1

**NeedsCompilation** no

**Encoding** UTF-8

**git\_url** <https://git.bioconductor.org/packages/tximport>

**git\_branch** RELEASE\_3\_10

**git\_last\_commit** ac0c64b

**git\_last\_commit\_date** 2020-03-22

**Date/Publication** 2020-04-14

## R topics documented:

makeCountsFromAbundance . . . . .	2
summarizeToGene . . . . .	2
tximport . . . . .	3

<b>Index</b>	<b>7</b>
--------------	----------

makeCountsFromAbundance

*Low-level function to make counts from abundance using matrices*

### Description

Simple low-level function used within [tximport](#) to generate scaledTPM or lengthScaledTPM counts, taking as input the original counts, abundance and length matrices. NOTE: This is a low-level function exported in case it is needed for some reason, but the recommended way to generate counts-from-abundance is using [tximport](#) with the countsFromAbundance argument.

### Usage

```
makeCountsFromAbundance(countsMat, abundanceMat, lengthMat,
  countsFromAbundance = c("scaledTPM", "lengthScaledTPM"))
```

### Arguments

countsMat        a matrix of original counts  
 abundanceMat    a matrix of abundances (typically TPM)  
 lengthMat       a matrix of effective lengths  
 countsFromAbundance  
                   the desired type of count-from-abundance output

### Value

a matrix of count-scale data generated from abundances. for details on the calculation see [tximport](#).

summarizeToGene

*Summarize estimated quantities to gene-level*

### Description

Summarizes abundances, counts, lengths, (and inferential replicates or variance) from transcript- to gene-level.

### Usage

```
summarizeToGene(object, ...)
```

```
## S4 method for signature 'list'
summarizeToGene(object, tx2gene, varReduce = FALSE,
  ignoreTxVersion = FALSE, ignoreAfterBar = FALSE,
  countsFromAbundance = c("no", "scaledTPM", "lengthScaledTPM"))
```

**Arguments**

object	the list of matrices of transcript-level abundances, counts, lengths produced by <a href="#">tximport</a> , with a countsFromAbundance element that tells how the counts were generated.
...	additional arguments, ignored
tx2gene	see <a href="#">tximport</a>
varReduce	see <a href="#">tximport</a>
ignoreTxVersion	see <a href="#">tximport</a>
ignoreAfterBar	see <a href="#">tximport</a>
countsFromAbundance	see <a href="#">tximport</a>

**Value**

a list of matrices of gene-level abundances, counts, lengths, (and inferential replicates or variance if inferential replicates are present).

**See Also**

[tximport](#)

---

tximport	<i>Import transcript-level abundances and counts for transcript- and gene-level analysis packages</i>
----------	---

---

**Description**

tximport imports transcript-level estimates from various external software and optionally summarizes abundances, counts, and transcript lengths to the gene-level (default) or outputs transcript-level matrices (see txOut argument).

**Usage**

```
tximport(files, type = c("none", "salmon", "sailfish", "alevin",
  "kallisto", "rsem", "stringtie"), txIn = TRUE, txOut = FALSE,
  countsFromAbundance = c("no", "scaledTPM", "lengthScaledTPM",
  "dtuScaledTPM"), tx2gene = NULL, varReduce = FALSE,
  dropInfReps = FALSE, infRepStat = NULL, ignoreTxVersion = FALSE,
  ignoreAfterBar = FALSE, geneIdCol, txIdCol, abundanceCol, countsCol,
  lengthCol, importer = NULL, existenceOptional = FALSE,
  sparse = FALSE, sparseThreshold = 1, readLength = 75,
  forceSlow = FALSE)
```

**Arguments**

files	a character vector of filenames for the transcript-level abundances
type	character, the type of software used to generate the abundances. Options are "salmon", "sailfish", "alevin", "kallisto", "rsem", "stringtie", or "none". This argument is used to autofill the arguments below (geneIdCol, etc.) "none" means that the user will specify these columns.
txIn	logical, whether the incoming files are transcript level (default TRUE)
txOut	logical, whether the function should just output transcript-level (default FALSE)
countsFromAbundance	<p>character, either "no" (default), "scaledTPM", "lengthScaledTPM", or "dtuScaledTPM". Whether to generate estimated counts using abundance estimates:</p> <ul style="list-style-type: none"> <li>• scaled up to library size (scaledTPM),</li> <li>• scaled using the average transcript length over samples and then the library size (lengthScaledTPM), or</li> <li>• scaled using the median transcript length among isoforms of a gene, and then the library size (dtuScaledTPM).</li> </ul> <p>dtuScaledTPM is designed for DTU analysis in combination with txOut=TRUE, and it requires specifying a tx2gene data.frame. dtuScaledTPM works such that within a gene, values from all samples and all transcripts get scaled by the same fixed median transcript length. If using scaledTPM, lengthScaledTPM, or geneLengthScaledTPM, the counts are no longer correlated across samples with transcript length, and so the length offset matrix should not be used.</p>
tx2gene	a two-column data.frame linking transcript id (column 1) to gene id (column 2). the column names are not relevant, but this column order must be used. this argument is required for gene-level summarization for methods that provides transcript-level estimates only (kallisto, Salmon, Sailfish)
varReduce	whether to reduce per-sample inferential replicates information into a matrix of sample variances variance (default FALSE). alevin computes inferential variance by default for bootstrap inferential replicates, so this argument is ignored/not necessary
dropInfReps	whether to skip reading in inferential replicates (default FALSE). For alevin, tximport will still read in the inferential variance matrix if it exists
infRepStat	a function to re-compute counts and abundances from the inferential replicates, e.g. matrixStats::rowMedians to re-compute counts as the median of the inferential replicates. The order of operations is: first counts are re-computed, then abundances are re-computed. Following this, if countsFromAbundance is not "no", tximport will again re-compute counts from the re-computed abundances. infRepStat should operate on rows of a matrix. (default is NULL)
ignoreTxVersion	logical, whether to split the tx id on the '.' character to remove version information to facilitate matching with the tx id in tx2gene (default FALSE)
ignoreAfterBar	logical, whether to split the tx id on the ' ' character to facilitate matching with the tx id in tx2gene (default FALSE)
geneIdCol	name of column with gene id. if missing, the tx2gene argument can be used
txIdCol	name of column with tx id
abundanceCol	name of column with abundances (e.g. TPM or FPKM)
countsCol	name of column with estimated counts

lengthCol	name of column with feature length information
importer	a function used to read in the files
existenceOptional	logical, should tximport not check if files exist before attempting import (default FALSE, meaning files must exist according to <code>file.exists</code> )
sparse	logical, whether to try to import data sparsely (default is FALSE). Initial implementation for <code>txOut=TRUE</code> , <code>countsFromAbundance="no"</code> or <code>"scaledTPM"</code> , no inferential replicates. Only counts matrix is returned (and abundance matrix if using <code>"scaledTPM"</code> )
sparseThreshold	the minimum threshold for including a count as a non-zero count during sparse import (default is 1)
readLength	numeric, the read length used to calculate counts from StringTie's output of coverage. Default value (from StringTie) is 75. The formula used to calculate counts is: $\text{cov} * \text{transcript length} / \text{read length}$
forceSlow	logical, argument used for testing. Will force the use of the slower R code for importing alevin, even if fishpond library is installed. Default is FALSE

## Details

tximport will also load in information about inferential replicates – a list of matrices of the Gibbs samples from the posterior, or bootstrap replicates, per sample – if these data are available in the expected locations relative to the files. The inferential replicates, stored in `infReps` in the output list, are on estimated counts, and therefore follow counts in the output list. By setting `varReduce=TRUE`, the inferential replicate matrices will be replaced by a single matrix with the sample variance per transcript/gene and per sample.

While tximport summarizes to the gene-level by default, the user can also perform the import and summarization steps manually, by specifying `txOut=TRUE` and then using the function `summarizeToGene`. Note however that this is equivalent to tximport with `txOut=FALSE` (the default).

Solutions to the error "tximport failed at summarizing to the gene-level":

1. provide a `tx2gene` data.frame linking transcripts to genes (more below)
2. avoid gene-level summarization by specifying `txOut=TRUE`
3. set `geneIdCol` to an appropriate column in the files

See `vignette('tximport')` for example code for generating a `tx2gene` data.frame from a `TxDb` object. Note that the keys and select functions used to create the `tx2gene` object are documented in the man page for [AnnotationDb-class](#) objects in the `AnnotationDbi` package (`TxDb` inherits from `AnnotationDb`). For further details on generating `TxDb` objects from various inputs see `vignette('GenomicFeatures')` from the `GenomicFeatures` package.

For `type="alevin"` all arguments other than `files`, `dropInfReps`, and `forceSlow` are ignored, and `files` should point to a single `quants_mat.gz` file, in the directory structure created by the alevin software (e.g. do not move the file or delete the other important files). Note that importing alevin quantifications will be much faster by first installing the fishpond package, which contains a C++ importer for alevin's EDS format. For alevin, tximport is importing the gene-by-cell matrix of counts, as `txi$counts`, and effective lengths are not estimated. `txi$variance` may also be imported if inferential replicates were used, as well as inferential replicates if these were output by alevin. Length correction should not be applied to datasets where there is not an expected correlation of counts and feature length.

**Value**

a simple list containing matrices: abundance, counts, length. Another list element 'countsFromAbundance' carries through the character argument used in the tximport call. The length matrix contains the average transcript length for each gene which can be used as an offset for gene-level analysis. If detected, and txOut=TRUE, inferential replicates for each sample will be imported and stored as a list of matrices, itself an element infReps in the returned list. An exception is alevin, in which the infReps are a list of bootstrap replicate matrices, where each matrix has genes as rows and cells as columns. If varReduce=TRUE the inferential replicates will be summarized according to the sample variance, and stored as a matrix variance. alevin already computes the variance of the bootstrap inferential replicates and so this is imported without needing to specify varReduce=TRUE (note that alevin uses the 1/N variance estimator, so not the same as var).

**References**

Charlotte Sonesson, Michael I. Love, Mark D. Robinson (2015): Differential analyses for RNA-seq: transcript-level estimates improve gene-level inferences. F1000Research. <http://dx.doi.org/10.12688/f1000research.7563.1>

**Examples**

```
# load data for demonstrating tximport
# note that the vignette shows more examples
# including how to read in files quickly using the readr package

library(tximportData)
dir <- system.file("extdata", package="tximportData")
samples <- read.table(file.path(dir,"samples.txt"), header=TRUE)
files <- file.path(dir,"salmon", samples$run, "quant.sf.gz")
names(files) <- paste0("sample",1:6)

# tx2gene links transcript IDs to gene IDs for summarization
tx2gene <- read.csv(file.path(dir, "tx2gene.gencode.v27.csv"))

txi <- tximport(files, type="salmon", tx2gene=tx2gene)
```

# Index

AnnotationDb-class, [5](#)

makeCountsFromAbundance, [2](#)

summarizeToGene, [2](#)

summarizeToGene, list-method  
(summarizeToGene), [2](#)

tximport, [2](#), [3](#), [3](#)