

# BSgenome.Ptroglydytes.UCSC.panTro3

August 27, 2020

---

BSgenome.Ptroglydytes.UCSC.panTro3

*Full genome sequences for Pan troglodytes (UCSC version panTro3)*

---

## Description

Full genome sequences for Pan troglodytes (Chimp) as provided by UCSC (panTro3, Oct. 2010) and stored in Biostrings objects.

## Note

This BSgenome data package was made from the following source data files:

panTro3.fa.gz from <http://hgdownload.cse.ucsc.edu/goldenPath/panTro3/bigZips/>

See [?BSgenomeForge](#) and the BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

## Author(s)

The Bioconductor Dev Team

## See Also

- [BSgenome](#) objects and the [available.genomes](#) function in the **BSgenome** software package.
- [DNAString](#) objects in the **Biostrings** package.
- The BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

## Examples

```
BSgenome.Ptroglydytes.UCSC.panTro3
genome <- BSgenome.Ptroglydytes.UCSC.panTro3
seqlengths(genome)
genome$chr1 # same as genome[["chr1"]]
```

```
## -----
## Upstream sequences
```

```
## -----  
## Starting with BioC 3.0, the upstream1000, upstream2000, and  
## upstream5000 sequences for panTro3 are not included in the BSgenome  
## data package anymore. However they can easily be extracted from the  
## full genome sequences with something like:  
  
library(GenomicFeatures)  
txdb <- makeTranscriptDbFromUCSC("panTro3", "refGene")  
gn <- sort(genes(txdb))  
up1000 <- flank(gn, width=1000)  
up1000seqs <- getSeq(genome, up1000)  
  
## IMPORTANT: Make sure you use a TxDb package (or TranscriptDb object),  
## that contains a gene model based on the exact same reference genome  
## as the BSgenome object you pass to getSeq(). Note that you can make  
## your own custom TranscriptDb object from various annotation resources.  
## See the makeTranscriptDbFromUCSC(), makeTranscriptDbFromBiomart(),  
## and makeTranscriptDbFromGFF() functions in the GenomicFeatures  
## package.  
  
## -----  
## Genome-wide motif searching  
## -----  
## See the GenomeSearching vignette in the BSgenome software  
## package for some examples of genome-wide motif searching using  
## Biostrings and the BSgenome data packages:  
if (interactive())  
  vignette("GenomeSearching", package="BSgenome")
```

# Index

## \* **data**

BSgenome.Ptroglydytes.UCSC.panTro3,  
[1](#)

## \* **package**

BSgenome.Ptroglydytes.UCSC.panTro3,  
[1](#)

available.genomes, [1](#)

BSgenome, [1](#)

BSgenome.Ptroglydytes.UCSC.panTro3, [1](#)

BSgenome.Ptroglydytes.UCSC.panTro3-package  
(BSgenome.Ptroglydytes.UCSC.panTro3),  
[1](#)

BSgenomeForge, [1](#)

DNAStrng, [1](#)

Ptroglydytes

(BSgenome.Ptroglydytes.UCSC.panTro3),  
[1](#)