

Package ‘ReQON’

March 30, 2021

Type Package

Title Recalibrating Quality Of Nucleotides

Version 1.36.0

Date 2020-09-01

Author Christopher Cabanski, Keary Cavin, Chris Bizon

Maintainer Christopher Cabanski <cabansk@gmail.com>

Description Algorithm for recalibrating the base quality scores
for aligned sequencing data in BAM format.

License GPL-2

biocViews Sequencing, HighThroughputSequencing, Preprocessing,
QualityControl

Imports rJava, graphics, stats, utils, grDevices

Depends R (>= 3.0.2), Rsamtools, seqbias

Suggests BiocStyle

SystemRequirements Java version >= 1.6

git_url <https://git.bioconductor.org/packages/ReQON>

git_branch RELEASE_3_12

git_last_commit 1ab211a

git_last_commit_date 2020-10-27

Date/Publication 2021-03-29

R topics documented:

FWSEplot	2
QualFreqPlot	3
ReadPosErrorPlot	4
ReQON	5
Index	8

FWSEplot

*Plot reported vs. empirical quality.***Description**

Plots reported vs. empirical quality scores. Also calculates and outputs Frequency-Weighted Squared Error (FWSE) and reports FWSE on the plot. The points are shaded according to the relative frequency of bases assigned that quality score.

Usage

```
FWSEplot(ErrRates, QualFreq, FWSE_out = TRUE, col = "blue", max_freq = 0.25,
         lim = c(0, length(QualFreq) - 1), collegend = TRUE, xlabel = "Reported Quality",
         ylabel = "Empirical Quality", main_title = "Reported vs. Empirical Quality")
```

Arguments

ErrRates	vector of empirical error rates on the Phred scale.
QualFreq	vector of relative frequencies of quality scores.
FWSE_out	option to output FWSE and report FWSE on the plot. Default = TRUE.
col	color of plotted points. Currently allows for only "blue" and "red". Default = "blue".
max_freq	Maximum value for color scale, where all quality scores with relative frequency greater than this value are shaded the darkest color. Because the colors are evenly distributed between 0 and max_freq, changing this maximum value may change the color of many points. Default = 0.25.
lim	common axis limits for both the x-axis and y-axis. Default = c(0, length(QualFreq) - 1).
collegend	include color legend. Default = TRUE.
xlabel	x-axis label. Default = "Reported Quality".
ylabel	y-axis label. Default = "Empirical Quality".
main_title	title. Default = "Reported vs. Empirical Quality".

Details

FWSEplot plots the reported quality score against the empirical quality score and reports FWSE. If the quality scores accurately reflect the probability of a sequencing error, then the points should fall close to the 45-degree line and FWSE should be close to zero. If the input vectors are \$ErrRatesBefore and \$QualFreqBefore from the ReQON output, this function will create the bottom left diagnostic plot that is output from ReQON. Similarly, if the input vectors are \$ErrRatesAfter and \$QualFreqAfter from ReQON output, then the bottom right diagnostic plot is created.

For more details and interpretation, see the vignette by: `browseVignettes("ReQON")`.

Value

In addition to the plot, FWSEplot calculates and outputs Frequency-Weighted Squared Error (FWSE), a measure of how close the points lie to the 45-degree line.

Author(s)

Christopher Cabanski <ccabansk@genome.wustl.edu>

Examples

```
## Create relative frequency example data
require( stats )
after <- dnorm( c( 0:40 ), mean = 30, sd = 8 )
  after <- after / sum( after )
err_rate <- c( 0:40 ) + rnorm( 41, mean = 0, sd = 5)
  err_rate[ which( err_rate < 0 ) ] <- (-1) * err_rate[ which( err_rate < 0 ) ]
  ## to guarantee that all values are positive

## plot and calculate FWSE
FWSEplot( err_rate, after, col = "red" )
```

QualFreqPlot

Plot frequency distributions of quality scores.

Description

Plots the relative frequency distribution of quality scores before and after recalibration.

Usage

```
QualFreqPlot(QualFreqBefore, QualFreqAfter, before_col = "blue",
  after_col = "red", inc_legend = TRUE, xlabel = "Quality Score",
  ylabel = "Relative Frequency",
  main_title = "Frequency Distributions of Quality Scores")
```

Arguments

QualFreqBefore vector of relative frequencies of quality scores before recalibration. The first element in the vector corresponds to a quality score of zero.

QualFreqAfter vector of relative frequencies of quality scores after recalibration. The first element in the vector corresponds to a quality score of zero.

before_col color of line plotting the frequency before recalibration. Default = "blue".

after_col color of line plotting the frequency after recalibration. Default = "red".

inc_legend option for including a legend. Default = TRUE.

xlabel x-axis label. Default = "Quality Score".

ylabel y-axis label. Default = "Relative Frequency".

main_title title. Default = "Frequency Distributions of Quality Scores".

Details

QualFreqPlot plots the relative frequency distribution of quality scores before and after recalibration. If the input vectors are \$QualFreqBefore and \$QualFreqAfter from ReQON output, this function will create the top right diagnostic plot that is output from ReQON.

For more details and interpretation, see the vignette by: `browseVignettes("ReQON")`.

Author(s)

Christopher Cabanski <ccabansk@genome.wustl.edu>

Examples

```
## Create data of frequencies
require( stats )
before <- dpois( c( 0:40 ), 40 )
before <- before / sum( before )
after <- dnorm( c( 0:40 ), mean = 30, sd = 8 )
after <- after / sum( after )

## plot
QualFreqPlot( before, after )
```

ReadPosErrorPlot *Plot distribution of errors by read position.*

Description

Plots the number of sequencing errors by read position.

Usage

```
ReadPosErrorPlot(ReadPosErrors, startpos = 1, error_col = "blue", thresh = 1.5,
  thresh_col = "cyan", xlabel = "Read Position", ylabel = "# Errors",
  main_title = "Distribution of Errors by Read Position")
```

Arguments

ReadPosErrors	vector of sequencing error counts by read position.
startpos	Starting read position, typically 0 or 1. Default = 1.
error_col	color of line plotting the errors counts. Default = "blue".
thresh	Threshold for identifying read positions with large numbers of errors, plotted as a horizontal dashed line. Threshold is set as "thresh * (average number of errors per read position)". Default = 1.5.
thresh_col	color of threshold line. Default = "cyan".
xlabel	x-axis label. Default = "Read Position".
ylabel	y-axis label. Default = "# Errors".
main_title	title. Default = "Distribution of Errors by Read Position".

Details

ReadPosErrorPlot plots the distribution of sequencing errors by read position. If the input vector is \$ReadPosErrors from ReQON output, this function will create the top left diagnostic plot that is output from ReQON.

For more details and interpretation, see the vignette by: `browseVignettes("ReQON")`.

Author(s)

Christopher Cabanski <ccabansk@genome.wustl.edu>

Examples

```
## Create data of error counts
x <- c( 1:30 )
err <- x^2 + ( 30 - x )^1.6 + rnorm(30, 0, 100)

## plot errors by read position
ReadPosErrorPlot( err )
```

 ReQON

Recalibrating Quality Of Nucleotides

Description

Recalibrate the nucleotide quality scores of either single-end or paired-end next-generation sequencing data that has been aligned.

Usage

```
ReQON(in_bam, out_bam, region, max_train = -1, SNP = "",
      RefSeq = "", nerr = 2, nraf = 0.05, plotname = "", temp_files = 0)
```

Arguments

in_bam	file name of sorted BAM file of single-end or paired-end aligned sequencing data. The corresponding index file (.bai file) must be located in the same directory.
out_bam	file name for output BAM file with original quality scores replaced with recalibrated quality scores.
region	training region for recalibration, as “chromosome:start-end”. Cannot span more than one chromosome. See note. Example: "chr1:1-10000".
max_train	maximum number of nucleotides to include in training region. Useful if you want to train on e.g. the first 5 million bases of chromosome 10. Default = -1 (use all nucleotides from training region).
SNP	file of SNP locations to remove from training set before recalibration. Text or Rdata file (with variable name “snp”) with no header and two columns: [1] chromosome, [2] position. See note. Default: do not remove any nucleotides from training set.
RefSeq	file of reference sequence for training set to identify sequencing errors (i.e. nucleotide is error if it does not match RefSeq). Text or Rdata file (with variable name “ref”) with no header and three columns: [1] chromosome, [2] position, [3] reference nucleotide (A,C,G,T). See note. Default: errors are nucleotides not matching major allele(s) for coverage > 2, removing all nucleotides at positions with coverage of 2 or less.

nerr	maximum number of errors tolerated at a genomic position. Positions with more than “nerr” errors may likely be true variants, so bases from these positions are removed from the training set. Default = 2.
nraf	maximum non-reference allele frequency at a genomic position that is allowed. Positions with non-reference allele frequency greater than “nraf” are removed from the training set for the same reason as above. Default = 0.05.
plotname	file name for saving recalibration plots in pdf. If not specified, plots will not be produced.
temp_files	option for keeping temporary files. 0: (default) remove all temporary files. 1: keep temporary files in working directory.

Details

ReQON uses logistic regression to recalibrate the nucleotide quality scores of a sorted BAM file. The BAM file contains either single-end or paired-end next-generation sequencing data that has been aligned using any alignment tool. For help with sorting and indexing BAM files in R, see Rsamtools.

ReQON also has the option to output diagnostic plots which show the effectiveness of the recalibration on the training set.

For a detailed description of usage, output and images, see the vignette by: `browseVignettes("ReQON")`.

ReQON utilizes various java tools provided by Picard. For more information on Picard, see <http://picard.sourceforge.net>

Value

ReQON returns a BAM file, replacing the original quality scores with the recalibrated quality scores in the QUAL field.

ReQON also outputs a data object of diagnostic data from the training set that is plotted in the output diagnostic plots. The object variables are:

\$ReadPosErrors	vector of error counts by read position.
\$QualFreqBefore	relative frequency of quality scores before recalibration. The first element in the vector corresponds to a quality score of zero.
\$QualFreqAfter	relative frequency of quality scores after recalibration. The first element in the vector corresponds to a quality score of zero.
\$ErrRatesBefore	vector of empirical error rates before recalibration, reported on the Phred scale. The first element in the vector corresponds to a quality score of zero.
\$ErrRatesAfter	vector of empirical error rates after recalibration, reported on the Phred scale. The first element in the vector corresponds to a quality score of zero.
\$FWSE	vector of Frequency-Weighted Squared Error (FWSE) values. The first element is FWSE before recalibration and the second element is FWSE after recalibration.
\$FlagPos	vector of high-error read positions (above dashed cyan line in top left output plot). Each of these positions receives an indicator variable in the model.
\$coeff	vector of regression coefficient obtained from training set used to recalibrate entire BAM file.

Note

Be aware of how the chromosomes are referenced when specifying the training region. For example, one BAM file may require specifying “10:1-2000” while another may need “chr10:1-2000”.

If providing SNP or RefSeq files, computations will speed up if your file only covers the positions in the training region. For example, if you set region = “chr10:1-2000”, then we recommend only having rows corresponding to chr10:1-2000 in the RefSeq/SNP file.

Author(s)

Christopher Cabanski <ccabansk@genome.wustl.edu>

Examples

```
## Read in sample data from seqbias package
library( ReQON )
library( seqbias )
library( Rsamtools )
ref_fn <- system.file( "extra/example.fa", package = "seqbias" )
ref_f <- FaFile( ref_fn )
open.FaFile( ref_f )
reads_fn <- system.file( "extra/example.bam", package = "seqbias" )

## Set up file of reference sequence
seqs <- scanFa( ref_f )
len <- length( seqs[[1]] )
ref <- matrix( nrow = len, ncol = 3 )
ref[,1] <- rep( "seq1", len )
ref[,2] <- c( 1:len )
str <- toString( subseq( seqs[[1]], 1, len ) )
s <- strsplit( str, NULL )
ref[,3] <- s[[1]]
write.table( ref, file = "ref_seq.txt", sep = "\t", quote = FALSE,
  row.names = FALSE, col.names = FALSE )

## Recalibrate File
sorted <- sortBam( reads_fn, tempfile() )
indexBam( sorted )
reg <- paste( "seq1:1-", len, sep = "" )
diagnostics <- ReQON( sorted, "Recalibrated_example.bam", reg,
  RefSeq = "ref_seq.txt", nerr = 20, nraf = 0.25,
  plotname = "Recalibrated_example_plots.pdf" )

#Remove temporary file
unlink( "ref_seq.txt" )
```

Index

FWSEplot, [2](#)

QualFreqPlot, [3](#)

ReadPosErrorPlot, [4](#)

ReQON, [5](#)