

Package ‘flowViz’

March 30, 2021

Type Package

Title Visualization for flow cytometry

Version 1.54.0

Author B. Ellis, R. Gentleman, F. Hahne, N. Le Meur, D. Sarkar, M. Jiang

Maintainer Mike Jiang <wjiang2@fhcrc.org>, Jake Wagner <jpwagner@fhcrc.org>

Description Provides visualization tools for flow cytometry data.

Depends R (>= 2.7.0), flowCore(>= 1.41.9), lattice

Imports stats4, Biobase, flowCore, graphics, grDevices, grid,
KernSmooth, lattice, latticeExtra, MASS, methods, RColorBrewer,
stats, utils, hexbin, IDPmisc

Suggests colorspace, flowStats, knitr, testthat

License Artistic-2.0

biocViews ImmunoOncology, Infrastructure, FlowCytometry,
CellBasedAssays, Visualization

VignetteBuilder knitr

RoxygenNote 6.1.1

git_url <https://git.bioconductor.org/packages/flowViz>

git_branch RELEASE_3_12

git_last_commit f80fd24

git_last_commit_date 2020-10-27

Date/Publication 2021-03-29

R topics documented:

flowViz-package	2
.process_flowFrame_overlay	3
.process_overlay_flowSet	3
addName-methods	4
contour-methods	5
densityplot	6
flowPlot	9
flowViz.par.get	11
glines-methods	13
glpoints-methods	14

glpolygon-methods	16
gpoints-methods	18
gpolygon-methods	19
levelplot,formula,flowSet-method	21
plot	23
prepanel.ecdfplot.flowset	24
splom	25
timeLinePlot	27
xyplot,flowFrame,missing-method	28

Index	36
--------------	-----------

flowViz-package	<i>Visualization for flow cytometry</i>
-----------------	---

Description

Functions and methods to visualize flow cytometry data. This package heavily depends on the flowCore package.

Details

Package: flowViz
 Type: Package
 Version: 0.2.1
 Date: 2006-11-16
 License: Artistic

Traditionally, large parts of the analysis process of flow cytometry data has been mostly qualitative. To this end, dedicated visualization techniques have been used for both quality control and inference of the data. This package provides a number of different visualization tools for flow data.

Author(s)

Maintainer: Florian Hahne <f.hahne@dkfz.de> Authors: T. Duong, B. Ellis, R. Gentleman, F. Hahne, N. Le Meur, D. Sarkar, M. Tang

See Also

[flowCore](#)

Examples

examples go here

.process_flowFrame_overlay

convert a single flowFrame or a list of flowFrames to a list of flowSet

Description

convert a single flowFrame or a list of flowFrames to a list of flowSet

Usage

```
.process_flowFrame_overlay(overlay, sn)
```

Arguments

overlay	flowFrame or a list of flowFrame objects
sn	sample name

.process_overlay_flowSet

extract the respective flowFrame from each flowSet based on the given sampleName

Description

extract the respective flowFrame from each flowSet based on the given sampleName

Usage

```
.process_overlay_flowSet(overlay, nm)
```

Arguments

overlay	a list of flowSet
nm	sample name

 addName-methods

Add gate names to a flowViz plot.

Description

These methods add gate names to a flowViz plot, either derived from the population identifiers or as provided by the user. These methods are ment for internal use and are usually not called directly by the user.

Usage

```
## S4 method for signature 'rectangleGate,character'
addName(x, name, data, gp, pos = 0.5,
        abs = FALSE, xlim, ylim, ...)
```

Arguments

x	rectangleGate, ellipsoidGate, quadGate, polygonGate or kmeansFilter
name	character or logical or matrix
data	flowFrame
gp	a list of graphical parameters
pos, abs	specifying location of the name. see 'help(xyplot)' for more details
xlim, ylim	limits of axis
...	other arguments

Value

The methods are called for their side effects. No value is returned.

Methods

```
x = "curv1Filter", name = "character" User-provided names.
x = "curv1Filter", name = "logical" Get names from the filter or filterResult object
x = "curv2Filter", name = "character" see above
x = "curv2Filter", name = "logical" see above
x = "ellipsoidGate", name = "character" see above
x = "ellipsoidGate", name = "logical" see above
x = "kmeansFilter", name = "character" see above
x = "kmeansFilter", name = "logical" see above
x = "polygonGate", name = "character" see above
x = "polygonGate", name = "logical" see above
x = "quadGate", name = "character" see above
x = "quadGate", name = "logical" see above
x = "quadGate", name = "matrix" see above
x = "rectangleGate", name = "character" see above
x = "rectangleGate", name = "logical" see above
```

Author(s)

F. Hahne

contour-methods

*Contour plots for flow data***Description**

Basic contour plots for both `flowFrames` and `flowSets`. The densities for the contours are estimated using the fast kernel density estimation algorithm `bkde2D`.

Usage

```
## S4 method for signature 'flowFrame'
contour(x, y = 1:2, nlevels = 10, bw,
        grid.size = c(65, 65), add = FALSE, xlab, ylab, xlim, ylim,
        lwd = 1, lty = 1, col = par("fg"), fill = "transparent", ...)
```

Arguments

<code>x</code>	An object of class <code>flowFrame</code> or <code>flowSet</code> .
<code>y</code>	Numeric or character vector of length 2 indicating the channels to plot.
<code>nlevels</code>	The approximate number of contour line levels, see <code>contour</code> for details.
<code>bw</code>	The bandwidth factor used for the kernel density estimation, see <code>bkde2D</code> for details.
<code>grid.size</code>	The grid size used for the kernel density estimation, see <code>bkde2D</code> for details.
<code>add</code>	Logical, indicating whether contour lines should be superimposed on an existing plot.
<code>xlab, ylab</code>	The axis annotation.
<code>xlim, ylim</code>	The plotting ranges.
<code>lwd, lty, col, fill</code>	The usual plotting parameters, i.e. the line width, line type, line color and fill color. When using a fill color you should consider alpha blending to improve the results.
<code>...</code>	Parameters that are passed on to the plotting functions.

Methods

x = "flowFrame" A regular contour plot of the flow data in the frame. It can be added on top of an existing plot using the `add` argument.

x = "flowSet" Overlay of contours of densities for each individual frame in the set. You should consider using different colors and alpha blending to improve the result. This is only useful for a very limited number of frames in a set (~5), for larger sets you should consider a panelled lattice-type plot. Note that `bw`, `gridSize` and `nlevels` are passed on via the `...` argument.

Author(s)

F. Hahne

See Also

[bkde2D](#), [contour](#), [flowFrame](#), [flowSet](#)

Examples

```
library(flowCore)
data(GvHD)

## simple contour plot
contour(GvHD[[1]])

## overlay with existing plot
plot(GvHD[[1]], c("FSC-H", "SSC-H"))
contour(GvHD[[1]], add=TRUE, col="lightgray", lty=3)

## colored contours
contour(GvHD[[1]], fill="red")
cols <- rainbow(3, alpha=0.1)
contour(GvHD[[1]], fill=cols, col=cols)

## overlay of multiple flowFrames in a flowSet
contour(GvHD[1:3], col=cols, fill=cols)
```

densityplot

One-dimensional density/histogram plots for flow data

Description

For [flowSets](#) the idea is to horizontally stack plots of density estimates for all frames in the `flowSet` for one or several flow parameters. In the latter case, each parameter will be plotted in a separate panel, i.e., we implicitly condition on parameters.

Usage

```
## S4 method for signature 'formula,flowSet'
densityplot(x, data, ...)

prepanel.densityplot.flowset.stack(x, y, frames, overlap = 0.3,
  subscripts, ..., which.channel)

panel.densityplot.flowset.stack(x, y, darg = list(n = 50, na.rm = TRUE),
  frames, channel, overlap = 0.3, channel.name, filter = NULL,
  fill = superpose.polygon$col, lty = superpose.polygon$lty,
  lwd = superpose.polygon$lwd, alpha = superpose.polygon$alpha,
  col = superpose.polygon$border, groups = NULL, reflines = NULL,
  margin = 0.005, stats = FALSE, pos = 0.5, digits = 2,
  abs = FALSE, fitGate = TRUE, checkName = TRUE,
  plotType = "densityplot", hist.type = "density",
  breaks = "Sturges", gp, ...)
```

```

## S4 method for signature 'formula,flowFrame'
densityplot(x, data, overlay = NULL, ...)

## S4 method for signature 'formula,view'
densityplot(x, data, ...)

## S4 method for signature 'formula,ncdfFlowSet'
densityplot(x, data, ...)

## S4 method for signature 'formula,ncdfFlowList'
densityplot(x, data, ...)

## S4 method for signature 'formula,flowSet'
histogram(x, data, plotType, ...)

## S4 method for signature 'formula,flowFrame'
histogram(x, data, ...)

## S4 method for signature 'formula,ncdfFlowSet'
histogram(x, data, ...)

## S4 method for signature 'formula,ncdfFlowList'
histogram(x, data, ...)

```

Arguments

x	A formula describing the structure of the plot and the variables to be used in the display. The structure of the formula is <code>factor ~ parameter</code> , where <code>factor</code> can be any of the phenotypic factors in the <code>phenoData</code> slot or an appropriate factor object and <code>parameter</code> is a flow parameter. Panels for multiple parameters are drawn if the formula structure is similar to <code>factor ~ parameter1 + parameter2</code> , and <code>factor</code> can be missing, in which case the sample names are used as y-variable. To facilitate programatic access, the formula can be of special structure <code>factor ~ .</code> , in which case the optional <code>channel</code> argument is considered for parameter selection. For the workflow methods, <code>x</code> can also be one of the several workflow objects.
data	A flow data object that serves as a source of data, either a flowFrame or flowSet
...	More arguments, usually passed on to the underlying lattice methods. <ul style="list-style-type: none"> • <code>channels</code> A character vector of parameters that are supposed to be plotted when the formula in <code>x</code> is of structure <code>factor ~ .</code> • <code>xlab</code>: Label for data x axis, with suitable defaults taken from the formula • <code>prepanel</code>: The <code>prepanel</code> function. See xyplot • <code>panel</code>: the <code>panel</code> function. See xyplot • <code>axis</code>: axis function passed to lattice, default is <code>axis.grid</code> • ... : other arguments passed to <code>panel.densityplot.flowset.stack</code> or <code>panel.histogram.flowframe</code>
frames	An environment containing frame-specific data.
overlap	The amount of overlap between stacked density plots. This argument is ignored for the <code>flowFrame</code> method.
subscripts, which.channel, channel.name, y	Internal indices necessary to map panels to parameters.

darg	These arguments are passed unchanged to the corresponding methods in lattice, and are listed here only because they provide different defaults. See documentation for the original methods for details. darg gets passed on to density .
channel	The name of the currently plotted flow parameter.
filter	A filter , filterResult or filterResultList object or a list of such objects of the same length as the flowSet. If applicable, the gate region will be superimposed on the density curves using color shading. The software will figure out whether the filter needs to be evaluated in order to be plotted (in which case providing a filterResult can speed things up considerably).
col, fill, lty, lwd, alpha	Graphical parameters. These mostly exist for convenience and much more control is available through the lattice-like <code>par.setting</code> and <code>flowViz.par.set</code> customization. The relevant parameter category for density plots is <code>gate.density</code> with available parameters <code>col</code> , <code>fill</code> , <code>lwd</code> , <code>alpha</code> and <code>lty</code> . See flowViz.par.set for details.
groups	Use identical colors for grouping. The value of the argument is expected to be a phenotypic variable in the flowSet, or a factor.
refline	Logical. Add one or more vertical reference lines to the plot. This argument is directly passed to panel.abline .
margin	Either Logical value 'FALSE' or Numeric value in $[0, 1]$. When 'FALSE', it doesn't do anything to the margin events. When Numeric value, it indicates margin events by horizontal bars. The value of margin is interpreted as the proportion of events on the margin over which the bars are added. E.g., a value of 0.5 means to indicate margin events if there are more than 0.5 times the total number of events. 1 means to ignore margin events completely. For 0 bars are added even if there is only a single margin event.
stats, pos, digits, abs	Arguments to control statistics that is associated with filter to be plotted. see xyplot for details.
fitGate	A logical scalar indicating whether to display the gate as fitted 1d density gate region or simply display the gate boundaries using vertical lines. The latter would be helpful to display the gate when the gated density region is too small to see.
checkName	A logical scalar indicating whether to validity check the channel name. Default is TRUE, which consider '(' as invalid character in channel names
plotType	either 'densityplot' or 'histogram'
hist.type	see 'type' argument in 'help(panel.histogram)'
breaks	see 'help(hist)'
gp	A list of graphical parameters that are passed down to the low level panel functions. This is for internal use only. The public user interface to set graphical parameters is either <code>par.settings</code> for customization of a single call or <code>flowViz.par.set</code> for customization of session-wide defaults.
overlay	see help(xyplot) .

Details

Not all standard lattice arguments will have the intended effect, but many should. For a fuller description of possible arguments and their effects, consult documentation on lattice (Trellis docs would also work for the fundamentals).

Examples

```

library(flowCore)
library(flowStats)
data(GvHD)
GvHD <- GvHD[pData(GvHD)$Patient %in% 6:7]

densityplot(~ `FSC-H`, GvHD)

densityplot(~ `FSC-H` + `SSC-H`, GvHD)

densityplot(~ ., GvHD[1:3])

## include a filter
densityplot(~ `FSC-H`, GvHD, filter=curv1Filter("FSC-H"))

#display the gate by its boundaries with statistics
densityplot(~ `FSC-H`, GvHD[1:2], filter=curv1Filter("FSC-H"),fitGate=FALSE,stats=TRUE)

## plot a single flowFrame
densityplot(~ `SSC-H`, GvHD[[1]], margin=FALSE)

## plot histogram
histogram(~ `SSC-H`, GvHD[[1]]) #default type is 'density'
#change the type to 'count' and adjust breaks
histogram(~ `SSC-H`, GvHD[[1]], margin=FALSE, type = "count", breaks = 50)

```

flowPlot

*Standard Plots for Flow Cytometry Data***Description**

A method that makes standard plots from a flowFrame. The user may also provide various filter or filterResult arguments to customize the plot.

Usage

```

## S4 method for signature 'flowFrame'
flowPlot(x, child, filter = NULL,
  plotParameters = c("FSC-H", "SSC-H"), logx = FALSE, logy = FALSE,
  parent, colParent = "Grey", colChild = "Blue", showFilter = TRUE,
  gate.fill = "transparent", gate.border = "black", xlab, ylab, xlim,
  ylim, ...)

```

Arguments

x	An object of class flowFrame that contains the data to be plotted.
child	An optional argument of class filterResult that specifies a subset of the data that are included in the filterResult
filter	A filter, filterResult or filterResultList object.

plotParameters	A vector of characters defining the x and y variables in terms of columns in the data.
logx, logy	Logical controlling whether the corresponding variables will be log transformed before passing to the panel function. Default to FALSE.
parent	An optional argument of class <code>filterResult</code> that specifies a subset of the data that are included in the <code>filterResult</code> .
colParent	Specifying the color for parent. See parent above.
colChild	Specifies the color for child. See child above.
showFilter	Logical, specifying whether to show the filter.
gate.fill	Specifies the fill color of the gate. Default to transparent.
gate.border	Character or specifying the color of the gate border. Default to black.
xlab, ylab	Labels for data axes.
xlim, ylim	Numeric vectors of length 2 specifying axis limits.
...	More arguments, usually passed on to the underlying lattice methods.

Details

The plot that is most commonly used in flow cytometry data analysis is usually called a "dot plot". In common statistical language, we would call this a scatter plot. The basic idea is a 2-dimensional plot that shows the location of every cell in regard to the measurements made on it, for example, forward scatter vs side scatter. Most applications will, in addition to the data, want to show information about one or more filters (gates). Since there can be a very large number of cells in a sample, it is common to show a smoothed version of the data that doesn't involve registering every point on the graph.

Author(s)

P. Haaland

See Also

[flowCore](#)

Examples

```
library(flowCore)
data(GvHD)
flowPlot(GvHD[["s5a01"]])
flowPlot(transform("SSC-H"=asinh,"FSC-H"=asinh) %on% GvHD[["s5a01"]])
```

flowViz.par.get *Query and set session-wide graphical parameter defaults.*

Description

flowViz.par.get is the equivalent to [trellis.par.get](#). It queries the session wide defaults for all lattice and flowViz graphical parameters.

Usage

```
flowViz.par.get(name = NULL)
```

```
flowViz.par.set(name, value, ..., theme, warn = TRUE, strict = FALSE,
               reset = FALSE)
```

Arguments

name	The name of a parameter category to set.
value	A named list of values to set for category name or a list of such lists if name is missing.
...	Further arguments that get passed on.
theme	The theme to set. See trellis.par.set for details.
warn	This gets passed on directly to trellis.par.set .
strict	This gets passed on directly to trellis.par.set .
reset	logical scalar. When TRUE, drop the entire list of old graphical parameters and reset it with the supplied one. Default is FALSE, which updates the existing parameters.

Details

flowViz.par.set is the equivalent to [trellis.par.set](#). It sets the same set of graphical parameters, either in the flowViz package or directly in lattice.

Getting and setting graphical parameters in flowViz follows exactly the mechanism of the lattice package. For all purpose and intentions, flowViz.par.get and flowViz.par.set can be viewed as wrappers around their lattice counterparts [trellis.par.get](#) and [trellis.par.set](#) and you should consult their documentation for further details.

We introduce four new categories of graphical parameters that are relevant for flowViz plots:

gate Controls the appearance of gate boundaries in xyplots (if smooth=TRUE) or of the points within a gate region (smooth=FALSE). Available parameters are col, cex,pch,alpha,lwd,lty and fill.

gate.density Controls the appearance of gate boundaries in densityplots. Available parameters are col, alpha,lwd,lty and fill.

flow.symbol Controls the appearance of 'regular' points in a flowViz plot. Available parameters are col, cex,pch,alpha and fill.

gate.text Controls the appearance of the text used for gate names. Available parameters are col, cex,font,alpha and lineheight.

Value

flowViz.par.get returns a list of graphical parameter defaults, if name is not empty, only for this particular category. For an empty name argument, the function returns all parameter defaults, including the ones specified in the lattice package.

flowViz.par.set is called for its side-effects of setting default parameters.

Note

Because parameter settings in lattice are device-dependent, flowViz.par.get will open a (default) device none is open at the time of the query.

Author(s)

F. Hahne

References

Deepayan Sarker, *Lattice, Multivariate Data Visualization with R*, Springer, New York, 2008

See Also

[trellis.par.get](#) and [trellis.par.set](#)

Examples

```
## Return all available parameters, including lattice ones
flowViz.par.get()

## Set the font for gate names
flowViz.par.set("gate.text", list(font=2))

## Query only the gate.text category
flowViz.par.get("gate.text")

## Set a lattice parameter
plot.symbol <- trellis.par.get("plot.symbol")
flowViz.par.set("plot.symbol", list(col="red"))
trellis.par.get("plot.symbol")

## undo all settings
flowViz.par.set(list(plot.symbol=plot.symbol, gate.text=list(font=1)))
library(flowCore)
data(GvHD)
fs <- GvHD[1:2]

# using default ggplot2like theme
densityplot(~`FSC-H`, fs)
xyplot(`SSC-H`~`FSC-H`, fs, smooth = FALSE)

# reset it with default lattice theme
flowViz.par.set(theme = trellis.par.get(), reset = TRUE)
densityplot(~`FSC-H`, fs)
xyplot(`SSC-H`~`FSC-H`, fs, smooth = FALSE)
```

Description

These methods extend the basic graphics `lines` methods for drawing of `filter` boundaries. They allow for multiple dispatch, since not all `filter` types need to be evaluated for plotting, but this decision should be made internally.

Usage

```
## S4 method for signature 'filter,missing'
glines(x, data, verbose = TRUE, ...)
```

Arguments

<code>x</code>	filter or filterResult or any derived filter class
<code>data</code>	flowFrame or filterResult or character or missing or ANY
<code>verbose</code>	logical
<code>...</code>	other arguments

x = "filter", data = "missing" General method for all objects inheriting from `filter`. This is used as the default when no more explicit method is found. It tries to find the plotted parameters from the internal `flowViz.state` environment. This only works if the flow data has been plotted using the `plot` or `xypplot` methods provided by this `flowViz` package.

x = "filterResult", data = "ANY" General method for all `filterResult` object. This basically extracts the `filter` from the `filterResult` and dispatches on that.

x = "filterResult", data = "flowFrame" For some `filter` types we need the raw data to re-evaluate the filter.

x = "curv1Filter", data = "ANY" We either need a `filterResult` or the raw data as a `flowFrame` for `curv1Filter`.

x = "curv1Filter", data = "flowFrame" see above

x = "curv1Filter", data = "missing" see above

x = "curv1Filter", data = "multipleFilterResult" see above

x = "curv2Filter", data = "ANY" We either need a `filterResult` or the raw data as a `flowFrame` for `curv2Filter`.

x = "curv2Filter", data = "flowFrame" see above

x = "curv2Filter", data = "multipleFilterResult" see above

x = "kmeansFilter", data = "ANY" We don't know how to plot outlines of a `kmeansFilter`, hence we warn.

x = "norm2Filter", data = "ANY" We either need a `filterResult` or the raw data as a `flowFrame` for `norm2Filter`.

x = "norm2Filter", data = "flowFrame" see above

x = "norm2Filter", data = "logicalFilterResult" see above

```

x = "polygonGate", data = "character" We can plot a polygonGate directly
from the gate definition.
x = "polygonGate", data = "filterResult" see above
x = "polygonGate", data = "flowFrame" see above
x = "quadGate", data = "character" We can plot a quadGate directly from
the gate definition.
x = "quadGate", data = "filterResult" see above
x = "quadGate", data = "flowFrame" see above
x = "rectangleGate", data = "character" We can plot a rectangleGate di-
rectly from the gate definition.
x = "rectangleGate", data = "filterResult" see above
x = "rectangleGate", data = "flowFrame" see above
x = "ellipsoidGate", data = "character" We can plot a rectangleGate di-
rectly from the gate definition.
x = "ellipsoidGate", data = "filterResult" see above
x = "ellipsoidGate", data = "flowFrame" see above

```

Details

When plotting [flowFrames](#) using the `plot` or `xyplot` methods provided by `flowViz`, the plotted parameters are recorded, which makes it possible to correctly overlay the outlines of [filter](#) assuming that they are defined for the respective parameters. Warnings and error will be cast for the cases where the parameters are non-distinct or ambiguous.

The flow parameters plotted can be passed on to any of the methods through the optional `channels` argument, which always gets precedence over automatically detected parameters.

The methods support all plotting parameters that are available for the base lines functions.

Author(s)

F. Hahne

See Also

[filter](#), [flowFrame](#), [gpoints](#)

glpoints-methods

Adding points within a gate to a plot

Description

These methods extend the lattice [lpoints](#) methods for drawing of points contained within a [filter](#). They allow for multiple dispatch, since not all [filter](#) types need to be evaluated for plotting, but this decision should be made internally. In any case, we need the raw data in the form of a [flowFrame](#).

Usage

```

## S4 method for signature 'filter,flowFrame,missing'
glpoints(x, data, channels,
         verbose = TRUE, filterResult = NULL, ...)

```

Arguments

x	filter, filterResult or any derived filter class
data	flowFrame or missing
channels	character or missing
verbose	logical
filterResult	filterResult class
...	other arguments

Details

When plotting `flowFrames` using the `plot` method provided by `flowViz`, the plotted parameters are recorded, which makes it possible to correctly overlay the points within `filters` assuming that they are defined for the respective parameters. Warnings and error will be cast for the cases where the parameters are non-distinct or ambiguous. These methods are meant to be used within lattice panel functions and are probably not of much use outside of those.

Methods

x = "filter", data = "flowFrame", channels = "missing" General method for all objects inheriting from `filter`. This is used as the default when no more explicit method is found. It tries to find the plotted parameters from the internal `flowViz.state` environment. This only works if the flow data has been plotted using the `plot` methods provided by this `flowViz` package.

x = "filter", data = "missing", channels = "ANY" This gives a useful error message when we don't get what we need.

x = "filterResult", data = "flowFrame", channels = We can get all the information about a `filter` from its `filterResult` without the need to re-evaluate.

"character" We can get all the information about a `filter` from its `filterResult` without the need to re-evaluate.

x = "curv1Filter", data = "ANY" We either need a `filterResult` or the raw data as a `flowFrame` for `curv1Filters`.

x = "curv1Filter", data = "flowFrame" see above

x = "curv1Filter", data = "missing" see above

x = "curv1Filter", data = "multipleFilterResult" see above

x = "curv2Filter", data = "ANY" We either need a `filterResult` or the raw data as a `flowFrame` for `curv2Filters`.

x = "curv1Filter", data = "flowFrame", channels = We evaluate the `filter` on the `flowFrame` and plot the subset of selected points. By default, every subpopulation (if there are any) is colored differently.

"character" We evaluate the `filter` on the `flowFrame` and plot the subset of selected points. By default, every subpopulation (if there are any) is colored differently.

x = "curv2Filter", data = "flowFrame", channels = "character" see above

x = "kmeansFilter", data = "flowFrame", channels = see above

"character" see above

x = "norm2Filter", data = "flowFrame", channels = see above

"character" see above

x = "polygonGate", data = "flowFrame", channels = see above

"character" see above
x = "quadGate", data = "flowFrame", channels = "character" see above
x = "rectangleGate", data = "flowFrame", channels = see above
 "character" see above
x = "ellipsoidGate", data = "flowFrame", channels = see above
 "character" see above

Author(s)

F. Hahne

See Also

[filter](#), [flowFrame](#), [glpolygon](#)

glpolygon-methods *Drawing filter regions*

Description

These methods extend the lattice [lpolygon](#) methods for drawing of [filter](#) regions. They allow for multiple dispatch, since not all [filter](#) types need to be evaluated for plotting, but this decision should be made internally.

Usage

```
## S4 method for signature 'filter,missing'
glpolygon(x, data, verbose = TRUE,
          gpar = flowViz.par.get(), strict = TRUE, ...)
```

Arguments

x	filter or filterResult or any derived filter class
data	flowFrame or filterResult or character or missing or ANY
verbose	logical
gpar	a list of graphical parameters. see 'help(flowViz.par.get)' for details.
strict	logical
...	other arguments

Details

When plotting [flowFrames](#) using the any of the lattice-type plot method provided by flowViz, the plotted parameters are recorded, which makes it possible to correctly overlay the outlines of [filter](#) assuming that they are defined for the respective parameters. Warnings and error will be cast for the cases where the parameters are non-distinct or ambiguous. These methods are meant to be used within lattice panel functions and are probably not of much use outside of those.

Value

The methods will return the outlines of the gate region as polygon vertices.

Methods

- x = "filter", data = "missing"** General method for all objects inheriting from `filter`. This is used as the default when no more explicit method is found. It tries to find the plotted parameters from the internal `flowViz.state` environment. This only works if the flow data has been plotted using the plot methods provided by this `flowViz` package.
- x = "filterResult", data = "missing"** General method for all `filterResult` object. This basically extracts the `filter` from the `filterResult` and dispatches on that.
- x = "filterResult", data = "flowFrame"** For some `filter` types we need the raw data to re-evaluate the filter.
- x = "curv1Filter", data = "ANY"** We either need a `filterResult` or the raw data as a `flowFrame` for `curv1Filters`.
- x = "curv1Filter", data = "flowFrame"** see above
- x = "curv1Filter", data = "missing"** see above
- x = "curv1Filter", data = "multipleFilterResult"** see above
- x = "curv2Filter", data = "ANY"** We either need a `filterResult` or the raw data as a `flowFrame` for `curv2Filter`.
- x = "curv2Filter", data = "flowFrame"** see above
- x = "curv2Filter", data = "multipleFilterResult"** see above
- x = "kmeansFilter", data = "ANY"** We don't know how to plot regions of a `kmeansFilter`, hence we warn.
- x = "norm2Filter", data = "ANY"** We either need a `filterResult` or the raw data as a `flowFrame` for `norm2Filter`.
- x = "norm2Filter", data = "flowFrame"** see above
- x = "norm2Filter", data = "logicalFilterResult"** see above
- x = "polygonGate", data = "character"** We can plot a `polygonGate` directly from the gate definition.
- x = "polygonGate", data = "filterResult"** see above
- x = "polygonGate", data = "flowFrame"** see above
- x = "quadGate", data = "character"** We can plot a `quadGate` directly from the gate definition.
- x = "quadGate", data = "filterResult"** see above
- x = "quadGate", data = "flowFrame"** see above
- x = "rectangleGate", data = "character"** We can plot a `rectangleGate` directly from the gate definition.
- x = "rectangleGate", data = "filterResult"** see above
- x = "rectangleGate", data = "flowFrame"** see above
- x = "ellipsoidGate", data = "character"** We can plot a `rectangleGate` directly from the gate definition.
- x = "ellipsoidGate", data = "filterResult"** see above
- x = "ellipsoidGate", data = "flowFrame"** see above

Author(s)

F. Hahne

See Also

`filter`, `flowFrame`, `glpoints`

Description

These methods extend the basic graphics `points` methods for drawing of points contained within a `filter`. They allow for multiple dispatch, since not all `filter` types need to be evaluated for plotting, but this decision should be made internally. In any case, we need the raw data in the form of a `flowFrame`.

Usage

```
## S4 method for signature 'filter,flowFrame,missing'
gpoints(x, data, channels,
        verbose = TRUE, filterResult = NULL, ...)
```

Arguments

<code>x</code>	filter, filterResult or any derived filter class
<code>data</code>	flowFrame or missing
<code>channels</code>	character or missing
<code>verbose</code>	logical
<code>filterResult</code>	filterResult class
<code>...</code>	other arguments

Details

When plotting `flowFrames` using the `plot` method provided by `flowViz`, the plotted parameters are recorded, which makes it possible to correctly overlay the points within `filters` assuming that they are defined for the respective parameters. Warnings and error will be cast for the cases where the parameters are non-distinct or ambiguous.

Methods

`x = "filter", data = "flowFrame", channels = "missing"` General method for all objects inheriting from `filter`. This is used as the default when no more explicit method is found. It tries to find the plotted parameters from the internal `flowViz.state` environment. This only works if the flow data has been plotted using the `plot` methods provided by this `flowViz` package.

`x = "filter", data = "missing", channels = "ANY"` This gives a useful error message when we don't get what we need.

`x = "filterResult", data = "flowFrame", channels =` We can get all the information about a `filter` from its `filterResult` without the need to re-evaluate.

`"character"` We can get all the information about a `filter` from its `filterResult` without the need to re-evaluate.

`x = "curv1Filter", data = "ANY"` We either need a `filterResult` or the raw data as a `flowFrame` for `curv1Filters`.

`x = "curv1Filter", data = "flowFrame"` see above

`x = "curv1Filter", data = "missing"` see above

`x = "curv1Filter", data = "multipleFilterResult"` see above

`x = "curv2Filter", data = "ANY"` We either need a [filterResult](#) or the raw data as a [flowFrame](#) for [curv2Filters](#).

`x = "curv1Filter", data = "flowFrame", channels =` We evaluate the [filter](#) on the [flowFrame](#) and plot the subset of selected points. By default, every subpopulation (if there are any) is colored differently.

`"character"` We evaluate the [filter](#) on the [flowFrame](#) and plot the subset of selected points. By default, every subpopulation (if there are any) is colored differently.

`x = "curv2Filter", data = "flowFrame", channels = "character"` see above

`x = "kmeansFilter", data = "flowFrame", channels =` see above

`"character"` see above

`x = "norm2Filter", data = "flowFrame", channels =` see above

`"character"` see above

`x = "polygonGate", data = "flowFrame", channels =` see above

`"character"` see above

`x = "quadGate", data = "flowFrame", channels = "character"` see above

`x = "rectangleGate", data = "flowFrame", channels =` see above

`"character"` see above

Author(s)

F. Hahne

See Also

[filter](#), [flowFrame](#), [glines](#), [gpolygon](#)

gpolygon-methods

Drawing filter regions

Description

These methods extend the basic graphics [polygon](#) methods for drawing of [filter](#) regions. They allow for multiple dispatch, since not all [filter](#) types need to be evaluated for plotting, but this decision should be made internally.

Usage

```
## S4 method for signature 'filter,missing'
gpolygon(x, data, verbose = TRUE, ...)
```

Arguments

<code>x</code>	filter or filterResult or any derived filter class
<code>data</code>	flowFrame or filterResult or character or missing or ANY
<code>verbose</code>	logical
<code>...</code>	other arguments

Details

When plotting `flowFrames` using the `plot` method provided by `flowViz`, the plotted parameters are recorded, which makes it possible to correctly overlay the outlines of `filters` assuming that they are defined for the respective parameters. Warnings and error will be cast for the cases where the parameters are non-distinct or ambiguous.

The flow parameters plotted can be passed on to any of the methods through the optional `channels` argument, which always gets precedence over automatically detected parameters.

The methods support all plotting parameters that are available for the base polygon functions.

Methods

- x = "filter", data = "missing"** General method for all objects inheriting from `filter`. This is used as the default when no more explicit method is found. It tries to find the plotted parameters from the internal `flowViz.state` environment. This only works if the flow data has been plotted using the `plot` methods provided by this `flowViz` package.
- x = "filterResult", data = "ANY"** General method for all `filterResult` object. This basically extracts the `filter` from the `filterResult` and dispatches on that.
- x = "filterResult", data = "flowFrame"** For some `filter` types we need the raw data to re-evaluate the filter.
- x = "curv1Filter", data = "ANY"** We either need a `filterResult` or the raw data as a `flowFrame` for `curv1Filters`.
- x = "curv1Filter", data = "flowFrame"** see above
- x = "curv1Filter", data = "missing"** see above
- x = "curv1Filter", data = "multipleFilterResult"** see above
- x = "curv2Filter", data = "ANY"** We either need a `filterResult` or the raw data as a `flowFrame` for `curv2Filter`.
- x = "curv2Filter", data = "flowFrame"** see above
- x = "curv2Filter", data = "multipleFilterResult"** see above
- x = "kmeansFilter", data = "ANY"** We don't know how to plot regions of a `kmeansFilter`, hence we warn.
- x = "norm2Filter", data = "ANY"** We either need a `filterResult` or the raw data as a `flowFrame` for `norm2Filter`.
- x = "norm2Filter", data = "flowFrame"** see above
- x = "norm2Filter", data = "logicalFilterResult"** see above
- x = "polygonGate", data = "character"** We can plot a `polygonGate` directly from the gate definition.
- x = "polygonGate", data = "filterResult"** see above
- x = "polygonGate", data = "flowFrame"** see above
- x = "quadGate", data = "character"** We can plot a `quadGate` directly from the gate definition.
- x = "quadGate", data = "filterResult"** see above
- x = "quadGate", data = "flowFrame"** see above
- x = "rectangleGate", data = "character"** We can plot a `rectangleGate` directly from the gate definition.
- x = "rectangleGate", data = "filterResult"** see above
- x = "rectangleGate", data = "flowFrame"** see above

`x = "ellipsoidGate", data = "character"` We can plot a [ellipsoidGate](#) directly from the gate definition.

`x = "ellipsoidGate", data = "filterResult"` see above

`x = "ellipsoidGate", data = "flowFrame"` see above

Author(s)

F. Hahne

See Also

[filter](#), [flowFrame](#), [glines](#), [gpoints](#)

levelplot, formula, flowSet-method

Methods implementing Lattice displays for flow data

Description

Various methods implementing multipanel visualizations for flow data using infrastructure provided in the lattice package. The original generics for these methods are defined in lattice, and these S4 methods (mostly) dispatch on a formula and the data argument which must be of class `flowSet` or `flowFrame`. The formula has to be fairly basic: conditioning can be done using phenodata variables and channel names (the `colnames` slot) can be used as panel variables. See examples below for sample usage.

Usage

```
## S4 method for signature 'formula,flowSet'
levelplot(x, data, xlab, ylab,
  as.table = TRUE, contour = TRUE, labels = FALSE, n = 50, ...)

## S4 method for signature 'formula,flowSet'
qqmath(x, data, xlab, ylab,
  f.value = function(n) ppoints(ceiling(sqrt(n))),
  distribution = qnorm, ...)

## S4 method for signature 'flowFrame,missing'
parallel(x, data, reorder.by = function(x)
  var(x, na.rm = TRUE), time = "Time", exclude.time = TRUE, ...)

## S4 method for signature 'formula,flowSet'
parallel(x, data, time = "Time",
  exclude.time = TRUE, filter = NULL, xlab = NULL, ylab = NULL,
  ...)
```

Arguments

<code>x</code>	a formula describing the structure of the plot and the variables to be used in the display.
<code>data</code>	a <code>flowSet</code> object that serves as a source of data.
<code>xlab, ylab</code>	Labels for data axes, with suitable defaults taken from the formula
<code>as.table, contour, labels</code>	These arguments are passed unchanged to the corresponding methods in <code>lattice</code> , and are listed here only because they provide different defaults. See documentation for the original methods for details.
<code>n</code>	the number of bins on each axis to be used when evaluating the density
<code>...</code>	more arguments, usually passed on to the underlying <code>lattice</code> methods.
<code>f.value, distribution</code>	number of points used in Q-Q plot, and the reference distribution used. See qqmath for details.
<code>reorder.by</code>	a function, which is applied to each column. The columns are ordered by the results. Reordering can be suppressed by setting this to <code>NULL</code> .
<code>time</code>	A character string giving the name of the column recording time.
<code>exclude.time</code>	logical, specifying whether to exclude the time variable from a scatter plot matrix or parallel coordinates plot. It is rarely meaningful not to do so.
<code>filter</code>	<code>flowCore</code> filter

Details

Not all standard `lattice` arguments will have the intended effect, but many should. For a fuller description of possible arguments and their effects, consult documentation on `lattice` (Trellis docs would also work for the fundamentals).

Methods

qqmath signature(`x = "formula"`, `data = "flowSet"`): creates theoretical quantile plots of a given channel, with one or more samples per panel

levelplot signature(`x = "formula"`, `data = "flowSet"`): similar to the `xyplot` method, but plots estimated density (using [kde2d](#)) with a common z-scale and an optional color key.

parallel signature(`x = "flowFrame"`, `data = "missing"`): draws a parallel coordinates plot of all channels (excluding time, by default) of a `flowFrame` object. This is rarely useful without transparency, but that is currently only possible with the [pdf](#) device (and perhaps the `aqua` device as well).

Examples

```
library(flowCore)
data(GvHD)

qqmath(~ `FSC-H` | factor(Patient), GvHD,
       grid = TRUE, type = "l",
       f.value = ppoints(100))

## contourplot of bivariate density:
```

```

require(colorspace)
Y10rBr <- c("#FFFFD4", "#FED98E", "#FE9929", "#D95F0E", "#993404")
colori <- colorRampPalette(Y10rBr)
levelplot(asinh(`SSC-H`) ~ asinh(`FSC-H`) | Visit + Patient, GvHD, n = 20,
          col.regions = colori(50), main = "Contour Plot")

## parallel coordinate plots

parallel(GvHD[["s6a01"]])

## Not run:

## try with PDF device
parallel(GvHD[["s7a01"]], alpha = 0.01)

## End(Not run)

```

plot

Very basic plotting of flowFrames

Description

A basic method to plot [flowFrame](#) objects. Depending on the number of dimensions, different types of plots are generated. See below for details.

Usage

```
## S4 method for signature 'flowFrame,missing'
plot(x, y, smooth = TRUE, ...)
```

```
## S4 method for signature 'flowFrame,character'
plot(x, y, smooth = TRUE, pch, ...)
```

Arguments

x	flowFrame
y	(optional) channel names
smooth	logical
...	other arguments
pch	point type

Details

Basic plots for [flowFrame](#) objects. If the object has only a single parameter this produces a [histogram](#). For exactly two parameters we plot a bivariate density map (see [smoothScatter](#)) and for more than two parameters we produce a simple [splom](#) plot. To select specific parameters

from a `flowFrame` for plotting, either subset the object or specify the parameters as a character vector in the second argument to `plot`. The `smooth` parameters lets you toggle between density-type `smoothScatter` plots and regular scatter or pairs plots. For far more sophisticated plotting of flow cytometry data, see the lattice-style plot methods provided by this package.

Author(s)

F. Hahne

See Also

[xyplot](#), [flowFrame](#), [densityplot](#)

```
prepanel.ecdfplot.flowset
```

Method implementing Lattice ECDF plots for flow data

Description

This function creates Trellis displays of Empirical Cumulative Distribution Functions from flow cytometry data using a formula interface.

Usage

```
prepanel.ecdfplot.flowset(x, frames, channel, f.value, ...)

panel.ecdfplot.flowset(x, frames, channel, f.value, ref = TRUE,
  groups = NULL, subscripts, col = superpose.symbol$col,
  col.points = col, pch = superpose.symbol$pch,
  cex = superpose.symbol$cex, alpha = superpose.symbol$alpha,
  col.line = col, lty = superpose.line$lty, lwd = superpose.line$lwd,
  ...)

## S4 method for signature 'formula,flowSet'
ecdfplot(x, data, xlab, f.value = function(n)
  ppoints(ceiling(sqrt(n))), prepanel = prepanel.ecdfplot.flowset,
  panel = panel.ecdfplot.flowset, type = "l", as.table = TRUE, ...)
```

Arguments

<code>x</code>	a formula describing the structure of the plot and the variables to be used in the display. For the <code>prepanel</code> and <code>panel</code> functions, a vector of names for the flow frames to be used in the panel.
<code>frames</code>	environment containing frame-specific data
<code>channel</code>	expression involving names of columns in the data
<code>f.value</code>	determines the number of points used in the plot <code>ecdfplot</code> for details.
<code>...</code>	more arguments, usually passed on to the underlying lattice methods and the panel function.
<code>ref</code>	logical; whether to add reference lines at 0 and 1

groups, subscripts	grouping variable, if specified, and subscripts indexing which frames are being used in the panel. See <code>xyplot</code> for details.
col, col.points, pch, cex, alpha, col.line, lty, lwd	vector of graphical parameters that are replicated for each group
data	a <code>flowSet</code> object that serves as a source of data
xlab	Labels for data axes, with suitable defaults taken from the formula
panel, prepanel	the panel and prepanel functions.
type	type of rendering; by default lines are drawn
as.table	logical; whether to draw panels from top left

Methods

ecdfplot signature(`x = "formula"`, `data = "flowSet"`): plote empirical CDF for a given channel, with one or more samples per panel

See Also

Not all standard lattice arguments will have the intended effect, but many should. For a fuller description of possible arguments and their effects, consult documentation on lattice.

Examples

```
library(flowCore)
data(GvHD)

ecdfplot(~ `FSC-H` | Patient, GvHD, f.value = ppoints(100))

ecdfplot(~ asinh(`FSC-H`) | Patient, GvHD,
  strip = strip.custom(strip.names = TRUE),
  ref = FALSE)

ecdfplot(~ asinh(`FSC-H`) | Patient, GvHD, groups = Visit,
  strip = strip.custom(strip.names = TRUE),
  ref = FALSE, auto.key = list(columns = 4))
```

splom

Method implementing Lattice scatter plot matrices for flow data.

Description

This function create Trellis scatter plots matrices (splom) from flow cytometry data.

Usage

```
## S4 method for signature 'flowFrame,missing'
splom(x, data, pscales, time,
  exclude.time = TRUE, names = FALSE, ...)
```

Arguments

<code>x</code>	A formula describing the structure of the plot and the variables to be used in the display.
<code>data</code>	A <code>flowFrame</code> object that serves as the source of data.
<code>pscales</code>	This arguments is passed unchanged to the corresponding methods in <code>lattice</code> , and is listed here only because it provides a different default. See documentation for the original methods for details.
<code>time</code>	A character string giving the name of the data column recording time. If not provided, we try to guess from the available parameters.
<code>exclude.time</code>	Logical, specifying whether to exclude the time variable from a scatter plot matrix. Defaults to TRUE.
<code>names</code>	Logical specifying whether gate names should be added to the plot. Currently, this feature is not supported for <code>splom</code> plots.
<code>...</code>	More arguments, usually passed on to the underlying <code>lattice</code> methods.

Details

The function draws a scatter plot matrix of the data for each flow parameter in a `flowFrame`. For the most, one can think about this as a rectangular arrangement of separate `xyplots`, and most of that functionality is also available here. To be more precise, the function repeatedly calls `panel.xyplot.flowframe` to do the actual plotting. Please see its documentation for details.

Author(s)

F. Hahne, D. Sarkar

See Also

Not all standard `lattice` arguments will have the intended effect, but many should. For a fuller description of possible arguments and their effects, consult documentation on `lattice`.

Examples

```
library(flowCore)
data(GvHD)
library(flowStats)

tf <- transformList(colnames(GvHD)[3:7], asinh)
dat <- tf %on% GvHD[[3]]

## scatter plot matrix of individual flowFrames
lattice.options(panel.error=NULL)
splom(dat)

splom(dat[,1:3], smooth = FALSE)

## displaying filters
rg <- rectangleGate("FSC-H"=c(200,400), "SSC-H"=c(300,700),
"FL1-H"=c(2,4), "FL2-A"=c(4,7))
splom(dat, filter=rg)
```

```
splom(dat, filter=rectangleGate("FSC-H"=c(400,800)))
splom(dat[,1:4], smooth = FALSE, filter=norm2Filter("FSC-H", "SSC-H", scale=1.5))
```

timeLinePlot	<i>Plot channel values against time</i>
--------------	---

Description

Plots values of one parameter for each flowFrame in a flowSet against time.

Usage

```
timelineplot(x, channel, type = c("stacked", "scaled", "native",
  "frequency"), col, ylab = names(x), binSize, varCut = 1, ...)

## S4 method for signature 'flowSet,character'
timeLinePlot(x, channel,
  type = c("stacked", "scaled", "native", "frequency"), col = NULL,
  ylab = sampleNames(x), binSize, varCut = 1, ...)

## S4 method for signature 'flowFrame,character'
timeLinePlot(x, channel, ...)

## S4 method for signature 'ANY,missing'
timeLinePlot(x, channel, ...)
```

Arguments

x	An object of class <code>flowFrame</code> or <code>flowSet</code> containing the data to be plotted.
channel	The parameter for which the data is to be plotted
type	One in 'stacked', 'scaled' or 'native'. 'stacked' will plot the measurements for the frames on top of each other. 'scaled' will align the median values around zero and 'native' will plot the values in the original dimensions of the measurement range.
col	Optional color parameter.
ylab	The axis annotation to add on the y-axis for stacked plots.
binSize	The number of events per bin. If not set, a reasonable default is computed.
varCut	The cutoff in the adjusted variance to which the quality score is computed. Basically, all values that are outside of the confidence interval defined by $[-\sigma * \text{varCut}, \sigma * \text{varCut}]$ will contribute to a positive quality score value.
...	Further arguments that are passed on to the base plotting functions.

Details

Plotting flow cytometry data against the time domain can help to identify problems with the fluidics or drifts in the instrument setting during measurement runs.

This function creates plots for all flowFrames in a flowSet for a given parameter against time. A barplot legend indicates the deviation from the median for each sample. There is also a flowFrame method, which will create a plot for a single flowFrame only.

In addition, the function computes a quality score for each frame, which essentially is the sum of the positive distances of each bin mean from a frame-specific confidence interval, divided by the number of bins. Values larger than zero indicate a problem.

Value

A numeric vector of quality scores.

Author(s)

F. Hahne

See Also

[flowFrame](#), [flowSet](#)

Examples

```
library(flowCore)
data(GvHD)
opar <- par(ask=TRUE)

res <- timeLinePlot(GvHD[[1]], "SSC-H")
res

res <- timeLinePlot(GvHD, "SSC-H")

res <- timeLinePlot(GvHD, "SSC-H", type="scaled", varCut=4)

res <- timeLinePlot(GvHD[1:4], "SSC-H", type="native", binSize=50)

par(opar)
```

xyplot,flowFrame,missing-method

Methods implementing Lattice xyplots for flow data.

Description

These functions create Trellis scatter plots (a.k.a. dot plots in the Flow Cytometry community) from flow cytometry data.

Usage

```

## S4 method for signature 'flowFrame,missing'
xyplot(x, data, time, xlab, ylab = "",
       layout, prepanel = prepanel.xyplot.flowframe.time,
       panel = panel.xyplot.flowframe.time, type = "discrete", ...)

prepanel.xyplot.flowframe.time(x, y, frame, time, xlim, ylim, ...)

panel.xyplot.flowframe.time(x, y, frame, time, type = "discrete",
                             nrpoints = 0, binSize = 100, ...)

## S4 method for signature 'formula,flowFrame'
xyplot(x, data, filter = NULL,
       overlay = NULL, stats = FALSE, strip.text = NULL, ...)

prepanel.xyplot.flowframe(frame, channel.x.name, channel.y.name, x, y,
                           xlim, ylim, ...)

panel.xyplot.flowframe(frame, filter = NULL, smooth = TRUE,
                        margin = TRUE, outline = FALSE, channel.x.name, channel.y.name,
                        pch = gp$flow.symbol$pch, alpha = gp$flow.symbol$alpha,
                        cex = gp$flow.symbol$cex, col = gp$flow.symbol$col, gp, xbins = 0,
                        binTrans = sqrt, stats = FALSE, pos = 0.5, digits = 2,
                        abs = FALSE, overlay = NULL, checkName = TRUE, sample.ratio = 1,
                        overlay.symbol = NULL, ...)

## S4 method for signature 'formula,flowSet'
xyplot(x, data, ...)

prepanel.xyplot.flowset(x, frames, channel.x.name, channel.y.name, xlim,
                        ylim, ...)

panel.xyplot.flowset(x, frames, filter = NULL, channel.x, channel.y,
                     overlay = NULL, stats = FALSE, ...)

## S4 method for signature 'formula,view'
xyplot(x, data, ...)

## S4 method for signature 'view,missing'
xyplot(x, data, ...)

## S4 method for signature 'formula,gateView'
xyplot(x, data, filter = NULL, par.settings,
       ...)

## S4 method for signature 'formula,ncdfFlowSet'
xyplot(x, data, ...)

## S4 method for signature 'formula,ncdfFlowList'
xyplot(x, data, ...)

```

Arguments

x	A formula describing the structure of the plot and the variables to be used in the display. In the <code>prepanel</code> and <code>panel</code> functions, also the names of <code>flowFrames</code> or any of the annotation data columns in the <code>phenoData</code> slot.
data, y, frame	a <code>flowSet</code> , <code>flowFrame</code> , <code>ncdfFlowSet</code> , or <code>ncdfFlowList</code> object that serves as the source of data.
time	A character string giving the name of the data column recording time. If not provided, we try to guess from the available parameters.
xlab, ylab	Labels for data axes, with suitable defaults taken from the formula.
layout	These arguments are passed unchanged to the corresponding methods in <code>lattice</code> , and are listed here only because they provide different defaults. See documentation for the original methods for details.
prepanel	The <code>prepanel</code> function. See <code>xyplot</code> .
panel	The <code>panel</code> function. See <code>xyplot</code> .
type	type of rendering; see <code>panel.xyplot</code> for details. For the basic <code>flowFrame</code> method without a detailed formula, the additional type <code>discrete</code> is available, which plots a smoothed average of the flow cytometry values against time.
...	<code>marker.only</code> logical specifies whether to show both channel and marker names More arguments, usually passed on to the underlying <code>lattice</code> methods.
xlim, ylim	limits for data axes. If not given, they are taken from the ranges stored in <code>flowFrame</code>
nrpoints	The number of points plotted on the smoothed plot in sparse regions. This is only listed here because we use a different default. See <code>panel.smoothScatter</code> for details.
binSize	The size of a bin (i.e., the number of events within a bin) used for the smoothed average timeline plots.
filter	A <code>filter</code> , <code>filterResult</code> or <code>filterResultList</code> object or a list of such objects of the same length as the <code>flowSet</code> . Also a <code>filters</code> or a <code>filtersList</code> can be passed to <code>xyplot</code> in order to plot multiple filters/gates (with the same x,y parameters) on one panel to represent multiple sub-populations. The appropriate spherical 2D representation of this filter will be superimposed on the plot if <code>smooth=TRUE</code> , or the result of the filtering operation will be indicated by grouping if <code>smooth=FALSE</code> . The software will figure out whether the filter needs to be evaluated in order to be plotted (in which case providing a <code>filterResult</code> can speed things up considerably).
overlay	The extra cell events plotted on top of the current cell population. It is a <code>flowSet</code> for <code>panel.xyplot.flowset</code> function and a <code>flowFrame</code> for <code>xyplot(c("formula", "flowFrame"))</code> method.
stats, pos, digits, abs	Arguments to control statistics that is associated with <code>filter</code> to be plotted. Currently only population proportion/percentage is supported. <code>stats</code> is a logical scalar indicating whether to display statistics. Default is <code>FALSE</code> . <code>pos</code> is the numeric scalar (range within <code>c(0,1)</code>) or vector (length of 2, first is for x-axis, second for y-axis) to control the position of the statistics label. It is set as 0.5, which is the center. <code>digits</code> is an integer indicating the number of significant digits to be used when displaying the percentage of population statistics. Default is 2. see more details from <code>format</code> <code>abs</code> is a logical scalar indicating whether the <code>pos</code> is relative to the gate boundary or the entire xy-axis (absolute position). By default it is set as <code>FALSE</code> , which indicates the position is relative to gate.

strip.text	A character that customizes the text in strip. Default is NULL, which does not display the strip box at all. It is only valid when plotting a flowFrame
channel.x.name, channel.y.name	Character strings giving corresponding names used to match filter parameters if applicable.
smooth	Logical. If TRUE, panel.smoothScatter is used to display a partially smoothed version of the data. Otherwise, events are plotted individually, as in a standard scatter plot. If FALSE, a graphical parameter colramp can be used to obtain a coloring of points that is indicative of their local density.
margin	Logical indicating whether to truncate the density estimation on the margins of the measurement range and plot margin events as lines if smooth=TRUE. To avoid visual artifacts it is highly recommended to set this option to TRUE.
outline	Logical, specifying whether to add the boundaries of a gate to the plot when smooth=FALSE in addition to the grouping. Defaults to FALSE.
pch, cex, col, alpha	Graphical parameters used when smooth=FALSE. These mostly exist for convenience and much more control is available through the lattice-like par.setting and flowViz.par.set customization. See flowViz.par.set for details.
gp	A list of graphical parameters that are passed down to the low level panel functions. This is for internal use only. The public user interface to set graphical parameters is either par.settings for customization of a single call or flowViz.par.set for customization of session-wide defaults.
xbins	The argument passed to hexbin , which is the number of bins partitioning the range of xbands. It is set as 0 by default, which plots all the events without binning. When it is larger than 0, hexbin plot engine is used for the faster plotting. Note that it is only valid when smooth is set as FALSE.
binTrans	The argument passed to grid.hexagons , which is a transformation function (or NULL) for the count. It is sqrt by default.
checkName	logical indicating whether to skip checking the bracket '(' in channel name
sample.ratio	numeric the ratio of sub-sampling of events to speed up plotting.
overlay.symbol	list of the lattice graphic parameters to format the overlay points.
frames	An environment containing frame-specific data.
channel.x, channel.y	Expressions defining the x and y variables in terms of columns in the data. Can involve functions or multiple columns from the data, however this usage is discouraged.
par.settings	A list of lists of graphical parameters. See flowViz.par.set for details.

Details

The implementation of xyplot in flowViz is very close to the original lattice version. Concepts like conditioning and the use of panels apply directly to the flow cytometry data. The single fundamental difference is that conditioning variables are not evaluated in the context of the raw data, but rather in the phenoData slot environment (only for the flowSet methods). Thus, we can directly condition on phenotypic variables like sample groups, patients or treatments.

In the formula interface, the primary and secondary variables (separated by the tilde) have to be valid parameter names. Please note that frequently used variants like FSC-H and SSC-H are not syntactically correct R symbols, and need to be wrapped in ``. E.g., `FSC-H`. For flowSets, the use of a conditioning variable is optional. We implicitly condition on flowFrames and the default is to arrange panels by sample names.

Methods

xyplot signature(x = "flowFrame", data = "missing"): Creates diagnostic time series plots of flow parameter values against time. These plots are useful to detect quality issues in the raw data. If not provided explicitly via the time argument, the time parameter will be automatically detected. The additional arguments xlab, ylab, nrpoin, and layout are only listed because flowViz provides different defaults. Internally, they are directly passed on to the underlying lattice functions. Argument type can be a combination of any of the types allowed in lattice xyplots, or discrete, in which case a smoothed average of the parameter against time is plotted. binSize controls the binning that is used for the smoothing procedure.

xyplot signature(x = "formula", data = "flowFrame"): Creates scatter plots (a.k.a. dot plots) of a pair of FCM channels. Depending on the setting of the smooth argument, the data will be rendered as a partially smoothed density estimate (smooth=TRUE, the default) or as a regular scatter plot with separate points for individual events. The formula interface allows for fairly general plotting, however there are certain limitations on the use of expressions as part of the formulae. Unless you are sure about what you are doing, you should transform the raw data in a separate step using one of the tools in the flowCore package rather than inline using the formula interface. The method allows to superimpose gating results through the filter argument. If smooth=TRUE, we try to add spherical 2D representations of the gates if applicable. For smooth=FALSE, gates are indicated by a grouping mechanism using different point shapes or colors (unless outline is also TRUE, in which case the gate outlines are superimposed in addition to the grouping). Argument margins controls how events on the margins of the measurement range are treated. The default (TRUE) is to discard them from any density estimation and later add them as separate glyphs. Argument par.settings can be used to supply lists of graphical parameters. See flowViz.par.set for details on controlling graphical parameters in these plots.

xyplot signature(x = "formula", data = "flowSet"): Scatter plots from a flowSet object. We allow for conditioning on variables in the phenoData slot of the flowSet. All additional arguments that apply to the flowFrame method are also valid for flowSets.

Author(s)

F. Hahne, D. Sarkar

See Also

Not all standard lattice arguments will have the intended effect, but many should. For a fuller description of possible arguments and their effects, consult documentation on lattice.

Examples

```
library(flowCore)
data(GvHD)
GvHD <- GvHD[pData(GvHD)$Patient %in% 5:6]

## a bivariate scatterplot
## by default ('smooth=TRUE') panel.smoothScatter is used
xyplot(`FSC-H` ~ `SSC-H`, GvHD[["s5a05"]], nbin = 100,
main="A single flowFrame")

## A non-smooth version of the same data
xyplot(`FSC-H` ~ `SSC-H`, GvHD[["s5a05"]], nbin = 100,
main="A single flowFrame", smooth=FALSE)
```



```

## A non-smooth version of the same data with customized color scheme
require(IDPmisc)
colramp <- colorRampPalette(IDPcolorRamp(21))
xyplot(`FSC-H` ~ `SSC-H`, GvHD[["s5a05"]], nbin = 100,
      main="A single flowFrame", smooth=FALSE,
      colramp=colramp, pch=20, cex=0.1)

## A hexbin version of non-smooth scatter plot
xyplot(`FSC-H` ~ `SSC-H`, GvHD[["s5a05"]], xbin = 128
      ,main="A single flowFrame", smooth=FALSE)

## Visual artifacts created by the pileup of margin events
xyplot(`FSC-H` ~ `SSC-H`, GvHD[["s5a05"]], nbin = 100,
      main="A single flowFrame", margin=FALSE)

## simple bivariate scatter plot (a.k.a. dot plot)
## for the whole flowSet, conditioning on Patient and
## Visit
xyplot(`SSC-H` ~ `FSC-H` | Patient:Visit, data = GvHD)

## Same bivariate scatter plot with replacing default color
require(IDPmisc)
cols <- colorRampPalette(IDPcolorRamp(21))
xyplot(`SSC-H` ~ `FSC-H` | Patient:Visit, data = GvHD, colramp=cols)

## several examples with time on the X axis
## first for a flowFrame
xyplot(GvHD[[1]])

## and for flowSets
xyplot(`FSC-H` ~ Time | Visit, GvHD,
      smooth = FALSE, type = "l",
      subset = (Patient == 5), xbin = 32)

xyplot(`FSC-H` ~ Time | Patient+Visit, GvHD,
      smooth = FALSE, type = "a",
      strip = FALSE, strip.left = TRUE,
      aspect = "xy", xbin = 32)

## combine plots for two channels
ssc.time <-
  xyplot(`SSC-H` ~ Time | factor(Patient):factor(Visit), GvHD,
        smooth = FALSE, type = "a",
        strip = FALSE,
        strip.left = strip.custom(horizontal = TRUE),
        par.strip.text = list(lines = 3),
        between = list(y = rep(c(0, 0.5), c(6, 1))),
        scales = list(x = list(axes = "i"), y = list(draw = FALSE)),
        layout = c(1, 14), xbin = 32)

fsc.time <-
  xyplot(`FSC-H` ~ Time | factor(Patient):factor(Visit), GvHD,

```

```

    smooth = FALSE, type = "a",
    strip = FALSE,
    strip.left = strip.custom(horizontal = TRUE),
    par.strip.text = list(lines = 3),
    between = list(y = rep(c(0, 0.5), c(6, 1))),
    scales = list(x = list(axes = "i"), y = list(draw = FALSE)),
    layout = c(1, 14), xbin = 32)

plot(fsc.time, split = c(1, 1, 2, 1))
plot(ssc.time, split = c(2, 1, 2, 1), newpage = FALSE)

## saving plots as variables allows more manipulation
plot(update(fsc.time[8:14], layout = c(1, 7)),
      split = c(1, 1, 1, 2))

plot(update(ssc.time[8:14], layout = c(1, 7)),
      split = c(1, 2, 1, 2), newpage = FALSE)

## displaying filters
library(flowStats)
n2gate <- norm2Filter("SSC-H", "FSC-H")

xyplot(`SSC-H` ~ `FSC-H` | Patient:Visit, data = GvHD,
       filter=n2gate, subset=Patient==5)

xyplot(`SSC-H` ~ `FSC-H` | Patient:Visit,
       data=transform("SSC-H"=asinh,"FSC-H"=asinh) %on% GvHD,
       smooth=FALSE, filter=n2gate, subset=Patient == 5, xbin = 32)

## displaying filters with stats
n2gate.results <- filter(GvHD, n2gate)

xyplot(`SSC-H` ~ `FSC-H` | Visit, data=GvHD,
       subset=Patient == "6",
       filter=n2gate.results, smooth=FALSE, xbin = 32
       ,stats=TRUE
       ,abs=TRUE
       ,digits=3
       )

## displaying multiple filters in one panel with stats
recGate1<-rectangleGate("FL3-H"=c(2.3,4.1),"FL2-H"=c(6.8,9))
recGate2<-rectangleGate("FL3-H"=c(1,3),"FL2-H"=c(4,6))
filters1<-filters(list(recGate1,recGate2))
trans<-transform("FL2-H"=asinh,"FL3-H"=asinh)
trans_data<-transform(GvHD[1:2],trans)
#replicate filters object across samples
flist <- list(filters1 , filters1)
names(flist) <- sampleNames(trans_data)
xyplot(`FL2-H` ~ `FL3-H`
       ,data=trans_data
       ,filter= flist
       ,stats=TRUE

```

```
    ,margin=FALSE
    , xbin = 32
    , smooth = FALSE
  )

#display recGate2 as a overlay
overlay <- Subset(trans_data,recGate1)
xyplot(`FL2-H` ~ `FL3-H`
      ,data=trans_data
      ,filter=recGate2
      ,stats=TRUE
      ,margin=FALSE
      , smooth = FALSE
      , xbin = 32
      ,overlay= list(rect2 = overlay)
      ,par.settings = list(overlay.symbol = list(cex = 0.1))
  )
```

Index

* **dplot**

- levelplot, formula, flowSet-method, 21
- prepanel.ecdfplot.flowset, 24
- splom, 25
- timeLinePlot, 27
- xypLOT, flowFrame, missing-method, 28

* **methods**

- addName-methods, 4
- contour-methods, 5
- flowPlot, 9
- glines-methods, 13
- glpoints-methods, 14
- glpolygon-methods, 16
- gpolygon-methods, 18
- gpolygon-methods, 19
- levelplot, formula, flowSet-method, 21
- plot, 23
- prepanel.ecdfplot.flowset, 24
- splom, 25
- timeLinePlot, 27
- xypLOT, flowFrame, missing-method, 28

* **package**

- flowViz-package, 2
- .process_flowFrame_overlay, 3
- .process_overlay_flowSet, 3

- addName (addName-methods), 4
- addName, curv1Filter, character-method (addName-methods), 4
- addName, curv1Filter, logical-method (addName-methods), 4
- addName, curv2Filter, character-method (addName-methods), 4
- addName, curv2Filter, logical-method (addName-methods), 4
- addName, ellipsoidGate, character-method (addName-methods), 4
- addName, ellipsoidGate, logical-method (addName-methods), 4

- addName, kmeansFilter, character-method (addName-methods), 4
- addName, kmeansFilter, logical-method (addName-methods), 4
- addName, polygonGate, character-method (addName-methods), 4
- addName, polygonGate, logical-method (addName-methods), 4
- addName, quadGate, character-method (addName-methods), 4
- addName, quadGate, logical-method (addName-methods), 4
- addName, quadGate, matrix-method (addName-methods), 4
- addName, rectangleGate, character-method (addName-methods), 4
- addName, rectangleGate, logical-method (addName-methods), 4
- addName-methods, 4

- bkde2D, 5, 6

- contour, 5, 6
- contour (contour-methods), 5
- contour, ANY-method (contour-methods), 5
- contour, flowFrame-method (contour-methods), 5
- contour, flowSet-method (contour-methods), 5
- contour-methods, 5
- curv1Filter, 13, 15, 17, 18, 20
- curv2Filter, 13, 15, 17, 19, 20

- density, 8
- densityplot, 6, 24
- densityplot, formula, flowFrame-method (densityplot), 6
- densityplot, formula, flowSet-method (densityplot), 6
- densityplot, formula, ncdfFlowList-method (densityplot), 6
- densityplot, formula, ncdfFlowSet-method (densityplot), 6

- densityplot, formula, view-method
(densityplot), 6
- ecdfplot, 24
- ecdfplot (prepanel.ecdfplot.flowset), 24
- ecdfplot, formula, flowSet-method
(prepanel.ecdfplot.flowset), 24
- ellipsoidGate, 21
- filter, 4, 8, 13–21, 30
- filterResult, 4, 8, 13, 15, 17–20, 30
- filterResultList, 8, 30
- filters, 30
- filtersList, 30
- flowCore, 2, 10, 32
- flowFrame, 5–7, 13–21, 23, 24, 26–28, 30
- flowFrames, 14, 16, 30
- flowPlot, 9
- flowPlot, flowFrame-method (flowPlot), 9
- flowSet, 5–7, 27, 28
- flowSets, 6
- flowViz (flowViz-package), 2
- flowViz-package, 2
- flowViz.par.get, 11
- flowViz.par.set, 8, 31, 32
- flowViz.par.set (flowViz.par.get), 11
- format, 30
- glines, 19, 21
- glines (glines-methods), 13
- glines, curv1Filter, ANY-method
(glines-methods), 13
- glines, curv1Filter, flowFrame-method
(glines-methods), 13
- glines, curv1Filter, missing-method
(glines-methods), 13
- glines, curv1Filter, multipleFilterResult-method
(glines-methods), 13
- glines, curv2Filter, ANY-method
(glines-methods), 13
- glines, curv2Filter, flowFrame-method
(glines-methods), 13
- glines, curv2Filter, multipleFilterResult-method
(glines-methods), 13
- glines, ellipsoidGate, character-method
(glines-methods), 13
- glines, ellipsoidGate, filterResult-method
(glines-methods), 13
- glines, ellipsoidGate, flowFrame-method
(glines-methods), 13
- glines, filter, missing-method
(glines-methods), 13
- glines, filterResult, ANY-method
(glines-methods), 13
- glines, filterResult, flowFrame-method
(glines-methods), 13
- glines, kmeansFilter, ANY-method
(glines-methods), 13
- glines, norm2Filter, ANY-method
(glines-methods), 13
- glines, norm2Filter, flowFrame-method
(glines-methods), 13
- glines, norm2Filter, flowStats-method
(glines-methods), 13
- glines, norm2Filter, logicalFilterResult-method
(glines-methods), 13
- glines, polygonGate, character-method
(glines-methods), 13
- glines, polygonGate, filterResult-method
(glines-methods), 13
- glines, polygonGate, flowFrame-method
(glines-methods), 13
- glines, quadGate, character-method
(glines-methods), 13
- glines, quadGate, filterResult-method
(glines-methods), 13
- glines, quadGate, flowFrame-method
(glines-methods), 13
- glines, rectangleGate, character-method
(glines-methods), 13
- glines, rectangleGate, filterResult-method
(glines-methods), 13
- glines, rectangleGate, flowFrame-method
(glines-methods), 13
- glines-methods, 13
- glpoints, 17
- glpoints (glpoints-methods), 14
- glpoints, curv1Filter, flowFrame, character-method
(glpoints-methods), 14
- glpoints, curv2Filter, flowFrame, character-method
(glpoints-methods), 14
- glpoints, ellipsoidGate, flowFrame, character-method
(glpoints-methods), 14
- glpoints, filter, flowFrame, missing-method
(glpoints-methods), 14
- glpoints, filter, missing, ANY-method
(glpoints-methods), 14
- glpoints, filterResult, flowFrame, ANY-method
(glpoints-methods), 14
- glpoints, filterResult, flowFrame, character-method
(glpoints-methods), 14
- glpoints, kmeansFilter, flowFrame, character-method
(glpoints-methods), 14
- glpoints, norm2Filter, flowFrame, character-method

- (glpoints-methods), 14
- glpoints, polygonGate, flowFrame, character-method (glpoints-methods), 14
- glpoints, quadGate, flowFrame, character-method (glpoints-methods), 14
- glpoints, rectangleGate, flowFrame, character-method (glpoints-methods), 14
- glpoints, subsetFilter, flowFrame, ANY-method (glpoints-methods), 14
- glpoints-methods, 14
- glpolygon, 16
- glpolygon (glpolygon-methods), 16
- glpolygon, complementFilter, ANY-method (glpolygon-methods), 16
- glpolygon, curv1Filter, ANY-method (glpolygon-methods), 16
- glpolygon, curv1Filter, flowFrame-method (glpolygon-methods), 16
- glpolygon, curv1Filter, missing-method (glpolygon-methods), 16
- glpolygon, curv1Filter, multipleFilterResult-method (glpolygon-methods), 16
- glpolygon, curv2Filter, ANY-method (glpolygon-methods), 16
- glpolygon, curv2Filter, flowFrame-method (glpolygon-methods), 16
- glpolygon, curv2Filter, multipleFilterResult-method (glpolygon-methods), 16
- glpolygon, ellipsoidGate, character-method (glpolygon-methods), 16
- glpolygon, ellipsoidGate, filterResult-method (glpolygon-methods), 16
- glpolygon, ellipsoidGate, flowFrame-method (glpolygon-methods), 16
- glpolygon, filter, missing-method (glpolygon-methods), 16
- glpolygon, filterResult, ANY-method (glpolygon-methods), 16
- glpolygon, filterResult, flowFrame-method (glpolygon-methods), 16
- glpolygon, filterResult, missing-method (glpolygon-methods), 16
- glpolygon, kmeansFilter, ANY-method (glpolygon-methods), 16
- glpolygon, norm2Filter, ANY-method (glpolygon-methods), 16
- glpolygon, norm2Filter, flowFrame-method (glpolygon-methods), 16
- glpolygon, norm2Filter, logicalFilterResult-method (glpolygon-methods), 16
- glpolygon, polygonGate, character-method (glpolygon-methods), 16
- glpolygon, polygonGate, filterResult-method (glpolygon-methods), 16
- glpolygon, polygonGate, flowFrame-method (glpolygon-methods), 16
- glpolygon, quadGate, character-method (glpolygon-methods), 16
- glpolygon, quadGate, filterResult-method (glpolygon-methods), 16
- glpolygon, quadGate, flowFrame-method (glpolygon-methods), 16
- glpolygon, rectangleGate, character-method (glpolygon-methods), 16
- glpolygon, rectangleGate, filterResult-method (glpolygon-methods), 16
- glpolygon, rectangleGate, flowFrame-method (glpolygon-methods), 16
- glpolygon, subsetFilter, ANY-method (glpolygon-methods), 16
- glpolygon-methods, 16
- gpolygon, 14, 21
- gpolygon (gpolygon-methods), 18
- gpolygon, curv1Filter, flowFrame, character-method (gpolygon-methods), 18
- gpolygon, curv2Filter, flowFrame, character-method (gpolygon-methods), 18
- gpolygon, filter, flowFrame, missing-method (gpolygon-methods), 18
- gpolygon, filter, missing, ANY-method (gpolygon-methods), 18
- gpolygon, filterResult, flowFrame, character-method (gpolygon-methods), 18
- gpolygon, kmeansFilter, flowFrame, character-method (gpolygon-methods), 18
- gpolygon, norm2Filter, flowFrame, character-method (gpolygon-methods), 18
- gpolygon, polygonGate, flowFrame, character-method (gpolygon-methods), 18
- gpolygon, quadGate, flowFrame, character-method (gpolygon-methods), 18
- gpolygon, rectangleGate, flowFrame, character-method (gpolygon-methods), 18
- gpolygon-methods, 18
- gpolygon, 19
- gpolygon (gpolygon-methods), 19
- gpolygon, curv1Filter, ANY-method (gpolygon-methods), 19
- gpolygon, curv1Filter, flowFrame-method (gpolygon-methods), 19
- gpolygon, curv1Filter, missing-method (gpolygon-methods), 19
- gpolygon, curv1Filter, multipleFilterResult-method (gpolygon-methods), 19

- gpolygon, curv2Filter, ANY-method
(gpolygon-methods), 19
- gpolygon, curv2Filter, flowFrame-method
(gpolygon-methods), 19
- gpolygon, curv2Filter, multipleFilterResult-method
(gpolygon-methods), 19
- gpolygon, ellipsoidGate, character-method
(gpolygon-methods), 19
- gpolygon, ellipsoidGate, filterResult-method
(gpolygon-methods), 19
- gpolygon, ellipsoidGate, flowFrame-method
(gpolygon-methods), 19
- gpolygon, filter, missing-method
(gpolygon-methods), 19
- gpolygon, filterResult, ANY-method
(gpolygon-methods), 19
- gpolygon, filterResult, flowFrame-method
(gpolygon-methods), 19
- gpolygon, kmeansFilter, ANY-method
(gpolygon-methods), 19
- gpolygon, norm2Filter, ANY-method
(gpolygon-methods), 19
- gpolygon, norm2Filter, flowFrame-method
(gpolygon-methods), 19
- gpolygon, norm2Filter, logicalFilterResult-method
(gpolygon-methods), 19
- gpolygon, polygonGate, character-method
(gpolygon-methods), 19
- gpolygon, polygonGate, filterResult-method
(gpolygon-methods), 19
- gpolygon, polygonGate, flowFrame-method
(gpolygon-methods), 19
- gpolygon, quadGate, character-method
(gpolygon-methods), 19
- gpolygon, quadGate, filterResult-method
(gpolygon-methods), 19
- gpolygon, quadGate, flowFrame-method
(gpolygon-methods), 19
- gpolygon, rectangleGate, character-method
(gpolygon-methods), 19
- gpolygon, rectangleGate, filterResult-method
(gpolygon-methods), 19
- gpolygon, rectangleGate, flowFrame-method
(gpolygon-methods), 19
- gpolygon-methods, 19
- grid.hexagons, 31
- hexbin, 31
- histogram, 23
- histogram, formula, flowFrame-method
(densityplot), 6
- histogram, formula, flowSet-method
(densityplot), 6
- histogram, formula, ncdfflowList-method
(densityplot), 6
- histogram, formula, ncdfflowSet-method
(densityplot), 6
- kde2d, 22
- kmeansFilter, 13, 17, 20
- lattice-methods
(levelplot, formula, flowSet-method),
21
- levelplot, formula, flowSet-method, 21
- lines, 13
- lpoints, 14
- lpolygon, 16
- norm2Filter, 13, 17, 20
- panel.abline, 8
- panel.densityplot.flowset.stack
(densityplot), 6
- panel.ecdfplot.flowset
(prepanel.ecdfplot.flowset), 24
- panel.smoothScatter, 30
- panel.splom.flowframe (splom), 25
- panel.xyplot, 30
- panel.xyplot.flowframe
(xyplot, flowFrame, missing-method),
28
- panel.xyplot.flowset
(xyplot, flowFrame, missing-method),
28
- parallel, flowFrame, missing-method
(levelplot, formula, flowSet-method),
21
- parallel, formula, flowSet-method
(levelplot, formula, flowSet-method),
21
- pdf, 22
- plot, 23
- plot, flowFrame, character-method (plot),
23
- plot, flowFrame, missing-method (plot), 23
- points, 18
- polygon, 19
- polygonGate, 14, 17, 20
- prepanel.densityplot.flowset.stack
(densityplot), 6
- prepanel.ecdfplot.flowset, 24
- prepanel.xyplot.flowframe
(xyplot, flowFrame, missing-method),
28

- prepanel.xyplot.flowset
 - (xyplot, flowFrame, missing-method),
28
- qqmath, 22
- qqmath, formula, flowSet-method
 - (levelplot, formula, flowSet-method),
21
- quadGate, 14, 17, 20
- rectangleGate, 14, 17, 20
- smoothScatter, 23, 24
- splom, 23, 25
- splom, flowFrame, missing-method (splom),
25
- sqrt, 31
- timeLinePlot, 27
- timelineplot (timeLinePlot), 27
- timeLinePlot, ANY, missing-method
 - (timeLinePlot), 27
- timeLinePlot, flowFrame, character-method
 - (timeLinePlot), 27
- timeLinePlot, flowSet, character-method
 - (timeLinePlot), 27
- trellis.par.get, 11, 12
- trellis.par.set, 11, 12
- xyplot, 7, 8, 24, 25, 30
- xyplot
 - (xyplot, flowFrame, missing-method),
28
 - xyplot, flowFrame, missing-method, 28
 - xyplot, formula, flowFrame-method
 - (xyplot, flowFrame, missing-method),
28
 - xyplot, formula, flowSet-method
 - (xyplot, flowFrame, missing-method),
28
 - xyplot, formula, gateView-method
 - (xyplot, flowFrame, missing-method),
28
 - xyplot, formula, ncdfFlowList-method
 - (xyplot, flowFrame, missing-method),
28
 - xyplot, formula, ncdfFlowSet-method
 - (xyplot, flowFrame, missing-method),
28
 - xyplot, formula, view-method
 - (xyplot, flowFrame, missing-method),
28
 - xyplot, view, missing-method
 - (xyplot, flowFrame, missing-method),
28
 - xyplots, 26