

Package ‘snifter’

March 30, 2021

Type Package

Title R wrapper for the python openTSNE library

Version 1.0.0

Date 2020-10-14

Depends R (>= 4.0.0)

Imports basilisk, reticulate, assertthat

Description Provides an R wrapper for the implementation of FI-tSNE from the python package openTSNE. See Poličar et al. (2019) <doi:10.1101/731877> and the algorithm described by Linderman et al. (2018) <doi:10.1038/s41592-018-0308-4>.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

VignetteBuilder knitr

biocViews DimensionReduction, Visualization, Software, SingleCell, Sequencing

StagedInstall no

BugReports <https://github.com/Alanocallaghan/snifter/issues>

Suggests knitr, rmarkdown, scRNAseq, BiocStyle, scater, scan, scuttle, ggplot2, testthat

git_url <https://git.bioconductor.org/packages/snifter>

git_branch RELEASE_3_12

git_last_commit 9f53809

git_last_commit_date 2020-10-27

Date/Publication 2021-03-29

Author Alan O'Callaghan [aut, cre],
Aaron Lun [aut]

Maintainer Alan O'Callaghan <alan.ocallaghan@outlook.com>

R topics documented:

project	2
snifter	3

Index

7

project	<i>Project new data into an existing t-SNE embedding object.</i>
---------	--

Description

Project new data into an existing t-SNE embedding object.

Usage

```
project(
  x,
  new,
  old,
  perplexity = 5,
  initialization = c("median", "weighted", "random"),
  k = 25L,
  learning_rate = 0.1,
  early_exaggeration = 4,
  early_exaggeration_iter = 0L,
  exaggeration = 1.5,
  n_iter = 250L,
  initial_momentum = 0.5,
  final_momentum = 0.8,
  max_grad_norm = 0.25,
  tolerance = 1e-04
)
```

Arguments

x	t-SNE embedding created with fitsne .
new	New data to project into existing embedding
old	Data used to create the original embedding.
perplexity	Numeric scalar. Perplexity can be thought of as the continuous number of nearest neighbors, for which t-SNE will attempt to preserve distances. However, when projecting, we only consider neighbors in the existing embedding i.e. each data point is placed into the embedding, independently of other new data points.
initialization	Character scalar specifying the method used to compute the initial point positions to be used in the embedding space. Can be "median", "weighted" or "random". In all cases, "median" or "weighted" should be preferred.
k	Integer scalar specifying the number of nearest neighbors to consider when initially placing the point onto the embedding. This is different from "perplexity" because perplexity affects optimization while this only affects the initial point positions.
learning_rate	The learning rate for t-SNE optimization. When learning_rate="auto" the appropriate learning rate is selected according to $\max(200, N / 12)$, as determined in Belkina et al. Otherwise, a numeric scalar.
early_exaggeration	Numeric scalar; the exaggeration factor to use during the <i>*early exaggeration*</i> phase. Typical values range from 12 to 32.

early_exaggeration_iter	The number of iterations to run in the *early exaggeration* phase.
exaggeration	The exaggeration factor to use during the normal optimization phase. This can be used to form more densely packed clusters and is useful for large data sets.
n_iter	The number of iterations to run in the normal optimization regime.
initial_momentum	The momentum to use during the *early exaggeration* phase.
final_momentum	The momentum to use during the normal optimization phase.
max_grad_norm	Maximum gradient norm. If the norm exceeds this value, it will be clipped. When adding points into an existing embedding, and the new points overlap with the reference points, this may lead to large gradients. This can make points "shoot off" from the embedding, causing the interpolation method to compute a very large grid, and leads to worse results.
tolerance	Numeric scalar specifying the numeric tolerance used to ensure the affinities calculated on the old data match those of the original embedding.

Value

Numeric matrix of t-SNE co-ordinates resulting from embedding new into the t-SNE embedding x.

References

Automated optimized parameters for T-distributed stochastic neighbor embedding improve visualization and analysis of large datasets. Belkina, A.C., Ciccolella, C.O., Anno, R. et al. Nature Communications 10, 5415 (2019). doi: <https://doi.org/10.1038/s41467-019-13055-y>

Examples

```
set.seed(42)
m <- matrix(rnorm(2000), ncol=20)
out_binding <- fitsne(m[-(1:2), ], random_state = 42L)
new_points <- project(out_binding, new = m[1:2, ], old = m[-(1:2), ])
plot(as.matrix(out_binding), col = "black", pch = 19,
     xlab = "t-SNE 1", ylab = "t-SNE 2")
points(new_points, col = "red", pch = 19)
```

snifter

snifter: fast interpolated t-SNE in R An R package for running openTSNE's implementation of fast interpolated t-SNE.

Description

See [the openTSNE documentation](#) for further details on these arguments and the general usage of this algorithm.

Usage

```
fitsne(
  x,
  simplified = FALSE,
  n_components = 2L,
  n_jobs = 1L,
  perplexity = 30,
  n_iter = 500L,
  initialization = c("pca", "spectral", "random"),
  neighbors = c("auto", "exact", "annoy", "pynndescent", "approx"),
  negative_gradient_method = c("fft", "bh"),
  learning_rate = "auto",
  early_exaggeration = 12,
  early_exaggeration_iter = 250L,
  exaggeration = NULL,
  dof = 1,
  theta = 0.5,
  n_interpolation_points = 3L,
  min_num_intervals = 50L,
  ints_in_interval = 1,
  metric = "euclidean",
  metric_params = NULL,
  initial_momentum = 0.5,
  final_momentum = 0.8,
  max_grad_norm = NULL,
  random_state = NULL,
  verbose = FALSE
)
```

Arguments

<code>x</code>	Input data matrix.
<code>simplified</code>	Logical scalar. When <code>FALSE</code> , the function returns an object of class <code>snifter</code> . This contains all information necessary to project new data into the embedding using project . If <code>TRUE</code> , all extra attributes will be omitted, and the return value is a base matrix.
<code>n_components</code>	Number of t-SNE components to be produced.
<code>n_jobs</code>	Integer scalar specifying the number of cores to be used.
<code>perplexity</code>	Numeric scalar controlling the neighborhood used when estimating the embedding.
<code>n_iter</code>	Integer scalar specifying the number of iterations to complete.
<code>initialization</code>	Character scalar specifying the initialization to use. "pca" may preserve global distance better than other options.
<code>neighbors</code>	Character scalar specifying the nearest neighbour algorithm to use.
<code>negative_gradient_method</code>	Character scalar specifying the negative gradient approximation to use. "bh", referring to Barnes-Hut, is more appropriate for smaller data sets, while "fft" referring to fast Fourier transform, is more appropriate.
<code>learning_rate</code>	Numeric scalar specifying the learning rate, or the string "auto", which uses $\max(200, N / 12)$, where N is the number of observations.

early_exaggeration	Numeric scalar specifying the exaggeration factor to use during the early exaggeration phase. Typical values range from 12 to 32.
early_exaggeration_iter	Integer scalar specifying the number of iterations to run in the early exaggeration phase.
exaggeration	Numeric scalar specifying the exaggeration factor to use during the normal optimization phase. This can be used to form more densely packed clusters and is useful for large data sets.
dof	Numeric scalar specifying the degrees of freedom, as described in Kobak et al. "Heavy-tailed kernels reveal a finer cluster structure in t-SNE visualisations", 2019.
theta	Numeric scalar, only used when <code>negative_gradient_method="bh"</code> . This is the trade-off parameter between speed and accuracy of the tree approximation method. Typical values range from 0.2 to 0.8. The value 0 indicates that no approximation is to be made and produces exact results also producing longer runtime.
n_interpolation_points	Integer scalar, only used when <code>negative_gradient_method="fft"</code> . The number of interpolation points to use within each grid cell for interpolation based t-SNE. It is highly recommended leaving this value at the default 3.
min_num_intervals	Integer scalar, only used when <code>negative_gradient_method="fft"</code> . The minimum number of grid cells to use, regardless of the <code>ints_in_interval</code> parameter. Higher values provide more accurate gradient estimations.
ints_in_interval	Numeric scalar, only used when <code>negative_gradient_method="fft"</code> . Indicates how large a grid cell should be e.g. a value of 3 indicates a grid side length of 3. Lower values provide more accurate gradient estimations.
metric	Character scalar specifying the metric to be used to compute affinities between points in the original space.
metric_params	Named list of additional keyword arguments for the metric function.
initial_momentum	Numeric scalar specifying the momentum to use during the early exaggeration phase.
final_momentum	Numeric scalar specifying the momentum to use during the normal optimization phase.
max_grad_norm	Numeric scalar specifying the maximum gradient norm. If the norm exceeds this value, it will be clipped.
random_state	Integer scalar specifying the seed used by the random number generator.
verbose	Logical scalar controlling verbosity.

Value

A matrix of t-SNE embeddings.

References

openTSNE: a modular Python library for t-SNE dimensionality reduction and embedding Pavlin G. Poličar, Martin Stražar, Blaž Zupan bioRxiv (2019) 731877; doi: <https://doi.org/10.1101/731877>

Fast interpolation-based t-SNE for improved visualization of single-cell RNA-seq data George C. Linderman, Manas Rachh, Jeremy G. Hoskins, Stefan Steinerberger, and Yuval Kluger *Nature Methods* 16, 243–245 (2019) doi: <https://doi.org/10.1038/s41592-018-0308-4>

Accelerating t-SNE using Tree-Based Algorithms Laurens van der Maaten *Journal of Machine Learning Research* (2014) <http://jmlr.org/papers/v15/vandermaaten14a.html>

openTSNE: a modular Python library for t-SNE dimensionality reduction and embedding Pavlin G. Poličar, Martin Stražar, Blaž Zupan *bioRxiv* (2019) 731877; doi: <https://doi.org/10.1101/731877>

Fast interpolation-based t-SNE for improved visualization of single-cell RNA-seq data George C. Linderman, Manas Rachh, Jeremy G. Hoskins, Stefan Steinerberger, and Yuval Kluger *Nature Methods* 16, 243–245 (2019) doi: <https://doi.org/10.1038/s41592-018-0308-4>

Accelerating t-SNE using Tree-Based Algorithms Laurens van der Maaten *Journal of Machine Learning Research* (2014) <http://jmlr.org/papers/v15/vandermaaten14a.html>

Examples

```
set.seed(42)
m <- matrix(rnorm(2000), ncol=20)
out <- fitsne(m, random_state = 42L)
plot(out, pch = 19, xlab = "t-SNE 1", ylab = "t-SNE 2")

## openTSNE allows us to project new points into the existing
## embedding - useful for extremely large data.
## see https://opentsne.readthedocs.io/en/latest/api/index.html

out_binding <- fitsne(m[-(1:2), ], random_state = 42L)
new_points <- project(out_binding, new = m[1:2, ], old = m[-(1:2), ])
plot(as.matrix(out_binding), col = "black", pch = 19,
     xlab = "t-SNE 1", ylab = "t-SNE 2")
points(new_points, col = "red", pch = 19)
```

Index

fitsne, [2](#)
fitsne (snifter), [3](#)
project, [2](#), [4](#)
snifter, [3](#)