

Package ‘HighlyReplicatedRNASeq’

March 29, 2021

Type Package

Title Collection of Bulk RNA-Seq Experiments With Many Replicates

Version 1.2.0

Description Gene-level count matrix data for bulk RNA-seq dataset with many replicates. The data are provided as easy to use SummarizedExperiment objects. The source data that is made accessible through this package comes from <https://github.com/bartongroup/profDGE48>.

URL <https://github.com/const-ae/HighlyReplicatedRNASeq>

BugReports <https://github.com/const-ae/HighlyReplicatedRNASeq/issues>

License MIT + file LICENSE

Encoding UTF-8

Depends SummarizedExperiment, ExperimentHub

Imports S4Vectors

Suggests BiocStyle, BiocFileCache, knitr, rmarkdown

biocViews ExperimentHub, ExperimentData, ExpressionData, SequencingData, RNASeqData

RoxygenNote 7.1.0

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/HighlyReplicatedRNASeq>

git_branch RELEASE_3_12

git_last_commit 8de508b

git_last_commit_date 2020-10-27

Date/Publication 2021-03-29

Author Constantin Ahlmann-Eltze [aut, cre]
(<<https://orcid.org/0000-0002-3762-068X>>)

Maintainer Constantin Ahlmann-Eltze <artjom31415@gmail.com>

R topics documented:

HighlyReplicatedRNASeq	2
Schurch16	2
Index	4

HighlyReplicatedRNASeq

HighlyReplicatedRNASeq: Collection of Bulk RNA-Seq Experiments With Many Replicates

Description

The HighlyReplicatedRNASeq package provides access to the count matrix results from studies with many replicates. These datasets can be valuable for benchmarking tools designed to handle RNA-seq data.

Details

Available datasets:

- Schurch et al. (2016): 86 samples of *S. cerevisiae* in two conditions
 - [Schurch16\(\)](#) / [Schurch16_metadata\(\)](#)

At the moment, this package contains only one dataset, but more datasets can be added in the future.

Schurch16

Get the RNA-seq counts from Schurch et al. (2016)

Description

The data contains bulk RNA-seq count on 86 samples in two conditions. The first condition is wild type *S. cerevisiae* (taxonomic id: 1247190). The second condition is the same strain with a snf2 knockout.

Usage

```
Schurch16(hub = ExperimentHub())
```

```
Schurch16_metadata(hub = ExperimentHub())
```

Arguments

hub an [ExperimentHub](#) object that is used to load the resource "EH3315" and "EH3316".
Default: [ExperimentHub\(\)](#)

Details

Schurch et al. originally generated this dataset to benchmark RNA-seq differential expression tools and find out how many replicates are necessary to detect most differentially expressed genes. The data that is returned by this package comes from the [GitHub repository](#) that accompanied the study.

Value

Schurch16() returns a [SummarizedExperiment](#) with 7126 genes and 86 samples.

Schurch16_metadata() returns a [ExperimentHub](#) object with the metadata on the Schurch16 dataset.

Author(s)

Constantin Ahlmann-Eltze

References

Schurch, N. J., Schofield, P., Gierliński, M., Cole, C., Sherstnev, A., Singh, V., . . . Barton, G. J. (2016). How many biological replicates are needed in an RNA-seq experiment and which differential expression tool should you use? *RNA*, 22(6), 839–851. <https://doi.org/10.1261/rna.053959.115>

Examples

```
Schurch16_metadata()

se <- Schurch16()

dim(se)
colData(se)
summary(c(assay(se, "counts")))
```

Index

ExperimentHub, [2](#)
ExperimentHub(), [2](#)

HighlyReplicatedRNASeq, [2](#)

Schurch16, [2](#)
Schurch16(), [2](#)
Schurch16_metadata (Schurch16), [2](#)
Schurch16_metadata(), [2](#)
SummarizedExperiment, [2](#)