

Package ‘CellaRepertorium’

October 14, 2021

Type Package

Title Data structures, clustering and testing for single cell immune receptor repertoires (scRNAseq RepSeq/AIRR-seq)

Version 1.2.0

Description Methods to cluster and analyze high-throughput single cell immune cell repertoires, especially from the 10X Genomics VDJ solution. Contains an R interface to CD-HIT (Li and Godzik 2006). Methods to visualize and analyze paired heavy-light chain data. Tests for specific expansion, as well as omnibus oligoclonality under hypergeometric models.

License GPL-3

Depends R (>= 4.0)

Imports dplyr, tibble, stringr, Biostrings, Rcpp, reshape2, methods, rlang (>= 0.3), purrr, Matrix, S4Vectors, BiocGenerics, tidy, forcats, progress, stats, utils

Suggests testthat, readr, knitr, rmarkdown, ggplot2, BiocStyle, ggdendro, broom, lme4, RColorBrewer, SingleCellExperiment, scater, broom.mixed, cowplot

LinkingTo Rcpp

VignetteBuilder knitr

Encoding UTF-8

NeedsCompilation yes

RoxygenNote 7.1.1

URL <https://github.com/amcdavid/CellaRepertorium>

BugReports <https://github.com/amcdavid/CellaRepertorium/issues>

Roxygen list(markdown = TRUE)

biocViews RNASeq, Transcriptomics, SingleCell, TargetedResequencing, Technology, ImmunoOncology, Clustering

git_url <https://git.bioconductor.org/packages/CellaRepertorium>

git_branch RELEASE_3_13

git_last_commit 86b7f10

git_last_commit_date 2021-05-19

Date/Publication 2021-10-14

Author Andrew McDavid [aut, cre],
 Yu Gu [aut],
 Erik VonKaenel [aut],
 Thomas Lin Pedersen [ctb]

Maintainer Andrew McDavid <Andrew_McDavid@urmc.rochester.edu>

R topics documented:

.cluster_permute_test	3
canonicalize_cell	3
canonicalize_cluster	5
ccdb_ex	6
ccdb_join	7
cdhit	7
cdhit_ccdb	9
cluster_filterset	10
cluster_germline	10
cluster_permute_test	11
cluster_plot	12
cluster_test_by	13
ContigCellDB	15
contigs_qc	16
crossstab_by_celltype	17
entropy	18
equalize_ccdb	19
fancy_name_contigs	20
filter_cdb	21
fine_clustering	22
fine_cluster_seqs	23
generate_pseudobulk	24
guess_celltype	25
hushWarning	25
ig_chain_recode	26
map_axis_labels	27
pairing_tables	28
purity	30
rank_prevalence_ccdb	30
rbind,ContigCellDB-method	32
right_join_warn	32
split_cdb	33
[[,ContigCellDB,character,missing-method	34
\$.ContigCellDB-method	35

Index

37

.cluster_permute_test *Cell permutation tests (internal)*

Description

Cell permutation tests (internal)

Usage

```
.cluster_permute_test(  
  labels,  
  covariates,  
  strata,  
  statistic,  
  n_perm,  
  alternative,  
  ...  
)
```

Arguments

labels	factor of length n
covariates	data.frame of length n
strata	factor
statistic	function of label (vector) and covariate (data.frame). Must return a scalar
n_perm	number of permutations to run
alternative	character naming the direction statistic should be fall under the alternative hypothesis
...	passed along to statistic

Value

a list containing the observed value of the statistic, its expectation (under independence), a p-value, and the Monte Carlo standard error (of the expected value).

canonicalize_cell *Find a canonical contig to represent a cell*

Description

Using filtering in `contig_filter_args` and sorting in `tie_break_keys` and order find a single, canonical contig to represent each cell Fields in `contig_fields` will be copied over to the `cell_tbl`.

Usage

```
canonicalize_cell(
  ccdb,
  contig_filter_args = TRUE,
  tie_break_keys = c("umis", "reads"),
  contig_fields = tie_break_keys,
  order = 1,
  overwrite = TRUE
)
```

Arguments

ccdb	ContigCellDB()
contig_filter_args	an expression passed to dplyr::filter() . Unlike filter, multiple criteria must be & together, rather than using commas to separate. These act on <code>ccdb\$contig_tbl</code>
tie_break_keys	(optional) character naming fields in <code>contig_tbl</code> that are used sort the contig table in descending order. Used to break ties if <code>contig_filter_args</code> does not return a unique contig for each cluster
contig_fields	Optional fields from <code>contig_tbl</code> that will be copied into the <code>cluster_tbl</code> from the canonical contig.
order	The rank order of the contig, based on <code>tie_break_keys</code> to return. If <code>tie_break_keys</code> included an ordered factor (such as <code>chain</code>) this could be used to return the second chain.
overwrite	logical – should non-key fields in <code>y</code> be overwritten using <code>x</code> , or should a suffix (".y") be added

Value

[ContigCellDB\(\)](#) with some number of clusters/contigs/cells but with "canonical" values copied into `cell_tbl`

See Also

[canonicalize_cluster\(\)](#)

Examples

```
# Report beta chain with highest umi-count, breaking ties with reads
data(ccdb_ex)
beta = canonicalize_cell(ccdb_ex, chain == 'TRB',
  tie_break_keys = c('umis', 'reads'),
  contig_fields = c('umis', 'reads', 'chain', 'v_gene', 'd_gene', 'j_gene'))
head(beta$cell_tbl)

# Stable: only adds fields to `cell_tbl`
stopifnot(dplyr::all_equal(beta$cell_tbl[ccdb_ex$cell_pk],
```

```
ccdb_ex$cell_tbl[ccdb_ex$cell_pk], ignore_row_order = TRUE))

#Report cdr3 with highest UMI count, but only when > 5 UMIs support it
umi5 = canonicalize_cell(ccdb_ex, umis > 5,
  tie_break_keys = c('umis', 'reads'), contig_fields = c('umis', 'cdr3'))
stopifnot(all(umi5$cell_tbl$umis > 5, na.rm = TRUE))
```

canonicalize_cluster *Find a canonical contig to represent a cluster*

Description

Find a canonical contig to represent a cluster

Usage

```
canonicalize_cluster(
  ccdb,
  contig_filter_args,
  tie_break_keys = character(),
  order = 1,
  representative = ccdb$cluster_pk[1],
  contig_fields = c("cdr3", "cdr3_nt", "chain", "v_gene", "d_gene", "j_gene"),
  overwrite = TRUE
)
```

Arguments

ccdb	ContigCellDB()
contig_filter_args	an expression passed to dplyr::filter() . Unlike filter, multiple criteria must be & together, rather than using commas to separate. These act on <code>ccdb\$contig_tbl</code>
tie_break_keys	(optional) character naming fields in <code>contig_tbl</code> that are used sort the contig table in descending order. Used to break ties if <code>contig_filter_args</code> does not return a unique contig for each cluster
order	The rank order of the contig, based on <code>tie_break_keys</code> to return. If <code>tie_break_keys</code> included an ordered factor (such as <code>chain</code>) this could be used to return the second chain.
representative	an optional field from <code>contig_tbl</code> that will be made unique. Serve as a surrogate <code>cluster_pk</code> .
contig_fields	Optional fields from <code>contig_tbl</code> that will be copied into the <code>cluster_tbl</code> from the canonical contig.
overwrite	logical – should non-key fields in <code>y</code> be overwritten using <code>x</code> , or should a suffix (<code>".y"</code>) be added

Value

[ContigCellDB\(\)](#) with some number of clusters/contigs/cells but with "canonical" values copied into `cluster_tbl`

See Also

[canonicalize_cell\(\)](#) [left_join_warn\(\)](#)

Examples

```
library(dplyr)
data(ccdb_ex)
ccdb_ex_small = ccdb_ex
ccdb_ex_small$cell_tbl = ccdb_ex_small$cell_tbl[1:200,]
ccdb_ex_small = cdhit_ccdb(ccdb_ex_small,
  sequence_key = 'cdr3_nt', type = 'DNA', cluster_name = 'DNA97',
  identity = .965, min_length = 12, G = 1)
ccdb_ex_small = fine_clustering(ccdb_ex_small, sequence_key = 'cdr3_nt', type = 'DNA')

# Canonicalize with the medoid contig is probably what is most common
ccdb_medoid = canonicalize_cluster(ccdb_ex_small)

# But there are other possibilities.
# To pass multiple "AND" filter arguments must use &
ccdb_umi = canonicalize_cluster(ccdb_ex_small,
  contig_filter_args = chain == 'TRA' & length > 500, tie_break_keys = 'umis',
  contig_fields = c('chain', 'length'))
ccdb_umi$cluster_tbl %>% dplyr::select(chain, length) %>% summary()
```

ccdb_ex

A preconstructed ContigClusterDB from the contigs_qc data

Description

A preconstructed ContigClusterDB from the contigs_qc data

Usage

```
data(ccdb_ex)
```

Format

```
ccdb_ex = ContigCellDB_10XVDJ(contigs_qc, contig_pk = c('pop', 'sample', 'barcode', 'contig_id'), cell_pk = c('pop', 'sample', 'barcode'))
```

See Also

[contigs_qc](#)

ccdb_join	<i>Join dataframe or SingleCellExperiment object with ContigCellDB object</i>
-----------	---

Description

Join dataframe or SingleCellExperiment object with ContigCellDB object

Usage

```
ccdb_join(template, ccdb, join_fun = dplyr::left_join, by = ccdb$cell_pk)
```

Arguments

template	data.frame or SingleCellExperiment object to be joined with ccdb.
ccdb	A ContigCellDB object.
join_fun	Function used for the join operation.
by	A character vector of variables to join by.

Value

[ContigCellDB\(\)](#)

Examples

```
data(ccdb_ex)
to_join = dplyr::bind_rows(ccdb_ex$cell_tbl[1:10,],
  dplyr::tibble(barcode = c('extra1', 'extra2'), sample = LETTERS[1:2],
  pop = LETTERS[1:2]))
ccdb_join(to_join, ccdb_ex)
```

cdhit	<i>R interface to CDHIT/CDHITest</i>
-------	--------------------------------------

Description

CDHIT is a greedy algorithm to cluster amino acid or DNA sequences based on a minimum identity. By default, in this package it is configured perform ungapped, global alignments with no clipping at start or end. The `identity` is the number of identical characters in alignment divided by the full length of the shorter sequence. Set `s < 1` to change the minimum coverage of the shorter sequence, which will allow clipping at start or end. Changing `G = 0` changes the meaning of the `identity` to be the number of identical characters in the alignment divided by the length of the alignment. In this case, you must also set the alignment coverage controls `aL`, `AL`, `aS`, `AS`.

Usage

```
cdhit(
  seqs,
  identity = NULL,
  kmerSize = NULL,
  min_length = 6,
  s = 1,
  only_index = FALSE,
  showProgress = interactive(),
  ...
)
```

Arguments

seqs	AAsseq or DNAsseq
identity	minimum proportion identity
kmerSize	word size. If NULL, it will be chosen automatically based on the identity. You may need to lower it below 5 for AAsseq with identity less than .7.
min_length	Minimum length for sequences to be clustered. An error if something smaller is passed.
s	fraction of shorter sequence covered by alignment.
only_index	if TRUE only return the integer cluster indices, otherwise return a tibble.
showProgress	show a status bar
...	other arguments that can be passed to cdhit, see https://github.com/weizhongli/cdhit/wiki/3.-User's-Guide#CDHIT for details. These will override any default values.

Details

CDHit is by Fu, Niu, Zhu, Wu and Li (2012). The R interface is originally by Thomas Lin Pedersen and was transcribed here because it is not exported from the package FindMyFriends, which is orphaned.

Value

vector of integer of length seqs providing the cluster ID for each sequence, or a tibble. See details.

Examples

```
fasta_path = system.file('extdata', 'demo.fasta', package='CellaRepertorium')
aaseq = Biostrings::readAAStringSet(fasta_path)
# 100% identity, global alignment
cdhit(aaseq, identity = 1, only_index = TRUE)[1:10]
# 100% identity, local alignment with no padding of endpoints
cdhit(aaseq, identity = 1, G = 0, aL = 1, aS = 1, only_index = TRUE)[1:10]
# 100% identity, local alignment with .9 padding of endpoints
cdhit(aaseq, identity = 1, G = 0, aL = .9, aS = .9, only_index = TRUE)[1:10]
```



```
# a tibble
tbl = cdhit(aaseq, identity = 1, G = 0, aL = .9, aS = .9, only_index = FALSE)
```

cdhit_ccdb	Use <code>cdhit()</code> to cluster a <code>ContigCellDB()</code>
------------	---

Description

Use `cdhit()` to cluster a `ContigCellDB()`

Usage

```
cdhit_ccdb(
  ccdb,
  sequence_key,
  type = c("DNA", "AA"),
  cluster_pk = "cluster_idx",
  ...
)
```

Arguments

<code>ccdb</code>	An object of class <code>ContigCellDB()</code>
<code>sequence_key</code>	character naming the column in the <code>contig_tbl</code> containing the sequence to be clustered
<code>type</code>	one of 'DNA' or 'AA'
<code>cluster_pk</code>	character specifying key, and name for the clustering.
<code>...</code>	Arguments passed on to <code>cdhit</code>
<code>identity</code>	minimum proportion identity
<code>kmerSize</code>	word size. If NULL, it will be chosen automatically based on the identity. You may need to lower it below 5 for AAseq with identity less than .7.
<code>min_length</code>	Minimum length for sequences to be clustered. An error if something smaller is passed.
<code>s</code>	fraction of shorter sequence covered by alignment.
<code>showProgress</code>	show a status bar

Value

`ContigCellDB()`

See Also

`cdhit()`

Examples

```
data(ccdb_ex)
res = cdhit_ccdb(ccdb_ex, 'cdr3_nt', type = 'DNA',
cluster_name = 'DNA97', identity = .965, min_length = 12, G = 1)
res$cluster_tbl
res$contig_tbl
res$cluster_pk
```

cluster_filterset *A filtration of clusters*

Description

Return clusters that match all provided conditions

Usage

```
cluster_filterset(min_number = 0, min_freq = 0, white_list = NULL)
```

Arguments

min_number	integer	At least this many cells
min_freq	numeric	At least this frequency
white_list	data.frame	keyed by cluster_pk that must match

Value

object representing the filtration (currently a list)

Examples

```
cluster_filterset(min_number = 1, min_freq = 0)
```

cluster_germline *Cluster contigs by germline properties*

Description

Cluster contigs by germline properties

Usage

```
cluster_germline(
  ccdb,
  segment_keys = c("v_gene", "j_gene", "chain"),
  cluster_pk = "cluster_idx"
)
```

Arguments

ccdb [ContigCellDB\(\)](#)
 segment_keys fields in contig_tbl that identify a cluster
 cluster_pk name of cluster to be added to cluster_tbl

Value

[ContigCellDB\(\)](#)

Examples

```
data(ccdb_ex)
ccdb_ex = cluster_germline(ccdb_ex)
ccdb_ex$cluster_tbl
```

cluster_permute_test *Tests for independence between labels and covariates using permutation of cells*

Description

This tests a statistic for association between labels (for instance, cluster/clonal ID) and covariates (for instance, subject or treatment) by permuting the link between the two. Each observation represents a cell. statistic is any function of labels

Usage

```
cluster_permute_test(
  ccdb,
  cell_covariate_keys,
  cell_label_key = ccdb$cluster_pk,
  cell_stratify_keys,
  statistic,
  n_perm,
  alternative = c("two.sided", "less", "greater"),
  sanity_check_strata = TRUE,
  ...
)
```

Arguments

ccdb [ContigCellDB](#)
 cell_covariate_keys character naming fields in ccdb\$cell_tbl
 cell_label_key character naming a single field in ccdb\$cell_tbl

cell_stratify_keys	optional character naming fields in <code>ccdb\$cell_tbl</code> under which permutations of <code>cell_label_key</code> will occur. This means that the test will occur conditional on these covariates. Must be disjoint from <code>cell_covariate_keys</code> .
statistic	function of label (vector) and covariate (data.frame). Must return a scalar
n_perm	number of permutations to run
alternative	character naming the direction statistic should be fall under the alternative hypothesis
sanity_check_strata	logical, should <code>cell_stratify_keys</code> be checked for sanity?
...	passed to <code>statistic</code>

Value

a list containing the observed value of the statistic, its expectation (under independence), a p-value, and the Monte Carlo standard error (of the expected value).

See Also

[purity\(\)](#)

Examples

```
library(dplyr)
# covariate should name one or more columns in `cell_tbl`

cluster_idx = c(1, 1, 1, 2, 2, 3, 3)
subject = c('A', 'A', 'B', 'B', 'B', 'C', 'C')
contig_tbl = tibble(contig_pk = seq_along(cluster_idx), cluster_idx, subject)
ccdb_test = ContigCellDB(contig_tbl = contig_tbl, contig_pk = 'contig_pk',
  cell_pk = c('contig_pk', 'subject', 'cluster_idx'), cluster_pk = 'cluster_idx')
ccdb_test$cell_tbl

cluster_permute_test(ccdb_test, 'subject', 'cluster_idx',
  statistic = purity, n_perm = 50)
```

cluster_plot

Make a plot showing properties of the clustering

Description

The number of elements per cluster and the average distance between the medoid and other elements are plotted.

Usage

```
cluster_plot(cdb, return_plotlist = FALSE)
```

Arguments

cdb A fine_clustering ContigCellDB object
return_plotlist should a list of ggplot2 plots be returned. If FALSE, a cowplot composite is returned.

Value

a cowplot composite or a list of plots.

Examples

```

library(dplyr)
data(ccdb_ex)
ccdb_ex_small = ccdb_ex
ccdb_ex_small$cell_tbl = ccdb_ex_small$cell_tbl[1:200,]
ccdb_ex_small = cdhit_ccdb(ccdb_ex_small,
  sequence_key = 'cdr3_nt', type = 'DNA', cluster_name = 'DNA97',
  identity = .965, min_length = 12, G = 1)
ccdb_ex_small = fine_clustering(ccdb_ex_small, sequence_key = 'cdr3_nt', type = 'DNA')

# Canonicalize with the medoid contig is probably what is most common
ccdb_medoid = canonicalize_cluster(ccdb_ex_small)

# But there are other possibilities.
# To pass multiple "AND" filter arguments must use &
ccdb_umi = canonicalize_cluster(ccdb_ex_small,
  contig_filter_args = chain == 'TRA' & length > 500, tie_break_keys = 'umis',
  contig_fields = c('chain', 'length'))
ccdb_umi$cluster_tbl %>% dplyr::select(chain, length) %>% summary()
cluster_plot(ccdb_ex_small)
  
```

cluster_test_by *Test clusters for differential usage*

Description

Typically one will want to stratify by chain by calling cluster_test_by, as this will calculate the number of cell "trials" separately depending on the chain recovered.

Usage

```

cluster_test_by(ccdb, fields = "chain", tbl = "cluster_tbl", ...)

cluster_logistic_test(
  formula,
  ccdb,
  filterset = cluster_filterset(),
  ...
)
  
```

```

contig_filter_args = TRUE,
tie_break_keys = c("umis", "reads"),
add_cluster_tbl = FALSE,
keep_fit = FALSE,
fitter = glm_glmer,
silent = FALSE
)

```

Arguments

ccdb	ContigCellDB()
fields	character naming fields in tbl
tbl	one of contig_tbl, cell_tbl or cluster_tbl
...	passed to cluster_logistic_test
formula	the right-hand side of a glmer or glm-style formula.
filterset	a call to cluster_filterset() that will be used to subset clusters.
contig_filter_args	an expression passed to dplyr::filter() . Unlike filter, multiple criteria must be & together, rather than using commas to separate. These act on ccdb\$contig_tbl
tie_break_keys	(optional) character naming fields in contig_tbl that are used sort the contig table in descending order. Used to break ties if contig_filter_args does not return a unique contig for each cluster
add_cluster_tbl	logical should the output be joined to the cluster_tbl?
keep_fit	logical as to whether the fit objects should be returned as a list column
fitter	a function taking arguments formula, data, is_mixed and keep_fit that is run on each cluster. Should return a tibble or data.frame
silent	logical. Should warnings from fitting functions should be suppressed?

Value

table with one row per cluster/term.

Functions

- cluster_test_by: split ccdb and conduct tests within strata

Examples

```

library(dplyr)
data(ccdb_ex)
ccdb_ex = cluster_germline(ccdb_ex)
trav1 = filter(ccdb_ex$cluster_tbl, v_gene == 'TRAV1')
cluster_logistic_test(~pop + (1|sample), ccdb_ex,
filterset = cluster_filterset(white_list= trav1))
# Fixed effect analysis of each cluster, by chain

```

```
prev4 = ccdb_ex$contig_tbl %>% group_by(cluster_idx) %>%
summarize(n()) %>% filter(`n()`>= 4)
cluster_test_by(ccdb = ccdb_ex, fields = 'chain',
tbl = 'cluster_tbl', formula = ~ pop, filterset = cluster_filterset(white_list= prev4))
```

ContigCellDB

Construct a ContigCellDB

Description

Construct a ContigCellDB

Usage

```
ContigCellDB(
  contig_tbl,
  contig_pk,
  cell_tbl,
  cell_pk,
  cluster_tbl,
  cluster_pk = character(),
  equalize = TRUE
)

ContigCellDB_10XVDJ(
  contig_tbl,
  contig_pk = c("barcode", "contig_id"),
  cell_pk = "barcode",
  ...
)
```

Arguments

contig_tbl	a data frame of contigs, and additional fields describing their properties
contig_pk	character vector naming fields in contig_tbl that uniquely identify a row/contig
cell_tbl	a data frame of cell barcodes, and (optional) additional fields describing their properties
cell_pk	character vector naming fields in cell_tbl that uniquely identify a cell barcode
cluster_tbl	A data frame that provide cluster assignments for each contig
cluster_pk	If cluster_tbl was provided, a character vector naming fields in cluster_tbl that uniquely identify a cluster
equalize	logical. Should the contig, cells and clusters be equalized by taking the intersection of their common keys?
...	passed to ContigCellDB()

Value

ContigCellDB

Functions

- `ContigCellDB_10XVDJ`: provide defaults that correspond to identifiers in 10X VDJ data

Accessors/mutators

See [\\$,ContigCellDB-method](#) for more on how to access and mutate slots. See [mutate_cdb\(\)](#) and [filter_cdb\(\)](#) for endomorphic filtering/mutation methods. See [split_cdb\(\)](#) to split into a list, and [rbind.ContigCellDB\(\)](#) for the inverse operation.

See Also

[\\$,ContigCellDB-method](#)

Examples

```
data(contigs_qc)
contigs_qc

cdb = ContigCellDB(contigs_qc, contig_pk = c('barcode', 'pop', 'sample', 'contig_id'),
  cell_pk = c('barcode', 'pop', 'sample'))
cdb

# everything that was in contigs_qc
cdb$contig_tbl

# Only the cell_pk are included by default (until clustering/canonicalization)
cdb$cell_tbl

# Empty, since no cluster_pk was specified
cdb$cluster_tbl

# Keys
cdb$contig_pk
cdb$cell_pk
cdb$cluster_pk
```

contigs_qc

Filtered and annotated contigs of TCR from mice

Description

Data for c57bl6 and balbc mice TCR were downloaded from 10x Genomics website as shown in `system.file('script/10XMouseTCR_v3_chem.R', package = 'CellaRepertorium')`. Additional processing of these data is done in the vignette `mouse_tcell_qc` and are serialized to serve as an examples for other vignettes and documentation.

Usage

```
data(contigs_qc)
```

Format

A data frame of 3399 contigs and 22 fields, all except 4 are originally defined in <https://support.10xgenomics.com/single-cell-vdj/software/pipelines/latest/output/annotation#contig>. The following fields were defined ex post facto.

1. anno_file: Path to original csv file
2. pop: Mouse strain.
3. sample: An artificial "replicate" from the original data defined by subsampling with replacement
4. celltype: The putative cell type of the contig.

crosstab_by_celltype *Count contig UMIs by celltype*

Description

Count contig UMIs by celltype

Usage

```
crosstab_by_celltype(ccdb)
```

Arguments

ccdb A ContigCellDB object

Value

a table, keyed by cell_pk counting UMIs per celltype

See Also

[guess_celltype\(\)](#)

Examples

```
data(ccdb_ex)
nrow(ccdb_ex$cell_tbl)
total_umi = crosstab_by_celltype(ccdb_ex)
nrow(total_umi)
```

entropy *Calculate the entropy of a vector*

Description

Calculate the entropy of a vector

Usage

```
entropy(v, pseudo_count = length(v)/1000, na.action = na.fail)
```

```
np(v, p = 0.05, pseudo_count = p/5, na.action = na.fail)
```

```
modal_category(v, na.action = na.fail)
```

Arguments

v	categorical vector
pseudo_count	number of pseudo counts to add on, to stabilize empty categories
na.action	how to handle NA values
p	proportion threshold

Value

the sample entropy

Functions

- np: The number of categories exceeding p proportion of the total
- modal_category: The modal category of v. Ties are broken by lexicographic order of the factor levels.

Examples

```
v2 = gl(2, 4)
v4 = gl(4, 4)
stopifnot(entropy(v2) < entropy(v4))
v_empty = v2[1:4] #empty level 2
stopifnot(is.finite(entropy(v_empty))) # pseudo_count

np(v4, p = .2, pseudo_count = 0)
np(v4, p = .25, pseudo_count = 0)
np(v4, p = .25, pseudo_count = .0001)

modal_category(v4)
modal_category(v4[-1])
```

equalize_ccdb	<i>Take the intersection of keys in tables in x</i>
---------------	---

Description

The cells in `cell_tbl`, and clusters in `cluster_tbl` can potentially be a superset of the `contig_tbl`.

Usage

```
equalize_ccdb(x, cell = TRUE, contig = TRUE, cluster = TRUE, sort = FALSE)
```

Arguments

<code>x</code>	<code>ContigCellDB()</code>
<code>cell</code>	logical equalize cells
<code>contig</code>	logical equalize contigs
<code>cluster</code>	logical equalize clusters
<code>sort</code>	logical should equalized fields also be <code>order()</code> ed by their primary keys?

Details

- `equalize_ccdb(x, cell = TRUE)` trims cells that aren't in `contig_tbl` or `cluster_tbl`.
- `equalize_ccdb(x, cluster = TRUE)` trims clusters that aren't in `contig_tbl`.
- `equalize_ccdb(x, contig = TRUE)` trims contigs that aren't `cell_tbl` or `cluster_tbl`.

Value

`ContigCellDB()`

Default equalization

Modification to `contig_tbl` (with `$`) always equalizes contigs and clusters. Modification to `cell_tbl` equalizes only contigs. Modification to `cluster_tbl` equalizes contigs and clusters.

Examples

```
library(dplyr)
tbl = tibble(clust_idx = gl(3, 2), cell_idx = rep(1:3, times = 2), contig_idx = 1:6)
ccdb = ContigCellDB(tbl, contig_pk = c('cell_idx', 'contig_idx'),
  cell_pk = 'cell_idx', cluster_pk = 'clust_idx')
# 3 cells
ccdb
ccdb$cell_tbl = bind_rows(ccdb$cell_tbl, tibble(cell_idx = 0))
# 4 cells now
ccdb
# 3 cells again
equalize_ccdb(ccdb)
```

```
# remove all contigs from cell 1, and one contig from cell 2
ccdb$contig_tbl = ccdb$contig_tbl[-c(1, 2, 4),]
# no changes to cell_tbl yet
ccdb
# trim cell_tbl to 2 cells, keep all clusters
equalize_ccdb(ccdb, cluster = FALSE)
# trim both cells and clusters
equalize_ccdb(ccdb, cluster = TRUE)
```

fancy_name_contigs *Generate a legible name for a series of contigs*

Description

Generate a legible name for a series of contigs

Usage

```
fancy_name_contigs(contig_tbl, prefix)
```

Arguments

contig_tbl An all_contig_annotations.csv file, output from VDJ Cell ranger. Importantly, this should contain columns chain, v_gene, d_gene, j_gene

prefix an optional prefix added to each contig, eg, possibly a sample id.

Value

character

Examples

```
library(dplyr)
contig_anno_path = system.file('extdata', 'all_contig_annotations_balbc_1.csv.xz',
  package = 'CellaRepertorium')
contig_anno = readr::read_csv(contig_anno_path)
contig_anno = contig_anno %>% mutate(fancy_name =
  fancy_name_contigs(., prefix = 'b6_1'))
stopifnot(!any(duplicated(contig_anno$fancy_name)))
```

filter_cdb	<i>Create new or update existing columns of ContigCellDB tables</i>
------------	---

Description

Create new or update existing columns of ContigCellDB tables

Usage

```
filter_cdb(ccdb, ..., tbl = "contig_tbl")
```

```
mutate_cdb(ccdb, ..., tbl = "contig_tbl")
```

Arguments

ccdb	ContigCellDB()
...	name and value pair of column that will be updated
tbl	character. One of contig_tbl, cell_tbl or cluster_tbl, naming the table to be updated.

Value

ContigCellDB object with updated table

Functions

- filter_cdb: Filter rows of a table in a ContigCellDB object

See Also

[dplyr::mutate\(\)](#)

[dplyr::filter\(\)](#)

Examples

```
data(ccdb_ex)
subset_contig = filter_cdb(ccdb_ex,full_length, productive == 'True',
high_confidence, chain != 'Multi', nchar(cdr3) > 5)
subset_cell = filter_cdb(ccdb_ex, sample == 4, tbl = 'cell_tbl')
data(ccdb_ex)
new_contig = mutate_cdb(ccdb_ex, new_col = 1)
new_cell = mutate_cdb(ccdb_ex, new_col = 1, tbl = 'contig_tbl')
```

fine_clustering	<i>Perform additional clustering of sequences within groups</i>
-----------------	---

Description

Perform additional clustering of sequences within groups

Usage

```
fine_clustering(
  ccdb,
  sequence_key,
  type,
  max_affinity = NULL,
  keep_clustering_details = FALSE,
  ...
)
```

Arguments

ccdb	A ContigCellDB() object
sequence_key	character naming column in contig_tbl with sequence
type	'AA' or 'DNA'
max_affinity	numeric naming the maximal affinity for the sparse affinity matrix that is constructed. Not currently used.
keep_clustering_details	logical – should output of fine_cluster_seqs be kept as a list column
...	Arguments passed on to fine_cluster_seqs
big_memory_brute	attempt to cluster more than 4000 sequences? Clustering is quadratic, so this will take a long time and might exhaust memory
method	one of 'substitutionMatrix' or 'levenshtein'
substitution_matrix	a character vector naming a substitution matrix available in Biostrings, or a substitution matrix itself

Value

[ContigCellDB\(\)](#) object with updated contig_tbl and cluster_tbl

Examples

```
library(dplyr)
data(ccdb_ex)
ccdb_ex_small = ccdb_ex
ccdb_ex_small$cell_tbl = ccdb_ex_small$cell_tbl[1:200,]
ccdb_ex_small = cdhit_ccdb(ccdb_ex_small,
  sequence_key = 'cdr3_nt', type = 'DNA', cluster_name = 'DNA97',
```

```

identity = .965, min_length = 12, G = 1)
ccdb_ex_small = fine_clustering(ccdb_ex_small, sequence_key = 'cdr3_nt', type = 'DNA')

# Canonicalize with the medoid contig is probably what is most common
ccdb_medoid = canonicalize_cluster(ccdb_ex_small)

# But there are other possibilities.
# To pass multiple "AND" filter arguments must use &
ccdb_umi = canonicalize_cluster(ccdb_ex_small,
contig_filter_args = chain == 'TRA' & length > 500, tie_break_keys = 'umis',
contig_fields = c('chain', 'length'))
ccdb_umi$cluster_tbl %>% dplyr::select(chain, length) %>% summary()

```

fine_cluster_seqs	<i>Calculate distances and perform hierarchical clustering on a set of sequences</i>
-------------------	--

Description

The distances between AA sequences is defined to be $1 - \text{score} / \max(\text{score})$ times the median length of the input sequences. The distances between nucleotide sequences is defined to be $\text{edit_distance} / \max(\text{edit_distance})$ times the median length of input sequences.

Usage

```

fine_cluster_seqs(
  seqs,
  type = "AA",
  big_memory_brute = FALSE,
  method = "levenshtein",
  substitution_matrix = "BLOSUM100",
  cluster_fun = "none",
  cluster_method = "complete"
)

```

Arguments

seqs	character vector, DNASTringSet or AAStringSet
type	character either AA or DNA specifying type of seqs
big_memory_brute	attempt to cluster more than 4000 sequences? Clustering is quadratic, so this will take a long time and might exhaust memory
method	one of 'substitutionMatrix' or 'levenshtein'
substitution_matrix	a character vector naming a substitution matrix available in Biostrings, or a substitution matrix itself
cluster_fun	character, one of "hclust" or "none", determining if distance matrices should also be clustered with hclust
cluster_method	character passed to hclust

Value

list

See Also[hclust\(\)](#), [Biostrings::stringDist\(\)](#)**Examples**

```
fasta_path = system.file('extdata', 'demo.fasta', package='CellaRepertorium')
aaseq = Biostrings::readAAStringSet(fasta_path)[1:100]
cls = fine_cluster_seqs(aaseq, cluster_fun = 'hclust')
plot(cls$cluster)
```

generate_pseudobulk *Generate "pseudobulk" data from a ContigCellDB*

Description

Tabulate contigs with a unique combination of class_keys per total_keys. For instance, total_keys might be a sample identifier, and class_keys might be the V- and J- gene identities. The idea is that this might mimic the data generated in a bulk experiment.

Usage

```
generate_pseudobulk(ccdb, class_keys, total_keys, type = c("cell", "umi"))
```

Arguments

ccdb	ContigCellDB()
class_keys	character naming fields in contig_tbl that define unique classes of the repertoire
total_keys	character naming fields to be conditioned upon when calculating the total.
type	one of "cell" or "umi"

Details

This function is currently rather 10x-specific, in that it is assumed that columns barcode and umi exist.

Value

tibble

Examples

```
data(ccdb_ex)
ccdb_ex = cluster_germline(ccdb_ex)
pseudo = generate_pseudobulk(ccdb_ex, c('v_gene', 'j_gene', 'chain'), c('pop', 'sample'))
```

guess_celltype	<i>Guess the cell type of a contig from the chain ID</i>
----------------	--

Description

This function is likely dependent on annotations from 10X and may change or break as their pipeline changes.

Usage

```
guess_celltype(chain)
```

Arguments

chain character which will be parsed to try to infer celltype

Value

contig table with celltype column

See Also

[crosstab_by_celltype\(\)](#)

Examples

```
data(ccdb_ex)
table(guess_celltype(ccdb_ex$contig_tbl$chain))
```

hushWarning	<i>Selectively muffle warnings based on output</i>
-------------	--

Description

Selectively muffle warnings based on output

Usage

```
hushWarning(expr, regexp)
```

Arguments

expr an expression
regexp a regexp to be matched (with str_detect)

Value

the result of expr

Examples

```
CellaRepertorium::hushWarning(warning('Beware the rabbit'), 'rabbit')
CellaRepertorium::hushWarning(warning('Beware the rabbit'), 'hedgehog')
```

ig_chain_recode	<i>Categorize the pairing present in a cell</i>
-----------------	---

Description

For each cell (defined by `ccdb$cell_pk`) count the number of each level of `chain_key` occurs, and cross tabulate. Also for each cell, paste together all values `chain_key`. Return a tibble, keyed by cells that includes the counts of the chains, the `raw_chain_type` and any additional output from running `chain_recode_fun`.

Usage

```
ig_chain_recode(tbl)

tcr_chain_recode(tbl)

enumerate_pairing(ccdb, chain_key = "chain", chain_recode_fun = NULL)
```

Arguments

<code>tbl</code>	output from <code>enumerate_pairing</code> containing TRA/TRB or IGH/IHK/IHL columns
<code>ccdb</code>	ContigCellDB
<code>chain_key</code>	character naming the field in the <code>contig_tbl</code> identifying chain
<code>chain_recode_fun</code>	a function that operates on the output of this function that further reduces the chain combinations to some other summary. Set to 'guess' to apply functions that may work for 10X data or NULL to skip. See <code>CellaRepertorium::tcr_chain_recode</code> for an example.

Value

a tibble keyed by cells.

Functions

- `ig_chain_recode`: Recode a table with IG chains
- `tcr_chain_recode`: Recode a table with TCR chains

Examples

```
data(ccdb_ex)
enumerate_pairing(ccdb_ex)
enumerate_pairing(ccdb_ex, chain_recode_fun = 'guess')
```

map_axis_labels	<i>Color axis labels</i>
-----------------	--------------------------

Description

Color axis labels

Usage

```
map_axis_labels(
  plt,
  label_data_x = NULL,
  label_data_y = NULL,
  aes_label,
  scale = ggplot2::scale_color_hue(aesthetics = "axis_color")
)
```

Arguments

plt	ggplot2::ggplot() object
label_data_x	data.frame() containing the mapping between x-axis labels and aes_label
label_data_y	data.frame() containing the mapping between y-axis labels and aes_label
aes_label	character or bare symbol giving the column in label_data to be mapped
scale	ggplot2 discrete color

Value

plt with axis text modified

Examples

```
require(ggplot2)
require(dplyr)
plt = ggplot(mpg, aes(x = manufacturer, y = drv)) + geom_jitter()
label_data = mpg %>% select(manufacturer) %>% unique() %>%
mutate(euro = manufacturer %in% c('audi', 'volkswagen'))
map_axis_labels(plt, label_data_x = label_data, aes_label = euro)
```

pairing_tables	<i>Generate a list of tables representing clusters paired in cells</i>
----------------	--

Description

A contingency table of every combination of `cluster_idx` up to `table_order` is generated. Combinations that are found in at least `min_expansion` number of cells are reported. All cells that have these combinations are returned, as well as cells that only have `orphan_level` of matching `cluster_idx`.

Usage

```
pairing_tables(
  ccdb,
  ranking_key = "grp_rank",
  table_order = 2,
  min_expansion = 2,
  orphan_level = 1,
  cluster_keys = character(),
  cluster_whitelist = NULL,
  cluster_blacklist = NULL
)
```

Arguments

<code>ccdb</code>	ContigCellDB
<code>ranking_key</code>	field in <code>ccdb\$contig_tbl</code> giving the ranking of each contig per cell. Probably generated by a call to <code>rank_prevalence_ccdb()</code> or <code>rank_chain_ccdb()</code> .
<code>table_order</code>	Integer larger than 1. What order of <code>cluster_idx</code> will be paired, eg, <code>order = 2</code> means that the first and second highest ranked contigs will be sought and paired in each cell
<code>min_expansion</code>	the minimal number of times a pairing needs to occur for it to be reported
<code>orphan_level</code>	Integer in interval <code>[1, table_order]</code> . Given that at least <code>min_expansion</code> cells are found that have <code>table_order</code> chains identical, how many <code>cluster_idx</code> pairs will we match on to select other cells. Example: <code>orphan_level=1</code> means that cells that share just a single chain with an expanded pair will be reported.
<code>cluster_keys</code>	optional character naming additional columns in <code>ccdb\$cluster_tbl</code> to be reported in the pairing
<code>cluster_whitelist</code>	a table of pairings or clusters that should always be reported. Here the clusters must be named "cluster_idx.1", "cluster_idx.2" (if order-2 pairs are being selected) rather than with "ccdb\$cluster_pk"
<code>cluster_blacklist</code>	a table of pairings or clusters that will never be reported. Must be named as per <code>cluster_whitelist</code> .

Details

For example, if `table_order=2` and `min_expansion=2` then heavy/light or alpha/beta pairs found two or more times will be returned (as well as alpha-alpha pairs, etc, if those are present). If `orphan_level=1` then all cells that share just a single chain with an expanded clone will be returned.

The `cluster_idx.1_fct` and `cluster_idx.2_fct` fields in `cell_tbl`, `idx1_tbl`, `idx2_tbl` are cast to factors and ordered such that pairings will tend to occur along the diagonal when they are cross-tabulated. This facilitates plotting.

Value

list of tables. The `cell_tbl` is keyed by the `cell_identifiers`, with fields "cluster_idx.1", "cluster_idx.2", etc, IDing the contigs present in each cell. "cluster_idx.1_fct" and "cluster_idx.2_fct" cast these fields to factors and are reordered to maximize the number of pairs along the diagonal. The `idx1_tbl` and `idx2_tbl` report information (passed in about the `cluster_idx` by `feature_tbl`.) The `cluster_pair_tbl` reports all pairings found of contigs, and the number of times observed.

See Also

[rank_prevalence_ccdb\(\)](#)

Examples

```
library(dplyr)
tbl = tibble(clust_idx = gl(3, 2), cell_idx = rep(1:3, times = 2), contig_idx = 1:6)
ccdb = ContigCellDB(tbl, contig_pk = c('cell_idx', 'contig_idx'),
  cell_pk = 'cell_idx', cluster_pk = 'clust_idx')
# add `grp_rank` to ccdb$contig_tbl indicating how frequent a cluster is
ccdb = rank_prevalence_ccdb(ccdb, tie_break_keys = character())
# using `grp_rank` to determine pairing
# no pairs found twice
pt1 = pairing_tables(ccdb)
# all pairs found, found once.
pt2 = pairing_tables(ccdb, min_expansion = 1)
pt2$cell_tbl
tbl2 = bind_rows(tbl, tbl %>% mutate(cell_idx = rep(4:6, times = 2)))
ccdb2 = ContigCellDB(tbl2, contig_pk = c('cell_idx', 'contig_idx'), cell_pk = 'cell_idx',
  cluster_pk = 'clust_idx') %>% rank_prevalence_ccdb(tie_break_keys = character())
#all pairs found twice
pt3 = pairing_tables(ccdb2, min_expansion = 1)
pt3$cell_tbl
ccdb2$contig_tbl = ccdb2$contig_tbl %>%
  mutate(umis = 1, reads = 1, chain = rep(c('TRA', 'TRB'), times = 6))
ccdb2 = rank_chain_ccdb(ccdb2, tie_break_keys = character())
pt4 = pairing_tables(ccdb2, min_expansion = 1, table_order = 2)
```

purity	<i>Calculate number of cluster-subject singletons for the purposes of permutation testing</i>
--------	---

Description

Calculate number of cluster-subject singletons for the purposes of permutation testing

Usage

```
purity(cluster_idx, subject)
```

Arguments

cluster_idx	factor-like cluster variable
subject	factor-like subject

Value

average number of singletons

See Also

[cluster_permute_test\(\)](#)

Examples

```
message("see example(cluster_permute_test)")
```

rank_prevalence_ccdb	<i>Rank contigs, per cell, by experiment-wide prevalence of cluster_pk, which is added as the prevalence field</i>
----------------------	--

Description

Rank contigs, per cell, by experiment-wide prevalence of cluster_pk, which is added as the prevalence field

Usage

```
rank_prevalence_ccdb(
  ccdb,
  contig_filter_args = TRUE,
  tie_break_keys = c("umis", "reads")
)

rank_chain_ccdb(
  ccdb,
  contig_filter_args = TRUE,
  tie_break_keys = c("umis", "reads"),
  chain_key = "chain",
  contig_fields = tie_break_keys,
  chain_levels = c("IGL", "IGK", "TRA", "TRB", "IGH")
)
```

Arguments

ccdb	ContigCellDB()
contig_filter_args	an expression passed to dplyr::filter() . Unlike filter, multiple criteria must be & together, rather than using commas to separate. These act on ccdb\$contig_tbl
tie_break_keys	(optional) character naming fields in contig_tbl that are used sort the contig table in descending order. Used to break ties if contig_filter_args does not return a unique contig for each cluster
chain_key	character naming the field in contig_tbl to be sorted on.
contig_fields	Optional fields from contig_tbl that will be copied into the cluster_tbl from the canonical contig.
chain_levels	an optional character vector providing the sort order of the chain column in tbl. If set to length zero, then the the ordering will be alphabetical

Value

ContigCellDB with modified contig_tbl

Functions

- rank_chain_ccdb: return a canonical contig by chain type, with TRB/IGH returned first. By default, ties are broken by umis and reads.

Examples

```
data(ccdb_ex)
ccdb_ex = cluster_germline(ccdb_ex)
rank_prev = rank_prevalence_ccdb(ccdb_ex)
rank_prev$contig_tbl
rank_chain = rank_chain_ccdb(ccdb_ex)
rank_chain$contig_tbl
```

```
rbind, ContigCellDB-method
```

Combine ContigCellDB along rows (contigs, cells or clusters).

Description

The union of the rows in each of the objects is taken, thus removing any rows that has an exact duplicate. This includes all fields, not just the primary key for that table. The union of the various primary keys is taken.

Usage

```
## S4 method for signature 'ContigCellDB'
rbind(..., deparse.level = 1)
```

Arguments

```
...          ContigCellDB()
deparse.level ignored
```

Value

```
ContigCellDB()
```

Examples

```
data(ccdb_ex)
splat = split_cdb(ccdb_ex, 'chain', 'contig_tbl')
unite = equalize_ccdb(rbind(splat$TRA, splat$TRB), sort = TRUE)
stopifnot(all.equal(unite, ccdb_ex))
```

```
right_join_warn      Perform a dplyr::left_join() but check for non-key overlapping
                      fields
```

Description

Perform a dplyr join, but either warn if the two tables share non-key fields. If `overwrite = TRUE`, then shared columns will pull from `x` otherwise a suffix will be added to `y`. To perform this check, `by` must be specified, and it is an error if it is not.

Usage

```
right_join_warn(...)
```

```
left_join_warn(x, y, by, overwrite = FALSE, join = left_join, ...)
```


Arguments

...	passed to joining function
x	A pair of data frames, data frame extensions (e.g. a tibble), or lazy data frames (e.g. from dbplyr or dtplyr). See <i>Methods</i> , below, for more details.
y	A pair of data frames, data frame extensions (e.g. a tibble), or lazy data frames (e.g. from dbplyr or dtplyr). See <i>Methods</i> , below, for more details.
by	character specifying columns in x and y to key on.
overwrite	logical – should non-key fields in y be overwritten using x, or should a suffix (".y") be added
join	function giving the type of join to perform, eg, left, right, inner, outer.

Value

data.frame or tibble

Functions

- right_join_warn: perform a dplyr::right_join()

Examples

```
left_join_warn(mtcars, mtcars, by = 'mpg')
left_join_warn(mtcars, mtcars, by = 'mpg', overwrite = TRUE)
```

split_cdb

Split into a list of [ContigCellDB\(\)](#) by named fields

Description

Split into a list of [ContigCellDB\(\)](#) by named fields

Usage

```
split_cdb(ccdb, fields, tbl = "contig_tbl", drop = FALSE, equalize = TRUE)
```

Arguments

ccdb	ContigCellDB()
fields	character naming fields in tbl
tbl	one of contig_tbl, cell_tbl or cluster_tbl
drop	logical indicating if levels that do not occur should be dropped (if f is a factor or a list).
equalize	logical. Should the contig, cells and clusters be equalized by taking the intersection of their common keys?

Value

list of ContigCellDB

Examples

```
data(ccdb_ex)
splat = split_cdb(ccdb_ex, 'chain', 'contig_tbl')
stopifnot(all(splat$TRA$contig_tbl$chain == 'TRA'))
stopifnot(all(splat$TRB$contig_tbl$chain == 'TRB'))
```

```
[[,ContigCellDB,character,missing-method
      data.frame-like mutation/accessor generics for ContigCellDB ob-
      jects
```

Description

A ContigCellDB pretend to be a cell_tbl data.frame in several regards. This is to enable nesting ContigCellDB objects in the colData of a SingleCellExperiment and so that various plotting functionality in scater can do something sensible.

Usage

```
## S4 method for signature 'ContigCellDB,character,missing'
x[[i, j, ...]]

## S4 method for signature 'ContigCellDB,ANY,missing,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ContigCellDB'
dim(x)

## S4 method for signature 'ContigCellDB'
dimnames(x)

## S4 method for signature 'ContigCellDB'
nrow(x)

## S4 method for signature 'ContigCellDB'
ncol(x)
```

Arguments

x	ContigCellDB
i	integer or character index
j	ignored
...	ignored
drop	ignored

Details

If `x` a `ContigCellDB`, then `dim(x)` and `dimnames(x)` return `dim(x$cell_tbl)` and `dimnames(x$cell_tbl)`, respectively, and `x[[col]]` returns `x$cell_tbl[[col]]`. Likewise indexing with `x[i,]` returns cells indexed by `i`. Finally `as.data.frame(x)` returns `x$cell_tbl`.

Value

See details.

Examples

```
data(ccdb_ex)
ccdb_ex[1:10,]
head(ccdb_ex[['barcode']])
dim(ccdb_ex)
dimnames(ccdb_ex)
```

\$.ContigCellDB-method *Access public members of ContigCellDB object.*

Description

Modification to members will trigger various forms of equalization. See [equalize_ccdb\(\)](#) for details.

Usage

```
## S4 method for signature 'ContigCellDB'
x$name

## S4 replacement method for signature 'ContigCellDB'
x$name <- value
```

Arguments

<code>x</code>	A <code>ContigCellDB</code> object
<code>name</code>	a slot of a <code>ContigCellDB</code> object (one of <code>c('contig_tbl', 'cell_tbl', 'contig_pk', 'cell_pk', 'clus')</code>)
<code>value</code>	The value assigned to a slot of <code>ContigCellDB</code> object

Value

Update or return a slot of [ContigCellDB\(\)](#)

See Also

[equalize_ccdb\(\)](#)

Examples

```
data(ccdb_ex)
ccdb_ex$contig_tbl
ccdb_ex$cell_tbl
ccdb_ex$cluster_tbl
data(ccdb_ex)
ccdb_ex$contig_pk = c("sample", "barcode", "contig_id") # 'pop' is technically redundant with 'sample'
# Take a subset of ccdb_ex
ccdb_ex
ccdb_ex$contig_tbl = dplyr::filter(ccdb_ex$contig_tbl, pop == 'b6')
ccdb_ex
```

Index

* **datasets**
 ccdb_ex, 6
 contigs_qc, 16
 .cluster_permute_test, 3
[,ContigCellDB,ANY,missing,ANY-method
 ([[,ContigCellDB,character,missing-method), 34
[,ContigCellDB,ANY,missing-method
 ([[,ContigCellDB,character,missing-method), 34
[[,ContigCellDB,character,missing-method,
 34
\$,ContigCellDB-method, 35
\$<- ,ContigCellDB-method
 (\$,ContigCellDB-method), 35

Biostrings::stringDist(), 24

canonicalize_cell, 3
canonicalize_cell(), 6
canonicalize_cluster, 5
canonicalize_cluster(), 4
ccdb_ex, 6
ccdb_join, 7
cdhit, 7, 9
cdhit(), 9
cdhit_ccdb, 9
cluster_filterset, 10
cluster_filterset(), 14
cluster_germline, 10
cluster_logistic_test
 (cluster_test_by), 13
cluster_permute_test, 11
cluster_permute_test(), 30
cluster_plot, 12
cluster_test_by, 13
ContigCellDB, 15
ContigCellDB(), 4–7, 9, 11, 14, 15, 19, 21,
 22, 24, 31–33, 35

ContigCellDB-mutate
 (\$,ContigCellDB-method), 35
ContigCellDB_10XVDJ (ContigCellDB), 15
contigs_qc, 6, 16
crosstab_by_celltype, 17
crosstab_by_celltype(), 25

data.frame(), 27
diag,ContigCellDB-method
 ([[,ContigCellDB,character,missing-method),
 34
dimnames,ContigCellDB-method
 ([[,ContigCellDB,character,missing-method),
 34
dplyr::filter(), 4, 5, 14, 21, 31
dplyr::mutate(), 21

entropy, 18
enumerate_pairing (ig_chain_recode), 26
equalize_ccdb, 19
equalize_ccdb(), 35

fancy_name_contigs, 20
filter_cdb, 21
filter_cdb(), 16
fine_cluster_seqs, 22, 23
fine_clustering, 22

generate_pseudobulk, 24
ggplot2::ggplot(), 27
guess_celltype, 25
guess_celltype(), 17

hclust(), 24
hushWarning, 25

ig_chain_recode, 26

left_join_warn (right_join_warn), 32
left_join_warn(), 6

map_axis_labels, 27
modal_category (entropy), 18
mutate_cdb (filter_cdb), 21
mutate_cdb(), 16

ncol, ContigCellDB-method
 ([[, ContigCellDB, character, missing-method),
 34
np (entropy), 18
nrow, ContigCellDB-method
 ([[, ContigCellDB, character, missing-method),
 34

order(), 19

pairing_tables, 28
purity, 30
purity(), 12

rank_chain_ccdb (rank_prevalence_ccdb),
 30
rank_chain_ccdb(), 28
rank_prevalence_ccdb, 30
rank_prevalence_ccdb(), 28, 29
rbind, ContigCellDB-method, 32
rbind.ContigCellDB
 (rbind, ContigCellDB-method), 32
rbind.ContigCellDB(), 16
right_join_warn, 32

split_cdb, 33
split_cdb(), 16

tcr_chain_recode (ig_chain_recode), 26