

Package ‘STAN’

October 14, 2021

Version 2.20.0

Date 2017-08-10

Title The Genomic STate ANnotation Package

Author Benedikt Zacher, Julia Ertl, Rafael Campos-Martin, Julien Gagneur, Achim Tresch

Maintainer Rafael Campos-Martin <campos@mpipz.mpg.de>

Imports GenomicRanges, IRanges, S4Vectors, BiocGenerics, GenomeInfoDb,
Gviz, Rsolnp

Depends methods, poilog, parallel

VignetteBuilder knitr

Suggests BiocStyle, gplots, knitr

Description Genome segmentation with hidden Markov models has become a useful tool to annotate genomic elements, such as promoters and enhancers. STAN (genomic STate ANnotation) implements (bidirectional) hidden Markov models (HMMs) using a variety of different probability distributions, which can model a wide range of current genomic data (e.g. continuous, discrete, binary). STAN de novo learns and annotates the genome into a given number of 'genomic states'. The 'genomic states' may for instance reflect distinct genome-associated protein complexes (e.g. 'transcription states') or describe recurring patterns of chromatin features (referred to as 'chromatin states'). Unlike other tools, STAN also allows for the integration of strand-specific (e.g. RNA) and non-strand-specific data (e.g. ChIP).

License GPL (>= 2)

biocViews HiddenMarkovModel, GenomeAnnotation, Microarray, Sequencing,
ChIPSeq, RNASeq, ChipOnChip, Transcription, ImmunoOncology

LazyLoad yes

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/STAN>

git_branch RELEASE_3_13

git_last_commit 9c7a3b4

git_last_commit_date 2021-05-19

Date/Publication 2021-10-14

R topics documented:

STAN-package	3
bdHMM	3
bdHMM-class	4
binarizeData	5
c2optimize	6
call_dpoilog	6
data2Gviz	7
DimNames	7
DirScore	8
Emission	9
EmissionParams	9
example	10
fitBdClust	10
fitHMM	11
flags	13
getAvgSignal	13
getLogLik	14
getPosterior	15
getSizeFactors	16
getViterbi	16
HMM	17
HMM-class	18
HMMEmission	19
HMMEmission-class	19
initBdClust	20
initBdHMM	21
initHMM	22
InitProb	22
LogLik	23
observations	24
pilot.hg19	24
runningMean	24
StateNames	25
trainRegions	26
Transitions	26
ucscGenes	27
viterbi2GRanges	27
viterbi2Gviz	28
yeastTF_databychrom_ex	28
yeastTF_SGDGenes	29
[,bdHMM,ANY,ANY,ANY-method	29
[,HMM,ANY,ANY,ANY-method	30

 STAN-package

The genomic STate ANnotation package

Description

The genomic STate ANnotation package

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

References

Zacher, B. and Lidschreiber, M. and Cramer, P. and Gagneur, J. and Tresch, A. (2014): Annotation of genomics data using bidirectional hidden Markov models unveils variations in Pol II transcription cycle Mol. Syst. Biol. 10:768

 bdHMM

Create a bdHMM object

Description

This function creates a bdHMM function.

Usage

```
bdHMM(initProb = numeric(), transMat = matrix(numeric(), ncol = 0, nrow =
  0), emission, nStates = numeric(), status = character(),
  stateNames = character(), dimNames = character(),
  transitionsOptim = "analytical", directedObs = integer(),
  dirScore = numeric())
```

Arguments

<code>initProb</code>	Initial state probabilities.
<code>transMat</code>	Transition probabilities
<code>emission</code>	Emission parameters as an HMM Emission object.
<code>nStates</code>	Number of states.
<code>status</code>	Status of the bdHMM. 'Initial' means that the model was not fitted yet. 'EM' means that the model was optimized using Expectation maximization.
<code>stateNames</code>	Indicates directinality of states. States can be forward (F1, F2, ..., Fn), reverse (R1, R2, ..., Rn) or unidirectional (U1, U2, ..., Um). Number of F and R states must be equal and twin states are indicated by integers in id (e.g. F1 and R1 and twins).

dimNames	Names of data tracks.
transitionsOptim	There are three methods to choose from for fitting the transitions. Bidirectional transition matrices (invariant under reversal of time and direction) can be fitted using c('rsolnp', 'analytical'). 'None' uses standard update formulas and the resulting matrix is not constrained to be bidirectional.
directedObs	An integer indicating which dimensions are directed. Undirected dimensions are 0. Directed observations must be marked as unique integer pairs. For instance c(0,0,0,0,0,1,1,2,2,3,3) contains 5 undirected observations, and three pairs (one for each direction) of directed observations.
dirScore	Directionality score of states of a fitted bdHMM.

Value

bdHMM

See Also[HMMEmission](#)**Examples**

```

nStates = 5
stateNames = c('F1', 'F2', 'R1', 'R2', 'U1')
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
myEmission = list(d1=HMMEmission(type='Gaussian', parameters=list(mu=means, cov=Sigma), nStates=length(means)))

bdhmm = bdHMM(initProb=initProb, transMat=transMat, emission=myEmission, nStates=nStates, status='initial', stateNames=stateNames)

```

bdHMM-class

This class is a generic container for bidirectional Hidden Markov Models.

Description

This class is a generic container for bidirectional Hidden Markov Models.

Slots

initProb Initial state probabilities.
transMat Transition probabilities
emission Emission parameters as an HMMEmission object.
nStates Number of states.

status of the HMM. On of c('initial', 'EM').

stateNames State names.

dimNames Names of data tracks.

LogLik Log likelihood of a fitted HMM.

transitionsOptim There are three methods to choose from for fitting the transitions. Bidirectional transition matrices (invariant under reversal of time and direction) can be fitted using c('rsolnp', 'ipopt'). 'None' uses standard update formulas and the resulting matrix is not constrained to be bidirectional.

directedObs An integer indicating which dimensions are directed. Undirected dimensions are 0. Directed observations must be marked as unique integer pairs. For instance c(0,0,0,0,0,1,1,2,2,3,3) contains 5 undirected observations, and three pairs (one for each direction) of directed observations.

dirScore Directionality score of states of a fitted bdHMM.

See Also

[HMMEmission](#)

Examples

```
nStates = 5
stateNames = c('F1', 'F2', 'R1', 'R2', 'U1')
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
myEmission = list(d1=HMMEmission(type='Gaussian', parameters=list(mu=means, cov=Sigma), nStates=length(means)))

bdhmm = bdHMM(initProb=initProb, transMat=transMat, emission=myEmission, nStates=nStates, status='initial', stateNames=stateNames)
```

binarizeData

Binarize Sequencing data with the default ChromHMM binarization

Description

Binarize Sequencing data with the default ChromHMM binarization

Usage

```
binarizeData(obs, thresh = 1e-04)
```

Arguments

obs The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).

thresh Upper tail probability to find a value equal or higher than Y ($P(Y \geq y)$)

Value

Binarized observation sequences as a list.

Examples

```
data(trainRegions)
binData = binarizeData(obs = trainRegions, thresh = 1e-4)
```

c2optimize

Optimize transitions

Description

The function is called from C++ to optimize transitions.

Usage

```
c2optimize(pars)
```

Arguments

pars Parameters for optimization.

Value

optimized transitions

call_dpoilog

Calculate density of the Poisson-Log-Normal distribution.

Description

Calculate density of the Poisson-Log-Normal distribution.

Usage

```
call_dpoilog(x)
```

Arguments

x A vector $c(n, \mu, \sigma)$, where n is the number of observed counts, μ the mean of the Log-Normal distribution and σ its variance.

Value

Density of the Poisson-Log-Normal distribution.

Examples

```
call_dpoilog(c(5, 2, 1))
```

data2Gviz	<i>Convert data for plotting with Gviz</i>
-----------	--

Description

Convert data for plotting with Gviz

Usage

```
data2Gviz(obs, regions, binSize, gen, col = "black", type = "h", chrom)
```

Arguments

obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
regions	GRanges object of the regions (e.g. chromosomes) stored in the viterbi path.
binSize	The bin size of the viterbi path.
gen	The genome id, e.g. hg19, hg38 for human.
col	The color of the data tracks.
type	Type of plot (See Gviz DataTrack documentation).
chrom	Chromosome in which to create the object.

Value

A list containing the data tracks converted to Gviz objects for plotting.

DimNames	<i>Get dimNames of a (bd)HMM</i>
----------	----------------------------------

Description

This function returns the names of dimensions (data tracks).

Usage

```
DimNames(hmm)
```

Arguments

hmm	An object of class HMM or bdHMM.
-----	----------------------------------

Value

A character vector

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(dimNames="1", initProb=initProb, transMat=transMat, emission=HMMEmission(type='Gaussian', parameters=1
DimNames(hmm)
```

DirScore

Get directionality score of a bdHMM

Description

This function returns the directionality score of a bdHMM.

Usage

```
DirScore(bdhmm)
```

Arguments

bdhmm An object of class bdHMM.

Value

Directionality score of the bdHMM after model fitting.

Examples

```
data(example)
bdhmm_ex = initBdHMM(observations, dStates=3, method="Gaussian", directedObs=0)

# without flags
bdhmm_fitted_noFlags = fitHMM(observations, bdhmm_ex)
DirScore(bdhmm_fitted_noFlags)

# with flags
bdhmm_fitted_flags = fitHMM(observations, bdhmm_ex, dirFlags=flags)
DirScore(bdhmm_fitted_flags)
```

Emission	<i>Get Emission functions of a (bd)HMM</i>
----------	--

Description

This function returns the Emission functions of a (bd)HMM.

Usage

```
Emission(hmm)
```

Arguments

hmm An object of class HMM or bdHMM.

Value

An object of class HMM Emission

See Also

[HMMEmission](#)

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(initProb=initProb, transMat=transMat, emission=HMMEmission(type='Gaussian', parameters=list(mu=means,
Emission(hmm)
```

EmissionParams	<i>Get Emission parameters of a (bd)HMM.</i>
----------------	--

Description

This function returns the parameters of emission functions of a (bd)HMM object.

Usage

```
EmissionParams(hmm)
```

Arguments

hmm An object of class (bd)HMM.

Value

A list containing the parameters of the Emission functions.

See Also

[HMMEmission](#), [HMM](#), [bdHMM](#)

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(initProb=initProb, transMat=transMat, emission=HMMEmission(type='Gaussian', parameters=list(mu=means,
EmissionParams(hmm))
```

example	<i>The data for the bdHMM example in the vignette and examples in the manual</i>
---------	--

Description

The data for the bdHMM example in the vignette and examples in the manual

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

fitBdClust	<i>Fit a bidirectional Clustering</i>
------------	---------------------------------------

Description

The function is used to fit (bidirectional) Clusters, given one or more observation sequence.

Usage

```
fitBdClust(obs=list(), BdClust , convergence=1e-6, maxIters=1000, dirFlags=list(), emissionProbs=list
```

Arguments

obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
BdClust	The initial Bidirectional Cluster.
convergence	Convergence cutoff for EM-algorithm (default: 1e-6).
maxIters	Maximum number of iterations.
dirFlags	The flag sequence is needed when a bdHMM is fitted on undirected data (e.g.) ChIP only. It is a list of character vectors indication for each position its known directionality. U allows all states. F allows undirected states and states in forward direction. R allows undirected states and states in reverse direction.
emissionProbs	List of precalculated emission probabilities of emission function is of type 'null'.
effectiveZero	Transitions below this cutoff are analytically set to 0 to speed up computations.
verbose	logical for printing algorithm status or not.
nCores	Number of cores to use for computations.
incrementalEM	When TRUE, the incremental EM is used to fit the model, where parameters are updated after each iteration over a single observation sequence.
updateTransMat	Whether transitions should be updated during model learning, default: TRUE.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.

Value

A list containing the trace of the log-likelihood during EM learning and the fitted HMM model.

Examples

```
data(example)
bdclust_ex = initBdClust(observations, dStates=3, method="Gaussian")
bdclust_fitted = fitBdClust(observations, bdclust_ex)
```

fitHMM

Fit a Hidden Markov Model

Description

The function is used to fit (bidirectional) Hidden Markov Models, given one or more observation sequence.

Usage

```
fitHMM(obs=list(), hmm, convergence=1e-6, maxIters=1000, dirFlags=list(), emissionProbs=list(), effec
```

Arguments

<code>obs</code>	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
<code>hmm</code>	The initial Hidden Markov Model. This is a HMM .
<code>convergence</code>	Convergence cutoff for EM-algorithm (default: 1e-6).
<code>maxIters</code>	Maximum number of iterations.
<code>dirFlags</code>	The flag sequence is needed when a bdHMM is fitted on undirected data (e.g.) ChIP only. It is a list of character vectors indication for each position its known directionality. U allows all states. F allows undirected states and states in forward direction. R allows undirected states and states in reverse direction.
<code>emissionProbs</code>	List of precalculated emission probabilities of emission function is of type 'null'.
<code>effectiveZero</code>	Transitions below this cutoff are analytically set to 0 to speed up computations.
<code>verbose</code>	logical for printing algorithm status or not.
<code>nCores</code>	Number of cores to use for computations.
<code>incrementalEM</code>	When TRUE, the incremental EM is used to fit the model, where parameters are updated after each iteration over a single observation sequence.
<code>updateTransMat</code>	Whether transitions should be updated during model learning, default: TRUE.
<code>sizeFactors</code>	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a <code>length(obs) x ncol(obs[[1]])</code> matrix.
<code>clustering</code>	Boolean variable to specify whether it should be fit as an HMM or as bdClustering. Please, use function <code>bdClust</code> when <code>bdClust</code> is preferred.

Value

A list containing the trace of the log-likelihood during EM learning and the fitted HMM model.

See Also

[HMM](#)

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
hmm_fitted = fitHMM(observations, hmm_ex)
```

flags	<i>Pre-computed flag sequence for the 'example' data.</i>
-------	---

Description

Pre-computed flag sequence for the 'example' data.

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

getAvgSignal	<i>Compute average signal in state segmentation</i>
--------------	---

Description

Compute average signal in state segmentation

Usage

```
getAvgSignal(viterbi, obs, fct=mean)
```

Arguments

viterbi	A list containing the viterbi paths as factors. The output from getViterbi.
obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
fct	The averaging function, default: mean.

Value

A state x data track matrix containing the average signal.

Examples

```
data(yeastTF_databychrom_ex)
dStates = 6
dirobs = as.integer(c(rep(0,10), 1, 1))
bdhmm_gauss = initBdHMM(yeastTF_databychrom_ex, dStates = dStates, method = "Gaussian", directedObs=dirobs)
bdhmm_fitted_gauss = fitHMM(yeastTF_databychrom_ex, bdhmm_gauss)
viterbi_bdhmm_gauss = getViterbi(bdhmm_fitted_gauss, yeastTF_databychrom_ex)
avg_signal = getAvgSignal(viterbi_bdhmm_gauss, yeastTF_databychrom_ex)
```

getLogLik

Calculate log likelihood state distribution.

Description

The function calculates log likelihood for one or more observation sequence.

Usage

```
getLogLik(hmm, obs = list(), emissionProbs = list(), dirFlags = list(), verbose = FALSE, nCores = 1, sizeFactors = list())
```

Arguments

hmm	The Hidden Markov Model.
obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
emissionProbs	List of precalculated emission probabilities of emission function is of type 'null'.
dirFlags	The flag sequence is needed when a bdHMM is fitted on undirected data (e.g.) ChIP only. It is a list of character vectors indication for each position its known directionality. U allows all states. F allows undirected states and states in forward direction. R allows undirected states and states in reverse direction.
verbose	logical for printing algorithm status or not.
nCores	Number of cores to use for computations.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.

Value

The log likelihood of the observations sequences, given the model.

See Also

[HMM](#)

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
hmm_fitted = fitHMM(observations, hmm_ex)
loglik = getLogLik(hmm_fitted, observations)
loglik
```

getPosterior *Calculate posterior state distribution.*

Description

The function calculates posterior state probabilities for one or more observation sequence.

Usage

```
getPosterior(hmm, obs=list(), emissionProbs=list(), dirFlags=list(), verbose=FALSE, nCores=1, sizeFac
```

Arguments

hmm	The Hidden Markov Model.
obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
emissionProbs	List of precalculated emission probabilities of emission function is of type 'null'.
dirFlags	The flag sequence is needed when a bdHMM is fitted on undirected data (e.g.) ChIP only. It is a list of character vectors indication for each position its known directionality. U allows all states. F allows undirected states and states in forward direction. R allows undirected states and states in reverse direction.
verbose	logical for printing algorithm status or not.
nCores	Number of cores to use for computations.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.

Value

A list containing for the observation sequences the posterior state (col) distribution at each position (row).

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
hmm_fitted = fitHMM(observations, hmm_ex)
posterior = getPosterior(hmm_fitted, observations)
```

getSizeFactors *Compute size factors*

Description

Compute size factors

Usage

```
getSizeFactors(obs, celltypes)
```

Arguments

obs The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).

celltypes Indicates the cell type/tissue for each entry in obs.

Value

A celltype/tissue x data tracks matrix containing the size factors.

Examples

```
data(trainRegions)
celltypes = list("E123"=grep("E123", names(trainRegions)),
                "E116"=grep("E116", names(trainRegions)))
sizeFactors = getSizeFactors(trainRegions, celltypes)
sizeFactors
```

getViterbi *Calculate the most likely state path*

Description

Given a Hidden Markov Model, the function calculates the most likely state path (viterbi) for one or more observation sequence.

Usage

```
getViterbi(hmm, obs=list(), NAtol=5, emissionProbs=list(), verbose=FALSE, sizeFactors=matrix(1, nrow=
```


Arguments

hmm	The initial Hidden Markov Model.
obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
NAtol	Successive positions having NAs longer than this threshold are masked in the viterbi path.
emissionProbs	List of precalculated emission probabilities of emission function is of type 'null'.
verbose	logical for printing algorithm status or not.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.

Value

A list containint the vterbi paths.

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
hmm_fitted = fitHMM(observations, hmm_ex)
viterbi = getViterbi(hmm_fitted, observations)
```

HMM

Create a HMM object

Description

This function creates a HMM object.

Usage

```
HMM(initProb = numeric(), transMat = matrix(numeric(), ncol = 1, nrow = 1),
     emission, nStates = numeric(), status = character(),
     stateNames = character(), dimNames = character(), LogLik = numeric())
```

Arguments

initProb	Initial state probabilities.
transMat	Transition probabilities
emission	Emission parameters as an HMM Emission object.
nStates	Number of states.
status	of the HMM. On of c('initial', 'EM').
stateNames	State names.
dimNames	Names of data tracks.
LogLik	Log likelihood of a fitted HMM.

Value

HMM

See Also[HMMEmission](#)**Examples**

```

nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
HMM(initProb=initProb, transMat=transMat, emission=HMMEmission(type='Gaussian', parameters=list(mu=means, cov=S

```

HMM-class

*This class is a generic container for Hidden Markov Models.***Description**

This class is a generic container for Hidden Markov Models.

Slots

initProb Initial state probabilities.
transMat Transition probabilities
emission Emission parameters as an HMMEmission object.
nStates Number of states.
status of the HMM. On of c('initial', 'EM').
stateNames State names.
dimNames Names of data tracks.
LogLik Log likelihood of a fitted HMM.

See Also[HMMEmission](#)**Examples**

```

nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)

HMM(initProb=initProb, transMat=transMat, emission=HMMEmission(type='Gaussian', parameters=list(mu=means, cov=S

```

HMMemission	<i>Create a HMMemission object</i>
-------------	------------------------------------

Description

This function creates a HMMemission object.

Usage

```
HMMemission(type = character(), parameters = list(), nStates = numeric())
```

Arguments

type	The type of emission function c('Gaussian').
parameters	A list containing the the parameters for each state.
nStates	The number of states.

Value

HMMemission

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
HMMemission(type='Gaussian', parameters=list(mu=means, cov=Sigma), nStates=length(means))
```

HMMemission-class	<i>This class is a generic container for different emission functions of Hidden Markov Models.</i>
-------------------	--

Description

This class is a generic container for different emission functions of Hidden Markov Models.

Slots

type	The type of emission function c('Gaussian').
parameters	A list containing the the parameters for each state.
dim	Number of dimensions.
nStates	The number of states.

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
HMMemission(type='Gaussian', parameters=list(mu=means, cov=Sigma), nStates=length(means))
```

initBdClust	<i>Initialization of bidirectional Clustering</i>
-------------	---

Description

Initialization of bidirectional Clustering

Usage

```
initBdClust(obs, dStates = 0, uStates = 0, method, directedObs = rep(0, ncol(obs[[1]])), sizeFactors = m
```

Arguments

obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
dStates	The number of directed states.
uStates	The number of undirected states.
method	Emission distribution of the model. One out of c("NegativeBinomial", "Poisson-LogNormal", "NegativeMultinomial", "ZINegativeBinomial", "Poisson", "Bernoulli", "Gaussian", "IndependentGaussian")
directedObs	Integer vector defining the directionality (or strand-specificity) of the data tracks. Undirected (non-strand-specific) data tracks (e.g. ChIP) are indicated by '0'. Directed (strand-specific) data tracks are indicated by increasing pairs of integers. For instance c(0,0,0,1,1,2,2): The first three data tracks are undirected, followed by two pairs of directed measurements.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.
sharedCov	If TRUE, (co-)variance of (Independent)Gaussian is shared over states. Only applicable to 'Gaussian' or 'IndependentGaussian' emissions. Default: FALSE.
dirFlags	The flag sequence is needed when a bdHMM is fitted on undirected data (e.g.) ChIP only. It is a list of character vectors indication for each position its known directionality. U allows all states. F allows undirected states and states in forward direction. R allows undirected states and states in reverse direction.

Value

A HMM object.

initBdHMM

Initialization of bidirectional hidden Markov models

Description

Initialization of bidirectional hidden Markov models

Usage

```
initBdHMM(obs, dStates = 0, uStates = 0, method, dirFlags = NULL, directedObs = rep(0, ncol(obs[[1]])),
```

Arguments

obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
dStates	The number of directed states.
uStates	The number of undirected states.
method	Emission distribution of the model. One out of c("NegativeBinomial", "Poisson-LogNormal", "NegativeMultinomial", "ZINegativeBinomial", "Poisson", "Bernoulli", "Gaussian", "IndependentGaussian")
dirFlags	The flag sequence is needed when a bdHMM is fitted on undirected data (e.g.) ChIP only. It is a list of character vectors indication for each position its known directionality. U allows all states. F allows undirected states and states in forward direction. R allows undirected states and states in reverse direction.
directedObs	Integer vector defining the directionality (or strand-specificity) of the data tracks. Undirected (non-strand-specific) data tracks (e.g. ChIP) are indicated by '0'. Directed (strand-specific) data tracks are indicated by increasing pairs of integers. For instance c(0,0,0,1,1,2,2): The first three data tracks are undirected, followed by two pairs of directed measurements.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.
sharedCov	If TRUE, (co-)variance of (Independent)Gaussian is shared over states. Only applicable to 'Gaussian' or 'IndependentGaussian' emissions. Default: FALSE.

Value

A HMM object.

Examples

```
data(example)
bdHMM_ex = initBdHMM(observations, dStates=3, method="Gaussian")
```

<code>initHMM</code>	<i>Initialization of hidden Markov models</i>
----------------------	---

Description

Initialization of hidden Markov models

Usage

```
initHMM(obs, nStates, method, sizeFactors = matrix(1, nrow = length(obs), ncol = ncol(obs[[1]])), sharedCov = FALSE)
```

Arguments

<code>obs</code>	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
<code>nStates</code>	The number of states.
<code>method</code>	Emission distribution of the model. One out of <code>c("NegativeBinomial", "Poisson-LogNormal", "NegativeMultinomial", "ZINegativeBinomial", "Poisson", "Bernoulli", "Gaussian", "IndependentGaussian")</code>
<code>sizeFactors</code>	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a <code>length(obs) x ncol(obs[[1]])</code> matrix.
<code>sharedCov</code>	If TRUE, (co-)variance of (Independent)Gaussian is shared over states. Only applicable to 'Gaussian' or 'IndependentGaussian' emissions. Default: FALSE.

Value

A HMM object.

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
```

<code>InitProb</code>	<i>Get initial state probabilities of a (bd)HMM</i>
-----------------------	---

Description

This function returns the initial state probabilities of a (bd)HMM.

Usage

```
InitProb(hmm)
```

Arguments

`hmm` An object of class HMM or bdHMM.

Value

The initial state probabilities as a numeric vector.

See Also

[HMM](#), [bdHMM](#)

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(initProb=initProb, transMat=transMat, emission=HMMemission(type='Gaussian', parameters=list(mu=means,
InitProb(hmm)
```

LogLik

Get stateNames of a (bd)HMM

Description

This function returns the Log-Likelihood of a (bd)HMM.

Usage

```
LogLik(hmm)
```

Arguments

`hmm` An object of class HMM or bdHMM.

Value

Log likelihood during model fitting.

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
hmm_fitted = fitHMM(observations, hmm_ex)
LogLik(hmm_fitted)
```

observations	<i>Observation sequence for the 'example' data.</i>
--------------	---

Description

Observation sequence for the 'example' data.

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

pilot.hg19	<i>Genomic positions of processed signal for the Roadmap Epigenomics data set. Regions from the ENCODE pilot phase.</i>
------------	---

Description

Genomic positions of processed signal for the Roadmap Epigenomics data set. Regions from the ENCODE pilot phase.

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

runningMean	<i>Smooth data with running mean</i>
-------------	--------------------------------------

Description

Smooth data with running mean

Usage

```
runningMean(x, winHalfSize = 2)
```

Arguments

x	A vector with the data.
winHalfSize	The smoothing window half size.

Value

A vector containing the smoothed data.

Examples

```
data(trainRegions)
celltypes = list("E123"=grep("E123", names(trainRegions)),
                 "E116"=grep("E116", names(trainRegions)))
sizeFactors = getSizeFactors(trainRegions, celltypes)
sizeFactors
```

StateNames

Get stateNames of a (bd)HMM

Description

This function returns the names of states.

Usage

```
StateNames(hmm)
```

Arguments

hmm An object of class HMM or bdHMM.

Value

A character vector

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(stateNames=as.character(1:5), initProb=initProb, transMat=transMat, emission=HMMemission(type='Gaussian'))
StateNames(hmm)
```

trainRegions	<i>Training regions for the Roadmap Epigenomics data set. Three ENCODE pilot regions with data from two cell lines.</i>
--------------	---

Description

Training regions for the Roadmap Epigenomics data set. Three ENCODE pilot regions with data from two cell lines.

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

Transitions	<i>Get transitions of a (bd)HMM</i>
-------------	-------------------------------------

Description

This function returns the transition matrix of a (bd)HMM.

Usage

```
Transitions(hmm)
```

Arguments

hmm An object of class HMM or bdHMM.

Value

The transitions as a nStates x nStates matrix.

See Also

[HMM](#), [bdHMM](#)

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(initProb=initProb, transMat=transMat, emission=HMMemission(type='Gaussian', parameters=list(mu=means,
Transitions(hmm)
```

ucscGenes	<i>UCSC gene annotation for the Roadmap Epigenomics data set.</i>
-----------	---

Description

UCSC gene annotation for the Roadmap Epigenomics data set.

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

viterbi2GRanges	<i>Convert the viterbi path to a GRanges object</i>
-----------------	---

Description

Convert the viterbi path to a GRanges object

Usage

```
viterbi2GRanges(viterbi, regions, binSize)
```

Arguments

viterbi	A list containing the viterbi paths as factors. The output from <code>getViterbi</code> .
regions	GRanges object of the regions (e.g. chromosomes) stored in the viterbi path.
binSize	The bin size of the viterbi path.

Value

The viterbi path as GRanges object.

Examples

```
library(GenomicRanges)
data(yeastTF_databychrom_ex)
dStates = 6
dirobs = as.integer(c(rep(0,10), 1, 1))
bdhmm_gauss = initBdHMM(yeastTF_databychrom_ex, dStates = dStates, method = "Gaussian", directedObs=dirobs)
bdhmm_fitted_gauss = fitHMM(yeastTF_databychrom_ex, bdhmm_gauss)
viterbi_bdhmm_gauss = getViterbi(bdhmm_fitted_gauss, yeastTF_databychrom_ex)
yeastGRanges = GRanges(IRanges(start=1214616, end=1225008), seqnames="chrIV")
names(viterbi_bdhmm_gauss) = "chrIV"
viterbi_bdhmm_gauss_gr = viterbi2GRanges(viterbi_bdhmm_gauss, yeastGRanges, 8)
```

viterbi2Gviz *Convert state segmentation for plotting with Gviz*

Description

Convert state segmentation for plotting with Gviz

Usage

```
viterbi2Gviz(viterbi, chrom, gen, from, to, statecols, col = NULL)
```

Arguments

viterbi	A list containing the viterbi paths as factors. The output from getViterbi.
chrom	The chromosome/sequence id to convert.
gen	The genome id, e.g. hg19, hg38 for human.
from	Genomic start position.
to	Genomic end position.
statecols	Named vector with state colors.
col	Background color.

Value

A list containing the viterbi path converted to Gviz objects for plotting.

yeastTF_databychrom_ex

Processed ChIP-on-chip data for yeast TF example

Description

Processed ChIP-on-chip data for yeast TF example

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

yeastTF_SGDGenes *SGD annotation for the yeast TF example*

Description

SGD annotation for the yeast TF example

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

[,bdHMM,ANY,ANY,ANY-method
 extract parts of bdHMM

Description

extract parts of bdHMM

Usage

```
## S4 method for signature 'bdHMM,ANY,ANY,ANY'
x[i, j, ..., drop = "missing"]
```

Arguments

x	A bidirectional hidden Markov model.
i	State ids to extract.
j	Emissions to extract.
...	...
drop	...

Value

Extract parts of bdHMM

[,HMM,ANY,ANY,ANY-method
extract parts of HMM

Description

extract parts of HMM

Usage

```
## S4 method for signature 'HMM,ANY,ANY,ANY'  
x[i, j, ..., drop = "missing"]
```

Arguments

x	A hidden Markov model.
i	State ids to extract.
j	Emissions to extract.
...	...
drop	...

Value

extract parts of HMM

Index

* data

example, 10
flags, 13
observations, 24
pilot.hg19, 24
trainRegions, 26
ucscGenes, 27
yeastTF_databychrom_ex, 28
yeastTF_SGDGenes, 29

* package

STAN-package, 3
.HMM (HMM-class), 18
.HMMEmission (HMMEmission-class), 19
.bdHMM (bdHMM-class), 4
[,HMM, ANY, ANY, ANY-method, 30
[,bdHMM, ANY, ANY, ANY-method, 29

bdHMM, 3, 10, 23, 26
bdHMM-class, 4
binarizeData, 5

c2optimize, 6
call_dpoilog, 6

data2Gviz, 7
DimNames, 7
DirScore, 8

Emission, 9
EmissionParams, 9
example, 10

fitBdClust, 10
fitHMM, 11
flags, 13

getAvgSignal, 13
getLogLik, 14
getPosterior, 15
getSizeFactors, 16
getViterbi, 16

HMM, 10, 12, 14, 17, 23, 26
HMM-class, 18
HMMEmission, 4, 5, 9, 10, 18, 19
HMMEmission-class, 19

initBdClust, 20
initBdHMM, 21
initHMM, 22
InitProb, 22

LogLik, 23

observations, 24

pilot.hg19, 24

runningMean, 24

STAN-package, 3
StateNames, 25

trainRegions, 26
Transitions, 26

ucscGenes, 27

viterbi2GRanges, 27
viterbi2Gviz, 28

yeastTF_databychrom_ex, 28
yeastTF_SGDGenes, 29