

# Package ‘treekoR’

October 14, 2021

**Type** Package

**Title** Cytometry Cluster Hierarchy and Proportions to Parent

**Version** 1.0.0

**biocViews** Clustering, DifferentialExpression, FlowCytometry, ImmunOncology, MassSpectrometry, SingleCell, Software, StatisticalMethod, Visualization

**Description** treekoR is a novel framework that aims to utilise the hierarchical nature of single cell cytometry data to find robust and interpretable associations between cell subsets and patient clinical end points. These associations are aimed to recapitulate the nested proportions prevalent in workflows involving manual gating, which are often overlooked in workflows using automatic clustering to identify cell populations. We developed treekoR to: Derive a hierarchical tree structure of cell clusters; measure the proportions to parent (proportions of cells each node in the tree relative to the number of cells belonging its parent node), in addition to the proportions to all (proportion of cells in each node relative to all cells); perform significance testing using the calculated proportions; and provide an interactive html visualisation to help highlight key results.

**Depends** R (>= 4.1)

**Imports** stats, utils, tidyr, dplyr, magrittr, data.table, ggiraph, ggplot2, hopach, ape, ggtree, patchwork, SingleCellExperiment

**License** GPL-3

**Encoding** UTF-8

**LazyData** false

**RoxygenNote** 7.1.1

**Suggests** knitr, rmarkdown, BiocStyle, CATALYST, testthat (>= 3.0.0)

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/treekoR>

**git\_branch** RELEASE\_3\_13

**git\_last\_commit** 2b645b7

**git\_last\_commit\_date** 2021-05-19

**Date/Publication** 2021-10-14

**Author** Adam Chan [aut, cre],  
Ellis Patrick [ctb]

**Maintainer** Adam Chan <adam.s.chan@sydney.edu.au>

## R topics documented:

addFreqBars . . . . .	2
addHeatMap . . . . .	3
addTree . . . . .	4
colourTree . . . . .	5
DeBiasi_COVID_CD8_samp . . . . .	6
findChildren . . . . .	7
getCellProp . . . . .	7
getClusterTree . . . . .	8
getTreeResults . . . . .	9
hopachToPhylo . . . . .	10
plotInteractiveHeatmap . . . . .	11
plotSigScatter . . . . .	13
runHOPACH . . . . .	14
testTree . . . . .	15
<b>Index</b>	<b>17</b>

---

addFreqBars	<i>Title</i>
-------------	--------------

---

### Description

a function to add the frequency bars for each cluster

### Usage

```
addFreqBars(
  p,
  clusters,
  offset = 0.75,
  bar_length = 3,
  bar_width = 0.4,
  freq_labels = FALSE
)
```

**Arguments**

p	a phylogenetic tree plot created from the <code>ggtree()</code> function
clusters	a vector representing the cell type or cluster of each cell (can be character or numeric)
offset	distance between the heatmap and frequency bars
bar_length	length of bar with max frequency
bar_width	width of each frequency bar
freq_labels	boolean indicated whether or not to show frequency bar labels

**Value**

an interactive ggplot graph object with frequency bars of clusters alongside heatmap of cluster median expression

---

addHeatMap	<i>Title</i>
------------	--------------

---

**Description**

a function to add a heatmap of cluster medians alongside the phylogenetic tree

**Usage**

```
addHeatMap(
  p,
  cluster_medians,
  offset = 0.5,
  width = 1,
  expand_y_lim = 20,
  low = "#313695",
  mid = "ivory",
  high = "#A50026",
  colnames_angle = 90,
  metric_name = "Column z-score"
)
```

**Arguments**

p	a phylogenetic tree plot created from the <code>ggtree()</code> function
cluster_medians	a dataframe with the cluster medians. The rownumbers of the clusters median data frame should correspond to the nodes in the phylo tree. The column names should also correspond to the labels you want to use
offset	the distance between the tree plot and heatmap

width	width of each tile in the heatmap
expand_y_lim	white space below heatmap
low	colour used for low values on heatmap
mid	colour used for medium values on heatmap
high	colour used for large values on heatmap
colnames_angle	angle for x-axis label
metric_name	legend title

**Value**

an interactive ggplot graph object with heatmap of median cluster expressions plotted alongside hierarchical tree

---

addTree	<i>Title</i>
---------	--------------

---

**Description**

a function to create a skeleton tree diagram to display significance testing results on each node

**Usage**

```
addTree(p, offset = 0.3, font_size = 2.5, hjust = 0)
```

**Arguments**

p	a phylogenetic tree plot created from the ggtree() function
offset	distance between leaf nodes on the tree and their labels
font_size	font size of leaf labels
hjust	horizontal justification as defined in ggplot2

**Value**

a ggtree graph object with the hierarchical tree of clusters and corresponding labels



```
tested_tree <- testTree(clust_tree$clust_tree,
                        clusters=clusters,
                        samples=samples,
                        classes=classes,
                        pos_class_name=NULL,
                        subjects=NULL,
                        paired = FALSE)

colourTree(tested_tree)
```

---

DeBiasi\_COVID\_CD8\_samp

*COVID-19 Sample data*

---

### **Description**

Data from a an experiment investigating T cell compositions between COVID-19 patients and healthy control. This data has been transformed using a arcsinh transform using a co-factor of 5 and randomly subsetted

### **Usage**

```
data(COVIDSampleData)
```

### **Format**

An object of class "SingeCellExperiment"

### **Source**

[FlowRepository](#)

### **References**

De Biasi et al. (2020) Nat Commun 11, 3434 ([Nature](#))

### **Examples**

```
data(COVIDSampleData)
```

---

findChildren	<i>Title</i>
--------------	--------------

---

**Description**

Title

**Usage**

```
findChildren(tree)
```

**Arguments**

tree	a ggtree object
------	-----------------

**Value**

a ggtree object with the data containing a column with the clusters contained in each node

---

getCellProp	<i>getCellProp</i>
-------------	--------------------

---

**Description**

getCellProp

**Usage**

```
getCellProp(phylo, clusters, samples, classes)
```

**Arguments**

phylo	a phylogram with tip.labels corresponding to cell types/cluster contained in 'clusters' vector
clusters	a vector representing the cell type or cluster of each cell (can be character or numeric). If numeric, cluster names need to be consecutive starting from 1.
samples	a vector identifying the patient each cell belongs to
classes	a vector containing the patient outcome/class each cell belongs to

**Value**

a dataframe containing proportions calculated for each sample

**Examples**

```

library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_tree <- getClusterTree(exprs,
                             clusters,
                             hierarchy_method="hopach")

prop_df <- getCellProp(clust_tree$clust_tree,
                      clusters=clusters,
                      samples=samples,
                      classes=classes)

```

---

getClusterTree	<i>getClusterTree</i> This function takes a CATALYST sce with clusters and creates a hierarchical tree
----------------	--

---

**Description**

getClusterTree This function takes a CATALYST sce with clusters and creates a hierarchical tree

**Usage**

```

getClusterTree(
  exprs,
  clusters,
  hierarchy_method = "hopach",
  hopach_kmax = 5,
  hopach_K = 10
)

```

**Arguments**

exprs	a dataframe containing single cell expression data
clusters	a vector representing the cell type or cluster of each cell (can be character or numeric). If numeric, cluster names need to be consecutive starting from 1.
hierarchy_method	a string indicating the hierarchical tree construction method to be used
hopach_kmax	integer between 1 and 9 specifying the maximum number of children at each node in the tree
hopach_K	positive integer specifying the maximum number of levels in the tree. Must be 15 or less, due to computational limitations (overflow)



**Value**

a list containing the cluster median frequencies and a phylogram of the hierarchical tree

**Examples**

```
library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_tree <- getClusterTree(exprs,
                             clusters,
                             hierarchy_method="hopach")
```

---

getTreeResults

*getTreeResults*


---

**Description**

getTreeResults

**Usage**

```
getTreeResults(testedTree, sort_by = "parent")
```

**Arguments**

testedTree	a ggtree object outputed from testTree()
sort_by	whether to sort by p-values testing via proportions to parent or p-values testing via absolute proportions. Values can be c(NA, "parent", "all")

**Value**

a dataframe with hierarchical tree nodes, corresponding clusters and corresponding significance testing results

**Examples**

```
library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
```

```

classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_tree <- getClusterTree(exprs,
                             clusters,
                             hierarchy_method="hopach")

tested_tree <- testTree(clust_tree$clust_tree,
                       clusters=clusters,
                       samples=samples,
                       classes=classes,
                       pos_class_name=NULL,
                       subjects=NULL,
                       paired = FALSE)

res_df <- getTreeResults(tested_tree)

head(res_df, 10)

```

---

hopachToPhylo

*Title*

---

### Description

Title

### Usage

```
hopachToPhylo(res)
```

### Arguments

`res` an object returned from the runHOPACH() function

### Value

a phylogram converted from the outputted list from the runHOPACH function

### Examples

```

library(SingleCellExperiment)
library(data.table)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

```

```
clust_med_dt <- as.data.table(exprs)
clust_med_dt[, cluster_id := clusters]
res <- clust_med_dt[, lapply(.SD, median, na.rm=TRUE), by=cluster_id]
res2 <- res[, .SD, .SDcols = !c('cluster_id')]

hopach_res <- runHOPACH(as.data.frame(scale(res2)))
phylo <- hopachToPhylo(hopach_res)
```

---

plotInteractiveHeatmap

*Title*

---

### Description

This function takes a hierarchical tree which has been tested for proportion to all and proportion to parent cluster

### Usage

```
plotInteractiveHeatmap(
  testedTree,
  clust_med_df,
  clusters,
  svg_width = 13,
  svg_height = 9,
  tr_offset = 0.3,
  tr_font_size = 2,
  tr_point_size = 1.5,
  tr_col_high = "#00c434",
  tr_col_low = "purple",
  tr_col_mid = "ivory2",
  hm_offset = 1,
  hm_tile_width = 1,
  hm_expand_y_lim = 20,
  hm_col_high = "#cc2010",
  hm_col_mid = "#fff8de",
  hm_col_low = "#66a6cc",
  fb_offset = 0.75,
  fb_bar_length = 3,
  fb_bar_width = 0.4,
  fb_freq_labels = FALSE
)
```

### Arguments

testedTree      a ggtree object that has been run through the testTree

<code>clust_med_df</code>	a dataframe with the cluster medians. The rownumbers of the clusters median data frame should correspond to the nodes in the phylo tree. The column names should also correspond to the labels you want to use
<code>clusters</code>	a vector representing the cell type or cluster of each cell (can be character or numeric)
<code>svg_width</code>	width of svg canvas
<code>svg_height</code>	height of svf canvas
<code>tr_offset</code>	distance between leaf nodes on the tree and their labels
<code>tr_font_size</code>	font size of leaf labels
<code>tr_point_size</code>	size of each node in the tree
<code>tr_col_high</code>	colour used for high test statistics, coloured on the nodes and branches of the tree
<code>tr_col_low</code>	colour used for low test statistics, coloured on the nodes and branches of the tree
<code>tr_col_mid</code>	colour used for medium test statistics, coloured on the nodes and branches of the tree
<code>hm_offset</code>	distance between the tree and the heatmap
<code>hm_tile_width</code>	width of each tile in the heatmap
<code>hm_expand_y_lim</code>	white space below heatmap
<code>hm_col_high</code>	colour used for large values on heatmap
<code>hm_col_mid</code>	colour used for medium values on heatmap
<code>hm_col_low</code>	colour used for low values on heatmap
<code>fb_offset</code>	distance between the heatmap and frequency bars
<code>fb_bar_length</code>	length of bar with max frequency
<code>fb_bar_width</code>	width of each frequency bar
<code>fb_freq_labels</code>	boolean indicated whether or not to show frequency bar labels

**Value**

an interactive ggplot object containing the hierarchical tree of clusters coloured by significance testing results, with corresponding heatmap and a scatterplot comparing significance whne testing using proportions to parent vs. absolute proportions

**Examples**

```
library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id
```

```
clust_tree <- getClusterTree(exprs,
                             clusters,
                             hierarchy_method="hopach")

tested_tree <- testTree(clust_tree$clust_tree,
                       clusters=clusters,
                       samples=samples,
                       classes=classes,
                       pos_class_name=NULL,
                       subjects=NULL,
                       paired = FALSE)

plotInteractiveHeatmap(tested_tree,
                      clust_med_df = clust_tree$median_freq,
                      clusters=clusters)
```

---

plotSigScatter

*plotSigScatter*

---

## Description

plotSigScatter

## Usage

```
plotSigScatter(testedTree, scatter_tooltip, max_val)
```

## Arguments

testedTree	an output from the function testTree()
scatter_tooltip	vector containing tooltips for interactive plot
max_val	maximum value to set as x/y axis limits

## Value

a ggplot object, containing test statistics from testing proportions relative to parent against the test statistics from testing absolute proportions.

runHOPACH

*runHOPACH***Description**

runHOPACH

**Usage**

```
runHOPACH(data, K = 10, kmax = 5, dissimilarity_metric = "cor")
```

**Arguments**

data	dataframe containing the median expression of the clusters/cell types
K	positive integer specifying the maximum number of levels in the tree. Must be 15 or less, due to computational limitations (overflow)
kmax	integer between 1 and 9 specifying the maximum number of children at each node in the tree
dissimilarity_metric	metric used to calculate dissimilarities between clusters/cell types

**Value**

a list containing the groups each cluster belongs to at each level of the hopach tree

**Examples**

```
library(SingleCellExperiment)
library(data.table)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_med_dt <- as.data.table(exprs)
clust_med_dt[, cluster_id := clusters]
res <- clust_med_dt[, lapply(.SD, median, na.rm=TRUE), by=cluster_id]
res2 <- res[, .SD, .SDcols = !c('cluster_id')]

hopach_res <- runHOPACH(as.data.frame(scale(res2)))
```

---

testTree	<i>Title</i>
----------	--------------

---

### Description

This function takes a hierarchical tree of the cluster medians of a cytometry dataset, and then uses this structure to perform t-tests between conditions of patients testing for difference using the proportion of cluster relative to sample's n and proportion of cluster relative to sample's n of hierarchical parent cluster. Takes a ggtree object and returns a ggtree object with testing results appended in the data

### Usage

```
testTree(
  phylo,
  clusters,
  samples,
  classes,
  pos_class_name = NULL,
  subjects = NULL,
  paired = FALSE
)
```

### Arguments

phylo	a ggtree object
clusters	a vector representing the cell type or cluster of each cell (can be character or numeric). If numeric, cluster names need to be consecutive starting from 1.
samples	a vector identifying the patient each cell belongs to
classes	a vector containing the patient outcome/class each cell belongs to
pos_class_name	a character indicating which class is positive
subjects	a vector containing which subject the cell belongs to, used to identify matched samples in paired t-tests (not yet tested)
paired	a boolean indicating whether to performed paired t-tests (not yet tested)

### Value

a ggtree object with significance testing results in embedded data

### Examples

```
library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
```

```
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_tree <- getClusterTree(exprs,
                             clusters,
                             hierarchy_method="hopach")

tested_tree <- testTree(clust_tree$clust_tree,
                       clusters=clusters,
                       samples=samples,
                       classes=classes,
                       pos_class_name=NULL,
                       subjects=NULL,
                       paired = FALSE)
```



# Index

## \* datasets

DeBiasi\_COVID\_CD8\_samp, [6](#)

addFreqBars, [2](#)

addHeatMap, [3](#)

addTree, [4](#)

colourTree, [5](#)

DeBiasi\_COVID\_CD8\_samp, [6](#)

findChildren, [7](#)

getCellProp, [7](#)

getClusterTree, [8](#)

getTreeResults, [9](#)

hopachToPhylo, [10](#)

plotInteractiveHeatmap, [11](#)

plotSigScatter, [13](#)

runHOPACH, [14](#)

testTree, [15](#)