

Package ‘diffcoexp’

April 12, 2022

Title Differential Co-expression Analysis

Version 1.14.0

Date 2020-11-23

Author Wenbin Wei, Sandeep Amberkar, Winston Hide

Description A tool for the identification of differentially coexpressed links (DCLs) and differentially coexpressed genes (DCGs). DCLs are gene pairs with significantly different correlation coefficients under two conditions. DCGs are genes with significantly more DCLs than by chance.

Maintainer Wenbin Wei <wenbin.wei2@durham.ac.uk>

Depends R (>= 3.5), WGCNA, SummarizedExperiment

Imports stats, DiffCorr, psych, igraph, BiocGenerics

Suggests GEOquery

URL <https://github.com/hidelab/diffcoexp>

biocViews GeneExpression, DifferentialExpression, Transcription, Microarray, OneChannel, TwoChannel, RNASeq, Sequencing, Coverage, ImmunoOncology

License GPL (>2)

Encoding UTF-8

LazyData true

git_url <https://git.bioconductor.org/packages/diffcoexp>

git_branch RELEASE_3_14

git_last_commit 05e288d

git_last_commit_date 2021-10-26

Date/Publication 2022-04-12

R topics documented:

coexpr	2
comparecor	3
diffcoexp	4
exprs.1	8
exprs.2	8

Index**9**

coexpr	<i>Identification of gene pairs coexpressed in at least one of two conditions</i>
--------	---

Description

This function identifies gene pairs coexpressed in at least one of two conditions.

Usage

```
coexpr(exprs.1, exprs.2, r.method = c("pearson", "spearman")[1],
       q.method = c("BH", "holm", "hochberg", "hommel", "bonferroni", "BY", "fdr",
                    "none")[1], rth = 0.5, qth = 0.1)
```

Arguments

exprs.1	a SummarizedExperiment, data frame or matrix for condition 1, with gene IDs as rownames and sample IDs as column names.
exprs.2	a SummarizedExperiment, data frame or matrix for condition 2, with gene IDs as rownames and sample IDs as column names.
r.method	a character string specifying the method to be used to calculate correlation coefficients. It is passed to the cor function of the WGCNA package.
q.method	a character string specifying the method for adjusting p values. It is passed to the p.adjust function of the stats package.
rth	the cutoff of absolute value of correlation coefficients; must be within [0,1].
qth	the cutoff of q-value (adjusted p value); must be within [0,1].

Value

a data frame containing gene pairs that are coexpressed in at least one of the conditions with the criteria that absolute value of correlation coefficient is greater than rth and q value less than qth. It has the following columns:

Gene.1	Gene ID
Gene.2	Gene ID
cor.1	correlation coefficients under condition 1
cor.2	correlation coefficients under condition 2
cor.diff	difference between correlation coefficients under condition 2 and condition 1
p.1	p value under null hypothesis that correlation coefficient under condition 1 equals to zero
p.2	p value under null hypothesis that correlation coefficient under condition 2 equals to zero

p.diffcor	p value under null hypothesis that difference between two correlation coefficients under two conditions equals to zero using Fisher's r-to-Z transformation
q.1	adjusted p value under null hypothesis that correlation coefficient under condition 1 equals to zero
q.2	adjusted p value under null hypothesis that correlation coefficient under condition 2 equals to zero
q.diffcor	adjusted p value under null hypothesis that the difference between two correlation coefficients under two conditions equals to zero using Fisher's r-to-Z transformation

Examples

```
data(gse4158part)
allowWGCNAThreads()
res=coexpr(exprs.1 = exprs.1, exprs.2 = exprs.2, r.method = "spearman")
#The result is a data frames.
str(res)
```

comparecor

Compare gene-gene correlation coefficients under two conditions

Description

This function calculates correlation coefficients of all gene pairs under two conditions and compare them using Fisher's Z-transformation.

Usage

```
comparecor(exprs.1, exprs.2, r.method = c("pearson", "spearman")[1],
  q.method = c("BH", "holm", "hochberg", "hommel", "bonferroni", "BY", "fdr",
    "none")[1])
```

Arguments

exprs.1	a SummarizedExperiment, data frame or matrix for condition 1, with gene IDs as rownames and sample IDs as column names.
exprs.2	a SummarizedExperiment, data frame or matrix for condition 2, with gene IDs as rownames and sample IDs as column names.
r.method	a character string specifying the method to be used to calculate correlation coefficients. It is passed to the cor function of the WGCNA package.
q.method	a character string specifying the method for adjusting p values. It is passed to the p.adjust function of the stats package.

Value

a data frame containing the differences between the correlation coefficients under two conditions and their p values. It has the following columns:

Gene.1	Gene ID
Gene.2	Gene ID
cor.1	correlation coefficients under condition 1
cor.2	correlation coefficients under condition 2
cor.diff	difference between correlation coefficients under condition 2 and condition 1
p.1	p value under null hypothesis that correlation coefficient under condition 1 equals to zero
p.2	p value under null hypothesis that correlation coefficient under condition 2 equals to zero
p.diffcor	p value under null hypothesis that difference between two correlation coefficients under two conditions equals to zero using Fisher's r-to-Z transformation
q.1	adjusted p value under null hypothesis that correlation coefficient under condition 1 equals to zero
q.2	adjusted p value under null hypothesis that correlation coefficient under condition 2 equals to zero
q.diffcor	adjusted p value under null hypothesis that the difference between two correlation coefficients under two conditions equals to zero using Fisher's r-to-Z transformation

Examples

```
data(gse4158part)
allowWGCNAThreads()
res=comparecor(exprs.1 = exprs.1, exprs.2 = exprs.2, r.method = "spearman")
#The result is a data frames.
str(res)
```

diffcoexp

Differential co-expression analysis

Description

This function identifies differentially coexpressed links (DCLs) and differentially coexpressed genes (DCGs).

Usage

```
diffcoexp(exprs.1, exprs.2, r.method = c("pearson", "kendall", "spearman")[1],
q.method = c("BH", "holm", "hochberg", "hommel", "bonferroni", "BY", "fdr",
"none")[1], rth = 0.5, qth = 0.1, r.diffth = 0.5, q.diffth = 0.1,
q.dcgth = 0.1)
```

Arguments

<code>exprs.1</code>	a SummarizedExperiment, data frame or matrix for condition 1, with gene IDs as rownames and sample IDs as column names.
<code>exprs.2</code>	a SummarizedExperiment, data frame or matrix for condition 2, with gene IDs as rownames and sample IDs as column names.
<code>r.method</code>	a character string specifying the method to be used to calculate correlation coefficients. It is passed to the <code>cor</code> function of the WGCNA package.
<code>q.method</code>	a character string specifying the method for adjusting p values. It is passed to the <code>p.adjust</code> function of the stats package.
<code>rth</code>	the cutoff of absolute value of correlation coefficients; must be within [0,1].
<code>qth</code>	the cutoff of q-value (adjusted p value); must be within [0,1].
<code>r.diffth</code>	the cutoff of absolute value of the difference between the correlation coefficients of the two conditions; must be within [0,1].
<code>q.diffth</code>	the cutoff of q-value (adjusted p value) of the difference between the correlation coefficients of the two conditions; must be within [0,1].
<code>q.dcgth</code>	the cutoff of q-value (adjusted p value) of the genes enriched in the differentially correlated gene pairs between the two conditions; must be within [0,1].

Details

`diffcoexp` function identifies differentially coexpressed links (DCLs) and differentially coexpressed genes (DCGs). DCLs are gene pairs with significantly different correlation coefficients under two conditions (de la Fuente 2010, Jiang et al., 2016). DCGs are genes with significantly more DCLs than by chance (Yu et al., 2011, Jiang et al., 2016). It takes two gene expression matrices or data frames under two conditions as input, calculates gene-gene correlations under two conditions and compare them with Fisher's Z transformation, filter the correlation with the `rth` and `qth` and the correlation changes with `r.diffth` and `q.diffth`. It identifies DCGs using binomial probability model (Jiang et al., 2016).

The main steps are as follows:

- a). Correlation coefficients and p values of all gene pairs under two conditions are calculated.
- b). The difference between the correlation coefficients under two conditions are calculated and the p value is calculated using Fisher's Z-transformation.
- c). p values are adjusted.
- d). Gene pairs (links) coexpressed in at least one condition are identified using the criteria that at least one of the correlation coefficients under two conditions has absolute value greater than the threshold `rth` and adjusted p value less than the threshold `qth`. The links that meet the criteria are included in CLs.
- e). Differentially coexpressed gene pairs (links) are identified from CLs using the criteria that the absolute value of the difference between the two correlation coefficients is greater the threshold `r.diffth` and adjusted p value is less than the threshold `q.diffth`. The links that meet the criteria are included in DCLs.
- f). The DCLs are classified into three categories: "same signed", "diff signed", or "switched opposites". "same signed" indicates that the gene pair has same signed correlation coefficients under both

conditions. "diff signed" indicates that the gene pair has oppositely signed correlation coefficients under two conditions and only one of them meets the criteria that absolute correlation coefficient is greater than the threshold r_{th} and adjusted p value less than the threshold q_{th} . "switched opposites" indicates that the gene pair has oppositely signed correlation coefficients under two conditions and both of them meet the criteria that absolute correlation coefficient is greater than the threshold r_{th} and adjusted p value less than the threshold q_{th} .

g). All the genes in DCLs are tested for their enrichment of DCLs, i.e, whether they have more DCLs than by chance using binomial probability model (Jiang et al., 2016). Those with adjusted p value less than the threshold q_{dcgth} are included in DCGs.

Value

a list of two data frames.

The DCGs data frame contains genes that contribute to differentially correlated links (gene pairs) with q value less than q_{dcgth} . It has the following columns:

Gene	Gene ID
CLs	Number of links with absolute correlation coefficient greater than r_{th} and q value less than q_{th} in at least one condition
DCLs	Number of links that meet the criteria for CLs and the criteria that absolute difference between the correlation coefficients of the two condition is greater than r_{diffth} and q value less than q_{diffth}
DCL.same	Number of subset of DCLs with same signed correlation coefficients in both conditions
DCL.diff	Number of subset of DCLs with oppositely signed correlation coefficients under two conditions but only one of them has absolute correlation coefficient greater than r_{th} and q value less than q_{th}
DCL.switch	Number of subset of DCLs with oppositely signed correlation coefficients under two conditions and both of them have absolute correlation coefficient greater than r_{th} and q value less than q_{th}
p	p value of having \geq DCLs given CLs
q	adjusted p value

The DCLs data frame contains the differentially correlated links (gene pairs) that meet the criteria that at least one of their correlation coefficients ($cor.1$ and/or $cor.2$) is greater than r_{th} with q value ($q.1$ and/or $q.2$) less than q_{th} and the absolute value of the difference between the correlation coefficients under two conditions ($cor.diff$) is greater than r_{diffth} with $q_{diffcor}$ less than q_{diffth} . It has the following columns:

Gene.1	Gene ID
Gene.2	Gene ID
cor.1	correlation coefficients under condition 1
cor.2	correlation coefficients under condition 2
cor.diff	difference between correlation coefficients under condition 2 and condition 1
p.1	p value under null hypothesis that correlation coefficient under condition 1 equals to zero

p.2	p value under null hypothesis that correlation coefficient under condition 2 equals to zero
p.diffcor	p value under null hypothesis that difference between two correlation coefficients under two conditions equals to zero using Fisher's r-to-Z transformation
q.1	adjusted p value under null hypothesis that correlation coefficient under condition 1 equals to zero
q.2	adjusted p value under null hypothesis that correlation coefficient under condition 2 equals to zero
q.diffcor	adjusted p value under null hypothesis that the difference between two correlation coefficients under two conditions equals to zero using Fisher's r-to-Z transformation
type	can have value "same signed", "diff signed", or "switched opposites". "same signed" indicates that the gene pair has same signed correlation coefficients under both conditions. "diff signed" indicates that the gene pair has oppositely signed correlation coefficients under two conditions and only one of them meets the criteria that absolute correlation coefficient is greater than rth and q value less than qth. "switched opposites" indicates that the gene pair has oppositely signed correlation coefficients under two conditions and both of them meet the criteria that absolute correlation coefficient is greater than rth and q value less than qth.

Author(s)

Wenbin Wei

References

1. de la Fuente A. From "differential expression" to "differential networking" - identification of dysfunctional regulatory networks in diseases. *Trends in Genetics*. 2010 Jul;26(7):326-33.
2. Jiang Z, Dong X, Li Z-G, He F, Zhang Z. Differential Coexpression Analysis Reveals Extensive Rewiring of Arabidopsis Gene Coexpression in Response to *Pseudomonas syringae* Infection. *Scientific Reports*. 2016 Dec;6(1):35064.
3. Yu H, Liu B-H, Ye Z-Q, Li C, Li Y-X, Li Y-Y. Link-based quantitative methods to identify differentially coexpressed genes and gene pairs. *BMC bioinformatics*. 2011;12(1):315.

Examples

```
data(gse4158part)
allowWGCNAThreads()
res=diffcoexp(exprs.1 = exprs.1, exprs.2 = exprs.2, r.method = "spearman")
#The results are a list of two data frames, one for differentially co-expressed
#links (DCLs, gene pairs) and one for differentially co-expressed genes (DCGs).
str(res)
```

exprs.1

exprs.1

Description

expression of 400 genes in 14 samples (GSM94988 to GSM95001) of yeast after pulses 2 g/l glucose, <https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE4158>.

Usage

exprs.1

Format

A matrix with 400 genes and 14 samples.

exprs.2

exprs.2

Description

expression of 400 genes in 14 samples (GSM94988 to GSM95001) of yeast after pulses 0.2 g/l glucose, <https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE4158>.

Usage

exprs.2

Format

A matrix with 400 genes and 12 samples.

Index

* **coexpression**

coexpr, [2](#)

comparecor, [3](#)

diffcoexp, [4](#)

* **datasets**

exprs.1, [8](#)

exprs.2, [8](#)

coexpr, [2](#)

comparecor, [3](#)

diffcoexp, [4](#)

exprs.1, [8](#)

exprs.2, [8](#)