

FDb.FANTOM4.promoters.hg19

April 10, 2016

hg18ToHg19

UCSC liftOver chain for hg18 to hg19, used in build scripts

Description

In the subdirectory `inst/build/`, there are several scripts that rebuild this FeatureDb from scratch. Since this is lifted from hg18, a chain is included.

Author(s)

Tim Triche, Jr.

Examples

```
data(hg18ToHg19)
hg18ToHg19
```

FDb.FANTOM4.promoters.hg19

Annotation package for FANTOM4 CAGE promoters from THP-1 cells

Description

This package loads one or more FeatureDb objects. Such FeatureDb objects are an R interface to prefabricated databases contained by this package. In the case of the FANTOM4 promoter database, it is FDb.FANTOM4.promoters.hg19 (hg18 is available directly from `unibas.ch`).

Author(s)

Tim Triche, Jr.

See Also

[features makeFeatureDbFromUCSC import.bed](#)

Examples

```
## load the library
library(FDb.FANTOM4.promoters.hg19)

## list the contents that are loaded into memory
ls('package:FDb.FANTOM4.promoters.hg19')

## show the db object that is loaded by calling it's name
FDb.FANTOM4.promoters.hg19

## extract features for use in annotating data
FANTOM4.hg19 <- features(FDb.FANTOM4.promoters.hg19)

## we'd prefer if R would stop us from comparing across assemblies:
met <- metadata(FDb.FANTOM4.promoters.hg19) ## need to fetch genome
genome(FANTOM4.hg19) <- met[which(met[, 'name'] == 'Genome'), 'value']

## Plot the observed/expected CpG ratio look like across promoters
## (computed as  $\Pr(\text{CG}) / \Pr(\text{C})\Pr(\text{G})\Pr(\text{CG}|\text{G}, \text{C})$  within a 3kb window)
## Conversion back to numeric is due to an artifact of features()
values(FANTOM4.hg19)$oecg <- as.numeric(values(FANTOM4.hg19)$oecg)
hist(values(FANTOM4.hg19)$oecg, breaks=200,
      xlab='Observed/expected CpG content from hg19',
      main='FANTOM4 promoter CpG content, 3kb windows')

## The function used for this is FDb.FANTOM4.promoters.hg19:::oecg()
```

Index

*Topic **data**

FDb.FANTOM4.promoters.hg19, [1](#)

hg18ToHg19, [1](#)

*Topic **package**

FDb.FANTOM4.promoters.hg19, [1](#)

FDb.FANTOM4.promoters.hg19, [1](#)

FDb.FANTOM4.promoters.hg19-package

(FDb.FANTOM4.promoters.hg19), [1](#)

features, [2](#)

hg18ToHg19, [1](#)

import.bed, [2](#)

makeFeatureDbFromUCSC, [2](#)