

Package ‘bioDist’

April 11, 2018

Title Different distance measures

Version 1.50.0

Author B. Ding, R. Gentleman and Vincent Carey

Description A collection of software tools for calculating distance measures.

Maintainer Bioconductor Package Maintainer

<maintainer@bioconductor.org>

License Artistic-2.0

Depends R (>= 2.0), methods, Biobase, KernSmooth

Suggests locfit

biocViews Clustering, Classification

NeedsCompilation no

R topics documented:

closest.top	1
cor.dist	2
euc	3
KLD.matrix	4
KLdist.matriX	5
man	7
mutualInfo	8
spearman.dist	9
tau.dist	10
Index	11

closest.top *Find the closest genes.*

Description

Find the closest genes to the supplied target gene based on the supplied distances.

Usage

```
closest.top(x, dist.mat, top)
```

Arguments

x the name of the gene (feature) to use.
dist.mat either a dist object or a matrix of distances.
top the number of closest genes desired.

Details

The feature named x must be in the supplied distances. If so, then the top closest other features are returned.

Value

A vector of names of the top closest features.

Author(s)

Beiyong Ding

See Also

[cor.dist](#), [spearman.dist](#), [tau.dist](#), [euc](#), [man](#), [KLdist.matrix](#), [KLD.matrix](#), [mutualInfo](#)

Examples

```
data(sample.ExpressionSet)
sE <- sample.ExpressionSet[1:100,]
d1 <- KLdist.matrix(sE, sample = FALSE)
closest.top(featureNames(sE)[1], d1, 5)
```

cor.dist

Pearson correlational distance

Description

Calculate pairwise Pearson correlational distances, i.e. 1-COR or 1-|COR|, and saves as a 'dist' object

Usage

```
cor.dist(x, ...)
```

Arguments

- `x` n by p matrix or ExpressionSet; if x is an ExpressionSet, then the function uses its 'exprs' slot.
- `...` arguments passed to `cor.dist`:
- `absif` TRUE, then $1-|\text{COR}|$ else $1-\text{COR}$, default is TRUE.
 - `diagif` TRUE, then the diagonal of the distance matrix will be displayed, default is FALSE.
 - `upperif` TRUE, then the upper triangle of the distance matrix will be displayed, default is FALSE.
 - `samplefor` objects of classes that extend `eSet`: if TRUE, then distances are computed between samples(columns) , otherwise, they are computed between features(rows).

Details

The `cor` function is used to compute the pairwise distances between rows of an input matrix, except if the input is an object of a class that extends `eSet` and `sample` is TRUE.

Value

Pairwise Pearson correlational distance object

Author(s)

Beiyong Ding

See Also

[spearman.dist](#), [tau.dist](#), [euc](#), [man](#), [KLdist.matrix](#), [KLD.matrix](#), [mutualInfo](#)

Examples

```
x <- matrix(rnorm(200), nrow = 5)
cor.dist(x)
```

euc

Euclidean distance

Description

Calculate pairwise Euclidean distances and saves the result as a 'dist' object

Usage

```
euc(x, ...)
```

Arguments

- `x` n by p matrix or an object of a class that extends `eSet`; if `x` is a matrix, pairwise distances are calculated between the rows of a matrix. If `x` is an object of a class that extends `eSet`, the method makes use of the `'exprs'` method and pairwise distances are calculated between `samples(columns)` if `sample` is `TRUE`
- `...` arguments passed to `euc`:
- `diagif TRUE`, then the diagonal of the distance matrix will be displayed; default is `FALSE`.
 - `upperif TRUE`, then the upper triangle of the distance matrix will be displayed; default is `FALSE`.
 - `sampleFor` objects of classes that extends `eSet`, pairwise distances are calculated between `samples(columns)` if `sample` is `TRUE` ; default value is `TRUE`

Details

The method calculates pairwise euclidean distances, assuming that all samples have the same number of observations

Value

An object of class `dist` with the pairwise Euclidean distance between rows except in case of objects of class that extend `eSet` when `sample` is `TRUE`

Author(s)

Beiyong Ding

See Also

[spearman.dist](#), [tau.dist](#), [man, KLdist.matrix](#), [KLD.matrix](#), [mutualInfo](#)

Examples

```
x <- matrix(rnorm(200), nrow = 5)
euc(x)
```

KLD.matrix

Continuous version of Kullback-Leibler Distance (KLD)

Description

Calculate KLD by estimating by smoothing $\log(f(x)/g(x)) * f(x)$ and then integrating.

Usage

```
KLD.matrix(x, ...)
```

Arguments

- `x` n by p matrix or list or an object of a class that extends `eSet`; if `x` is an object of a class that extends `eSet` (eg `ExpressionSet`), then the function works against its `'exprs'` slot.
- `...` arguments passed to `KLD.matrix`:
- `method` `locfit` or `density` to estimate integrand; default is `c("locfit", "density")` (i.e. both methods).
 - `supp` upper and lower limits of the integral; default is `NULL` in which case the limits of the integral are calculated from the range of the data.
 - `subdivisions` subdivisions for the integration; default is 1000.
 - `diag` if `TRUE`, then the diagonal of the distance matrix will be displayed; default is `FALSE`.
 - `upper` if `TRUE`, then the upper triangle of the distance matrix will be displayed; default is `FALSE`.
 - `sample` for `ExpressionSet` methods: if `TRUE`, then distances are computed between samples, otherwise, they are computed between genes.

Details

The distance is computed between rows of the input matrix (except if the input is an object of a class that extends `eSet` and `sample` is `TRUE`).

The presumption is that all samples have the same number of observations. The list method is meant for use when samples sizes are unequal.

Value

An object of class `dist` with the pairwise, between rows, Kullback-Leibler distances.

Author(s)

Beiyong Ding, Vincent Carey

See Also

[cor.dist](#), [spearman.dist](#), [tau.dist](#), [dist](#), [KLdist.matrix](#), [mutualInfo](#)

Examples

```
x <- matrix(rnorm(100), nrow = 5)
KLD.matrix(x, method = "locfit", supp = range(x))
```

KLdist.matrix

Discrete version of Kullback-Leibler Distance (KLD)

Description

Calculate the KLD by binning continuous data.

KL distance is calculated using the formula

$$KLD(f_1(x), f_2(x)) = \sum_{i=1}^N f_1(x_i) * \log \frac{f_1(x_i)}{f_2(x_i)}$$

Usage

```
KLdist.matrix(x, ...)
```

Arguments

x n by p matrix or a list or an object of a class that extends eSet. If x is an object of a class derived from eSet (ExpressionSet, SnpSet etc), then the values returned by the `exprs` function are used.

... arguments passed to `KLdist.matrix`:

gridsize the number of grid points used to select the optimal bin width of the histogram used to estimate density. If no value is supplied, the grid size is calculated internally; default is NULL.

symmetrize if TRUE, then symmetrize; the default is FALSE.

diag if TRUE, then the diagonal of the distance matrix will be displayed; the default is FALSE.

upper if TRUE, then the upper triangle of the distance matrix will be displayed; default is FALSE.

sample for eSet methods: if TRUE, then the distances are computed between samples, otherwise, between features; the default is TRUE.

Details

The data are binned, and then the KL distance between the two discrete distributions is computed and used. The distance is computed between rows of the input matrix (except if the input is an object of a class that extends eSet and `sample` is TRUE).

The presumption is that all samples have the same number of observations. The list method is meant for use when samples sizes are unequal.

Value

An object of class `dist` is returned.

Author(s)

Beiyong Ding

See Also

[cor.dist](#), [spearman.dist](#), [tau.dist](#), [euc](#), [man](#), [KLD.matrix](#), [mutualInfo](#)

Examples

```
x <- matrix(rnorm(100), nrow = 5)
KLdist.matrix(x, symmetrize = TRUE)
```

man	<i>Manhattan distance</i>
-----	---------------------------

Description

Calculate pairwise Manhattan distances and saves as a `dist` object.

Usage

```
man(x, ...)
```

Arguments

x	n by p matrix or an object of class that extends <code>eSet</code> . If x is an object of class that extends <code>eSet</code> , (eg <code>ExpressionSet</code>) then the function uses its 'exprs' slot.
...	arguments passed to <code>man</code> : <ul style="list-style-type: none">• <code>diagif TRUE</code>, then the diagonal of the distance matrix will be displayed; default is <code>FALSE</code>.• <code>upperif TRUE</code>, then the upper triangle of the distance matrix will be displayed; default is <code>FALSE</code>.

Details

This is just an interface to `dist` with the right parameters set.

Value

An instance of the `dist` class with the pairwise Manhattan distances between the rows of x in case of a matrix or between the features (rows) in case of a class that extends `eSet`.

Author(s)

Beiyong Ding

See Also

[cor.dist](#), [spearman.dist](#), [tau.dist](#), [euc](#), [KLdist.matrix](#), [KLD.matrix](#), [mutualInfo](#)

Examples

```
x <- matrix(rnorm(200), nrow = 5)
man(x)
```

mutualInfo

*Mutual Information***Description**

Calculate mutual information via binning

Usage

```
mutualInfo(x, ...)
MIdist(x, ...)
```

Arguments

x	an n by p matrix or ExpressionSet; if x is an ExpressionSet, then the function uses its 'exprs' slot.
...	arguments passed to mutualInfo and MIdist: <ul style="list-style-type: none"> • nbnumber of bins to calculate discrete probabilities; default is 10. • diagif TRUE, then the diagonal of the distance matrix will be displayed; default is FALSE. • upperif TRUE, then the upper triangle of the distance matrix will be displayed; default is FALSE. • samplefor ExpressionSet methods, if TRUE, then distances are computed between samples, otherwise, between genes.

Details

For mutualInfo each row of x is divided into nbins groups and then the mutual information is computed, treating the data as if they were discrete.

For MIdist we use the transformation proposed by Joe (1989), $\delta^* = (1 - \exp(-2\delta))^{1/2}$ where δ is the mutual information. The MIdist is then $1 = \delta^*$. Joe argues that this measure is then similar to Kendall's tau, [tau.dist](#).

Value

An object of class dist which contains the pairwise distances.

Author(s)

Robert Gentleman

References

H. Joe, Relative Entropy Measures of Multivariate Dependence, JASA, 1989, 157-164.

See Also

[dist](#), [Kldist.matrix](#), [cor.dist](#), [KLD.matrix](#)

Examples

```
x <- matrix(rnorm(100), nrow = 5)
mutualInfo(x, nbin = 3)
```

spearman.dist	<i>Spearman correlational distance</i>
---------------	--

Description

Calculate pairwise Spearman correlational distances, i.e. 1-SPEAR or 1-|SPEAR|, for all rows of a matrix and return a dist object.

Usage

```
spearman.dist(x, ...)
```

Arguments

x	n by p matrix or ExpressionSet; if x is an ExpressionSet, then the function uses its 'exprs' slot.
...	arguments passed to spearman.dist: <ul style="list-style-type: none"> • absif TRUE, then 1- SPEAR else 1-SPEAR; default is TRUE. • diagif TRUE, then the diagonal of the distance matrix will be displayed; default is FALSE. • upperif TRUE, then the upper triangle of the distance matrix will be displayed; default is FALSE. • samplefor the ExpressionSet method: if TRUE (the default), then distances are computed between samples.

Details

We call cor with the appropriate arguments to compute the row-wise correlations.

Value

One minus the Spearman correlation, between rows of x, are returned, as an instance of the dist class.

Author(s)

Beiyong Ding

See Also

[cor.dist](#), [tau.dist](#), [euc](#), [man](#), [Kldist.matrix](#), [KLD.matrix](#), [mutualInfo](#), [dist](#)

Examples

```
x <- matrix(rnorm(200), nrow = 5)
spearman.dist(x)
```

tau.dist	<i>Kendall's tau correlational distance</i>
----------	---

Description

Calculate pairwise Kendall's tau correlational distances, i.e. $1 - \text{TAU}$ or $1 - |\text{TAU}|$, for all rows of the input matrix and return an instance of the `dist` class.

Usage

```
tau.dist(x, ...)
```

Arguments

<code>x</code>	n by p matrix or ExpressionSet; if x is an ExpressionSet, then the function uses its 'exprs' slot.
<code>...</code>	arguments passed to <code>tau.dist</code> : <ul style="list-style-type: none">• <code>absif</code> TRUE, then $1 - \text{TAU}$ else $1 - \text{TAU}$; default is TRUE.• <code>diagif</code> TRUE, then the diagonal of the distance matrix will be displayed; default is FALSE.• <code>upperif</code> TRUE, then the upper triangle of the distance matrix will be displayed; default is FALSE.• <code>samplefor</code> the ExpressionSet method: if TRUE (the default), then distances are computed between samples.

Details

Row-wise correlations are computed by calling the `cor` function with the appropriate arguments.

Value

One minus the row-wise Kendall's tau correlations are returned as an instance of the `dist` class. Note that this can be extremely slow for large data sets.

Author(s)

Beiyong Ding

See Also

[cor.dist](#), [spearman.dist](#), [euc](#), [man](#), [KLdist.matrix](#), [KLD.matrix](#), [mutualInfo](#)

Examples

```
x <- matrix(rnorm(200), nrow = 5)
tau.dist(x)
```

Index

*Topic **manip**

- KLD.matrix, [4](#)
 - KLdist.matrix, [5](#)
 - man, [7](#)
 - mutualInfo, [8](#)
 - spearman.dist, [9](#)
 - tau.dist, [10](#)
- closest.top, [1](#)
- cor.dist, [2](#), [2](#), [5–10](#)
- cor.dist,eSet-method (cor.dist), [2](#)
- cor.dist,matrix-method (cor.dist), [2](#)
- dist, [5](#), [8](#), [9](#)
- euc, [2](#), [3](#), [3](#), [6](#), [7](#), [9](#), [10](#)
- euc,eSet-method (euc), [3](#)
- euc,matrix-method (euc), [3](#)
- KLD.matrix, [2–4](#), [4](#), [6–10](#)
- KLD.matrix,eSet-method (KLD.matrix), [4](#)
- KLD.matrix,list-method (KLD.matrix), [4](#)
- KLD.matrix,matrix-method (KLD.matrix), [4](#)
- KLdist.matrix, [5](#)
- KLdist.matrix, [2–5](#), [7–10](#)
- KLdist.matrix (KLdist.matrix), [5](#)
- KLdist.matrix,eSet-method (KLdist.matrix), [5](#)
- KLdist.matrix,list-method (KLdist.matrix), [5](#)
- KLdist.matrix,matrix-method (KLdist.matrix), [5](#)
- man, [2–4](#), [6](#), [7](#), [9](#), [10](#)
- man,eSet-method (man), [7](#)
- man,matrix-method (man), [7](#)
- MIdist (mutualInfo), [8](#)
- MIdist,ExpressionSet-method (mutualInfo), [8](#)
- MIdist,matrix-method (mutualInfo), [8](#)
- mutualInfo, [2–7](#), [8](#), [9](#), [10](#)
- mutualInfo,ExpressionSet-method (mutualInfo), [8](#)
- mutualInfo,matrix-method (mutualInfo), [8](#)
- spearman.dist, [2–7](#), [9](#), [10](#)
- spearman.dist,ExpressionSet-method (spearman.dist), [9](#)
- spearman.dist,matrix-method (spearman.dist), [9](#)
- tau.dist, [2–9](#), [10](#)
- tau.dist,ExpressionSet-method (tau.dist), [10](#)
- tau.dist,matrix-method (tau.dist), [10](#)