

Package ‘BiocInstaller’

October 15, 2018

Title Install/Update Bioconductor, CRAN, and github Packages

Description This package is used to install and update Bioconductor, CRAN, and (some) github packages.

Version 1.30.0

Author Dan Tenenbaum and Biocore Team

Maintainer Bioconductor Package Maintainer <maintainer@bioconductor.org>

biocViews Infrastructure

Depends R (>= 3.5.0)

Suggests remotes, RUnit, BiocGenerics

License Artistic-2.0

git_url <https://git.bioconductor.org/packages/BiocInstaller>

git_branch RELEASE_3_7

git_last_commit 27bcb7a

git_last_commit_date 2018-04-30

Date/Publication 2018-10-15

R topics documented:

biocinstallRepos	2
biocLite	3
biocUpdatePackages	5
BiocUpgrade	6
biocValid	7
biocVersion	8
Package Groups	8
useDevel	9

Index	13
--------------	-----------

biocinstallRepos	<i>Display current Bioconductor and CRAN repositories.</i>
------------------	------------------------------------------------------------

Description

Displays the URLs of the repositories used by [biocLite](#) to install Bioconductor and CRAN packages.

Usage

```
biocinstallRepos(siteRepos=character(), version=biocVersion())
```

Arguments

siteRepos	(Optional) character(1) representing an additional repository (e.g., a URL to an organization's internally maintained repository) in which to look for packages to install. This repository will be prepended to the default repositories returned by the function.
version	(Optional) character(1) or package_version indicating the Bioconductor version (e.g., "3.1") for which repositories are required.

Value

Named character() of repositories.

See Also

[biocLite](#) Installs/updates Bioconductor/CRAN packages.

[install.packages](#) installs the packages themselves.

[chooseBioCmirror](#) lets you choose from a list of all public Bioconductor mirror URLs.

[chooseCRANmirror](#) lets you choose from a list of all public CRAN mirror URLs.

Examples

```
biocinstallRepos()

## Choose mirrors
## Not run:
chooseCRANmirror()
chooseBioCmirror()

## End(Not run)
```

Description

biocLite installs or updates Bioconductor and CRAN packages in a Bioconductor release. Upgrading to a new Bioconductor release requires additional steps; see <https://bioconductor.org/install>.

BIOCINSTALLER_ONLINE_DCF is an environment variable or global options() which, when set to FALSE, uses configuration information from a local archive rather than consulting the current online version.

Usage

```
biocLite(pkgs=c("Biobase", "IRanges", "AnnotationDbi"),
         suppressUpdates=FALSE,
         suppressAutoUpdate=FALSE,
         siteRepos=character(),
         ask=TRUE, ...)
```

Arguments

- | | |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pkgs | character() of package names to install or update. A missing value and suppressUpdates=FALSE updates installed packages, perhaps also installing Biobase, IRanges, and AnnotationDbi if they are not already installed. Package names containing a '/' are treated as github repositories and installed using the install_github() function of the remotes package. |
| suppressUpdates | logical(1) or character(). When FALSE, biocLite asks the user whether old packages should be update. When TRUE, the user is not prompted to update old packages. When character() a vector specifying which packages to NOT update. |
| suppressAutoUpdate | logical(1) indicating whether the BiocInstaller package updates itself. |
| siteRepos | character() representing an additional repository in which to look for packages to install. This repository will be prepended to the default repositories (which you can see with biocinstallRepos). |
| ask | logical(1) indicating whether to prompt user before installed packages are updated, or the character string 'graphics', which brings up a widget for choosing which packages to update. If TRUE, user can choose whether to update all outdated packages without further prompting, to pick and choose packages to update, or to cancel updating (in a non-interactive session, no packages will be updated). Otherwise, the value is passed to update.packages . |
| ... | Additional arguments.
When installing CRAN or Bioconductor packages, typical arguments include: lib.loc, passed to old.packages and used to determine the library location of installed packages to be updated; and lib, passed to install.packages to determine the library location where pkgs are to be installed. |

When installing github packages, ... is passed to the **remotes** package functions [install_github](#) and [install](#). A typical use is to build vignettes, via `dependencies=TRUE, build_vignettes=TRUE`.

Details

Installation of Bioconductor and CRAN packages use R's standard functions for library management – `install.packages()`, `available.packages()`, `update.packages()`. Installation of github packages uses the `install_github()` function from the `remotes` package. For this reason it usually makes sense, when complicated installation options are needed, to invoke `biocLite()` separately for Bioconductor / CRAN packages and for github packages.

Setting `BIOCINSTALLER_ONLINE_DCF` to `FALSE` can speed package loading when internet access is slow or non-existent, but may result in out-of-date information about the current release and development versions of Bioconductor.

Value

`biocLite()` returns the `pkgs` argument, invisibly.

See Also

[biocinstallRepos](#) returns the Bioconductor and CRAN repositories used by `biocLite`.

[install.packages](#) installs the packages themselves.

[update.packages](#) updates all installed packages.

[chooseBioCmirror](#) lets you choose from a list of all public Bioconductor mirror URLs.

[chooseCRANmirror](#) lets you choose from a list of all public CRAN mirror URLs.

[monograph_group](#), [RBioinf_group](#) and [biocases_group](#) return package names associated with Bioconductor publications.

[all_group](#) returns the names of all Bioconductor software packages.

Examples

```
## Not run:
## Change default Bioconductor and CRAN mirrors
chooseBioCmirror()
chooseCRANmirror()

## If you don't have the BiocInstaller package installed, you can
## quickly install and load it as follows:
source("https://bioconductor.org/biocLite.R") # 'http' if 'https' unavailable

## The most recent version of the BiocInstaller package is now loaded.
## No need to load it with library().

## installs default packages (if not already installed) and updates
## previously installed packages
biocLite()

## Now install a CRAN package:
biocLite("survival")

## install a Bioconductor package, but don't update all installed
## packages as well:
```

```

biocLite("GenomicRanges", suppressUpdates=TRUE)

## Install default packages, but do not update any package whose name
## starts with "org." or "BSgenome."
biocLite(suppressUpdates=c("^org\\.", "^BSgenome\\."))

## install a package from source:
biocLite("IRanges", type="source")

## install all Bioconductor software packages
biocLite(all_group())

## End(Not run)
## Show the Bioconductor and CRAN repositories that will be used to
## install/update packages.
biocinstallRepos()

## Use local archive rather than current online configuration
## information. Set this prior to loading the BiocInstaller package.
options(BIOCINSTALLER_ONLINE_DCF = FALSE)

```

biocUpdatePackages	<i>Update previously installed Bioconductor or CRAN packages and their dependencies.</i>
--------------------	------------------------------------------------------------------------------------------

Description

Update previously installed Bioconductor and CRAN packages and their dependencies. Use `biocLite` to install new packages or to update all out-of-date packages. Upgrading to a new Bioconductor release requires additional steps; see <https://bioconductor.org/install>.

Usage

```
biocUpdatePackages(pkgs, dependencies = NA, repos=biocinstallRepos(), ...)
```

Arguments

pkgs	character() of package names to install or update.
dependencies	character() describing out-of-date dependencies that are also updated. Defaults to <code>c("Depends", "Imports", "LinkingTo")</code> but can be a subset of <code>c("Depends", "Imports", "LinkingTo", "Suggests", "Enhances")</code> .
repos	character() of named repositories in which to look for package updates, in the style of <code>biocinstallRepos()</code> .
...	Additional arguments, passed to <code>update.packages</code> . For example, <code>ask=FALSE</code> to avoid prompts to update individual packages.

Value

'NULL', invisibly.

Author(s)

Martin Morgan mtmorgan@fhcrc.org

See Also

[biocLite](#)

Examples

```
## Not run:  
biocUpdatePackages("GenomicRanges", ask=FALSE)  
  
## End(Not run)
```

BiocUpgrade

Upgrade Bioconductor to the latest version available for this version of R

Description

Downloads the latest version of the BiocInstaller package, and upgrades all currently installed packages to the latest repositories **for this version of R**.

To upgrade, use:

```
## 'http' if 'https' unavailable  
source("https://bioconductor.org/biocLite.R")  
biocLite("BiocUpgrade")
```

See Also

[biocLite](#) Installs/updates Bioconductor/CRAN packages.

[chooseBioCmirror](#) lets you choose from a list of all public Bioconductor mirror URLs.

[chooseCRANmirror](#) lets you choose from a list of all public CRAN mirror URLs.

[biocinstallRepos](#) returns the Bioconductor and CRAN repositories used by biocLite.

[install.packages](#) installs the packages themselves.

Examples

```
## Not run:  
source("https://bioconductor.org/biocLite.R")  
biocLite("BiocUpgrade")  
  
## End(Not run)
```

biocValid*Validate installed package versions against biocLite versions.*

Description

Check that installed packages are consistent (neither out-of-date nor too new) with the version of R and Bioconductor in use, using `biocLite` for validation.

Usage

```
biocValid(pkgs = installed.packages(lib.loc, priority = priority),
  lib.loc = NULL, priority = "NA", type = getOption("pkgType"),
  filters = NULL, silent = FALSE, ..., fix=FALSE)
```

Arguments

<code>pkgs</code>	A character list of package names for checking, or a matrix as returned by installed.packages .
<code>lib.loc</code>	The library location(s) of packages to be validated; see installed.packages .
<code>priority</code>	check validity of all, "base", or "recommended" packages; see installed.packages .
<code>type</code>	The type of available package (e.g., binary, source) to check validity against; see available.packages .
<code>filters</code>	Filter available packages to check validity against; see available.packages .
<code>silent</code>	Report how packages are invalid (<code>silent=FALSE</code> , default) and abort execution, or return a logical(1) (<code>silent=TRUE</code>) indicating the overall validity of installed packages.
<code>...</code>	Additional arguments, passed to biocLite when <code>fix=TRUE</code> .
<code>fix</code>	When TRUE, invoke <code>biocLite</code> to reinstall (update or downgrade, as appropriate) invalid packages.

Details

This function compares the version of installed packages to the version of packages associated with the version of R and Bioconductor appropriate for the `BiocInstaller` package currently in use.

Packages are reported as 'out-of-date' if a more recent version is available at the repositories specified by `biocinstallRepos()`. Usually, `biocLite()` is sufficient to update packages to their most recent version.

Packages are reported as 'too new' if the installed version is more recent than the most recent available in the `biocinstallRepos()` repositories. It is possible to down-grade by re-installing a too new package "PkgA" with `biocLite("PkgA")`. It is important for the user to understand how their installation became too new, and to avoid this in the future.

Value

logical(1) indicating overall validity of installed packages.

Author(s)

Martin Morgan mtmorgan@fhcrc.org

See Also

[biocLite](#) to update installed packages.

Examples

```
try(biocValid())
```

biocVersion	<i>Bioconductor version</i>
-------------	-----------------------------

Description

This function reports the Bioconductor version in use, as determined by the BiocInstaller package.

Usage

```
biocVersion()
```

Value

package_version representing the Bioconductor version in use.

See Also

[biocLite](#) Installs/updates Bioconductor/CRAN packages.

[BiocUpgrade](#) Upgrading to new versions.

Examples

```
biocVersion()
```

Package Groups	<i>Convenience functions to return package names associated with Bioconductor publications.</i>
----------------	-------------------------------------------------------------------------------------------------

Description

Returns character vectors of packages associated with Bioconductor publications, which can then be passed to [biocLite\(\)](#)

Usage

```
monograph_group()  
RBioinf_group()  
biocases_group()  
all_group()
```

Value

character() of package names.

See Also

[biocLite](#) Installs/updates Bioconductor/CRAN packages.

[biocinstallRepos](#) returns the Bioconductor and CRAN repositories used by [biocLite](#).

[install.packages](#) installs the packages themselves.

[chooseBioCmirror](#) lets you choose from a list of all public Bioconductor mirror URLs.

[chooseCRANmirror](#) lets you choose from a list of all public CRAN mirror URLs.

Examples

```
## Get the names of packages used in the book
## "Bioconductor Case Studies":
biocases_group()

## Get the names of packages used in the book
## "R Programming for Bioinformatics":
RBioinf_group()

## Get the names of packages used in the monograph
## "Bioinformatics and Computational Biology Solutions
## Using R and Bioconductor":
monograph_group()

## Get the names of all Bioconductor software packages
all_group()
```

useDevel

Get the 'devel' version of the BiocInstaller package.

Description

Downloads the 'devel' version of the BiocInstaller package so that all subsequent invocations of [biocLite](#) and [biocinstallRepos](#) use the devel repositories.

Displays the URLs of the repositories used by [biocLite](#) to install Bioconductor and CRAN packages.

Should only be used with a release (or patched) version of R, freshly installed.

Usage

```
isDevel()
useDevel(devel=TRUE)
```

Arguments

`devel` Whether to look in the devel (TRUE) or release (FALSE) repositories in subsequent invocations of [biocLite](#) and [biocinstallRepos](#).

Details

Bioconductor has a 'release' branch and a 'devel' branch. The branch in use depends on the version of R and the version of the BiocInstaller.

`useDevel()` installs the correct version of the BiocInstaller package for use of the devel version of Bioconductor, provided it is supported by the version of R in use.

`isDevel()` returns TRUE when the version of BiocInstaller in use corresponds to the 'devel' version of Bioconductor.

In more detail, the version number of the BiocInstaller package determines whether to download packages from the release or devel repositories of Bioconductor. In keeping with Bioconductor versioning conventions, if the middle number (y in x.y.z) is even, the package is part of a release version; if odd, it's part of a devel version.

By default, when BiocInstaller is first installed and when the version of R supports the current release version of Bioconductor, BiocInstaller will use the release repository.

To change the version of BiocInstaller to support the 'devel' branch of Bioconductor, run `useDevel()`. With argument TRUE (the default), it will download the devel version of BiocInstaller and subsequently all packages downloaded with `biocLite` will be from the devel repository. You should run `useDevel` only once.

During release cycles where both the release and devel version of Bioconductor use the same version of R, it is possible to use release and devel versions of Bioconductor with the same installation of R. To do this, use the `R_LIBS_USER` environment variable. First, create two separate directories for your BioC release and devel packages. Suggested directory names are as follows:

Linux:

```
~/R/x86_64-unknown-linux-gnu-library/3.2-bioc-release
```

```
~/R/x86_64-unknown-linux-gnu-library/3.2-bioc-devel
```

Mac OS:

```
~/Library/R/3.2-bioc-release/library
```

```
~/Library/R/3.2-bioc-devel/library
```

Windows:

```
C:\Users\YOUR_USER_NAME\Documents\R\win-library\3.2-bioc-release
```

```
C:\Users\YOUR_USER_NAME\Documents\R\win-library\3.2-bioc-devel
```

(change YOUR_USER_NAME to your user name)

Invoke "R for bioc-devel" or "R for bioc-release" from the command line as follows:

Linux:

```
R_LIBS_USER=~R/x86_64-unknown-linux-gnu-library/3.2-bioc-release R
```

```
R_LIBS_USER=~R/x86_64-unknown-linux-gnu-library/3.2-bioc-devel R
```

Mac OS X:

```
R_LIBS_USER=~~/Library/R/3.2-bioc-release/library R R_LIBS_USER=~~/Library/R/3.2-bioc-devel/library R
```

Windows:

```
cmd /C "set R_LIBS_USER=C:\Users\YOUR_USER_NAME\Documents\R\win-library\3.2-bioc-release && R"
```

```
cmd /C "set R_LIBS_USER=C:\Users\YOUR_USER_NAME\Documents\R\win-library\3.2-bioc-devel && R"
```

(Note: this assumes that R.exe is in your PATH.)

If you launch R in this way and then invoke `.libPaths`, you'll see that the first item is your special release or devel directory. Packages will be installed to that directory and that is the first place that `library` will look for them. `biocLite`, `install.packages`, `update.packages` and friends all respect this setting.

On Linux and Mac OS X, you can create a bash alias to save typing. Add the following to your `~/bash_profile`:

Linux

```
alias Rdevel='R_LIBS_USER=~/.R/x86_64-unknown-linux-gnu-library/3.2-bioc-devel R'
alias Rrelease='R_LIBS_USER=~/.R/x86_64-unknown-linux-gnu-library/3.2-bioc-release R'
```

Mac OS X

```
alias Rdevel='R_LIBS_USER=~/.Library/R/3.2-bioc-devel/library R' alias Rrelease='R_LIBS_USER=~/.Library/R/3.2-bioc-release/library R'
```

You can then invoke these from the command line as

Rdevel

...and...

Rrelease

On Windows, you can create two shortcuts, one for devel and one for release. Go to My Computer and navigate to a directory that is in your PATH. Then right-click and choose New->Shortcut.

in the "type the location of the item" box, put:

```
cmd /C "set R_LIBS_USER=C:\Users\YOUR_USER_NAME\Documents\R\win-library\3.2-bioc-release && R"
```

...for release and

```
cmd /C "set R_LIBS_USER=C:\Users\YOUR_USER_NAME\Documents\R\win-library\3.0-bioc-devel && R"
```

...for devel.

(again, it's assumed R.exe is in your PATH)

Click "Next".

In the "Type a name for this shortcut" box, type

Rdevel

or

Rrelease

You can invoke these from the command line as

Rdevel.lnk

...and...

Rrelease.lnk

(You must type in the .lnk extension.)

Because `R_LIBS_USER` is an environment variable, its value should be inherited by any subprocesses started by R, so they should do the right thing as well.

Value

`useDevel()`: Invisible NULL.

`isDevel()`: logical(1) TRUE or FALSE.

See Also

[biocinstallRepos](#) returns the Bioconductor and CRAN repositories used by `biocLite`.

`biocLite` Installs/updates Bioconductor/CRAN packages.

`install.packages` installs the packages themselves.

`chooseBioCmirror` lets you choose from a list of all public Bioconductor mirror URLs.

`chooseCRANmirror` lets you choose from a list of all public CRAN mirror URLs.

Examples

```
isDevel()
```

```
## Not run: useDevel()
```

Index

*Topic **environment**

- biocinstallRepos, [2](#)
 - biocLite, [3](#)
 - biocUpdatePackages, [5](#)
 - BiocUpgrade, [6](#)
 - biocValid, [7](#)
 - biocVersion, [8](#)
 - Package Groups, [8](#)
 - useDevel, [9](#)
 - .libPaths, [11](#)
- [all_group](#), [4](#)
- [all_group](#) (Package Groups), [8](#)
- [available.packages](#), [7](#)
-
- [biocases_group](#), [4](#)
- [biocases_group](#) (Package Groups), [8](#)
- [BIOCINSTALLER_ONLINE_DCF](#) (biocLite), [3](#)
- [biocinstallRepos](#), [2](#), [3](#), [4](#), [6](#), [9](#), [12](#)
- [biocLite](#), [2](#), [3](#), [5–12](#)
- [biocUpdatePackages](#), [5](#)
- [BiocUpgrade](#), [6](#), [8](#)
- [biocValid](#), [7](#)
- [biocVersion](#), [8](#)
-
- [chooseBioCmirror](#), [2](#), [4](#), [6](#), [9](#), [12](#)
- [chooseCRANmirror](#), [2](#), [4](#), [6](#), [9](#), [12](#)
-
- [install](#), [4](#)
- [install.packages](#), [2–4](#), [6](#), [9](#), [11](#), [12](#)
- [install_github](#), [4](#)
- [installed.packages](#), [7](#)
- [isDevel](#) (useDevel), [9](#)
-
- [library](#), [11](#)
-
- [monograph_group](#), [4](#)
- [monograph_group](#) (Package Groups), [8](#)
-
- [old.packages](#), [3](#)
-
- Package Groups, [8](#)
-
- [RBioinf_group](#), [4](#)
- [RBioinf_group](#) (Package Groups), [8](#)
- [update.packages](#), [3–5](#), [11](#)
- [useDevel](#), [9](#), [10](#)