

Package ‘DEScan2’

October 15, 2018

Type Package

Title Differential Enrichment Scan 2

Version 1.0.0

Date 2018-04-19

Maintainer Dario Righelli <dario.righelli@gmail.com>

Description Integrated peak and differential caller, specifically designed for broad epigenomic signals.

License Artistic-2.0

LazyData TRUE

biocViews PeakDetection, Epigenetics, Software, Sequencing, Coverage

Depends R (>= 3.5), GenomicRanges

Imports BiocGenerics, ChIPpeakAnno, data.table, DelayedArray, GenomeInfoDb, GenomicAlignments, glue, IRanges, plyr, Rcpp (>= 0.12.13), rtracklayer, S4Vectors, SummarizedExperiment, tools, utils

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 6.0.1

Suggests BiocStyle, knitr, rmarkdown, testthat, edgeR, limma, EDASeq, RUVSeq, RColorBrewer, statmod

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/DEScan2>

git_branch RELEASE_3_7

git_last_commit ef0d956

git_last_commit_date 2018-04-30

Date/Publication 2018-10-15

Author Dario Righelli [aut, cre],
John Koberstein [aut],
Bruce Gomes [aut],
Nancy Zhang [aut],
Claudia Angelini [aut],
Lucia Peixoto [aut],
Davide Risso [aut]

R topics documented:

binnedCoverage	2
constructBedRanges	3
countFinalRegions	4
cutGRangesPerChromosome	5
DEScan2	5
divideEachSampleByChromosomes	6
finalRegions	6
findOverlapsOverSamples	7
findPeaks	8
fromSamplesToChrsGRangesList	9
keepRelevantChrs	10
readFilesAsGRangesList	11
RleListToRleMatrix	12
setGRGenomeInfo	12

Index	14
--------------	-----------

binnedCoverage	<i>binnedCoverage</i>
----------------	-----------------------

Description

this function computes the coverage over a binned chromosome, starting from a per base computed coverage.

Usage

```
binnedCoverage(bins, numvar, mcolname, covMethod = c("max", "mean", "sum",
"min"), roundingMethod = c("none", "floor", "ceiling", "round"))
```

Arguments

bins	a GRanges object representing a chromosome binned.
numvar	an RleList representing the per base coverage over the chr.
mcolname	the name of column where the sum have to be stored.
covMethod	a method to apply for the computing of the coverate it can be one of "max", "mean", "sum", "min". ("max" is default)
roundingMethod	a method to apply to round the computations it can be one of "none", "floor", "ceiling", "round". It's useful only when using covMethod="mean". ("none" is default)

Value

the bins GRanges with the mcolname attached

Examples

```
## dividing one chromosome in bins of 50 bp each
seqinfo <- GenomeInfoDb::Seqinfo(genome="mm9")
bins <- GenomicRanges::tileGenome(
  seqlengths=GenomeInfoDb::seqlengths(seqinfo)[1],
  tilewidth=50,
  cut.last.tile.in.chrom=TRUE)
gr <- GenomicRanges::GRanges(seqnames = S4Vectors::Rle("chr1", 100),
  ranges=IRanges::IRanges(start = seq(from=10, to=1000, by=10),
  end=seq(from=20, to=1010, by = 10)))
cov <- GenomicRanges::coverage(x=gr)
(binnedMaxCovGR <- binnedCoverage(bins, cov, "binned_cov"))
(binnedMeanCovGR <- binnedCoverage(bins, cov, "binned_cov",
  covMethod="mean", roundingMethod="floor"))
(binnedSumCovGR <- binnedCoverage(bins, cov, "binned_cov", covMethod="sum"))
```

constructBedRanges	<i>constructBedRanges</i>
--------------------	---------------------------

Description

Constructs a GRanges object from a bam/bed/bed.zip file in a consistent way.

Usage

```
constructBedRanges(filename, filetype = c("bam", "bed", "bed.zip"),
  genomeName = NULL, onlyStdChrs = FALSE, arePeaks = FALSE,
  verbose = FALSE)
```

Arguments

filename	the complete file path of a bam?bed file.
filetype	the file type bam/bed/bed.zip.
genomeName	the name of the genome used to map the reads (i.e. "mm9"). N.B. if NOT NULL the GRanges Seqinfo will be forced to genomeName Seqinfo (needs Internet access, but strongly suggested!)
onlyStdChrs	flag to keep only standard chromosome.
arePeaks	flag indicating if the file contains peaks.
verbose	flag to obtain verbose output.

Value

a GRanges object.

Examples

```
files <- list.files(system.file("extdata/bam/", package="DEScan2"),
  pattern="bam$", full.names=TRUE)
bgr <- constructBedRanges(files[1], filetype="bam", genomeName="mm9",
  onlyStdChrs=TRUE)
bgr
```

countFinalRegions *countFinalRegions*

Description

count reads falling within the final regions.

Usage

```
countFinalRegions(regionsGRanges, readsFilePath = NULL, fileType = c("bam",
  "bed"), minCarriers = 2, genomeName = NULL, onlyStdChrs = FALSE,
  carrierscolname = "k-carriers", ignStrandSO = TRUE, modeSO = "Union",
  saveFlag = FALSE, savePath = "finalRegions", verbose = TRUE)
```

Arguments

regionsGRanges	a GRanges objects representing the peaks to compute the coverage, with a "k-carriers" mcols. (typically generated by finalRegions function).
readsFilePath	the filepath of bam or bed files necessary to compute the coverage.
fileType	the file type of the input files.
minCarriers	minimum number of carriers (samples).
genomeName	code name of the genome of reads files (i.e. "mm9").
onlyStdChrs	a flag indicating if to keep only the standard chromosomes
carrierscolname	character describing the name of the column within the carriers number (default is "k-carriers").
ignStrandSO	a flag indicating if to ignore the reads strand. (see GenomicAlignments::summarizeOverlaps).
modeSO	the mode to use, default is "Union". (see GenomicAlignments::summarizeOverlaps).
saveFlag	a flag indicating if to save the results.
savePath	the path where to store the results.
verbose	verbose output.

Value

A SummarizedExperiment object containing as assays the read counts matrix with regions as rows and samples as columns, and as rowRanges the GRanges object representing the peaks used as rows in the matrix.

Examples

```
filename <- system.file("extdata/regions/regions.rds", package="DEScan2")
regionsGR <- readRDS(file=filename)
reads.path <- system.file("extdata/bam", package="DEScan2")
finalRegionsSE <- countFinalRegions(regionsGRanges=regionsGR,
  readsFilePath=reads.path, fileType="bam", minCarriers=1,
  genomeName="mm9", onlyStdChrs=TRUE, ignStrandSO=TRUE, saveFlag=FALSE,
  verbose=TRUE)
library("SummarizedExperiment")
assay(finalRegionsSE) ## matrix of counts
rowRanges(finalRegionsSE) ## the GRanges of the input regions
```

`cutGRangesPerChromosome`*cutGRangesPerChromosome*

Description

takes in input a GRanges object, producing a LIST of GRanges, one for each chromosome.

Usage

```
cutGRangesPerChromosome(GRanges)
```

Arguments

GRanges a GRanges object.

Value

a named list of GRanges, one for each chromosome.

Examples

```
library("GenomicRanges")
gr <- GRanges(
  seqnames=Rle(c("chr1", "chr2", "chr1", "chr3"), c(1, 3, 2, 4)),
  ranges=IRanges(1:10, end=10),
  strand=Rle(strand(c("-", "+", "*", "+", "-")), c(1, 2, 2, 3, 2)),
  seqlengths=c(chr1=11, chr2=12, chr3=13))
(grchrlist <- cutGRangesPerChromosome(gr))
```

`DEScan2`*DEScan2*

Description

integrated peak and differential caller, specifically designed for broad epigenomic signals.

Author(s)

some authors

```
divideEachSampleByChromosomes
      divideEachSampleByChromosomes
```

Description

taken in input a grangeslist of samples, generate a list of samples where each element has a GRangesList each element of the GRangesList represents a single chromosome.

Usage

```
divideEachSampleByChromosomes(samplesGRangesList)
```

Arguments

```
samplesGRangesList
      a GRangesList of samples.
```

Value

list of samples where each element is a list of chromosomes and each of these elements is a GRanges.

Examples

```
library("GenomicRanges")
gr1 <- GRanges(
  seqnames=Rle(c("chr1", "chr2", "chr1", "chr3"), c(1, 3, 2, 4)),
  ranges=IRanges(1:10, end=10),
  strand=Rle(strand(c("-", "+", "*", "+", "-")), c(1, 2, 2, 3, 2)),
  seqlengths=c(chr1=11, chr2=12, chr3=13))
gr2 <- GRanges(
  seqnames=Rle(c("chr1", "chr4", "chr1", "chr3"), c(1, 3, 2, 4)),
  ranges=IRanges(1:10, end=10),
  strand=Rle(strand(c("-", "+", "*", "+", "-")), c(1, 2, 2, 3, 2)),
  seqlengths=c(chr1=11, chr4=12, chr3=13))
sgr1 <- GRangesList(gr1, gr2)
names(sgr1) <- c("samp1", "samp2")
(sampChrGr1 <- divideEachSampleByChromosomes(sgr1))
```

```
finalRegions
```

```
finalRegions
```

Description

Align peaks to form common regions then filter regions for presence in multiple replicates taking in input a GRangesList where each element is a sample of called peaks.

Usage

```
finalRegions(peakSamplesGRangesList, zThreshold = 20, minCarriers = 2,
  saveFlag = TRUE, outputFolder = "overlappedPeaks", verbose = FALSE,
  scorecolname = "z-score")
```

Arguments

peakSamplesGRangesList	named GRangesList where each element is a sample of called peaks. A score mcols values is needed for each GRanges. The scorecolname param can be used as reference name for the score. (typically returned by findPeaks function).
zThreshold	a minimum threshold for the z score. All peaks lesser than this value will be ignored.
minCarriers	a threshold of minimum samples (carriers) for overlapped regions.
saveFlag	a flag for saving results in a tsv file.
outputFolder	the directory name to store the bed file.
verbose	verbose output.
scorecolname	character describing the name of the column within the peaks score.

Value

a GRanges of selected overlapping peaks with z-score, n-peaks, k-carriers as mcols object.

Examples

```
peak.path <- system.file("extdata/peaks/RData/peaksGRL_all_files.rds",
  package="DEScan2")
gr1 <- readRDS(peak.path)
gr1

regionsGR <- finalRegions(peakSamplesGRangesList=gr1, zThreshold=1,
  minCarriers=3, saveFlag=FALSE, verbose=TRUE)
```

findOverlapsOverSamples

findOverlapsOverSamples

Description

given in input a GRangelist where each element is a sample computes the coverage extending a both direction window of prefixed length.

Usage

```
findOverlapsOverSamples(samplePeaksGRangelist, extendRegions = 200,
  minOverlap = 0L, maxGap = -1L, zThresh = 10, verbose = FALSE,
  scorecolname = "z-score")
```

Arguments

samplePeaksGRangelist	given a granges list of samples finds the overlapping regions between them.
extendRegions	the number of bases to extend each region at its start and end.
minOverlap	the minimum overlap each peak needs to have. (see ChipPeakAnno::findOverlapsOfPeaks)
maxGap	the maximum gap admissible between the peaks. (see ChipPeakAnno::findOverlapsOfPeaks)
zThresh	a threshold value on z-score/scorecolname
verbose	verbose flag
scorecolname	character describing the name of the column within the peaks score.

Value

a GRanges of peaks overlapped and unique between samples.

Examples

```
(peaks.file <- system.file("extdata/peaks/RData/peaksGRL_all_files.rds",
                          package="DEScan2"))
peaksGRLFiles <- readRDS(peaks.file)
(overlPeaks <- findOverlapsOverSamples(peaksGRLFiles))
```

findPeaks

findPeaks

Description

This function calls peaks from bed or bam inputs using a variable window scan with a poisson model using the surrounding maxCompWinWidth (10kb) as background.

Usage

```
findPeaks(files, filetype = c("bam", "bed"), genomeName = NULL,
          binSize = 50, minWin = 50, maxWin = 1000, zthresh = 10,
          minCount = 0.1, minCompWinWidth = 5000, maxCompWinWidth = 10000,
          outputFolder = "Peaks", save = TRUE, force = TRUE, verbose = FALSE,
          sigwin = 10, onlyStdChrs = TRUE, chr = NULL)
```

Arguments

files	Character vector containing paths of files to be analyzed.
filetype	Character, either "bam" or "bed" indicating format of input file.
genomeName	the code of the genome to use as reference for the input files. (cfr. constructBedRanges function parameters)
binSize	Integer size in bases of the minimum window for scanning, 50 is the default.
minWin	Integer indicating the minimum window size in bases notation.
maxWin	Integer indicating the maximum window size in bases notation.
zthresh	Cutoff value for z-scores. Only windows with greater z-scores will be kept, default is 10.

minCount	A small constant (usually no larger than one) to be added to the counts prior to the log transformation to avoid problems with log(0).
minCompWinWidth	minimum bases width of a comparing window for Z-score.
maxCompWinWidth	maximum bases width of a comparing window for Z-score.
outputFolder	A string, Name of the folder to save the Peaks (optional) if the directory doesn't exist, it will be created. (Default is "Peaks")
save	Boolean, if TRUE files will be saved in a <code>./Peaks/chr*</code> directory created (if not already present) in the current working directory.
force	a boolean flag indicating if to force output overwriting.
verbose	if to show additional messages
sigwin	an integer value used to compute the length of the signal of a peak (default value is 10).
onlyStdChrs	a flag to work only with standard chromosomes. (cfr. <code>constructBedRanges</code> function parameters).
chr	if not NULL, a character like <code>"chr#"</code> indicating the chromosomes to use.

Value

A GRangesList where each element is a sample. Each GRanges represents the founded peaks and attached the z-score of the peak as mcols.

Examples

```
bam.files <- list.files(system.file("extdata/bam", package = "DEScan2"),
  full.names = TRUE)

peaks <- findPeaks(files=bam.files[1], filetype="bam",
  genomeName="mm9",
  binSize=50, minWin=50, maxWin=1000,
  zthresh=5, minCount=0.1, sigwin=10,
  minCompWinWidth=5000, maxCompWinWidth=10000,
  save=FALSE,
  onlyStdChrs=TRUE,
  chr=NULL,
  verbose=FALSE)

head(peaks)
```

fromSamplesToChrsGRangesList

fromSamplesToChrsGRangesList

Description

converts a GRangesList orgnized per samples to a GRangesList organized per Chromosomes where each element is a GRangesList of samples.

Usage

```
fromSamplesToChrsGRangesList(samplesGRangesList)
```

Arguments

`samplesGRangesList`
a GRangesList of samples. Typically generated by `findPeaks` function.

Value

A GRangesList of chromosomes where each element is a GRanges list of samples.

Examples

```
library("GenomicRanges")
gr1 <- GRanges(
  seqnames=Rle(c("chr1", "chr2", "chr1", "chr3"), c(1, 3, 2, 4)),
  ranges=IRanges(1:10, end=10),
  strand=Rle(strand(c("-", "+", "*", "+", "-")), c(1, 2, 2, 3, 2)),
  seqlengths=c(chr1=11, chr2=12, chr3=13))
gr2 <- GRanges(
  seqnames=Rle(c("chr1", "chr4", "chr1", "chr3"), c(1, 3, 2, 4)),
  ranges=IRanges(1:10, end=10),
  strand=Rle(strand(c("-", "+", "*", "+", "-")), c(1, 2, 2, 3, 2)),
  seqlengths=c(chr1=11, chr4=12, chr3=13))
sgr1 <- GRangesList(gr1, gr2)
names(sgr1) <- c("samp1", "samp2")
(chrGr1SampGr <- fromSamplesToChrsGRangesList(sgr1))
```

keepRelevantChrs	<i>keepRelevantChrs</i>
------------------	-------------------------

Description

subselect a list of GRanges created with `cutGRangesPerChromosome` returning only the relevant chromosomes GRanges.

Usage

```
keepRelevantChrs(chrGRangesList, chr = NULL)
```

Arguments

`chrGRangesList` where each element is a chromosome, typically created with `cutGRangesPerChromosome`.

`chr` a character vector of chromosomes names of the form "chr#".

Value

the input `chrGRangesList` with only the relevant chromosomes.

Examples

```
library("GenomicRanges")
gr1 <- GRanges(
  seqnames=Rle(c("chr1", "chr2", "chr1", "chr3"), c(1, 3, 2, 4)),
  ranges=IRanges(1:10, end=10),
  strand=Rle(strand(c("-", "+", "*", "+", "-")), c(1, 2, 2, 3, 2)),
  seqlengths=c(chr1=11, chr2=12, chr3=13))
gr1c <- cutGRangesPerChromosome(gr1)
(gr1Chr <- keepRelevantChrs(gr1c, c("chr1", "chr3")))
```

```
readFilesAsGRangesList
```

```
readFilesAsGRangesList
```

Description

Takes in input the path of bam/bed files to process and stores them in a GRangesList object, named with filePath/filenames. (for lazy people)

Usage

```
readFilesAsGRangesList(filePath, fileType = c("bam", "bed", "bed.zip"),
  genomeName = NULL, onlyStdChrs = TRUE, arePeaks = TRUE,
  verbose = TRUE)
```

Arguments

filePath	the path of input files.
fileType	the type of the files (bam/bed/bed.zip).
genomeName	the genome code to associate to the files. (reccommended) (i.e. "mm9", "hg17")
onlyStdChrs	a flag to keep only standard chromosomes.
arePeaks	a flag indicating if the files contain peaks.
verbose	verbose output flag.

Value

a GRangesList object

Examples

```
files.path <- system.file("extdata/bam", package="DEScan2")
gr1 <- readFilesAsGRangesList(filePath=files.path, fileType="bam",
  genomeName="mm9", onlyStdChrs=TRUE,
  verbose=TRUE)

class(gr1)
names(gr1)
gr1
```

RleListToRleMatrix	<i>RleListToRleMatrix</i>
--------------------	---------------------------

Description

a wrapper to create a RleMatrix from a RleList object.

Usage

```
RleListToRleMatrix(RleList, dimnames = NULL)
```

Arguments

RleList	an RleList object with all elements of the same length.
dimnames	the names for dimensions of RleMatrix (see DelayedArray pkg).

Value

a RleMatrix from DelayedArray package.

Examples

```
library("DelayedArray")
lengths <- c(3, 1, 2)
values <- c(15, 5, 20)
e1 <- S4Vectors::Rle(values=values, lengths=lengths)

e2 <- S4Vectors::Rle(values=sort(values), lengths=lengths)

rleList <- IRanges::RleList(e1, e2)
names(rleList) <- c("one", "two")
(rleMat <- RleListToRleMatrix(rleList))
```

setGRGenomeInfo	<i>setGRGenomeInfo</i> given a genome code (i.e. "mm9","mm10","hg19","hg38") retrieve the SeqInfo of that genome and assigns it to the input GRanges. Finally filters out those Infos not necessary to the GRanges.
-----------------	---

Description

setGRGenomeInfo given a genome code (i.e. "mm9","mm10","hg19","hg38") retrieve the SeqInfo of that genome and assigns it to the input GRanges. Finally filters out those Infos not necessary to the GRanges.

Usage

```
setGRGenomeInfo(GRanges, genomeName = NULL, verbose = FALSE)
```

Arguments

<code>GRanges</code>	a <code>GRanges</code> object.
<code>genomeName</code>	a genome code (i.e. "mm9")
<code>verbose</code>	verbose output

Value

a `GRanges` object with the `seqinfo` of the genome code

Examples

```
library("GenomicRanges")
gr <- GRanges(
  seqnames=Rle(c("chr1", "chr2", "chr1", "chr3"), c(1, 3, 2, 4)),
  ranges=IRanges(1:10, end=10),
  strand=Rle(strand(c("-", "+", "*", "+", "-")), c(1, 2, 2, 3, 2)),
  seqlengths=c(chr1=11, chr2=12, chr3=13))
mm9gr <- setGRGenomeInfo(GRanges=gr, genomeName="mm9", verbose=TRUE)
```

Index

[binnedCoverage](#), [2](#)

[constructBedRanges](#), [3](#)
[countFinalRegions](#), [4](#)
[cutGRangesPerChromosome](#), [5](#)

[DEScan2](#), [5](#)
[DEScan2-package \(DEScan2\)](#), [5](#)
[divideEachSampleByChromosomes](#), [6](#)

[finalRegions](#), [6](#)
[findOverlapsOverSamples](#), [7](#)
[findPeaks](#), [8](#)
[fromSamplesToChrsGRangesList](#), [9](#)

[keepRelevantChrs](#), [10](#)

[readFilesAsGRangesList](#), [11](#)
[RleListToRleMatrix](#), [12](#)

[setGRGenomeInfo](#), [12](#)