

Package ‘BubbleTree’

October 16, 2019

Type Package

Title BubbleTree: an intuitive visualization to elucidate tumoral aneuploidy and clonality in somatic mosaicism using next generation sequencing data

Version 2.14.0

Date 2018-11-20

Author Wei Zhu <zhuw@medimmune.com>,
Michael Kuziora <kuzioram@medimmune.com>,
Todd Creasy <creasyt@medimmune.com>,
Brandon Higgs <higgsb@medimmune.com>

Maintainer Todd Creasy <creasyt@medimmune.com>, Wei Zhu <weizhu365@gmail.com>

Description CNV analysis in groups of tumor samples.

License LGPL (>= 3)

Imports BiocGenerics (>= 0.7.5), BiocStyle, Biobase, ggplot2, WriteXLS, gtools, RColorBrewer, limma, grid, gtable, gridExtra, biovizBase, e1071, methods, grDevices, stats, utils

Depends R (>= 3.5), IRanges, GenomicRanges, plyr, dplyr, magrittr

Suggests knitr, rmarkdown

biocViews CopyNumberVariation, Software, Sequencing, Coverage

VignetteBuilder knitr

RoxygenNote 5.0.1

git_url <https://git.bioconductor.org/packages/BubbleTree>

git_branch RELEASE_3_9

git_last_commit 7c64327

git_last_commit_date 2019-05-02

Date/Publication 2019-10-15

R topics documented:

all.somatic.lst	2
allCall.lst	3
allCNV.lst	3
allHetero.lst	3
allRBD.lst	4

annoByGenesAndCyto	4
Annotate	5
bafTrack	5
btcompare	6
btpredict	7
BTreePlotter	8
BTreePredictor	8
cancer.genes.minus2	8
centromere.dat	9
cnv.gr	9
cyto.gr	9
drawBTree	10
drawBubbles	10
drawFeatures	11
gene.uni.clean.gr	12
getTracks	13
heteroLociTrack	14
hg19.seqinfo	15
info	15
loadRBD	16
makeRBD	17
mergeSnpCnv	19
RBD	19
RscoreTrack	20
saveXLS	21
snp.gr	22
trackBTree	22
TrackPlotter	23
vol.genes	23
xyTrack	24
Index	25

all.somatic.lst	<i>all.somatic.lst</i>
-----------------	------------------------

Description

A dataset containing pre-calculated BAF scores for annotated SNVs.

Format

S4 object with seqnames, genomic ranges, strand, BAF score

Source

internal

allCall.lst	<i>allCall.lst</i>
-------------	--------------------

Description

A dataset containing precalculated data from CNV segment analysis.

Format

S4 object with rbd, rbd.adj, results

Source

internal

allCNV.lst	<i>allCNV.lst</i>
------------	-------------------

Description

A dataset containing pre-calculated segment calls.

Format

S4 object with seqnames, genomic ranges, num.mark, score

Source

internal

allHetero.lst	<i>allHetero.lst</i>
---------------	----------------------

Description

S4 GRanges dataset containing pre-calculated heterozygosity data.

Format

S4

Source

internal

allRBD.lst

allRBD.lst

Description

A dataset containing precalculated data from CNV segment analysis.

Format

S4 object with rbd, rbd.adj

Source

internal

annoByGenesAndCyto

annoByGenesAndCyto

Description

get annotation for genes and cytobands

Usage

```
annoByGenesAndCyto(.Object, chr, beg, end, critical.genes, gene.uni.clean.gr,
  cyto.gr)
```

```
## S4 method for signature 'Annotate'
annoByGenesAndCyto(.Object, chr, beg, end, critical.genes,
  gene.uni.clean.gr, cyto.gr)
```

Arguments

.Object	the objet
chr	the chromosome
beg	genomic start coord
end	genomic end coord
critical.genes	set of critical genes
gene.uni.clean.gr	gr object of genes
cyto.gr	gr object of cyto positions

Value

list of annotation for genes and cytobands

Examples

```

load(system.file("data", "allCall.lst.RData", package="BubbleTree"))
load(system.file("data", "cancer.genes.minus2.rda", package="BubbleTree"))
load(system.file("data", "vol.genes.rda", package="BubbleTree"))
load(system.file("data", "gene.uni.clean.gr.rda", package="BubbleTree"))
load(system.file("data", "cyto.gr.rda", package="BubbleTree"))

comm <- btcompare(vol.genes, cancer.genes.minus2)
btreeplotter <- new("BTreePlotter", branch.col="gray50")
annotator <-new("Annotate")
nn <- "sam2"
cc <- allCall.lst[[nn]]
z <- drawBTree(btreeplotter, cc@rbd.adj) +
  ggplot2::labs(title=sprintf("%s (%s)", nn, info(cc)))
out <- cc@result$dist %>%
  filter(seg.size >= 0.1 ) %>%
  arrange(gtools::mixedorder(as.character(seqnames)), start)

ann <- annoByGenesAndCyto(annotator,
  as.character(out$seqnames),
  as.numeric(out$start),
  as.numeric(out$end),
  comm$comm,
  gene.uni.clean.gr=gene.uni.clean.gr,
  cyto.gr=cyto.gr)

```

Annotate

Annotate

Description

Annotate

Examples

```
annotate <- new("Annotate")
```

bafTrack

bafTrack

Description

get the BAF track

Usage

```

bafTrack(.Object, result.dat, gr2, somatic.gr = NULL, min.prev = 0.15,
  cex = 1.2)

## S4 method for signature 'TrackPlotter'
bafTrack(.Object, result.dat, gr2, somatic.gr = NULL,
  min.prev = 0.15, cex = 1.2)

```

Arguments

.Object	the object
result.dat	the result dataframe
gr2	the gr2 object
somatic.gr	somatic gr object annotation
min.prev	previous min
cex	the cex

Value

the highlighted BAF track

Examples

```
load(system.file("data", "allCall.lst.RData", package="BubbleTree"))
load(system.file("data", "centromere.dat.rda", package="BubbleTree"))
load(system.file("data", "all.somatic.lst.RData", package="BubbleTree"))
load(system.file("data", "hg19.seqinfo.rda", package="BubbleTree"))

trackplotter <- new("TrackPlotter")
gr2 = centromere.dat
nn <- "sam2"
p2 <- bafTrack(trackplotter,
               result.dat=allCall.lst[[nn]]@result,
               gr2=gr2,
               somatic.gr=all.somatic.lst[[nn]])
```

btcompare

btcompare

Description

btcompare

Usage

```
btcompare(set1, set2)
```

Arguments

set1	first set
set2	second set to compare

Value

combined, unique list of genes

Examples

```
load(system.file("data", "cancer.genes.minus2.rda", package="BubbleTree"))
load(system.file("data", "vol.genes.rda", package="BubbleTree"))

# 77 common cancer genes
comm <- btcompare(vol.genes, cancer.genes.minus2)
```

btpredict

btpredict

Description

btpredict

Usage

```
btpredict(.Object)

## S4 method for signature 'BTreePredictor'
btpredict(.Object)
```

Arguments

.Object the object

Value

.Object populated with the predictions

Examples

```
load(system.file("data", "allRBD.lst.RData", package="BubbleTree"))

btrepredictor <- new("BTreePredictor")
btrepredictor@config$cutree.h <- 0.15
high.ploidy <- rep(TRUE, length(allRBD.lst))
high.purity <- rep(TRUE, length(allRBD.lst))

high.ploidy[c("sam6",
              "ovary.wgs",
              "ovary.wes",
              "TCGA-06-0145-01A-01W-0224-08",
              "TCGA-13-1500-01A-01D-0472-01",
              "TCGA-A0-A0JJ-01A-11W-A071-09")] <- FALSE

high.purity[c("sam6", "ovary.wgs", "ovary.wes")] <- FALSE

rbd <- allRBD.lst[["sam6"]]
btrepredictor@config$high.ploidy <- high.ploidy["sam6"]
btrepredictor@config$high.purity <- high.purity["sam6"]
btrepredictor <- loadRBD(btrepredictor, rbd)
```

```
btreepredictor@config$min.segSize <- ifelse(max(btreepredictor@rbd$seg.size,  
                                              na.rm=TRUE) < 0.4, 0.1, 0.4)  
btreepredictor <- btpredict(btreepredictor)  
cat(info(btreepredictor), "\n")
```

BTreePlotter

BTreePlotter

Description

BTreePlotter

Examples

```
btreeplotter <- new("BTreePlotter")
```

BTreePredictor

BTreePredictor

Description

BTreePredictor

Examples

```
btreepredictor <- new("BTreePredictor")
```

cancer.genes.minus2

cancer.genes.minus2.rda

Description

A dataset containing a list of known cancer genes.

Format

list

Source

internal

centromere.dat	<i>centromere.dat</i>
----------------	-----------------------

Description

A dataset containing an annotated list of centromere locations.

Format

list

Source

internal

cnv.gr	<i>cnv.gr</i>
--------	---------------

Description

S4 GRanges object containing data on chromosomal locations with seqnames, genomic range, strand, name

Format

S4

Source

internal

cyto.gr	<i>cyto.gr</i>
---------	----------------

Description

S4 GRanges object containing data on chromosomal locations with seqnames, genomic range, strand, name, gieStain.

Format

S4

Source

internal

drawBTree
drawBTree

Description

draw the BTree track

Usage

```
drawBTree(.Object, rbd, size = 1)
```

```
## S4 method for signature 'BTreePlotter'
drawBTree(.Object, rbd, size = 1)
```

Arguments

.Object	the object
rbd	the rbd object
size	the size

Value

draw the BTree track

Examples

```
load(system.file("data", "allCall.lst.RData", package="BubbleTree"))
load(system.file("data", "cancer.genes.minus2.rda", package="BubbleTree"))
load(system.file("data", "vol.genes.rda", package="BubbleTree"))
load(system.file("data", "gene.uni.clean.gr.rda", package="BubbleTree"))
load(system.file("data", "cyto.gr.rda", package="BubbleTree"))

# 77 common cancer genes
comm <- btcompare(vol.genes, cancer.genes.minus2)

btreeplotter <- new("BTreePlotter", branch.col="gray50")
annotator <-new("Annotate")
cc <- allCall.lst[["sam2"]]
z <- drawBTree(btreeplotter, cc@rbd.adj) +
  ggplot2::labs(title=sprintf("%s (%s)", "sam2", info(cc)))
```

drawBubbles
drawBubbles

Description

draw the Bubbles

Usage

```
drawBubbles(.Object, rbd, col = NULL)

## S4 method for signature 'BTreePlotter'
drawBubbles(.Object, rbd, col = "gray80")
```

Arguments

.Object	the object
rbd	the rbd object
col	the col value

Value

draw the bubbles on the track

Examples

```
load(system.file("data", "allCall.lst.RData", package="BubbleTree"))

btreeplotter <- new("BTreePlotter", max.ploidy=5, max.size=10)
nn <- "sam2"
rbd1 <- allCall.lst[[nn]]@rbd
rbd2 <- allCall.lst[[nn]]@rbd.adj
arrows <- trackBTree(btreeplotter, rbd1, rbd2, min.srcSize=0.01,
                    min.trtSize=0.01)
btree <- drawBTree(btreeplotter, rbd1) +
  drawBubbles(btreeplotter, rbd2, "gray80") + arrows
```

drawFeatures

drawFeatures

Description

draw the features

Usage

```
drawFeatures(.Object, rbd, col = NULL)

## S4 method for signature 'BTreePlotter'
drawFeatures(.Object, rbd, col = "black")
```

Arguments

.Object	the object
rbd	the rbd object
col	the col value

Value

draw the annotation on the track

Examples

```
load(system.file("data", "allCall.lst.RData", package="BubbleTree"))
load(system.file("data", "cancer.genes.minus2.rda", package="BubbleTree"))
load(system.file("data", "vol.genes.rda", package="BubbleTree"))
load(system.file("data", "gene.uni.clean.gr.rda", package="BubbleTree"))
load(system.file("data", "cyto.gr.rda", package="BubbleTree"))

# 77 common cancer genes merged from 2 sets
comm <- btcompare(vol.genes, cancer.genes.minus2)

btreeplotter <- new("BTreePlotter", branch.col="gray50")
annotator <- new("Annotate")

nn <- "sam12"
cc <- allCall.lst[[nn]]
z <- drawBTree(btreeplotter, cc@rbd.adj) +
  ggplot2::labs(title=sprintf("%s (%s)", nn, info(cc)))
out <- cc@result$dist %>% filter(seg.size >= 0.1 ) %>%
  arrange(gtools::mixedorder(as.character(seqnames)), start)

ann <- with(out, {
  annoByGenesAndCyto(annotator,
    as.character(out$seqnames),
    as.numeric(out$start),
    as.numeric(out$end),
    comm$comm,
    gene.uni.clean.gr=gene.uni.clean.gr,
    cyto.gr=cyto.gr)
})

out$cyto <- ann$cyto
out$genes <- ann$ann
v <- z + drawFeatures(btreeplotter, out)
print(v)
```

gene.uni.clean.gr

gene.uni.clean.gr

Description

S4 GRanges object containing human gene annotation with seqnames, genomic coordinates, stand, gene.symbol.

Format

S4

Source

internal

getTracks	<i>getTracks</i>
-----------	------------------

Description

get all tracks

Usage

```
getTracks(p1, p2, title = "")
```

Arguments

p1	set 1
p2	set 2
title	the title

Value

all of the requested tracks

Examples

```
load(system.file("data", "allCall.lst.RData", package="BubbleTree"))
load(system.file("data", "centromere.dat.rda", package="BubbleTree"))
load(system.file("data", "all.somatic.lst.RData", package="BubbleTree"))
load(system.file("data", "hg19.seqinfo.rda", package="BubbleTree"))

trackplotter <- new("TrackPlotter")
gr2 = centromere.dat
nn <- "sam2"
ymax <- ifelse(nn %in% c("lung.wgs", "lung.wes"), 9, 4.3)
p1 <- xyTrack(trackplotter,
              result.dat=allCall.lst[[nn]]@result,
              gr2=gr2,
              ymax=ymax) + ggplot2::labs(title=nn)

p2 <- bafTrack(trackplotter,
               result.dat=allCall.lst[[nn]]@result,
               gr2=gr2,
               somatic.gr=all.somatic.lst[[nn]])

t1 <- getTracks(p1, p2)
```

```
heteroLociTrack      heteroLociTrack
```

Description

get the heteroLoci track

Usage

```
heteroLociTrack(.Object, result.dat, gr2, hetero.gr = NULL, min.prev = 0.15,
  ymax = 4.3, cex = 0.5)
```

```
## S4 method for signature 'TrackPlotter'
heteroLociTrack(.Object, result.dat, gr2,
  hetero.gr = NULL, min.prev = 0.15, ymax = 4.3, cex = 0.5)
```

Arguments

.Object	the object
result.dat	the results
gr2	the gr2 object
hetero.gr	hetero annotation
min.prev	previous min
ymax	max y
cex	the cex

Value

the highlightted heterozygosity track

Examples

```
load(system.file("data", "allCall.lst.RData", package="BubbleTree"))
load(system.file("data", "centromere.dat.rda", package="BubbleTree"))
load(system.file("data", "allHetero.lst.RData", package="BubbleTree"))
load(system.file("data", "hg19.seqinfo.rda", package="BubbleTree"))

trackplotter <- new("TrackPlotter")
gr2 = centromere.dat
nn <- "sam2"
z1 <- heteroLociTrack(trackplotter, allCall.lst[[nn]]@result,
  gr2, allHetero.lst[[nn]])
```

`hg19.seqinfo``hg19.seqinfo.Rd`

Description

Seqinfo object containing names and lengths of each chromosome of the human genome.

Format

Seqinfo

Source

internal

`info``info`

Description

info

Usage

```
info(.Object)
```

```
## S4 method for signature 'BTreePredictor'  
info(.Object)
```

Arguments

`.Object` the object

Value

print out info of prediction data

Examples

```
load(system.file("data", "allRBD.lst.RData", package="BubbleTree"))
```

```
btreepredictor <- new("BTreePredictor")  
btreepredictor@config$cutree.h <- 0.15
```

```
high.ploidy <- rep(TRUE, length(allRBD.lst))  
high.purity <- rep(TRUE, length(allRBD.lst))
```

```
high.ploidy[c("sam6",  
             "ovary.wgs"),
```

```

      "ovary.wes",
      "TCGA-06-0145-01A-01W-0224-08",
      "TCGA-13-1500-01A-01D-0472-01",
      "TCGA-AO-A0JJ-01A-11W-A071-09") <- FALSE

high.purity[c("sam6", "ovary.wgs", "ovary.wes")] <- FALSE

nn <- "sam6"

rbd <- allRBD.lst[[nn]]
btreepredictor@config$high.ploidy <- high.ploidy[nn]
btreepredictor@config$high.purity <- high.purity[nn]
btreepredictor <- loadRBD(btreepredictor, rbd)
btreepredictor@config$min.segSize <- ifelse(max(btreepredictor@rbd$seg.size,
                                                na.rm=TRUE) < 0.4, 0.1, 0.4)

btreepredictor <- btpredict(btreepredictor)
cat(info(btreepredictor), "\n")

```

loadRBD

loadRBD

Description

load the RBD data

Usage

```
loadRBD(.Object, rbd, total.mark = NA)
```

```
## S4 method for signature 'BTreePredictor'
loadRBD(.Object, rbd, total.mark = NA)
```

Arguments

.Object	the object
rbd	rbd object
total.mark	total mark

Value

.Object populated with the RBD list with updated segment size

Examples

```

load(system.file("data", "allRBD.lst.RData", package="BubbleTree"))

btreepredictor <- new("BTreePredictor")
btreepredictor@config$cutree.h <- 0.15

high.ploidy <- rep(TRUE, length(allRBD.lst))
high.purity <- rep(TRUE, length(allRBD.lst))

```



```

high.ploidy[c("sam6",
              "ovary.wgs",
              "ovary.wes",
              "TCGA-06-0145-01A-01W-0224-08",
              "TCGA-13-1500-01A-01D-0472-01",
              "TCGA-A0-A0JJ-01A-11W-A071-09")] <- FALSE

high.purity[c("sam6", "ovary.wgs", "ovary.wes")] <- FALSE

nn <- "sam6"

rbd <- allRBD.lst[[nn]]
btreepredictor@config$high.ploidy <- high.ploidy[nn]
btreepredictor@config$high.purity <- high.purity[nn]
btreepredictor <- loadRBD(btreepredictor, rbd)

```

makeRBD

makeRBD

Description

make the RBD object

Usage

```
makeRBD(.Object, ...)
```

```
## S4 method for signature 'RBD'
makeRBD(.Object, snp.gr, cnv.gr, unimodal.kurtosis = -0.1)
```

Arguments

.Object	the object
...	other input (not needed)
snp.gr	SNP GenomicRanges object
cnv.gr	CNV GenomicRanges object
unimodal.kurtosis	kurtosis

Value

RBD object

Examples

```

# load sample files
load(system.file("data", "cnv.gr.rda", package="BubbleTree"))
load(system.file("data", "snp.gr.rda", package="BubbleTree"))

# load annotations
load(system.file("data", "centromere.dat.rda", package="BubbleTree"))

```

```

load(system.file("data", "cyto.gr.rda", package="BubbleTree"))
load(system.file("data", "cancer.genes.minus2.rda", package="BubbleTree"))
load(system.file("data", "vol.genes.rda", package="BubbleTree"))
load(system.file("data", "gene.uni.clean.gr.rda", package="BubbleTree"))

# initialize RBD object
r <- new("RBD", unimodal.kurtosis=-0.1)

# create new RBD object with GenomicRanges objects for SNPs and CNVs
rbd <- makeRBD(r, snp.gr, cnv.gr)
head(rbd)

# create a new prediction
btrepredictor <- new("BTreePredictor", rbd=rbd, max.ploidy=6, prev.grid=seq(0.2,1, by=0.01))
pred <- btpredict(btrepredictor)

# create rbd plot
btrepplotter <- new("BTreePlotter", max.ploidy=5, max.size=10)
btree <- drawBTree(btrepplotter, pred@rbd)
print(btree)

# create rbd.adj plot
btrepplotter <- new("BTreePlotter", branch.col="gray50")
btree <- drawBTree(btrepplotter, pred@rbd.adj)
print(btree)

# create a combined plot with rbd and rbd.adj that shows the arrows indicating change
# THIS IS VERY MESSY WITH CURRENT DATA from Dong
btrepplotter <- new("BTreePlotter", max.ploidy=5, max.size=10)
arrows <- trackBTree(btrepplotter,
                    pred@rbd,
                    pred@rbd.adj,
                    min.srcSize=0.01,
                    min.trtSize=0.01)

btree <- drawBTree(btrepplotter, pred@rbd) + arrows
print(btree)

# create a plot with overlays of significant genes
btrepplotter <- new("BTreePlotter", branch.col="gray50")
annotator <- new("Annotate")

comm <- btcompare(vol.genes, cancer.genes.minus2)

sample.name <- "22_cnv_snv"

btree <- drawBTree(btrepplotter, pred@rbd.adj) +
  ggplot2::labs(title=sprintf("%s (%s)", sample.name, info(pred)))

out <- pred@result$dist %>%
  filter(seg.size >= 0.1) %>%
  arrange(gtools::mixedorder(as.character(seqnames)), start)

ann <- with(out, {
  annoByGenesAndCyto(annotator,

```

```

        as.character(out$seqnames),
        as.numeric(out$start),
        as.numeric(out$end),
        comm$comm,
        gene.uni.clean.gr=gene.uni.clean.gr,
        cyto.gr=cyto.gr)
    })

    out$cyto <- ann$cyto
    out$genes <- ann$ann

    btree <- btree + drawFeatures(btreetplotter, out)
    print(btree)

    # print out purity and ploidy values
    info <- info(pred)
    cat("\nPurity/Ploidy: ", info, "\n")

```

mergeSnpCnv

mergeSnpCnv

Description

merge snp and cnv data

Usage

```
mergeSnpCnv(.Object, snp.gr, cnv.gr)
```

```
## S4 method for signature 'RBD'
mergeSnpCnv(.Object, snp.gr, cnv.gr)
```

Arguments

.Object	the object
snp.gr	SNP GenomicRanges object
cnv.gr	CNV GenomicRanges object

Value

combined, unique list of genes

RBD

RBD

Description

RBD

Examples

```
rbd <- new("RBD")
```

RscoreTrack	<i>RscoreTrack</i>
-------------	--------------------

Description

get the RScore track

Usage

```
RscoreTrack(.Object, result.dat, gr2, cnv.gr = NULL, min.prev = 0.15,  
            ymax = 3, cex = 1.5)
```

```
## S4 method for signature 'TrackPlotter'  
RscoreTrack(.Object, result.dat, gr2, cnv.gr = NULL,  
            min.prev = 0.15, ymax = 3, cex = 1.5)
```

Arguments

.Object	the object
result.dat	the results
gr2	the gr2 object
cnv.gr	cnv annotation
min.prev	previous min
ymax	max y
cex	the cex

Value

the highlighted RScore track

Examples

```
load(system.file("data", "allCall.lst.RData", package="BubbleTree"))  
load(system.file("data", "centromere.dat.rda", package="BubbleTree"))  
load(system.file("data", "allCNV.lst.RData", package="BubbleTree"))  
load(system.file("data", "hg19.seqinfo.rda", package="BubbleTree"))  
  
gr2 = centromere.dat  
trackplotter <- new("TrackPlotter")  
nn <- "sam2"  
z <- RscoreTrack(trackplotter, allCall.lst[[nn]]@result, gr2, allCNV.lst[[nn]])
```

saveXLS	<i>saveXLS</i>
---------	----------------

Description

saveXLS

Usage

```
saveXLS(dat.lst, xls.fn, row.names = FALSE, ...)
```

Arguments

dat.lst	dataframe
xls.fn	filename
row.names	row names
...	misc

Value

new Excel file

Examples

```
load(system.file("data", "allCall.lst.RData", package="BubbleTree"))

all.summary <- plyr::ldply(allCall.lst, function(.Object) {
  purity <- .Object@result$prev[1]
  adj <- .Object@result$ploidy.adj["adj"]
  # when purity is low the calculation result is not reliable
  ploidy <- (2*adj -2)/purity + 2

  with(.Object@result,
    return(c(Purity=round(purity,3),
             Prevalences=paste(round(prev,3), collapse=" ", ),
             "Tumor ploidy"=round(ploidy,1))))
}) %>% plyr::rename(c(".id"="Sample"))

xls.filename <- paste("all_summary", "xlsx", sep=".")
saveXLS(list(Summary=all.summary), xls.filename)
```

snp.gr	<i>snp.gr</i>
--------	---------------

Description

S4 GRanges object containing data on chromosomal locations with seqnames, genomic position, strand, name

Format

S4

Source

internal

trackBTree	<i>trackBTree</i>
------------	-------------------

Description

get the geom_segment location of the BTree track

Usage

```
trackBTree(.Object, rbd1, rbd2, is.matched = FALSE, min.srcSize = 0.5,
  min.trtSize = 0.1, min.overlap = 1e+05)
```

```
## S4 method for signature 'BTreePlotter'
```

```
trackBTree(.Object, rbd1, rbd2, is.matched = FALSE,
  min.srcSize = 0.5, min.trtSize = 0.1, min.overlap = 1e+05)
```

Arguments

.Object	the object
rbd1	rbd one
rbd2	rbd two
is.matched	is it matched
min.srcSize	min src size
min.trtSize	min trt size
min.overlap	min overlap

Value

geom_segment location of BTree track

Examples

```
load(system.file("data", "allCall.lst.RData", package="BubbleTree"))

btreeplotter <- new("BTreePlotter", max.ploidy=5, max.size=10)
nn <- "sam2"
rbd1 <- allCall.lst[[nn]]@rbd
rbd2 <- allCall.lst[[nn]]@rbd.adj
arrows <- trackBTree(btreeplotter, rbd1, rbd2, min.srcSize=0.01,
                    min.trtSize=0.01)
btree <- drawBTree(btreeplotter, rbd1) +
        drawBubbles(btreeplotter, rbd2, "gray80") + arrows
```

TrackPlotter

TrackPlotter

Description

TrackPlotter

Examples

```
trackplotter <- new("TrackPlotter")
```

vol.genes

vol.genes

Description

A dataset containing a list of known cancer genes.

Format

list

Source

internal

`xyTrack``xyTrack`

Description

get the xy track

Usage

```
xyTrack(.Object, result.dat, gr2, min.prev = 0.15, ymax = 4.3)
```

```
## S4 method for signature 'TrackPlotter'  
xyTrack(.Object, result.dat, gr2, min.prev = 0.15,  
        ymax = 4.3)
```

Arguments

<code>.Object</code>	the object
<code>result.dat</code>	result dataframe
<code>gr2</code>	gr2 object
<code>min.prev</code>	previous min
<code>ymax</code>	the max y

Value

the highlighted xy track

Examples

```
load(system.file("data", "allCall.lst.RData", package="BubbleTree"))  
load(system.file("data", "centromere.dat.rda", package="BubbleTree"))  
load(system.file("data", "hg19.seqinfo.rda", package="BubbleTree"))  
  
trackplotter <- new("TrackPlotter")  
gr2 = centromere.dat  
nn <- "sam2"  
ymax <- ifelse(nn %in% c("lung.wgs", "lung.wes"), 9, 4.3)  
p1 <- xyTrack(trackplotter,  
              result.dat=allCall.lst[[nn]]@result,  
              gr2=gr2,  
              ymax=ymax) + ggplot2::labs(title=nn)
```


Index

*Topic **datasets**

- all.somatic.lst, 2
 - allCall.lst, 3
 - allCNV.lst, 3
 - allHetero.lst, 3
 - allRBD.lst, 4
 - cancer.genes.minus2, 8
 - centromere.dat, 9
 - cnv.gr, 9
 - cyto.gr, 9
 - gene.uni.clean.gr, 12
 - hg19.seqinfo, 15
 - snp.gr, 22
 - vol.genes, 23
-
- all.somatic.lst, 2
 - allCall.lst, 3
 - allCNV.lst, 3
 - allHetero.lst, 3
 - allRBD.lst, 4
 - annoByGenesAndCyto, 4
 - annoByGenesAndCyto, Annotate-method (annoByGenesAndCyto), 4
 - Annotate, 5
 - Annotate-package (Annotate), 5
 - bafTrack, 5
 - bafTrack, TrackPlotter-method (bafTrack), 5
 - btcompare, 6
 - btpredict, 7
 - btpredict, BTreePredictor-method (btpredict), 7
 - BTreePlotter, 8
 - BTreePlotter-package (BTreePlotter), 8
 - BTreePredictor, 8
 - BTreePredictor-package (BTreePredictor), 8
 - cancer.genes.minus2, 8
 - centromere.dat, 9
 - cnv.gr, 9
 - cyto.gr, 9
 - drawBTree, 10
 - drawBTree, BTreePlotter-method (drawBTree), 10
 - drawBubbles, 10
 - drawBubbles, BTreePlotter-method (drawBubbles), 10
 - drawFeatures, 11
 - drawFeatures, BTreePlotter-method (drawFeatures), 11
 - gene.uni.clean.gr, 12
 - getTracks, 13
 - heteroLociTrack, 14
 - heteroLociTrack, TrackPlotter-method (heteroLociTrack), 14
 - hg19.seqinfo, 15
 - info, 15
 - info, BTreePredictor-method (info), 15
 - loadRBD, 16
 - loadRBD, BTreePredictor-method (loadRBD), 16
 - makeRBD, 17
 - makeRBD, RBD-method (makeRBD), 17
 - mergeSnpCnv, 19
 - mergeSnpCnv, RBD-method (mergeSnpCnv), 19
 - RBD, 19
 - RBD-package (RBD), 19
 - RscoreTrack, 20
 - RscoreTrack, TrackPlotter-method (RscoreTrack), 20
 - saveXLS, 21
 - snp.gr, 22
 - trackBTree, 22
 - trackBTree, BTreePlotter-method (trackBTree), 22
 - TrackPlotter, 23
 - TrackPlotter-package (TrackPlotter), 23
 - vol.genes, 23

xyTrack, [24](#)
xyTrack, TrackPlotter-method (xyTrack),
[24](#)