

Package ‘netprioR’

November 23, 2024

Title A model for network-based prioritisation of genes

Description A model for semi-supervised prioritisation of genes integrating network data, phenotypes and additional prior knowledge about TP and TN gene labels from the literature or experts.

Imports stats, Matrix, dplyr, doParallel, foreach, parallel, sparseMVN, ggplot2, gridExtra, pROC

Depends methods, graphics, R(>= 3.3)

Suggests knitr, BiocStyle, pander

VignetteBuilder knitr

biocViews ImmunoOncology, CellBasedAssays, Preprocessing, Network

Type Package

Lazyload yes

LazyData true

Version 1.33.0

Date 2016-05-08

Author Fabian Schmich

Maintainer Fabian Schmich <fabian.schmich@bsse.ethz.ch>

License GPL-3

URL <http://bioconductor.org/packages/netprioR>

RoxygenNote 5.0.1

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/netprioR>

git_branch devel

git_last_commit 9afdf83

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2024-11-22

Contents

| | |
|--------------------------------------|-----------|
| netprioR-package | 2 |
| bandwidth | 3 |
| cmn | 3 |
| conjugate_gradient | 4 |
| cuthill_mckee | 4 |
| fit | 5 |
| laplacian | 6 |
| learn | 6 |
| netprioR-class | 7 |
| norm_kern | 9 |
| plot.netprioR | 9 |
| ranks | 10 |
| ROC | 11 |
| simulate_labels | 11 |
| simulate_network_random | 12 |
| simulate_network_scalefree | 13 |
| simulate_phenotype | 13 |
| simulation | 14 |
| weights | 15 |
| Index | 16 |

netprioR-package *Package: netprioR*

Description

This package provides a model for semi-supervised prioritisation of genes integrating network data, phenotypes and additional prior knowledge about TP and TN gene labels.

Author(s)

Fabian Schmich | Computational Biology Group, ETH Zurich | <fabian.schmich@bsse.ethz.ch>

References

Fabian Schmich et. al (2016).

| | |
|-----------|------------------|
| bandwidth | <i>bandwidth</i> |
|-----------|------------------|

Description

Compute the bandwidth of a matrix

Usage

```
bandwidth(x)
```

Arguments

| | |
|---|--------------|
| x | Input matrix |
|---|--------------|

Value

Bandwidth

Author(s)

Fabian Schmich

| | |
|-----|---|
| cmn | <i>Class Mass Normalization (CMN) from Zhu et al., 2003</i> |
|-----|---|

Description

Class Mass Normalization (CMN) from Zhu et al., 2003

Usage

```
cmn(yhat, l, u)
```

Arguments

| | |
|------|--|
| yhat | Response for labeled (l) and unlabeled (u) genes |
| l | Indices of labeled genes |
| u | Indices of unlabeled genes |

Value

Class normalized yhat

Author(s)

Fabian Schmich

conjugate_gradient *Conjugate Gradient Solver*

Description

Solves linear equation systems iteratively

Usage

```
conjugate_gradient(A, b, x0 = rep(0, ncol(A)), threshold = 1e-15,  
  verbose = FALSE)
```

Arguments

| | |
|-----------|-------------------------|
| A | Matrix |
| b | Coefficients |
| x0 | Starting solution |
| threshold | Termination threshold |
| verbose | Show iterative progress |

Value

Solution for equation system

Author(s)

Fabian Schmich

cuthill_mckee *Cuthill McKee (CM) algorithm*

Description

Transform sparse matrix into a band matrix

Usage

```
cuthill_mckee(x)
```

Arguments

| | |
|---|--------------|
| x | Input matrix |
|---|--------------|

Value

Band matrix

Author(s)

Fabian Schmich

`fit`*Fit netprioR model*

DescriptionFit `netprioR` model**Usage**

```
fit(object, ...)  
  
## S4 method for signature 'netprioR'  
fit(object, refit = FALSE, ...)
```

Arguments

| | |
|---------------------|--|
| <code>object</code> | A <code>netprioR</code> object |
| <code>...</code> | Additional arguments |
| <code>refit</code> | Flag whether to overwrite existing fit |

ValueA `netprioR` object with fitted model**Author(s)**

Fabian Schmich

Examples

```
data(simulation)  
np <- netprioR(networks = simulation$networks,  
               phenotypes = simulation$phenotypes,  
               labels = simulation$labels.obs,  
               model.fit = FALSE)  
  
summary(np)  
np <- fit(np, nrestarts = 1, verbose = FALSE)  
summary(np)
```

| | |
|-----------|------------------------|
| laplacian | <i>Graph Laplacian</i> |
|-----------|------------------------|

Description

Compute the Laplacian matrix of a graph given its adjacency matrix

Usage

```
laplacian(x, norm = c("none", "sym", "asym"))
```

Arguments

| | |
|------|-----------------------|
| x | Adjacency matrix |
| norm | Type of normalisation |

Value

Laplacian matrix

Author(s)

Fabian Schmich

| | |
|-------|---------------------------|
| learn | <i>Fit netprioR model</i> |
|-------|---------------------------|

Description

Infer parameters and hidden data using the EM algorithm of netprioR

Usage

```
learn(Yobs, X, G, l, u, a = 0.1, b = 0.1, sigma2 = 1, tau2 = 10,  
      eps = 1e-11, max.iter = 500, thresh = 0.001, use.cg = TRUE,  
      thresh.cg = 1e-05, nrestarts = 5, max.cores = detectCores(),  
      verbose = FALSE)
```

Arguments

| | |
|-----------|---|
| Yobs | Observed labels (NA, if not observed) |
| X | Phenotypes |
| G | Graph Laplacians |
| l | Indices of labelled instances |
| u | Indices of unlabelled instances |
| a | Shape parameter of Gamma prior for W |
| b | Scale parameter of Gamma prior for W |
| sigma2 | Cariance for Gaussian labels |
| tau2 | Variance for Gaussian prior for beta |
| eps | Small value added to diagonal of Q in order to make it non-singular |
| max.iter | Maximum number of iterations for EM |
| thresh | Threshold for termination of EM with respect to change in parameters |
| use.cg | Flag whether to use conjugate gradient instead of exact computation of expectations |
| thresh.cg | Threshold for the termination of the conjugate gradient solver |
| nrestarts | Number of restarts for EM |
| max.cores | Maximum number of cores to use for parallel computation |
| verbose | Print verbose output |

Value

List containing: Predicted labels \hat{Y} and inferred parameters W and β

Author(s)

Fabian Schmich

| | |
|----------------|-----------------|
| netprioR-class | <i>netprioR</i> |
|----------------|-----------------|

Description

Class that represents a netprioR model.

Usage

```
netprioR(networks, phenotypes, labels, ...)

## S4 method for signature 'list,matrix,factor'
netprioR(networks, phenotypes, labels,
  fit.model = FALSE, a = 0.1, b = 0.1, sigma2 = 0.1, tau2 = 100,
  eps = 1e-10, max.iter = 500, thresh = 1e-06, use.cg = FALSE,
  thresh.cg = 1e-06, nrestarts = 5, max.cores = detectCores(),
  verbose = TRUE, ...)
```

Arguments

| | |
|------------|---|
| networks | List of NxN adjacency matrices of gene-gene similarities |
| phenotypes | Matrix of dimension NxP containing covariates |
| labels | Vector of Nx1 labels for all genes (NA if no label available) |
| ... | Additional arguments |
| fit.model | Indicator whether to fit the model |
| a | Shape parameter of Gamma prior for W |
| b | Scale parameter of Gamma prior for W |
| sigma2 | Cariance for Gaussian labels |
| tau2 | Variance for Gaussian prior for beta |
| eps | Small value added to diagonal of Q in order to make it non-singular |
| max.iter | Maximum number of iterations for EM |
| thresh | Threshold for termination of EM with respect to change in parameters |
| use.cg | Flag whether to use conjugate gradient instead of exact computation of expectations |
| thresh.cg | Threshold for the termination of the conjugate gradient solver |
| nrestarts | Number of restarts for EM |
| max.cores | Maximum number of cores to use for parallel computation |
| verbose | Print verbose output |

Value

A [netprioR](#) object

Slots

networks List of NxN adjacency matrices of gene-gene similarities
 phenotypes Matrix of dimension NxP containing covariates
 labels Vector of Nx1 labels for all genes. NA if no label available.
 is.fitted Flag indicating if model is fitted
 model List containing estimated parameters and imputed missing data

Author(s)

Fabian Schmich

Examples

```
# runs long-ish
data(simulation)
np <- netprioR(networks = simulation$networks,
               phenotypes = simulation$phenotypes,
               labels = simulation$labels.obs,
               fit.model = TRUE)
summary(np)
```

| | |
|-----------|-------------------------|
| norm_kern | <i>Normalise kernel</i> |
|-----------|-------------------------|

Description

adopted from GeneMania, Mostafavi et al, 2009

Usage

```
norm_kern(x)
```

Arguments

| | |
|---|--------|
| x | kernel |
|---|--------|

Value

Normalised kernel

Author(s)

Fabian Schmich

| | |
|---------------|---|
| plot.netprioR | <i>Plot method for netprioR objects</i> |
|---------------|---|

Description

Plot method for [netprioR](#) objects

Usage

```
## S3 method for class 'netprioR'  
plot(x, which = c("all", "weights", "lik", "scores"), ...)
```

Arguments

| | |
|-------|---|
| x | A netprioR object |
| which | Flag for which plot should be shown, options: weights, lik, scores, all |
| ... | Additional paramters for plot |

Value

Plot of the weights, likelihood, ranks, or all three

Author(s)

Fabian Schmich

Examples

```
data(simulation)
plot(simulation$model)
```

ranks

Retrieve ranked prioritisation list

Description

Retrieve ranked prioritisation list

Usage

```
ranks(object)

## S4 method for signature 'netprioR'
ranks(object)
```

Arguments

object A [netprioR](#) object

Value

Ranked list of prioritised genes

Author(s)

Fabian Schmich

Examples

```
data(simulation)
ranks(simulation$model)
```

| | |
|-----|--|
| ROC | <i>Compute ROC curve from netprioR model and true labels</i> |
|-----|--|

Description

Compute ROC curve from netprioR model and true labels

Usage

```
ROC(object, ...)  
  
## S4 method for signature 'netprioR'  
ROC(object, true.labels, plot = FALSE, ...)
```

Arguments

| | |
|-------------|------------------------------------|
| object | A netprioR object |
| ... | Additional arguments |
| true.labels | True full set of underlying labels |
| plot | Flag whether to plot the AUC curve |

Value

ROC curve with AUC

Author(s)

Fabian Schmich

Examples

```
data(simulation)  
ROC(simulation$model, true.labels = simulation$labels.true)
```

| | |
|-----------------|------------------------|
| simulate_labels | <i>Simulate labels</i> |
|-----------------|------------------------|

Description

Simulate labels

Usage

```
simulate_labels(values, sizes, nobs)
```

Arguments

| | |
|--------|---|
| values | Vector of labels for groups |
| sizes | Vector of group sizes |
| nobs | Vector of number of observed labels per group |

Value

List of Y, Yobs and indices for labeled instances

Author(s)

Fabian Schmich

Examples

```
labels <- simulate_labels(values = c("Positive", "Negative"),
  sizes = c(10, 10),
  nobs = c(5, 5))
```

simulate_network_random

Simulate random networks with predefined number of members for each of the two groups and the number of neighbours for each node

Description

Simulate random networks with predefined number of members for each of the two groups and the number of neighbours for each node

Usage

```
simulate_network_random(nmemb, nnei = 1)
```

Arguments

| | |
|-------|--|
| nmemb | Vector of number of members for each group |
| nnei | Number of neighbours for each node |

Value

Adjacency matrix of graph

Author(s)

Fabian Schmich

Examples

```
network <- simulate_network_random(nmemb = c(10, 10), nnei = 1)
```

simulate_network_scalefree
Simulate scalefree networks

Description

Simulate scale free networks for predefined number of members for each of two groups and a parameter pclus that determines how strictly distinct the groups are

Usage

```
simulate_network_scalefree(nmemb, pclus = 1)
```

Arguments

nmemb Vector of numbers of members per group
pclus Scalar in [0, 1] determining how strictly distinct groups are

Value

Adjacency matrix

Author(s)

Fabian Schmich

Examples

```
network <- simulate_network_scalefree(nmemb = c(10, 10), pclus = 0.8)
```

simulate_phenotype *Simulate phenotypes correlated to labels pivoted into two groups*

Description

Simulate phenotypes correlated to labels pivoted into two groups

Usage

```
simulate_phenotype(labels.true, meandiff, sd)
```

Arguments

labels.true Vector of labels
meandiff difference of means between positive and negative groups
sd Standard deviation of the phenotype

Value

Simulated phenotype

Author(s)

Fabian Schmich

Examples

```
data(simulation)
phenotypes <- simulate_phenotype(labels.true = simulation$labels.true, meandiff = 0.5, sd = 1)
```

| | |
|------------|---|
| simulation | <i>Example data: Simulated networks, phenotypes and labels for N = 1000 genes</i> |
|------------|---|

Description

The data set contains simulated data for $N = 1000$ genes and $P = 1$ (univariate) phenotypes. The list of networks contains 2 low noise networks and two high noise networks. The class labels are "Positive" and "Negative".

Usage

```
data(simulation)
```

Details

The code used to simulate the data can be found in `system.file("example", "data_simulation.R", package = "netprioR")`

Value

List of simulated networks, phenotypes and labels for 1000 genes

| | |
|---------|---------------------------------|
| weights | <i>Retrieve network weights</i> |
|---------|---------------------------------|

Description

Retrieve network weights

Usage

```
weights(object, ...)
```

```
## S4 method for signature 'netprioR'  
weights(object)
```

Arguments

| | |
|--------|-----------------------------------|
| object | A netprioR object |
| ... | Additional arguments |

Value

Estimated network weights

Author(s)

Fabian Schmich

Examples

```
data(simulation)  
weights(simulation$model)
```

Index

- * **package**
 - netprioR-package, 2
- bandwidth, 3
- cmn, 3
- conjugate_gradient, 4
- cuthill_mckee, 4
- fit, 5
- fit, netprioR-method (fit), 5
- laplacian, 6
- learn, 6
- netprioR, 5, 8–11, 15
- netprioR (netprioR-class), 7
- netprioR, list, matrix, factor-method (netprioR-class), 7
- netprioR-class, 7
- netprioR-package, 2
- norm_kern, 9
- plot.netprioR, 9
- ranks, 10
- ranks, netprioR-method (ranks), 10
- ROC, 11
- ROC, netprioR-method (ROC), 11
- simulate_labels, 11
- simulate_network_random, 12
- simulate_network_scalefree, 13
- simulate_phenotype, 13
- simulation, 14
- weights, 15
- weights, netprioR-method (weights), 15