

# Package ‘seqLogo’

May 20, 2023

**Title** Sequence logos for DNA sequence alignments

**Version** 1.66.0

**Description** seqLogo takes the position weight matrix of a DNA sequence motif and plots the corresponding sequence logo as introduced by Schneider and Stephens (1990).

**LazyLoad** yes

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.1.2

**Imports** stats4, grDevices

**Depends** R (>= 4.2), methods, grid

**Suggests** knitr, BiocStyle, rmarkdown, testthat

**BugReports** <https://github.com/ivanek/seqLogo/issues>

**VignetteBuilder** knitr

**Collate** AllClasses.R AllGenerics.R pwm.R seqLogo.R

**License** LGPL (>= 2)

**biocViews** SequenceMatching

**git\_url** <https://git.bioconductor.org/packages/seqLogo>

**git\_branch** RELEASE\_3\_17

**git\_last\_commit** 6214c17

**git\_last\_commit\_date** 2023-04-25

**Date/Publication** 2023-05-19

**Author** Oliver Bembom [aut],  
Robert Ivanek [aut, cre] (<<https://orcid.org/0000-0002-8403-056X>>)

**Maintainer** Robert Ivanek <[robert.ivanek@unibas.ch](mailto:robert.ivanek@unibas.ch)>

## R topics documented:

makePWM . . . . .	2
pwm-class . . . . .	3
seqLogo . . . . .	4
<b>Index</b>	<b>6</b>

---

makePWM	<i>Constructing a pwm object</i>
---------	----------------------------------

---

### Description

This function constructs an object of class `pwm` from a matrix. It checks that the matrix has correct dimensions and that columns add up to 1.0.

### Usage

```
makePWM(pwm, alphabet = "DNA")
```

### Arguments

<code>pwm</code>	matrix. Numerical matrix representing the position weight matrix.
<code>alphabet</code>	character. The alphabet making up the sequence. Currently, only 'DNA' and 'RNA' is supported.

### Value

An object of class `pwm`.

### Author(s)

Oliver Bembom

### Examples

```
mFile <- system.file("extdata/pwm1", package = "seqLogo")
m <- read.table(mFile)
pwm <- makePWM(m)
```

---

pwm-class                      *An S4 class to represent a PWM matrix.*

---

### Description

An object of class 'pwm' represents the alphabet\*width position weight matrix of a sequence motif. In case of DNA sequence motif, the entry in row *i*, column *j* gives the probability of observing nucleotide `c('A', 'C', 'G', 'T')[i]` in position *j* of the motif.

### Usage

```
## S4 method for signature 'pwm'
show(object)

## S4 method for signature 'pwm'
summary(object, ...)

## S4 method for signature 'pwm,ANY'
plot(x, y = "missing", ...)

## S4 method for signature 'pwm'
pwm(pwm)

## S4 method for signature 'pwm'
ic(pwm)

## S4 method for signature 'pwm'
consensus(pwm)
```

### Arguments

object	object of pwm-class
...	additional parameters for plot function
x	object of pwm-class
y	default (missing) for plot function
pwm	object of pwm-class

### Value

pwm-class object with slots: pwm, width, ic and alphabet.

### Functions

- `show, pwm-method`: Shows the position weight matrix.
- `summary, pwm-method`: Prints the summary information about position weight matrix.
- `plot, pwm, ANY-method`: Plots the sequence logo of the position weight matrix.

- `pwm`, `pwm-method`: Access to 'pwm' slot
- `ic`, `pwm-method`: Access to 'ic' slot
- `consensus`, `pwm-method`: Access to 'consensus' slot

### Slots

`pwm` matrix. The position weight matrix.

`width` numeric. The width of the motif.

`ic` numeric. The information content (IC).

`alphabet` character. The sequence alphabet. Currently, only 'DNA' and 'RNA' is supported.

`consensus` character. The consensus sequence.

### Author(s)

Oliver Bembom

### Examples

```
mFile <- system.file("extdata/pwm1", package = "seqLogo")
m <- read.table(mFile)
p <- makePWM(m)
#
# slot access
pwm(p)
ic(p)
consensus(p)
```

---

seqLogo

*Plot a sequence logo for a given position weight matrix*

---

### Description

This function takes the `alphabet*width` position weight matrix of a sequence motif and plots the corresponding sequence logo.

### Usage

```
seqLogo(pwm, ic.scale=TRUE, xaxis=TRUE, yaxis=TRUE, xfontsize=15, yfontsize=15,
        fill=c(A='#61D04F', C='#2297E6', G='#F5C710', T='#DF536B'))
```

**Arguments**

<code>pwm</code>	numeric. The alphabet*width position weight matrix.
<code>ic.scale</code>	logical. If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height.
<code>xaxis</code>	logical. If TRUE, an X-axis will be plotted.
<code>yaxis</code>	logical. If TRUE, a Y-axis will be plotted.
<code>xfontsize</code>	numeric. Font size to be used for the X-axis.
<code>yfontsize</code>	numeric. Font size to be used for the Y-axis.
<code>fill</code>	character. Fill color to be used for the letters. Must be a named character vector of length equal to number of rows in <code>pwm</code> slot and names identical to its row-names.

**Value**

NULL.

**Author(s)**

Oliver Bembom

**Examples**

```
mFile <- system.file("extdata/pwm1", package = "seqLogo")
m <- read.table(mFile)
p <- makePWM(m)
seqLogo(p)
```

# Index

alphabet (pwm-class), [3](#)

consensus (pwm-class), [3](#)  
consensus, pwm-method (pwm-class), [3](#)

ic (pwm-class), [3](#)  
ic, pwm-method (pwm-class), [3](#)

makePWM, [2](#)

plot, pwm, ANY-method (pwm-class), [3](#)  
pwm (pwm-class), [3](#)  
pwm, pwm-method (pwm-class), [3](#)  
pwm-class, [3](#)

seqLogo, [4](#)  
show, pwm-method (pwm-class), [3](#)  
summary, pwm-method (pwm-class), [3](#)